INVERTED MAML: MODE B UNCOMPENSATED SILICON VERIFICATION REPORT

Run 01 (100 Epochs) | Hardware Jumpers set to MODE B (Compensation Loop Physically Disconnected)
Hardware: PCB v1.3.2 (Summing Attenuator 1k / 5.1k Ohm) | **SoC:** Trion T120 (0x20261030, v2.1-MAML)
Patent: SE 2630397-4 (Open Science Hardware)

Executive Summary: Verification of pure uncompensated Matrix 33 multiplier dynamics on physical silicon was conducted in Mode B. The physical jumpers were manually set to Mode B, disconnecting the active M3 / M8 compensation branch from the summing junction. Across 100 continuous epochs with arbitrary rotating white-noise input vectors, the uncompensated system demonstrated an empirical mean loss of **41614.9 ± 21416.1 LSB²** and an uncompensated mean ENOB of **2.63 ± 0.28 bits**. This establishes the raw physical silicon baseline against which Inverted MAML active Vernier compensation is benchmarked.

Metric	Uncompensated Mode B (Run 01)	Mode A Baseline (Ep 0..99)	Mode A Compensated (Peak)
Mean Loss	**41614.9 LSB²**	23,077.1 LSB²	**287.0 LSB² (-98.8%)**
Mean ENOB	**2.63 bits**	~3.13 bits	**6.23 bits (+3.3 bits)**
Peak ENOB	3.41 b (Ep 57)	3.63 bits	**6.74 bits**

