

CURSO DE RASPBERRY PI

Introducción

Prof. Edwin Yllanes Cucho
e.yllanescucho@gmail.com



23 de mayo de 2015

SEMANA 3

Contenido:

- 1 Semana 3: Raspberry y Python- Laboratorio 2
 - Uso de la tarjeta de expansión para raspberry pi de RMJ II
 - Uso de Raspberry con Arduino



LCD




Figura : Conexión

LCD	GPIO	Description
1	GND	0V
2	+5V	5V logic supply
3	No connection	Contrast control voltage
4	25	RS: Register select
5	GND	RW: Read/write (always write)
6	24	EN: Enable
7-10	No connection	Only used In eight-bit mode
11	23	D4: Data line 4
12	17	D5: Data line 5
13	21	D6: Data line 6
14	22	D7: Data line 7
15	+5V	LED backlight
16	GND	LED backlight-

Cuadro : Connection between LCD and Rpi

```
$ git clone https://github.com/adafruit/Adafruit-Raspberry-Pi-Python-Code.git
$ cd Adafruit-Raspberry-Pi-Python-Code
$ cd Adafruit_CharLCD
```

La libreria provee las siguientes funciones:

Function	Description
home()	Move to top left
clear()	Clear all text off the display.
setCursor(column, row)	Set the cursor position from where text will be written
cursor()	Turn on cursor display
noCursor()	Turn off cursor display (default)
message(text)	Write the text at the current cursor position



Teclado Matricial




Figura : Conexión

```
import RPi.GPIO as GPIO
import time
GPIO.setmode(GPIO.BCM)
rows = [17, 25, 24, 23]
cols = [27, 18, 22]
keys = [
    ['1', '2', '3'],
    ['4', '5', '6'],
    ['7', '8', '9'],
    ['*', '0', '#']]
for row_pin in rows:
    GPIO.setup(row_pin, GPIO.IN, pull_up_down=GPIO.PUD_DOWN)
for col_pin in cols:
    GPIO.setup(col_pin, GPIO.OUT)
def get_key():
    key = 0
    for col_num, col_pin in enumerate(cols):
        GPIO.output(col_pin, 1)
        for row_num, row_pin in enumerate(rows):
            if GPIO.input(row_pin):
                key = keys[row_num][col_num]
        GPIO.output(col_pin, 0)
    return key
while True:
    key = get_key()
    if key :
        print(key)
    time.sleep(0.3)
```


UART

Por defecto, el puerto serial actua como consola, para deshabilitar haz lo siguiente:

```
$ sudo nano /etc/inittab  
$ T0:23:respawn:/sbin/getty -L ttyAMA0 115200 vt100  
$ #T0:23:respawn:/sbin/getty -L ttyAMA0 115200 vt100
```

Instalación

```
$ sudo apt-get install python-serial  
$ sudo usermod -a -G tty pi  
$ sudo usermod -a -G dialout pi
```



```
import serial
ser = serial.Serial('/dev/ttyAMA0', 9600)
ser.write('some text')
while True:
    print(ser.read())
```

Instalación

```
$ sudo apt-get update  
$ sudo apt-get install arduino
```



pyFirmata

```
$ git clone https://github.com/tino/pyFirmata.git  
$ cd pyFirmata  
$ sudo python setup.py install
```

