



EMTI S.r.l.

EUROPEAN MACHINE TOOLS ITALIANA

VIA Stiatco, 2/3
40050 ARGELATO (BO) ITALY
www.emti.it info@emti.it
TEL. 051-897991 FAX. 051-893344
CODICE FISCALE: 03059620371
P.IVA (WAT NR.): IT00592551204
CCIAA 261451 MEC.M 137105



**10078 Maschiatrice a CNC :
BROTHER**



**10078 CNC Tapping machine :
BROTHER**

Item		Unit	TC-31A
ATC	Tool changing time (tool to tool)	sec	0.7(50Hz,60Hz)
	Tool changing time (chip to chip)	sec	2.0(50Hz,60Hz)
APC	Pallet Pallet exchange		2 pallets 0°/180°turn table method
	Positioning time	sec	2.5
Motor	Spindle motor		10000min-1(rpm)type
		kw	8.4(10min,rating)
		kw	4.9(30min,rating)
		kw	3.65(continuous,rating)
	Axis feed motor (X,Y,Z) (C axis)		22000min-1(rpm)type
		kw	11.1(10min,rating)
		kw	6.0(30min,rating)
		kw	4.9(continuous,rating)
	kw	1.2	
	kw	0.72	
power requirements	Power supply	V Hz	AC200±10% 50/60±1
Pwer capacity	Continuous rating 30-min. rating Instaneous rating		16000min-1(rpm)type
		kVA (A/phase)	6.6 (19.0)
		kVA (A/phase)	9.0 (26.0)
		kVA (A/phase)	20. 0(57.8)
			22000min-1(rpm)type
		kVA (A/phase)	8.5 (24.6)
	kVA (A/phase)	11.1 (31.8)	
	kVA (A/phase)	25.0 (72.3)	
Air supply	Pressure	MPa	0.4-0.6 (4-6kgf/cm2)
	Flow rate (total) (air blust and coolant) (QT clamp and unclamp)	L/min	100
		(ANR)	90
			10
TC31A/manual 2002TBL			

2-4 Machine Specifications

Table 2-1 machine specifications (1)

Item		Unit	TC-31A	
Travel	X-axis travel (Column longitudinal stroke)	mm	350 (13.7795 in)	
	Y-axis travel (Column cross stroke)	mm	250(9.8425 in)	
	Z-axis travel (Spindle head vertical stroke)	mm	350 (13.7795 in)	
	Distance from table top surface to spindle nose.		(including ATC 80mm(3.1496 in) 200-550	
	Distance from column front to axis of spindle.	mm	(7.8740-21.6535 in) 282(11.1024 in)	
Table	Table working surface	mm	500×270 (19.6850×10.6299in)	
	Max. load on table (Uniform load)	kg	80(176.36)	
	Table top surface configuration		X direction key-slot 3pcs. Y direction key-slot 1pce.	
Spindle	Spindle speed	min-1(rpm)	16-16000	22-22000
	Maximum spindle speed in tapping	min-1(rpm)	6000	8000
	Spindle taper hole	mm	7/24 taper No.30	
	Spindle dearing ID (Taper side × Motor side)		35×35 (1.38×1.38)	
Feedrate	Rapid traverse (X,Y and Z axis)	mm/m in (in./min)	50000 (1.181.1) (1968.5)	
	(C axis)	min-1(rpm)	25	
	Cutting feedrate (X,Y and Z axis)	mm/m in (in./min)	5-20000 (0.2-787.4)	
	Manual feedrate (X,Y and Z axis)	mm/m in (in./min)	50-4000 (2.0-154.8)	
			(22 steps)	
	Maximum tool storage capacity		18tools	26tools
	Tool shank		MAS BT30	MAS BT30
	Pullstud		MAS P30T	MAS P30T
	Maximum tool diameter*	mm (in)	-2(30°) Standard 55(2.17) Large 125(4.92)	-2(30°) Standard 55(2.17) Large 125(4.92)
	Maximum tool length*	mm (in)	200(7.87)	200(7.87)
	Maximum tool weight*	kg(lbs)	Standard 2.0(4.41)	Standard 2.0(4.41)
	Total tool weight*		Large 3.5(7.72)	Large 3.5(7.72)
	Tool selection	kg(lbs)	40(88.18)	55(121.25)
			Random access	Random access

TC31A manual 2003 TBL