

Package ‘PSTricks’

March 21, 2024

Title PSTricks, bindings for LaTeX's PSTricks package

Version 0.1.0

Description PSTricks provides R bindings for LaTeX's PSTricks package, higher level plot commands, the capability of generating a complete .tex file, and compiling it to a .pdf file.

License GPL (>= 3)

Depends R (>= 3.5.0)

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

Imports grDevices,
magrittr,
fs,
scriptName,
methods,
tools,
rconfig

NeedsCompilation no

Author Erik Olofsen [aut, cre]

Maintainer Erik Olofsen <e.olofsen@weggetjes.nl>

Suggests knitr,
rmarkdown,
testthat (>= 3.0.0)

Config/testthat/edition 3

VignetteBuilder knitr

R topics documented:

adjx0y0	6
aes	6
circlenode	7
clipbox	8

Cnode	8
cnode	9
cnodeput	10
cput	11
cx	11
cy	12
degrees	12
dianode	13
dotnode	13
endP2E	14
endpppicture	14
endpspicture	15
everypsbox	15
fnode	16
geom_abline	16
geom_ccurve	17
geom_curve	18
geom_dots	19
geom_ecurve	20
geom_errorbar	21
geom_everypsbox	22
geom_frame	22
geom_framebox	23
geom_grid	24
geom_hist	25
geom_hline	26
geom_legend	26
geom_line	27
geom_linewidth	28
geom_polygon	28
geom_rput	29
geom_set	30
geom_uput	31
geom_vline	32
icx	33
icy	33
labs	34
lims	34
MakeShortNab	35
MakeShortTablr	35
merge.list	36
multirput	37
naput	38
nbput	38
ncangle	39
ncangles	40
ncarc	40
ncarcbox	41

ncbar	42
ncbox	42
nccircle	43
nccoil	44
nccurve	44
ncdiag	45
ncdiagg	46
ncline	46
ncloop	47
ncput	48
nczigzag	48
newcmymkcolor	49
newgray	50
newhsbcolor	50
newrgbcolor	51
nput	51
ovalnode	52
parabola	53
pcangle	54
pcangles	54
pcarc	55
pcarcbox	56
pcbar	56
pcbox	57
pccoil	58
pccurve	58
pcdiag	59
pcdiagg	60
pcline	60
pclloop	61
pczigzag	62
pnode	62
ppappend	63
pparg	63
ppaxis	64
ppbuild	65
ppbuild3D	66
ppclosedoc	67
ppcoords	67
ppcoords3D	68
ppdefpicture	68
ppgeoms	69
ppgrid	69
pplegend	70
pplinewidth	71
ppmansubplot	72
ppnewpage	72
ppnewrgbcolor	73

ppopendoc	74
ppopt	74
pppicture	75
ppsetcartesian	76
ppsetlogx	77
ppsetlogxy	77
ppsetlogy	78
ppsetmargins	78
ppsetnologx	79
ppsetnologxy	79
ppsetnology	80
ppsetpolar	80
ppsetprimary	81
ppsetprimaryx	81
ppsetprimaryy	82
ppsetpsttoeps	82
ppsetsecondary	83
ppsetsecondaryx	83
ppsetsecondaryy	84
ppsetxlabsep	84
ppsetylabsep	85
ppsubplot	86
ppticks	87
pptitle	88
ppwrite	89
ppxticks	90
ppyticks	91
print.PSTricks	92
psarc	93
psarcn	94
psaxes	95
psbezier	95
psccurve	96
pscircle	97
pscirclebox	97
pscircleOA	98
psCoil	99
pscoil	99
pscurve	100
pscustom	101
psdblframebox	101
psdiabox	102
psdiamond	103
psdot	103
psdots	104
psecurve	105
psellipse	105
psellipticarc	106

psellipticarcn	107
psframe	108
psframebox	108
psgrid	109
psline	110
psovalbox	110
pspicture	111
pspolygon	112
psscalebox	113
psscaleboxto	113
psset	114
psshadowbox	114
psTextFrame	115
pstriangle	116
pstribox	116
PSTricks	117
pswedge	118
pszigzag	119
qdisk	120
qline	121
Rnode	121
rnode	122
rotatedown	123
rotateleft	123
rotateright	124
rput	124
sifelse	125
startP2E	126
taput	126
tbput	127
thput	127
ticks	128
tlput	129
trinode	130
trput	131
tvput	131
uput	132
xaspect	133
xlab	134
xlim	134
xyaspect	135
yaspect	136
ylab	137
ylim	137
%>%	138

`adjx0y0`*Calculate Origin of Axis based on Origin of Subplot*

Description

Calculate Origin of Axis based on Origin of Subplot

Usage

```
adjx0y0(p, xory, secondary)
```

Arguments

<code>p</code>	The PStricks object.
<code>xory</code>	A character 'x' or 'y' designating the axis.
<code>secondary</code>	A flag to designate a secondary axis.

Value

An origin.

`aes`*Construct Aesthetic Mappings*

Description

Construct Aesthetic Mappings

Usage

```
aes(...)
```

Arguments

<code>...</code>	Comma separated mappings such as in the example below.
------------------	--

Details

Note: `aes()` does not evaluate right hand sides of mappings.

Value

A structure containing the mapping.

See Also

[geom_set\(\)](#) for an example.

Examples

```
aes("x=time")
```

circlenode	<i>Put Stuff in a Circle</i>
------------	------------------------------

Description

Put Stuff in a Circle

Usage

```
circlenode(p = NULL, name, stuff, par = NULL, star = FALSE)
```

Arguments

p	The PStricks object.
name	The name of the node.
stuff	Stuff to put in a box at the node.
par	PStricks parameter string.
star	Flag to indicate starred version.

Value

The updated PStricks object.

See Also

[ovalnode\(\)](#) for an example.

clipbox	<i>Put Stuff in a Box with Clipping</i>
---------	---

Description

Put Stuff in a Box with Clipping

Usage

```
clipbox(p = NULL, stuff, dim = NULL)
```

Arguments

p	The PSTricks object.
stuff	The stuff to put in the box.
dim	Distance between the box and clipping.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),16,9) %>%
  rput(8,4,clipbox(",\"\\parbox[t][1cm][t]{2cm}{One of the best
    new plays I have seen all all year}\",-0.1))
```

Cnode	<i>Create Circle Node</i>
-------	---------------------------

Description

Create Circle Node

Usage

```
Cnode(p = NULL, x = NULL, y = NULL, name, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the node.
name	The name of the node.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  psset("radius=0.1") %>%
  Cnode(0,1,"A") %>%
  pnode(3,0,"B") %>%
  ncline("A","B",arrows="<-")
```

cnode

Create Circle Node

Description

Create Circle Node

Usage

```
cnode(p = NULL, x = NULL, y = NULL, radius, name, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the node.
radius	Radius of the circle.
name	The name of the node.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  cnode(0,1,0.25,"A") %>%
  pnode(3,0,"B") %>%
  ncline("A","B",arrows="<-")
```

cnodeput

*Put Stuff in a Circle***Description**

Put Stuff in a Circle

Usage

```
cnodeput(
  p = NULL,
  x = NULL,
  y = NULL,
  name,
  stuff,
  par = NULL,
  angle = NULL,
  star = FALSE
)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the node.
name	The name of the node.
stuff	Stuff to put in a box at the node.
par	PSTricks parameter string.
angle	Angle to put the stuff with.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  cnodeput(,"A","X",angle=45)
```

cput	<i>Put Stuff in a Circle</i>
------	------------------------------

Description

Put Stuff in a Circle

Usage

```
cput(p = NULL, x, y, stuff, par = NULL, angle = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the center of the circle.
stuff	The stuff to put in the box.
par	PSTricks parameter string.
angle	Rotation to apply to the stuff.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
ppicture(PSTricks(),2,1,par="showgrid=true") %>%
  cput(1,.5,"\\large $K_1$", "doubleline=true")
```

cx	<i>Convert Unscaled x Values to Scaled</i>
----	--

Description

Convert Unscaled x Values to Scaled

Usage

```
cx(p, x, logx = NULL)
```

Arguments

p	The PSTricks object.
x	Unscaled data.
logx	Flag to request log(10) transformation.

Value

Scaled data.

cy	<i>Convert Unscaled y Values to Scaled</i>
----	--

Description

Convert Unscaled y Values to Scaled

Usage

cy(p, y, logy = NULL)

Arguments

- p The PStricks object.
- y Unscaled data.
- logy Flag to request log(10) transformation.

Value

Scaled data.

degrees	<i>Set Unit for Angles</i>
---------	----------------------------

Description

Set Unit for Angles

Usage

degrees(p, degrees = 360)

Arguments

- p The PStricks object.
- degrees The number of units in a circle.

Value

The updated PStricks object.

See Also

[ppsetpolar\(\)](#).

dianode	<i>Put Stuff in a Diamond</i>
---------	-------------------------------

Description

Put Stuff in a Diamond

Usage

```
dianode(p = NULL, name, stuff, par = NULL, star = FALSE)
```

Arguments

p	The PStricks object.
name	The name of the node.
stuff	Stuff to put in a box at the node.
par	PStricks parameter string.
star	Flag to indicate starred version.

Value

The updated PStricks object.

See Also

[trinode\(\)](#) for an example.

dotnode	<i>Create a Dot Node</i>
---------	--------------------------

Description

Create a Dot Node

Usage

```
dotnode(p = NULL, x = NULL, y = NULL, name, par = NULL, star = FALSE)
```

Arguments

p	The PStricks object.
x, y	Coordinates of the node.
name	The name of the node.
par	PStricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  dotnode(,"A","dotstyle=triangle*,dotscale=2 1") %>%
  dotnode(3,2,"B","dotstyle=+") %>%
  ncline("A","B","nodesep=3pt")
```

endP2E	<i>End PSTtoEPS Feature</i>
--------	-----------------------------

Description

End PSTtoEPS Feature

Usage

```
endP2E(p, fileplot = FALSE)
```

Arguments

- p The PSTricks object.
- fileplot Flag to indicate cated values will be used for fileplot.

Value

The updated PSTricks object.

endpppicture	<i>Close the Picture</i>
--------------	--------------------------

Description

Close the Picture

Usage

```
endpppicture(p, ending = "")
```

Arguments

- p The PSTricks object.
- ending String to end the pppicture environment with.

Value

The updated PSTricks object.

endppicture	<i>End Picture Environment</i>
-------------	--------------------------------

Description

End Picture Environment

Usage

```
endppicture(p = NULL)
```

Arguments

p	The PSTricks object.
---	----------------------

Value

The updated PSTricks object.

See Also

[ppicture\(\)](#) for an example.

everypsbox	<i>Prepend String to every psbox</i>
------------	--------------------------------------

Description

Prepend String to every psbox

Usage

```
everypsbox(p, s)
```

Arguments

p	The PSTricks object.
s	The string to prepend.

Value

The updated PSTricks object.

Examples

```
everypsbox(PSTricks(), "\\Large")$lines[[1]]
```

fnode	<i>Create a Frame Node</i>
-------	----------------------------

Description

Create a Frame Node

Usage

```
fnode(p = NULL, x = NULL, y = NULL, name, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Optional coordinates of the center.
name	The name of the node.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  fnode(,"A") %>%
  fnode(2,2,"B","framesize=1 5pt",TRUE) %>%
  ncline("A","B","nodesep=3pt")
```

geom_abline	<i>Draw Straight Line</i>
-------------	---------------------------

Description

Draw Straight Line

Usage

```
geom_abline(p, slope = 1, intercept = 0, par = NULL)
```


Arguments

p	The PStricks object.
slope	The slope of the line, or an <code>lm</code> object.
intercept	The intercept of the line.
par	PStricks parameter string.

Value

The updated PStricks object.

Examples

```
PStricks() %>%
  pppicture(16,9) %>%
  ppsetlogxy() %>%
  geom_dots(aes(x=hp,y=mpg),mtcars,par="dotstyle=Bo") %>%
  geom_abline(lm(log10(mpg)~log10(hp),data=mtcars),par="linecolor=red") %>%
  geom_hline(20,par="linecolor=green") %>%
  geom_vline(100,par="linecolor=blue")
# Note that log10 needs to be used for lm with log axes
```

geom_ccurve

*Connect Observations using Smooth Lines***Description**

Connect Observations using Smooth Lines

Usage

```
geom_ccurve(
  p,
  mapping = NULL,
  data = NULL,
  par = NULL,
  dodge = 0,
  star = FALSE
)
```

Arguments

p	The PStricks object.
mapping	Aesthetic mapping from column names to x and y.
data	Data frame with coordinates of the observations.
par	PStricks parameter string.
dodge	Horizontal offset.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

See Also

[psccurve\(\)](#) for the base version.

Examples

```
geom_ccurve(PSTricks(),
  data=data.frame(x=c(.5,3.5,3.5,.5),y=c(0,1,0,1)),
  par="showpoints=true") %>%
  xlim(0,4) %>% ylim(-0.5,1.5) %>%
  geom_grid()
```

geom_curve

Connect Observations using Smooth Lines

Description

Connect Observations using Smooth Lines

Usage

```
geom_curve(p, mapping = NULL, data = NULL, par = NULL, dodge = 0, star = FALSE)
```

Arguments

p	The PSTricks object.
mapping	Aesthetic mapping from column names to x and y.
data	Data frame with coordinates of the observations.
par	PSTricks parameter string.
dodge	Horizontal offset.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

See Also

[pscurve\(\)](#) for the base version.

Examples

```
PSTricks() %>%
  newrgbcolor("verylightgray",.9,.9,.9) %>%
  ppsetmargins(mrgaxes=0) %>%
  geom_grid("linestyle=dotted,linecolor=gray",
    background="verylightgray") %>%
  geom_curve(data=data.frame(x=c(0,.7,3.3,4,.4),y=c(1.3,1.8,.5,1.6,.4)),
    par="showpoints=true") %>%
  geom_legend("top right","showpoints=true") %>%
  xlim(-1,5) %>% ylim(0,2)
# Note that autoscaling which uses the data only does not work optimally
```

geom_dots

*Plot Dots***Description**

Plot Dots

Usage

```
geom_dots(p, mapping = NULL, data = NULL, par = NULL, dodge = 0, star = FALSE)
```

Arguments

p	The PSTricks object.
mapping	Aesthetic mapping from column names to x and y.
data	Data frame with coordinates of the observations.
par	PSTricks parameter string.
dodge	Horizontal offset.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

See Also

[psdots\(\)](#) for the base version and [geom_abline\(\)](#) for another example.

Examples

```
geom_dots(PSTricks(),data=data.frame(x=c(0,1,2),y=c(1,1,1),
  par=paste0("dotstyle=",c('*', 'o', 'Bo'))))
```

geom_ecurve

*Connect Observations using Smooth Lines***Description**

Connect Observations using Smooth Lines

Usage

```
geom_ecurve(
  p,
  mapping = NULL,
  data = NULL,
  par = NULL,
  dodge = 0,
  star = FALSE
)
```

Arguments

p	The PStricks object.
mapping	Aesthetic mapping from column names to x and y.
data	Data frame with coordinates of the observations.
par	PStricks parameter string.
dodge	Horizontal offset.
star	Flag to indicate starred version.

Value

The updated PStricks object.

See Also[psecurve\(\)](#) for the base version.**Examples**

```
PStricks() %>%
  pppicture(16,9,star=TRUE) %>%
  geom_ecurve(data=data.frame(x=c(.125,.25,.5,1,2,4,8),
                                y=c(8,4,2,1,.5,.25,.125)),
              par="showpoints=true") %>%
  xlim(0,4) %>% ylim(0,4) %>%
  geom_grid()
```

geom_errorbar

*Vertical Errorbars***Description**

Vertical Errorbars

Usage

```
geom_errorbar(
  p,
  mapping = NULL,
  data = NULL,
  par = NULL,
  width = 0.1,
  dodge = 0
)
```

Arguments

p	The PStricks object.
mapping	Aesthetic mapping from column names to x, y, ymin, and ymax.
data	Data frame with values for the error bars.
par	PStricks parameters.
width	Horizontal width of the error bars.
dodge	Horizontal offset.

Value

The updated PStricks object.

Examples

```
pppicture(PStricks(),16,9,data=data.frame(x=c(1,2,3,4),y=c(2,4,6,8),
                                             ymin=c(1,2,3,4),ymax=c(3,6,9,12))) %>%
  geom_set("linecolor=blue") %>%
  geom_line(par="showpoints=true",dodge=-0.125) %>%
  geom_errorbar(dodge=-0.125) %>%
  geom_set("linecolor=green") %>%
  geom_line(par="showpoints=true",dodge=0.125) %>%
  geom_errorbar(aes(ymin=NA),dodge=0.125)
```

geom_everypsbox	<i>Set everypsbox during Geom Processing</i>
-----------------	--

Description

Set everypsbox during Geom Processing

Usage

```
geom_everypsbox(p, par = NULL)
```

Arguments

p	The PStricks object.
par	Stuff to apply to a psbox.

Value

The updated PStricks object.

See Also

[everypsbox\(\)](#) for the base version and [geom_set\(\)](#) for an example.

geom_frame	<i>Draw Frames</i>
------------	--------------------

Description

Draw Frames

Usage

```
geom_frame(p, mapping = NULL, data = NULL, par = NULL, dodge = 0, star = FALSE)
```

Arguments

p	The PStricks object.
mapping	Aesthetic mapping from column names to x and y.
data	Data frame with coordinates of the observations.
par	PStricks parameter string.
dodge	Horizontal offset.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

See Also

[psframe\(\)](#) for the base version.

Examples

```
geom_frame(PSTricks(),
  data=data.frame(x0=c(0,1),x1=c(4,.5),y0=c(0,.5),y1=c(2,1.5),
    par=c("linewidth=2pt,framearc=.3,fillstyle=solid,fillcolor=lightgray",
      "linecolor=white"),
    star=c(FALSE,TRUE)))
```

geom_framebox

Add Frameboxes

Description

Add Frameboxes

Usage

```
geom_framebox(
  p,
  mapping = NULL,
  data = NULL,
  par = NULL,
  refpoint = NULL,
  rotation = NULL,
  dodge = 0,
  star = FALSE
)
```

Arguments

p	The PSTricks object.
mapping	Aesthetic mapping from column names to x and y.
data	Data frame with coordinates of the observations.
par	PSTricks parameter string.
refpoint	The reference point for the stuff.
rotation	Rotation to apply to the stuff.
dodge	Horizontal offset.
star	Flag to indicate starred version.

Value

The updated PStricks object.

See Also

[psframebox\(\)](#) and [rput\(\)](#) for the base versions and [geom_set\(\)](#) for an example.

geom_grid

Draw Grid Lines

Description

Draw Grid Lines

Usage

```
geom_grid(p, par = "linestyle=dotted", background = NULL)
```

Arguments

p	The PStricks object.
par	PStricks parameters.
background	The background color.

Value

The updated PStricks object.

See Also

[ppgrid\(\)](#) for the base version and [geom_curve\(\)](#) for an example.

Examples

```
geom_grid(PStricks())
```

geom_hist	<i>Plot a Histogram</i>
-----------	-------------------------

Description

Plot a Histogram

Usage

```
geom_hist(  
  p,  
  mapping = aes(x = breaks, y = counts),  
  data = NULL,  
  par = "fillcolor=lightgray,fillstyle=solid",  
  star = FALSE  
)
```

Arguments

p	The PStricks object.
mapping	Either aes(x=breaks,y=counts) or aes(x=breaks,y=density).
data	Output of R's hist(..., plot=FALSE) function.
par	PStricks parameters.
star	Flag to use star version of psframe.

Details

Issue: The default mapping containing "breaks" and "counts" leads to a NOTE when running "R CMD check".

Value

The updated PStricks object.

Examples

```
geom_hist(PStricks(),data=hist(mtcars$mpg,plot=FALSE),  
  par="fillcolor=cyan,fillstyle=solid")
```

geom_hline	<i>Draw Horizontal Line</i>
------------	-----------------------------

Description

Draw Horizontal Line

Usage

```
geom_hline(p, yintercept = 0, par = NULL)
```

Arguments

p	The PStricks object.
yintercept	The y-intercept of the line.
par	PStricks parameter string.

Value

The updated PStricks object.

See Also

[geom_abline\(\)](#) for an example.

geom_legend	<i>Add Legend to Plot</i>
-------------	---------------------------

Description

Add Legend to Plot

Usage

```
geom_legend(  
  p,  
  s,  
  par = NULL,  
  position = "tr",  
  dx = 0,  
  dy = 0,  
  w = 1,  
  labelsep = "10pt"  
)
```

Arguments

p	The PStricks object.
s	The legend text.
par	PStricks parameter string.
position	Position for the legend (may be NULL).
dx, dy	x and y offsets w.r.t. default position.
w	Width of the psline that belongs to the legend text.
labelsep	The distance between the line and the label.

Value

The updated PStricks object.

See Also

[pplegend\(\)](#) for the base version and [geom_curve\(\)](#) for an example.

geom_line

Connect Observations using Lines

Description

Connect Observations using Lines

Usage

```
geom_line(p, mapping = NULL, data = NULL, par = NULL, dodge = 0, star = FALSE)
```

Arguments

p	The PStricks object.
mapping	Aesthetic mapping from column names to x and y.
data	Data frame with coordinates of the observations.
par	PStricks parameter string.
dodge	Horizontal offset.
star	Flag to indicate starred version.

Value

The updated PStricks object.

See Also

[psline\(\)](#) for the base version.

Examples

```
geom_line(PSTricks(),aes(x=xdata,y=ydata),data.frame(xdata=c(4,0,2),ydata=c(2,1,0)),
  "linewidth=2pt,linearc=.25,arrows=->")
# Note that the names in the data frame determine the axis label names by default
# and that a default `pppicture()` is called automatically
```

geom_linewidth	<i>Set PSTricks' linewidth Parameter during Geom Processing</i>
----------------	---

Description

Set PSTricks' linewidth Parameter during Geom Processing

Usage

```
geom_linewidth(p, linewidth = 0.8 * 2.54/72)
```

Arguments

p	The PSTricks object.
linewidth	The linewidth to use (default the PSTricks default (0.8 pt)).

Value

The updated PSTricks object.

See Also

[pplinewidth\(\)](#) for the base version and [geom_set\(\)](#) for an example.

geom_polygon	<i>Draw Polygons</i>
--------------	----------------------

Description

Draw Polygons

Usage

```
geom_polygon(
  p,
  mapping = NULL,
  data = NULL,
  par = NULL,
  dodge = 0,
  star = FALSE
)
```

Arguments

p	The PStricks object.
mapping	Aesthetic mapping from column names to x and y.
data	Data frame with coordinates of the observations.
par	PStricks parameter string.
dodge	Horizontal offset.
star	Flag to indicate starred version.

Value

The updated PStricks object.

See Also

[pspolygon\(\)](#) for the base version.

Examples

```
PStricks() %>%
  geom_polygon(data=data.frame(x=c(0,0,1),y=c(0,2,2)),par="linewidth=1.5pt") %>%
  geom_polygon(data=data.frame(x=c(1,1,4,4),y=c(0,2,0,2)),par="linearc=.2",star=TRUE)
# Note that the first coordinate (0,0) for the first polygon has to be given explicitly
```

geom_rput

Add Text Items

Description

Add Text Items

Usage

```
geom_rput(
  p,
  mapping = NULL,
  data = NULL,
  refpoint = NULL,
  rotation = NULL,
  dodge = 0,
  star = FALSE
)
```

Arguments

p	The PStricks object.
mapping	Aesthetic mapping from column names to x and y.
data	Data frame with coordinates of the observations.
refpoint	The reference point for the stuff.
rotation	Rotation to apply to the stuff.
dodge	Horizontal offset.
star	Flag to indicate starred version (but see geom_framebox()).

Value

The updated PStricks object.

See Also

[rput\(\)](#) for the base version.

Examples

```
geom_rput(PStricks(),
  aes(x=wt,y=mpg,stuff=stuff),
  cbind(mtcars,stuff=row.names(mtcars)),
  rotation=45,
  star=TRUE)
```

geom_set	<i>Set PStricks Parameter(s) during Geom Processing</i>
----------	---

Description

Set PStricks Parameter(s) during Geom Processing

Usage

```
geom_set(p, par)
```

Arguments

p	The PStricks object.
par	PStricks (comma separated) parameter(s).

Value

The updated PStricks object.

See Also

[psset\(\)](#) for the base version.

Examples

```
mtcars<-cbind(mtcars,stuff=row.names(mtcars));
PSTricks() %>%
  pppicture(16,26) %>%
# the following three commands affect the axes
  psset("arrows=c-c") %>%
  pplinewidth(.3) %>%
  everypsbox("\\large") %>%
# the following three commands affect the frameboxes
  geom_set("framearc=.3,fillstyle=solid,fillcolor=darkgray") %>%
  geom_linewidth(.1) %>%
  geom_everypsbox("\\green") %>%
  geom_framebox(aes(x=wt,y=mpg),mtcars[mtcars$cyl==4,]) %>%
  geom_linewidth(.3) %>%
  geom_everypsbox("\\cyan") %>%
  geom_framebox(aes(x=wt,y=mpg),mtcars[mtcars$cyl==6,]) %>%
  geom_linewidth(.5) %>%
  geom_everypsbox("\\red") %>%
  geom_framebox(aes(x=wt,y=mpg),mtcars[mtcars$cyl==8,]) %>%
  lims(c(1,6),c(10,35)) %>%
  labs("Weight (lb/1000)","Fuel efficiency (miles/gallon)") %>%
  pplegend("4 cylinders",par="linecolor=green",dx=-3) %>%
  pplegend("6 cylinders",par="linecolor=cyan",dx=-3,dy=-.5) %>%
  pplegend("8 cylinders",par="linecolor=red",dx=-3,dy=-1)
```

geom_uput

Add Text Items

Description

Add Text Items

Usage

```
geom_uput(
  p,
  mapping = NULL,
  data = NULL,
  refangle = NULL,
  rotation = NULL,
  labelsep = NULL,
  dodge = 0,
  star = FALSE
)
```

Arguments

p	The PStricks object.
mapping	Aesthetic mapping from column names to x and y.
data	Data frame with coordinates of the observations.
refangle	The reference angle.
rotation	Rotation to apply to the stuff.
labelsep	Distance between coordinates and the stuff.
dodge	Horizontal offset.
star	Flag to indicate starred version.

Value

The updated PStricks object.

See Also

[uput\(\)](#) for the base version.

Examples

```
geom_uput(PStricks(),
  aes(x=wt,y=mpg,stuff=stuff),
  cbind(mtcars,stuff=row.names(mtcars)),
  refangle=0,
  rotation=45,
  star=TRUE)
```

geom_vline	<i>Draw Vertical Line</i>
------------	---------------------------

Description

Draw Vertical Line

Usage

```
geom_vline(p, xintercept = 0, par = NULL)
```

Arguments

p	The PStricks object.
xintercept	The x-intercept of the line.
par	PStricks parameter string.

Value

The updated PStricks object.

See Also

[geom_abline\(\)](#) for an example.

 icx

Convert Scaled x Values to Unscaled

Description

Convert Scaled x Values to Unscaled

Usage

```
icx(p, x, logx = NULL)
```

Arguments

p	The PStricks object.
x	Scaled data.
logx	Flag to request log(10) transformation.

Value

Unscaled data.

 icy

Convert Scaled y Values to Unscaled

Description

Convert Scaled y Values to Unscaled

Usage

```
icy(p, y, logy = NULL)
```

Arguments

p	The PStricks object.
y	Scaled data.
logy	Flag to request log(10) transformation.

Value

Unscaled data.

labs	<i>Set Axis Labels and Title</i>
------	----------------------------------

Description

Set Axis Labels and Title

Usage

```
labs(p, x, y, title = NULL)
```

Arguments

p	The PStricks object.
x, y	x and y axis labels.
title	The title for the plot.

Value

The updated PStricks object.

See Also

[geom_set\(\)](#) for an example.

lims	<i>Set x and y Axes Limits</i>
------	--------------------------------

Description

Set x and y Axes Limits

Usage

```
lims(p, x = NULL, y = NULL)
```

Arguments

p	The PStricks object.
x, y	x and y lower and upper axis limits (two-element lists or NULL for automatic).

Value

The updated PStricks object.

See Also

[geom_set\(\)](#) for an example.

MakeShortNab

Define Short Form Characters

Description

Define Short Form Characters

Usage

MakeShortNab(p = NULL, char1, char2)

Arguments

p	The PSTricks object.
char1	Short form character for naput.
char2	Short form character for nbput.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  cnode(0,4,".5cm","root") %>%
  cnode(3,5.5,"4pt","A",star=TRUE) %>%
  cnode(3,2.5,"4pt","C",star=TRUE) %>%
  psset("nodesep=3pt,shortput=nab") %>%
  MakeShortNab("+","-") %>%
  ppappend(paste0(ncline("root","A"),"+{xx$}") %>%
  ppappend(paste0(ncline("root","C"),"-{yy$}")
# so short forms are not elegantly implemented
```

MakeShortTablr

Define Short Form Characters

Description

Define Short Form Characters

Usage

MakeShortTablr(p = NULL, char1, char2, char3, char4)

Arguments

p	The PStricks object.
char1	Short form character for taput.
char2	Short form character for tbput.
char3	Short form character for tlput.
char4	Short form character for trput.

Value

The updated PStricks object.

See Also

See [MakeShortNab\(\)](#) for how to use short forms.

merge.list

Merge Two Lists

Description

Merge Two Lists

Usage

```
## S3 method for class 'list'
merge(x, y, ...)
```

Arguments

x	The first list.
y	The second list, used to add missing elements in the first list.
...	Not used.

Value

The merged lists.

Examples

```
merge(list(a=3,b=4),list(a=30,c=40))
```

multirput*Put Copies of Stuff*

Description

Put Copies of Stuff

Usage

```
multirput(  
  p = NULL,  
  x,  
  y,  
  n,  
  stuff,  
  angle = NULL,  
  refpoint = NULL,  
  star = FALSE  
)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the stuff.
n	Number of copies.
stuff	Stuff to put at the reference point.
angle	Angle for the copies.
refpoint	The reference point for the stuff.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),3,3) %>%  
  multirput(c(.5,.3),c(0,.1),12,'*')
```

naput	<i>Put Label above Line</i>
-------	-----------------------------

Description

Put Label above Line

Usage

```
naput(p = NULL, stuff, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
stuff	The label to put on the line.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

See Also

[ncput\(\)](#) for an example.

nbput	<i>Put Label below Line</i>
-------	-----------------------------

Description

Put Label below Line

Usage

```
nbput(p = NULL, stuff, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
stuff	The label to put on the line.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

See Also

`ncput()` for an example.

ncangle

Draw Line Segments Between Two Nodes

Description

Draw Line Segments Between Two Nodes

Usage

```
ncangle(p = NULL, nodeA, nodeB, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

<code>p</code>	The PSTricks object.
<code>nodeA, nodeB</code>	Names of the nodes.
<code>par</code>	PSTricks parameter string.
<code>arrows</code>	Arrows at the end of the coil.
<code>star</code>	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  rput(0,3,rnode("A",psframebox("Node A")), "tl") %>%
  rput(4,0,ovalnode("B", "Node B"), "br") %>%
  ncangle("A", "B", "angleA=-90,angleB=90,armB=1cm")
```

ncangles

Draw Line Segments Between Two Nodes

Description

Draw Line Segments Between Two Nodes

Usage

```
ncangles(p = NULL, nodeA, nodeB, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
nodeA, nodeB	Names of the nodes.
par	PSTricks parameter string.
arrows	Arrows at the end of the coil.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  rput(0,4,rnode("A",psframebox("Node A")), "tl") %>%
  rput(4,0,ovalnode("B", "Node B"), "br") %>%
  ncangles("A", "B", "angleA=-90, armA=1cm, armB=.5cm, linearc=.15")
```

ncarc

Draw an Arc Between Two Nodes

Description

Draw an Arc Between Two Nodes

Usage

```
ncarc(p = NULL, nodeA, nodeB, par = NULL, arrows = NULL, star = FALSE)
```


Arguments

p	The PSTricks object.
nodeA, nodeB	Names of the nodes.
par	PSTricks parameter string.
arrows	Arrows at the end of the coil.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  cnodeput(0,0,"A","X") %>%
  cnodeput(3,2,"B","Y") %>%
  psset("nodesep=3pt") %>%
  ncarc("A","B",arrows="->") %>%
  ncarc("B","A",arrows="->")
```

ncarcbox

Enclose Two Nodes in Curved Box

Description

Enclose Two Nodes in Curved Box

Usage

```
ncarcbox(p = NULL, nodeA, nodeB, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
nodeA, nodeB	Names of the nodes.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  rput(.5,0,rnode(,"A","1"),"b1") %>%
  rput(3.5,2,rnode(,"B","2"),"tr") %>%
  ncarcbox("A","B",nodesep=.2cm,boxsize=.4,linear=.4,arcangle=50")
```

ncbar

Draw Line Segments Between Two Nodes

Description

Draw Line Segments Between Two Nodes

Usage

```
ncbar(p = NULL, nodeA, nodeB, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
nodeA, nodeB	Names of the nodes.
par	PSTricks parameter string.
arrows	Arrows at the end of the coil.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  rput(8,4,paste0(rnode("A","Connect")," some ",rnode("B","words"),"!!")) %>%
  ncbar("A","B","nodesep=3pt,angle=-90","<-**") %>%
  ncbar("A","B","nodesep=3pt,angle=70")
```

ncbox

Enclose Two Nodes in a Box

Description

Enclose Two Nodes in a Box

Usage

```
ncbox(p = NULL, nodeA, nodeB, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
nodeA, nodeB	Names of the nodes.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  rput(.5,0,rnode("A","Idea 1"),"bl") %>%
  rput(3.5,2,rnode("B","Idea 2"),"tr") %>%
  ncbox("A","B","nodesep=.5cm,boxsize=.6,linear=.2,linestyle=dashed")
```

nccircle	<i>Draw a Circle between a Node and Itself</i>
----------	--

Description

Draw a Circle between a Node and Itself

Usage

```
nccircle(p = NULL, node, radius, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
node	Name of the node.
radius	Radius of the circle.
par	PSTricks parameter string.
arrows	Arrows at the end of the coil.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  rnode("A","\\textbf{back}") %>%
  nccircle("A",".7cm","nodesep=3pt","->")
```

nccoil	<i>Draw a Coil between two Nodes</i>
--------	--------------------------------------

Description

Draw a Coil between two Nodes

Usage

```
nccoil(p = NULL, nodeA, nodeB, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
nodeA, nodeB	Names of the nodes.
par	PSTricks parameter string.
arrows	Arrows at the end of the coil.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-coil"),c(-1,5),c(-1,4),par="showgrid=true") %>%
  cnode(.5,.5,.5,"A") %>%
  cnode(3.5,2.5,.5,"B","fillstyle=solid,fillcolor=lightgray") %>%
  nccoil("A","B","coilwidth=.3","<->")
# Note that the `pst-node` macro package does not have to be specified.
```

nccurve	<i>Draw a Bezier Curve between Two Nodes</i>
---------	--

Description

Draw a Bezier Curve between Two Nodes

Usage

```
nccurve(p = NULL, nodeA, nodeB, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
nodeA, nodeB	Names of the nodes.
par	PSTricks parameter string.
arrows	Arrows at the end of the coil.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  rput(0,0,rnode("A",psframebox("Node A")), "bl") %>%
  rput(4,3,ovalnode("B", "Node B"), "tr") %>%
  nccurve("A", "B", "angleB=180")
```

ncdiag

*Draw Line Segments Between Two Nodes***Description**

Draw Line Segments Between Two Nodes

Usage

```
ncdiag(p = NULL, nodeA, nodeB, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
nodeA, nodeB	Names of the nodes.
par	PSTricks parameter string.
arrows	Arrows at the end of the coil.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  rput(0,3,rnode("A",psframebox("Node A")), "tl") %>%
  rput(4,0,ovalnode("B", "Node B"), "br") %>%
  ncdiag("A", "B", "angleA=-90,angleB=90,arm=.5,linear=.2")
```

ncdiag

Draw Line Segments Between Two Nodes

Description

Draw Line Segments Between Two Nodes

Usage

```
ncdiag(p = NULL, nodeA, nodeB, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
nodeA, nodeB	Names of the nodes.
par	PSTricks parameter string.
arrows	Arrows at the end of the coil.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  cnode(0,4,"12pt","a") %>%
  rput(3,5,rnode("b","H"),"1") %>%
  rput(3,3,rnode("c","T"),"1") %>%
  ncdiagg("b","a","angleA=180,armA=1.5,nodesepA=3pt") %>%
  ncdiag("c","a","angleA=180,armA=1.5,armB=0,nodesepA=3pt")
```

ncline

Draw a Line Between Two Nodes

Description

Draw a Line Between Two Nodes

Usage

```
ncline(p = NULL, nodeA, nodeB, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
nodeA, nodeB	Names of the nodes.
par	PSTricks parameter string.
arrows	Arrows at the end of the coil.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  rput(0,0,rnode("A","Idea 1"),"bl") %>%
  rput(4,3,rnode("B","Idea 2"),"tr") %>%
  ncline("A","B","nodesep=3pt","<->")
```

ncloop

Draw Line Segments Between a Node and Itself

Description

Draw Line Segments Between a Node and Itself

Usage

```
ncloop(p = NULL, nodeA, nodeB, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
nodeA, nodeB	Names of the node.
par	PSTricks parameter string.
arrows	Arrows at the end of the coil.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  rnode("a",psframebox("Huge A loop")) %>%
  ncloop("a","a","angleB=180,loopsize=1,arm=.5,linear=.2","->")
```

ncput

Put Label on Line

Description

Put Label on Line

Usage

```
ncput(p = NULL, stuff, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
stuff	The label to put on the line.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  cnode(0,4,".5cm","root") %>%
  cnode(3,5.5,"4pt","A",star=TRUE) %>%
  cnode(3,4,"4pt","B",star=TRUE) %>%
  cnode(3,2.5,"4pt","C",star=TRUE) %>%
  psset("nodesep=3pt") %>%
  ncline("root","A") %>%
  nput("above") %>%
  ncline("root","B") %>%
  ncput("on",star=TRUE) %>%
  ncline("root","C") %>%
  nbput("below")
```

nczigzag

Draw a Zigzag between two Nodes

Description

Draw a Zigzag between two Nodes

Usage

```
nczigzag(p = NULL, nodeA, nodeB, par = NULL, arrows = NULL, star = FALSE)
```


Arguments

p	The PSTricks object.
nodeA, nodeB	Names of the nodes.
par	PSTricks parameter string.
arrows	Arrows at the end of the zigzag.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-coil"),c(-1,5),c(-1,4),par="showgrid=true") %>%
  cnode(.5,.5,.5,"A") %>%
  cnode(3.5,2.5,.5,"B","fillstyle=solid,fillcolor=lightgray") %>%
  nczigzag("A","B","coilarm=.5,linear=.1","<->")
```

newcmymcolor

Define New CMYK Color

Description

Define New CMYK Color

Usage

```
newcmymcolor(p = NULL, color, num1, num2, num3, num4)
```

Arguments

p	The PSTricks object.
color	The name of the new color.
num1, num2, num3, num4	The cyan-magenta-yellow-black specification (between 0 and 1).

Value

The updated PSTricks object.

Examples

```
newcmymcolor(,"mycolor",0.1,0.2,0.3,0.4)
```

newgray	<i>Define New Gray Scale</i>
---------	------------------------------

Description

Define New Gray Scale

Usage

```
newgray(p = NULL, color, num)
```

Arguments

p	The PStricks object.
color	The name of the new gray scale.
num	The scale value (0 is black and 1 is white).

Value

The updated PStricks object.

Examples

```
newgray("gray10",0.1)
```

newhsbcolor	<i>Define New HSB Color</i>
-------------	-----------------------------

Description

Define New HSB Color

Usage

```
newhsbcolor(p = NULL, color, num1, num2, num3)
```

Arguments

p	The PStricks object.
color	The name of the new color.
num1, num2, num3	The hue-saturation-brightness specification (between 0 and 1).

Value

The updated PStricks object.

Examples

```
newhsbcolor("mycolor",0.1,0.2,0.3)
```

newrgbcolor	<i>Define New RGB Color</i>
-------------	-----------------------------

Description

Define New RGB Color

Usage

```
newrgbcolor(p = NULL, color, num1, num2, num3)
```

Arguments

p	The PStricks object.
color	The name of the new color.
num1, num2, num3	The red-green-blue specification (0 is dark and 1 is light).

Value

The updated PStricks object.

Examples

```
newrgbcolor("mycolor",0.1,0.2,0.3)
```

nput	<i>Attach Label to Node</i>
------	-----------------------------

Description

Attach Label to Node

Usage

```
nput(p = NULL, name, stuff, par = NULL, refangle, star = FALSE)
```

Arguments

p	The PSTricks object.
name	The name of the node.
stuff	The label to put on the line.
par	PSTricks parameter string.
refangle	The reference angle (see <code>uput()</code>).
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  rput(4,0,ovalnode("B","Node B"),"br") %>%
  rput(0,3,rnode("A",psframebox("Node A")), "tl") %>%
  nput("A",paste0(psarcn(,0,0,".4cm",0,-70),
    uput(,0,0,"\\texttt{angleA}",-35,labelsep=".4cm")), "labelsep=0",-70) %>%
  ncangle("A","B","angleA=-70,angleB=90,armB=1cm,linewidth=1.2pt") %>%
  ncput(psframe(c(0,.35),c(0,.35),"dimen=middle"),"nrot=:U,npos=1")
```

ovalnode	<i>Put Stuff in an Oval</i>
----------	-----------------------------

Description

Put Stuff in an Oval

Usage

```
ovalnode(p = NULL, name, stuff, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
name	The name of the node.
stuff	Stuff to put in a box at the node.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  rput(8,4,paste(circlenode("A","Circle"),"and",ovalnode("B","Oval"))) %>%
  ncbat("A","B","angle=90")
```

parabola	<i>Draw PSTricks Parabola</i>
----------	-------------------------------

Description

Draw PSTricks Parabola

Usage

```
parabola(p = NULL, x, y, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the parabola.
par	PSTricks parameter string.
arrows	Arrows at the end of the line.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),4,3,par="showgrid=true") %>%
  parabola(c(1,2), c(1,3), star=TRUE) %>%
  psset("xunit=.01") %>%
  parabola(c(400,200),c(3,0),arrows="<->")
```

pcangle

Draw Line Segments Between Two Nodes

Description

Draw Line Segments Between Two Nodes

Usage

```
pcangle(p = NULL, x, y, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates or names of the nodes.
par	PSTricks parameter string.
arrows	Arrows at the end of the line.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  pcangle(c(3,6),c(4,9))
```

pcangles

Draw Line Segments Between Two Nodes

Description

Draw Line Segments Between Two Nodes

Usage

```
pcangles(p = NULL, x, y, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates or names of the nodes.
par	PSTricks parameter string.
arrows	Arrows at the end of the line.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  pcangles(c(3,6),c(4,9))
```

pcarc

Draw an Arc Between Two Nodes

Description

Draw an Arc Between Two Nodes

Usage

```
pcarc(p = NULL, x, y, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates or names of the nodes.
par	PSTricks parameter string.
arrows	Arrows at the end of the line.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  pcarc(c(3,6),c(4,9))
```

pccrbox

Enclose Two Nodes in Curved Box

Description

Enclose Two Nodes in Curved Box

Usage

pccrbox(p = NULL, x, y, par = NULL, star = FALSE)

Arguments

p	The PSTricks object.
x, y	Coordinates or names of the nodes.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  pccrbox(c(3,6),c(4,9))
```

pbar

Draw Line Segments Between Two Nodes

Description

Draw Line Segments Between Two Nodes

Usage

pbar(p = NULL, x, y, par = NULL, arrows = NULL, star = FALSE)

Arguments

p	The PSTricks object.
x, y	Coordinates or names of the nodes.
par	PSTricks parameter string.
arrows	Arrows at the end of the line.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  pcbar(c(3,6),c(4,9))
```

pcbox

Enclose Two Nodes in a Box

Description

Enclose Two Nodes in a Box

Usage

```
pcbox(p = NULL, x, y, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates or names of the nodes.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  pcbox(c(3,6),c(4,9))
```

pccoil	<i>Draw a Coil between two Nodes</i>
--------	--------------------------------------

Description

Draw a Coil between two Nodes

Usage

```
pccoil(p = NULL, x, y, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates or names of the nodes.
par	PSTricks parameter string.
arrows	Arrows at the end of the coil.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-coil"),4,3,par="showgrid=true") %>%
  pccoil(c(.5,3.5),c(.5,2.5),"coilwidth=.3","<->")
```

pccurve	<i>Draw a Bezier Curve Between Two Nodes</i>
---------	--

Description

Draw a Bezier Curve Between Two Nodes

Usage

```
pccurve(p = NULL, x, y, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates or names of the nodes.
par	PSTricks parameter string.
arrows	Arrows at the end of the line.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  pccurve(c(3,6),c(4,9))
```

pcdiag

Draw Line Segments Between Two Nodes

Description

Draw Line Segments Between Two Nodes

Usage

```
pcdiag(p = NULL, x, y, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates or names of the nodes.
par	PSTricks parameter string.
arrows	Arrows at the end of the line.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  pcdiag(c(3,6),c(4,9))
```

pcdiagg	<i>Draw Line Segments Between Two Nodes</i>
---------	---

Description

Draw Line Segments Between Two Nodes

Usage

```
pcdiagg(p = NULL, x, y, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates or names of the nodes.
par	PSTricks parameter string.
arrows	Arrows at the end of the line.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  pcdiagg(c(3,6),c(4,9))
```

pcline	<i>Draw a Line Between Two Nodes</i>
--------	--------------------------------------

Description

Draw a Line Between Two Nodes

Usage

```
pcline(p = NULL, x, y, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the line segment.
par	PSTricks parameter string.
arrows	Arrows at the end of the line.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  pcline(c(3,6),c(4,9))
```

pcloop

Draw Line Segments Between a Node and Itself

Description

Draw Line Segments Between a Node and Itself

Usage

```
pcloop(p = NULL, x, y, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates or Name of the Node.
par	PSTricks parameter string.
arrows	Arrows at the end of the line.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  pcloop(c(3,6),c(4,9))
```

pczigzag	<i>Draw a Zigzag between two Nodes</i>
----------	--

Description

Draw a Zigzag between two Nodes

Usage

```
pczigzag(p = NULL, x, y, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates or names of the nodes.
par	PSTricks parameter string.
arrows	Arrows at the end of the zigzag.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-coil"),4,3,par="showgrid=true") %>%
  pczigzag(c(.5,3.5),c(.5,2.5),"coilarm=.5,linear=.1","<->")
```

pnode	<i>Create Zero-dimensional Node</i>
-------	-------------------------------------

Description

Create Zero-dimensional Node

Usage

```
pnode(p = NULL, x = NULL, y = NULL, name)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the node.
name	The name of the node.

Value

The updated PStricks object.

See Also

[cnode\(\)](#) for an example.

ppappend

Append Line to Lines Attribute in the PStricks Object

Description

Append Line to Lines Attribute in the PStricks Object

Usage

ppappend(p, s)

Arguments

p	The PStricks object.
s	The string to append.

Value

The updated PStricks object.

pparg

Construct pstricks Argument

Description

Construct pstricks Argument

Usage

pparg(arg = NULL)

Arguments

arg	Argument.
-----	-----------

Value

Argument string (using curly braces), or empty string if arg is NULL.

ppaxis

*Draw an X or Y Axis***Description**

Draw an X or Y Axis

Usage

```
ppaxis(
  p,
  xory,
  lims,
  label = "label",
  labsep = NULL,
  secondary = FALSE,
  noshow = FALSE
)
```

Arguments

p	The PStricks object.
xory	A character 'x' or 'y' designating which axis to draw.
lims	A vector with two elements, the minimum and maximum values for the axis.
label	The label to show at the middle of the axis.
labsep	The distance between the tickmark labels and the label.
secondary	A flag to indicate that a secondary (at the other side) axis should be drawn.
noshow	A flag to indicate that values should be scaled with respect to the axis, but that the axis should not be drawn.

Value

The updated PStricks object, with attributes xtpos and ytpos added for ppgrid().

Examples

```
p <- pppicture(PStricks(),16,9) %>%
  ppticks('x',6,3) %>%
  ppticks('y',6,4) %>%
  ppaxis('x',c(1,6),"wt") %>%
  ppaxis('y',c(10,35),"mpg") ;
  psdots(p,cx(p,mtcars$wt),cy(p,mtcars$mpg))
# Note that p has to have valid axes before using `cx()` or `cy()`
```


ppbuild

*Construct pstricks Macro Command***Description**

Construct pstricks Macro Command

Usage

```
ppbuild(
  psname,
  x = NULL,
  y = NULL,
  opt = NULL,
  arg = NULL,
  arg1 = NULL,
  arg2 = NULL,
  arg3 = NULL,
  arg4 = NULL,
  arg0 = NULL,
  star = FALSE,
  p = NULL
)
```

Arguments

psname	The name of the macro command to construct.
x, y	Coordinates.
opt	Optional parameters.
arg, arg1, arg2, arg3, arg4, arg0	Arguments.
star	Flag to indicate starred version.
p	The PSTricks object.

Value

The string or an updated PSTricks object.

Examples

```
ppbuild("ppbuild",1,2,"opt","arg","arg1","arg2","arg3","arg4","arg0",TRUE)
```

ppbuild3D

Construct pstricks Macro Command

Description

Construct pstricks Macro Command

Usage

```
ppbuild3D(
  psname,
  x = NULL,
  y = NULL,
  z = NULL,
  opt = NULL,
  arg = NULL,
  arg1 = NULL,
  arg2 = NULL,
  arg3 = NULL,
  arg4 = NULL,
  arg0 = NULL,
  star = FALSE,
  p = NULL
)
```

Arguments

psname	The name of the macro command to construct.
x, y, z	Coordinates.
opt	Optional parameters.
arg, arg1, arg2, arg3, arg4, arg0	Arguments.
star	Flag to indicate starred version.
p	The PSTricks object.

Value

The string or an updated PSTricks object.

Examples

```
ppbuild3D("ppbuild3D",1,2,3,"opt","arg","arg1","arg2","arg3","arg4","arg0",TRUE)
```

ppclosedoc	<i>Close the LaTeX Document</i>
------------	---------------------------------

Description

Adds a line to the `p` object to finish a self-contained LaTeX document. While this function is exported, it is called automatically when necessary.

Usage

```
ppclosedoc(p)
```

Arguments

<code>p</code>	The PStricks object.
----------------	----------------------

Value

The updated PStricks object.

Examples

```
p <- ppclosedoc(ppopendoc(PStricks()))
```

ppcoords	<i>Construct pstricks Macro Coordinates</i>
----------	---

Description

Construct pstricks Macro Coordinates

Usage

```
ppcoords(p = NULL, x, y)
```

Arguments

<code>p</code>	The PStricks object.
<code>x, y</code>	Coordinates.

Value

Coordinates string (using parentheses), or empty string if `x` or `y` is `NULL`.

ppcoords3D	<i>Construct pstricks Macro Coordinates</i>
------------	---

Description

Construct pstricks Macro Coordinates

Usage

```
ppcoords3D(p = NULL, x, y, z)
```

Arguments

p	The PStricks object.
x, y, z	Coordinates.

Value

Coordinates string (using parentheses), or empty string if x or y or z is NULL.

ppdefpicture	<i>Open a Default Picture</i>
--------------	-------------------------------

Description

Open a Default Picture

Usage

```
ppdefpicture(p)
```

Arguments

p	The PStricks object.
---	----------------------

Details

Used by geoms if no picture has been opened.

Value

The updated PStricks object.

ppgeoms

*Process Geoms***Description**

Process Geoms

Usage

ppgeoms(p)

Arguments

p The PStricks object.

Details

ppgeoms() is called automatically when the current subplot is closed. The example given below shows an instance where it is necessary to call it explicitly.

Value

The updated PStricks object.

Examples

```
pppicture(PStricks(),16,9,data=mtcars) %>%
  geom_dots(aes(x=wt,y=mpg),par="linecolor=green") %>%
  ppgeoms() %>%
  ppsetsecondary('y') %>%
  geom_dots(aes(x=wt,y=cyl),par="linecolor=blue")
```

ppgrid

*Draw Grid Lines***Description**

Draw Grid Lines

Usage

ppgrid(p, par = "linestyle=dotted", background = NULL)

Arguments

p The PStricks object.
 par PStricks parameters.
 background The optional background color.

Details

Axes should be drawn before a grid. Issue: with "linestyle=dotted" multiple dots are drawn at identical locations.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),16,9) %>%
  newrgbcolor("verylightgray",.9,.9,.9) %>%
  ppsetmargins(mrgaxes=0) %>%
  ppaxis('x',c(0,1)) %>%
  ppaxis('y',c(0,1)) %>%
  ppgrid("linestyle=dotted,linecolor=gray",background="verylightgray")
```

pplgend

Add Legend to Plot

Description

Add Legend to Plot

Usage

```
pplgend(
  p,
  s,
  par = NULL,
  position = "tr",
  dx = 0,
  dy = 0,
  w = 1,
  labelsep = "10pt"
)
```

Arguments

p	The PSTricks object.
s	The legend text.
par	PSTricks parameter string.
position	Position for the legend (may be NULL).
dx, dy	x and y offsets w.r.t. default position.
w	Width of the <code>psline()</code> that belongs to the legend text.
labelsep	The distance between the line and the label.

Value

The updated PStricks object.

Examples

```
p <- pppicture(PStricks(),16,9) %>%
  ppaxis('x',c(0,1)) %>%
  ppaxis('y',c(0,1)) ;
p <- p %>%
  psset("linecolor=green,showpoints=true") %>%
  psline(cx(p,seq(0,1,0.2)),cy(p,rep(0.5,5))) %>%
  pplegend("top right")
```

pplinewidth

*Set Line Width***Description**

Set Line Width

Usage

```
pplinewidth(p, linewidth)
```

Arguments

p	The PStricks object.
linewidth	The new default line width in mm.

Details

Parameter linewidth is a special one because it is needed at some places for proper alignment (`geom_frame()`, `geom_hist()`, `ppgrid()`, `pplegend()`, `cx()`, `cy()`, `endP2E()`).

Value

The updated PStricks object.

See Also

[geom_set\(\)](#) for an example.

ppmansubplot	<i>Set Parameters of Subplot Manually</i>
--------------	---

Description

Set Parameters of Subplot Manually

Usage

```
ppmansubplot(p, x0, y0, hx, hy, ntitle = 1)
```

Arguments

p	The PStricks object.
x0	The reference position of the x axis.
y0	The reference position of the y axis.
hx	The length of the x axis.
hy	The length of the y axis.
ntitle	Number of lines to reserve for the title.

Value

The updated PStricks object.

See Also

[adjx0y0\(\)](#) to get axis positions.

Examples

```
pppicture(PStricks(),20,28,par="showgrid=true") %>% ppmansubplot(2,2,8,6) %>%
  ppaxis('x',c(0,1)) %>% ppaxis('y',c(0,1)) %>% pptitle("title")
# note that (x0,y0) is the reference position, not where the axes start
```

ppnewpage	<i>Close the Current Picture and Open a New One</i>
-----------	---

Description

Close the Current Picture and Open a New One

Usage

```
ppnewpage(p)
```


Arguments

p The PSTricks object.

Details

Lower level option values will be reset, but higher level options will not.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(engine="latex"),16,9, data=mtcars, par="showgrid=true") %>%
  geom_dots(aes(x=wt,y=mpg)) %>%
  pptitle("\\Large picture 1") %>%
  ppnewpage() %>%
  geom_dots(aes(x=wt,y=cyl)) %>%
  pptitle("\\Large picture 2")
# Engine pdflatex gives one page...
```

ppnewrgbcolor	<i>Define New RGB Color(s) from R Color Specification(s)</i>
---------------	--

Description

Define New RGB Color(s) from R Color Specification(s)

Usage

```
ppnewrgbcolor(p = NULL, names, values = NULL)
```

Arguments

p The PSTricks object.
 names R color names.
 values Color values to parse.

Value

The updated PSTricks object.

Examples

```
ppnewrgbcolor(,"blue") # p=NULL works for one color only
```

ppopendoc*Open the LaTeX Document*

Description

Adds lines to the p object to start a self-contained LaTeX document. While this function is exported, it is called automatically when necessary.

Usage

```
ppopendoc(p)
```

Arguments

p The PSTricks object.

Value

The updated PSTricks object.

Examples

```
p <- ppopendoc(PSTricks())
```

ppopt*Construct psticks Option*

Description

Construct psticks Option

Usage

```
ppopt(opt = NULL)
```

Arguments

opt Option.

Value

Option string (using brackets), or empty string if arg is NULL.

pppicture

*Open a Picture and Prepare for using PSTricks Functions***Description**

Open a Picture and Prepare for using PSTricks Functions

Usage

```
pppicture(
  p,
  x = NULL,
  y = NULL,
  data = NULL,
  mapping = NULL,
  par = NULL,
  star = FALSE
)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of upper right corner (and optionally lower left corner).
data	Data to use with geoms.
mapping	Mapping to use with geoms.
par	Parameters for the underlying pspicture macro (see Voss' latest documentation).
star	Flag to indicate that objects should be clipped with respect to the boundaries.

Details

pppicture is not called pspicture because of the large difference in functionality. It is not needed for using PSTricks package per se (as in LaTeX itself). Most examples use pppicture().

Value

The updated PSTricks object with initial default values for the attributes

- datnam - Name of the data for reference.
- data - Data for geoms.
- mapping - Mapping for geoms.
- geoms - List of called geoms.
- xlim,ylim - Range of x and y data.
- xlab,ylab - Labels for the x and y axes.

- xlabsep,ylabsep - Distance between tickmark and axes labels.
- xa,xb,ya,yb - Scaling conversion parameters.
- xticks - See below.
- yticks - See below.
- logx,logy - Flags to indicate logarithmic x and/or y axes.
- secondx,secondy - Flags to indicate secondary x and/or y axes.
- pxad,pyad,sxad,syad - Flags to indicate which axes have been drawn.
- margin - Parameter that determines the layout of a graph.
- mrgaxes - A factor for the margins between the axes.
- polar - Flag to indicate whether coordinates should be interpreted as polar.
- degrees - The number of units in a circle.
- linewidth - The default line width in cm.
- picpar - Parameters saved for a possible subsequent pspicture with ppnewpage().
- psttoeps - Flag to indicate that the PSTtoEPS feature should be used with geoms.

xticks and yticks are lists with the items

- nticks - Number of tickmarks; if nticks=0, pretty tickmarks will be determined automatically.
- mticks - Number of minor tickmarks.
- nolabels - Flag to indicate that no labels should be printed.
- extlabs - Flag to indicate that labels at axis extrema should be printed.
- labels - List of labels instead of numbers to print at the tickmarks.
- ticklength - The length of the ticks.
- ticklengthi - The inward length of the ticks (default same as outward).
- rotation - The rotation for the labels at the tickmarks.

See Also

See [tvput\(\)](#) for a rare example where pppicture() is not used. And see [pspicture\(\)](#) for the lower level function.

ppsetcartesian

Set Interpretation of Coordinates to Cartesian

Description

Set Interpretation of Coordinates to Cartesian

Usage

ppsetcartesian(p)

Arguments

p The PSTricks object.

Value

The updated PSTricks object.

See Also

[ppsetpolar\(\)](#).

ppsetlogx	<i>Set Flag to use Logarithmic X Axis</i>
-----------	---

Description

Set Flag to use Logarithmic X Axis

Usage

```
ppsetlogx(p, logx = TRUE)
```

Arguments

p The PSTricks object.
logx The flag.

Value

The updated PSTricks object.

ppsetlogxy	<i>Set Flags to use Logarithmic X and Y Axes</i>
------------	--

Description

Set Flags to use Logarithmic X and Y Axes

Usage

```
ppsetlogxy(p, logxy = TRUE)
```

Arguments

p The PSTricks object.
logxy The flag.

Value

The updated PSTricks object.

See Also

[geom_abline\(\)](#) for an example.

ppsetlogy	<i>Set Flag to use Logarithmic Y Axis</i>
-----------	---

Description

Set Flag to use Logarithmic Y Axis

Usage

```
ppsetlogy(p, logy = TRUE)
```

Arguments

p	The PSTricks object.
logy	The flag.

Value

The updated PSTricks object.

ppsetmargins	<i>Set Overall Margin</i>
--------------	---------------------------

Description

Set Overall Margin

Usage

```
ppsetmargins(p, margin = 1, mrgaxes = 1)
```

Arguments

p	The PSTricks object.
margin	Parameter that determines the layout of a graph.
mrgaxes	A factor for the margins between the axes.

Value

The updated PStricks object with respect to the attributes margin and mrgaxes.

See Also

[ppgrid\(\)](#) for an example.

ppsetnologx

Reset Flag to use Logarithmic X Axis

Description

Reset Flag to use Logarithmic X Axis

Usage

```
ppsetnologx(p)
```

Arguments

p The PStricks object.

Value

The updated PStricks object.

ppsetnologxy

Reset Flags to use Logarithmic X and Y Axes

Description

Reset Flags to use Logarithmic X and Y Axes

Usage

```
ppsetnologxy(p)
```

Arguments

p The PStricks object.

Value

The updated PStricks object.

ppsetnology

Reset Flag to use Logarithmic Y Axis

Description

Reset Flag to use Logarithmic Y Axis

Usage

ppsetnology(p)

Arguments

p The PStricks object.

Value

The updated PStricks object.

ppsetpolar

Set Interpretation of Coordinates to Polar

Description

Set Interpretation of Coordinates to Polar

Usage

ppsetpolar(p)

Arguments

p The PStricks object.

Value

The updated PStricks object.

See Also

[degrees\(\)](#) and [ppsetcartesian\(\)](#), and [psarcn\(\)](#) for an example.

ppsetprimary	<i>Set Flag to use Primary X or Y Axis</i>
--------------	--

Description

Set Flag to use Primary X or Y Axis

Usage

```
ppsetprimary(p, xory, secondary = FALSE)
```

Arguments

p	The PStricks object.
xory	A character 'x' or 'y' designating the axis.
secondary	The flag.

Value

The updated PStricks object.

ppsetprimaryx	<i>Set Flag to use Primary X Axis</i>
---------------	---------------------------------------

Description

Set Flag to use Primary X Axis

Usage

```
ppsetprimaryx(p, secondary = FALSE)
```

Arguments

p	The PStricks object.
secondary	The flag.

Value

The updated PStricks object.

ppsetprimaryy	<i>Set Flag to use Primary Y Axis</i>
---------------	---------------------------------------

Description

Set Flag to use Primary Y Axis

Usage

```
ppsetprimaryy(p, secondary = FALSE)
```

Arguments

p	The PStricks object.
secondary	The flag.

Value

The updated PStricks object.

ppsetpsttoeps	<i>Set Flag to use PSTtoEPS Feature</i>
---------------	---

Description

Set Flag to use PSTtoEPS Feature

Usage

```
ppsetpsttoeps(p, psttoeps = TRUE)
```

Arguments

p	The PStricks object.
psttoeps	A flag to indicate that the PSTtoEPS feature should be used with geoms.

Details

The PSTtoEPS feature is explained in the original manual in section 55. It may be used for efficient EPS file processing, in particular in cases where TeX's capacity becomes exceeded with many plotting commands. It is needed only for the "latex" engine; "xelatex" and "lualatex" do not handle it properly. The "pstpkg=pst-eps" must be used when creating the PStricks() object.

ppsetsecondary	<i>Set Flag to use Secondary X or Y Axis</i>
----------------	--

Description

Set Flag to use Secondary X or Y Axis

Usage

```
ppsetsecondary(p, xory, secondary = TRUE)
```

Arguments

p	The PSTricks object.
xory	A character 'x' or 'y' designating the axis.
secondary	The flag.

Value

The updated PSTricks object.

See Also

[ppgeoms\(\)](#) for an example.

ppsetsecondaryx	<i>Set Flag to use Secondary X Axis</i>
-----------------	---

Description

Set Flag to use Secondary X Axis

Usage

```
ppsetsecondaryx(p, secondary = TRUE)
```

Arguments

p	The PSTricks object.
secondary	The flag.

Value

The updated PSTricks object.

See Also

[ppgeoms\(\)](#) for an example.

ppsetsecondaryy	<i>Set Flag to use Secondary Y Axis</i>
-----------------	---

Description

Set Flag to use Secondary Y Axis

Usage

```
ppsetsecondaryy(p, secondary = TRUE)
```

Arguments

p	The PStricks object.
secondary	The flag.

Value

The updated PStricks object.

See Also

[ppgeoms\(\)](#) for an example.

ppsetxlabsep	<i>Set x label separation distance</i>
--------------	--

Description

Set x label separation distance

Usage

```
ppsetxlabsep(p, labsep = 0.7)
```

```
ppxlabsep(p, labsep = 0.7)
```

Arguments

p	The PStricks object.
labsep	The distance.

Value

The updated PStricks object.

See Also

[geom_line\(\)](#) to view the default distances.

Examples

```
geom_line(PSTricks(),data=data.frame(x=c(4,0,2),y=c(2,1,0)),
  par="linewidth=2pt,linearc=.25,arrows=->") %>%
  ppsetxlabsep(1.5) %>% ppsetylabsep(2)
```

ppsetylabsep	<i>Set y label separation distance</i>
--------------	--

Description

Set y label separation distance

Usage

```
ppsetylabsep(p, labsep = 1)
```

```
ppylabsep(p, labsep = 1)
```

Arguments

p	The PSTricks object.
labsep	The distance.

Value

The updated PSTricks object.

See Also

[ppsetxlabsep\(\)](#) for an example.

ppsubplot

*Divide the Picture in Subplots***Description**

Divide the Picture in Subplots

Usage

```
ppsubplot(
  p,
  nx = NULL,
  ny = NULL,
  n = NULL,
  nxaxes = 1,
  nyaxes = 1,
  ntitle = NULL,
  width = 1,
  height = 1,
  newpage = FALSE,
  data = NULL,
  mapping = NULL
)
```

Arguments

<code>p</code>	The PStricks object.
<code>nx</code>	Number of plots in the x direction (if NULL, increment n automatically).
<code>ny</code>	Number of plots in the y direction.
<code>n</code>	Number of current plot (by default 1 if nx and ny specified).
<code>nxaxes</code>	Number of x axes to make space for.
<code>nyaxes</code>	Number of y axes to make space for.
<code>ntitle</code>	Number of title lines to make space for.
<code>width</code>	Number of subplots to occupy in the x direction.
<code>height</code>	Number of subplots to occupy in the y direction.
<code>newpage</code>	Flag to skip remaining subplots for the current page and go to the next page.
<code>data</code>	Override earlier specified data (in pppicture or ppsubplot).
<code>mapping</code>	Override earlier specified mapping (in pppicture or ppsubplot).

Details

Subsequent coordinates are relative to (p\$x0,p\$y0), so possibly different from (0,0). Plot parameters such as limits, ticks, and labels are not reset to default values.

Value

The updated PStricks object, with respect to the attributes

- x0 - The position of the x axis.
- y0 - The position of the y axis.
- dx - The space allocated for the subplot in the x direction.
- dy - The space allocated for the subplot in the y direction.
- hx - The length of the x axis.
- hy - The length of the y axis.
- nx - Saved nx for subsequent subplots.
- ny - Saved ny for subsequent subplots.
- isub - Saved n for subsequent subplots.
- pxad - Flag to indicate that primary x axis has been drawn.
- pyad - Flag to indicate that primary y axis has been drawn.
- sxad - Flag to indicate that secondary x axis has been drawn.
- syad - Flag to indicate that secondary y axis has been drawn.

Examples

```
pppicture(PStricks(),data=mtcars) %>%
  ppsubplot(2,3,data=mtcars,mapping=aes(x=wt,y=mpg)) %>%
  geom_dots() %>%
  ppsubplot() %>%
  geom_dots(aes(x=wt,y=cyl))
```

ppticks

Define Major and Minor Tickmarks at X or Y Axis

Description

Define Major and Minor Tickmarks at X or Y Axis

Usage

```
ppticks(
  p,
  xory,
  nticks = 0,
  mticks = 0,
  nolabels = FALSE,
  extlabs = FALSE,
  labels = NULL,
  rotation = 0,
  ticklength = 0.2,
  ticklengthi = NULL
)
```

Arguments

<code>p</code>	The PStricks object.
<code>xory</code>	A character 'x' or 'y' designating which axis to draw.
<code>nticks</code>	Number of tickmarks; if <code>nticks=0</code> , pretty tickmarks will be determined automatically.
<code>mticks</code>	Number of minor tickmarks.
<code>nolabels</code>	Flag to indicate that no labels should be printed.
<code>extlabs</code>	Flag to indicate that labels at axis extrema should be printed (however labels cannot be used).
<code>labels</code>	List of labels instead of numbers to print at the tickmarks.
<code>rotation</code>	The rotation for the labels at the tickmarks.
<code>ticklength</code>	The length of the ticks.
<code>ticklengthi</code>	<ul style="list-style-type: none"> The inward length of the ticks (default same as outward).

Details

To be used with `ppaxis()`.

Value

The updated PStricks object.

See Also

[ppaxis\(\)](#) for an example.

<code>pptitle</code>	<i>Set Plot Title</i>
----------------------	-----------------------

Description

Set Plot Title

Usage

```
pptitle(p, title, dx = 0, dy = 0)
```

Arguments

<code>p</code>	The PStricks object.
<code>title</code>	The title.
<code>dx, dy</code>	Offset with respect to the default position (top left).

Details

The title is shown using `uput()`.

Value

The updated PSTricks object.

See Also

[ppmansubplot\(\)](#) for an example.

ppwrite

Write Assembled PSTricks Picture(s) to a File

Description

`ppwrite()` is used to write the assembled LaTeX document to a file. It does not return the PSTricks object, as it will no longer be useful (a new `PSTricks()` call is needed). `ppwrite` may be called automatically by R via `print(print.PSTricks)`.

Usage

```
ppwrite(
  p,
  filename = NULL,
  topdf = TRUE,
  crop = FALSE,
  topng = FALSE,
  dsf = 4,
  toeps = FALSE,
  clean = TRUE
)
```

Arguments

<code>p</code>	The PSTricks object.
<code>filename</code>	The name of the .tex file to write the document to (by default the name of the script, or "pp" when interactive).
<code>topdf</code>	Flag to specify if a .pdf should be generated by the engine as specified with <code>PSTricks()</code> .
<code>crop</code>	Flag if a cropped version with name <code>-crop.pdf</code> should be created.
<code>topng</code>	Flag to specify if the .pdf should be converted to a .png.
<code>dsf</code>	DownScaleFactor for Ghostscript when converting to .png (resolution is $4 \times 72 = 288$ pixels per inch).
<code>toeps</code>	Flag to specify if an .eps should be generated (using <code>latex</code> and <code>dvips -E</code>).
<code>clean</code>	Flag to specify if intermediate files should be deleted after generating the .pdf.

Value

Nothing.

Examples

```
ppwrite(pppicture(PSTricks(engine="pdflatex"),par="showgrid=true"))
# where the "pdflatex" engine is the only one showing the grid labels
# with a full A4 picture.
```

ppxticks

Define Major and Minor Tickmarks at the X Axis

Description

Define Major and Minor Tickmarks at the X Axis

Usage

```
ppxticks(
  p,
  nticks = 0,
  mticks = 0,
  nolabels = FALSE,
  extlabs = FALSE,
  labels = NULL,
  rotation = 0,
  ticklength = 0.2,
  ticklengthi = NULL
)

xticks(
  p,
  nticks = 0,
  mticks = 0,
  nolabels = FALSE,
  extlabs = FALSE,
  labels = NULL,
  rotation = 0,
  ticklength = 0.2,
  ticklengthi = NULL
)
```

Arguments

p	The PSTricks object.
nticks	Number of tickmarks; if nticks=0, pretty tickmarks will be determined automatically.

mticks	Number of minor tickmarks.
nolabels	Flag to indicate that no labels should be printed.
extlabs	Flag to indicate that labels at axis extrema should be printed (however labels cannot be used).
labels	List of labels instead of numbers to print at the tickmarks.
rotation	The rotation for the labels at the tickmarks.
ticklength	The length of the ticks.
ticklengthi	<ul style="list-style-type: none"> The inward length of the ticks (default same as outward).

Value

The updated PStricks object.

Examples

```
PStricks() %>%
  geom_dots(aes(x=wt,y=mpg),mtcars) %>%
  xlim(0,6) %>%
  xticks(3,2)
```

ppyticks

Define Major and Minor Tickmarks at the Y Axis

Description

Define Major and Minor Tickmarks at the Y Axis

Usage

```
ppyticks(
  p,
  nticks = 0,
  mticks = 0,
  nolabels = FALSE,
  extlabs = FALSE,
  labels = NULL,
  rotation = 0,
  ticklength = 0.2,
  ticklengthi = NULL
)

yticks(
  p,
  nticks = 0,
  mticks = 0,
  nolabels = FALSE,
```

```

    extlabs = FALSE,
    labels = NULL,
    rotation = 0,
    ticklength = 0.2,
    ticklengthi = NULL
  )

```

Arguments

<code>p</code>	The PSTricks object.
<code>nticks</code>	Number of tickmarks; if <code>nticks=0</code> , pretty tickmarks will be determined automatically.
<code>mticks</code>	Number of minor tickmarks.
<code>nolabels</code>	Flag to indicate that no labels should be printed.
<code>extlabs</code>	Flag to indicate that labels at axis extrema should be printed (however labels cannot be used).
<code>labels</code>	List of labels instead of numbers to print at the tickmarks.
<code>rotation</code>	The rotation for the labels at the tickmarks.
<code>ticklength</code>	The length of the ticks.
<code>ticklengthi</code>	<ul style="list-style-type: none"> The inward length of the ticks (default same as outward).

Value

The updated PSTricks object.

Examples

```

PSTricks() %>%
  geom_dots(aes(x=wt,y=mpg),mtcars) %>%
  ylim(10,35) %>%
  yticks(6,0)

```

<code>print.PSTricks</code>	<i>print a PSTricks Object</i>
-----------------------------	--------------------------------

Description

print a PSTricks Object

Usage

```

## S3 method for class 'PSTricks'
print(x, ...)

```

Arguments

<code>x</code>	The PSTricks object.
<code>...</code>	Parameters for <code>ppwrite</code> .

psarc

Draw PSTricks Arc

Description

Draw PSTricks Arc

Usage

```
psarc(
  p = NULL,
  x = NULL,
  y = NULL,
  radius,
  angleA,
  angleB,
  par = NULL,
  arrows = NULL,
  star = FALSE
)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the arc.
radius	Radius of the arc.
angleA, angleB	Start and end angles of the arc.
par	PSTricks parameter string.
arrows	Arrows at the end of the line.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),3,2,par="showgrid=true") %>%
  psarc(1.5,1.5,1.5,215,0,"showpoints=true",star=TRUE)
```

psarcn

Draw PSTricks Arc Clockwise

Description

Draw PSTricks Arc Clockwise

Usage

```
psarcn(
  p = NULL,
  x = NULL,
  y = NULL,
  radius,
  angleA,
  angleB,
  par = NULL,
  arrows = NULL,
  star = FALSE
)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the arc.
radius	Radius of the arc.
angleA, angleB	End and start angles of the arc.
par	PSTricks parameter string.
arrows	Arrows at the end of the line.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),4,3,par="showgrid=true") %>%
  ppsetpolar() %>%
  psline(c(4,0,4),c(50,0,10),"linewidth=2pt") %>%
  psarcn(0,0,3,50,10,"arcsepB=2pt",arrows="<-")
```

psaxes	<i>Draw PSTricks Axes</i>
--------	---------------------------

Description

Draw PSTricks Axes

Usage

```
psaxes(p = NULL, x, y, par = NULL, arrows = NULL)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the axes.
par	PSTricks parameter string.
arrows	Arrows at the end of the line.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-plot"),4,3,par="showgrid=true") %>%
  psaxes(c(2,0,4), c(1,0,3),
    "linewidth=1.2pt,labels=none,ticks=none", "<->")
# observe interesting showgrid
```

psbezier	<i>Draw PSTricks Bezier Curve</i>
----------	-----------------------------------

Description

Draw PSTricks Bezier Curve

Usage

```
psbezier(p = NULL, x, y, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the line segment(s).
par	PSTricks parameter string.
arrows	Arrows at the end of the line.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),4,4) %>%
  psbezier(c(0,1,2,4),c(0,4,1,3.5),"linewidth=2pt,showpoints=true","->")
```

psccurve

Draw PSTricks Closed Curve

Description

Draw PSTricks Closed Curve

Usage

```
psccurve(p = NULL, x, y, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the curve.
par	PSTricks parameter string.
arrows	Arrows at the end of the line.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),4,1,par="showgrid=true") %>%
  psccurve(c(.5,3.5,3.5,.5),c(0,1,0,1),"showpoints=true")
```

pscircle	<i>Draw PSTricks Circle</i>
----------	-----------------------------

Description

Draw PSTricks Circle

Usage

```
pscircle(p = NULL, x = NULL, y = NULL, radius, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the center of the circle.
radius	Radius of the circle.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),c(-1,2),c(-1,2),par="showgrid=true") %>%
  pscircle(.5,.5,1.5,"linewidth=2pt")
```

pscirclebox	<i>Draw a Circle Box</i>
-------------	--------------------------

Description

Draw a Circle Box

Usage

```
pscirclebox(p = NULL, stuff, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
stuff	The stuff to put in the box.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),16,9) %>%
  rput(8,4,pscirclebox("{\\begin{tabular}{c} You are \\\\ here \\end{tabular}}"))
```

pscircleOA

Draw PSTricks Circle

Description

Draw PSTricks Circle

Usage

```
pscircleOA(p = NULL, x, y, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the center of the circle and one point on the circle.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(engine="latex"),8,8,par="showgrid=true") %>%
  pscircleOA(c(6,4),c(4,4)) %>%
  pscircleOA(c(4,4),c(6,4),"linecolor=blue") %>%
  pscircleOA(c(3,4),c(5,4),"linewidth=2pt,linecolor=yellow") %>%
  pscircleOA(c(2,4),c(4,4),"opacity=0.3,linecolor=red",TRUE)
```

psCoil

Draw PSTricks Coil

Description

Draw PSTricks Coil

Usage

```
psCoil(p = NULL, angle1, angle2, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
angle1, angle2	First and last angles of the coil.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-coil"),c(-1,5),c(-1,1),par="showgrid=true") %>%
  psCoil(0,1440,"coilaspect=0,coilheight=1.33,coilwidth=.75,linewidth=1.5pt")
```

pscoil

Draw PSTricks Coil

Description

Draw PSTricks Coil

Usage

```
pscoil(p = NULL, x, y, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the coil.
par	PSTricks parameter string.
arrows	Arrows at the end of the coil.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-coil"),c(-1,5),c(-1,3),par="showgrid=true") %>%
  pscoil(4,2,"coilarm=.5cm,linewidth=1.5pt,coilwidth=.5cm","<-|")
```

pscurve	<i>Draw PSTricks Curve</i>
---------	----------------------------

Description

Draw PSTricks Curve

Usage

```
pscurve(p = NULL, x, y, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

- | | |
|--------|-----------------------------------|
| p | The PSTricks object. |
| x, y | Coordinates of the curve. |
| par | PSTricks parameter string. |
| arrows | Arrows at the end of the line. |
| star | Flag to indicate starred version. |

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),4,2,par="showgrid=true") %>%
  pscurve(c(0,0.7,3.3,4,0.4),c(1.3,1.8,0.5,1.6,0.4),
    "showpoints=true","<->")
```

pscustom	<i>Custom graphics</i>
----------	------------------------

Description

Custom graphics

Usage

```
pscustom(p = NULL, commands, par = NULL)
```

Arguments

p	The PSTricks object.
commands	Commands to call.
par	PSTricks parameter string.

Value

The updated PSTricks object.

Examples

```
PSTricks() %>%
  pppicture(4,3,par="showgrid=true") %>%
  pscustom(paste0(pscurve(c(0,1,2,4),c(2,2.5,1.5,3)),
    pscurve(c(4,3,2,1,0),c(1,0.5,1,0,0.5),"liftpen=1")),
    "linewidth=2pt,fillstyle=solid,fillcolor=gray")
```

psdblframebox	<i>Put Stuff in a Box with a Double Frame</i>
---------------	---

Description

Put Stuff in a Box with a Double Frame

Usage

```
psdblframebox(p = NULL, stuff, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
stuff	The stuff to put in the box.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),16,9) %>%
  rput(8,4,psdblframebox(,"\\parbox[c]{6cm}{\\raggedright
    A double frame is drawn with the gap between lines equal to \\texttt{doublesep}}"))
```

psdiabox	<i>Put Stuff in a Diamond Box</i>
----------	-----------------------------------

Description

Put Stuff in a Diamond Box

Usage

```
psdiabox(p = NULL, stuff, par = NULL, star = FALSE)
```

Arguments

- p The PSTricks object.
- stuff The stuff to put in the box.
- par PSTricks parameter string.
- star Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),16,9) %>%
  rput(8,4,psdiabox(,"\\Large\\textbf{Happy?}","shadow=true"))
```

psdiamond	<i>Draw PSTricks Diamond</i>
-----------	------------------------------

Description

Draw PSTricks Diamond

Usage

```
psdiamond(p = NULL, x, y, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the diamond.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),4,2,par="showgrid=true") %>%  
  psdiamond(c(2,1.5),c(1,1),"framearc=.3,fillstyle=solid,fillcolor=lightgray")
```

psdot	<i>Draw PSTricks Dot</i>
-------	--------------------------

Description

Draw PSTricks Dot

Usage

```
psdot(p = NULL, x = NULL, y = NULL, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the dot.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),2,2) %>%  
  psdot(1,1)
```

psdots	<i>Draw PSTricks Dots</i>
--------	---------------------------

Description

Draw PSTricks Dots

Usage

```
psdots(p = NULL, x, y, par = NULL, star = FALSE)
```

Arguments

- p The PSTricks object.
- x, y Coordinates of the dots.
- par PSTricks parameter string.
- star Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),2,2) %>%  
  psdots(c(0,1,2),c(1,1,1),"dotstyle=Bo")
```

psecurve	<i>Draw PSTricks Extended Curve</i>
----------	-------------------------------------

Description

Draw PSTricks Extended Curve

Usage

```
psecurve(p = NULL, x, y, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the curve.
par	PSTricks parameter string.
arrows	Arrows at the end of the line.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),4,4,par="showgrid=true") %>%
  psecurve(c(.125,.25,.5,1,2,4,8),c(8,4,2,1,.5,.25,.125),
    "showpoints=true")
```

psellipse	<i>Draw PSTricks Ellipse</i>
-----------	------------------------------

Description

Draw PSTricks Ellipse

Usage

```
psellipse(p = NULL, x, y, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the center of and the horizontal and vertical radii.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),c(-1,2),c(-1,1),par="showgrid=true") %>%
  psellipse(c(.5,1.5),c(0,1),"fillcolor=lightgray")
```

psellipticarc	<i>Draw PSTricks Elliptic Arc</i>
---------------	-----------------------------------

Description

Draw PSTricks Elliptic Arc

Usage

```
psellipticarc(
  p = NULL,
  x,
  y,
  angleA,
  angleB,
  par = NULL,
  arrows = NULL,
  star = FALSE
)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the elliptic arc.
angleA, angleB	Start and end angles of the arc.
par	PSTricks parameter string.
arrows	Arrows at the end of the line.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),c(-1,2),c(-1,1),par="showgrid=true") %>%
  psellipticarc(c(.5,1.5),c(0,1),215,0,"showpoints=true,arrowscale=2","->")
```

psellipticarcn	<i>Draw PSTricks Elliptic Arc Clockwise</i>
----------------	---

Description

Draw PSTricks Elliptic Arc Clockwise

Usage

```
psellipticarcn(
  p = NULL,
  x,
  y,
  angleA,
  angleB,
  par = NULL,
  arrows = NULL,
  star = FALSE
)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the elliptic arc.
angleA, angleB	Start and end angles of the arc.
par	PSTricks parameter string.
arrows	Arrows at the end of the line.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),c(-1,2),c(-1,1),par="showgrid=true") %>%
  psellipticarcn(c(.5,1.5),c(0,1),0,215,"showpoints=true,arrowscale=2","<-")
```

psframe	<i>Draw PSTricks Frame</i>
---------	----------------------------

Description

Draw PSTricks Frame

Usage

```
psframe(p = NULL, x, y, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the frame.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),4,2,par="showgrid=true") %>%
  psframe(4,2,"linewidth=2pt,framearc=.3,fillstyle=solid,fillcolor=lightgray") %>%
  psframe(c(1,2),c(.5,1.5),"linecolor=white",star=TRUE)
```

psframebox	<i>Put Stuff in a Box with a Frame</i>
------------	--

Description

Put Stuff in a Box with a Frame

Usage

```
psframebox(p = NULL, stuff, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
stuff	The stuff to put in the box.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),3,2) %>%
  pspolygon(c(0,3,3,2),c(0,0,2,2),"fillcolor=gray,fillstyle=crosshatch*") %>%
  rput(2,1,psframebox("Label","framearc=.3",star=TRUE))
```

psgrid

Draw PSTricks Grid

Description

Draw PSTricks Grid

Usage

```
psgrid(p = NULL, x = NULL, y = NULL, par = NULL)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the grid.
par	PSTricks parameter string.

Value

The updated PSTricks object.

Examples

```
PSTricks() %>%
  pppicture(c(-2,4),c(-2,3)) %>%
  psgrid(c(0,-1,3), c(0,-1,2)) %>%
  pppicture(c(-1,3),c(-1,2)) %>%
  psgrid()
```

psline

Draw PSTricks Line

Description

Draw PSTricks Line

Usage

```
psline(p = NULL, x, y, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the line segment(s).
par	PSTricks parameter string.
arrows	Arrows at the end of the line.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

See Also

[geom_line\(\)](#) for the version with scaling.

Examples

```
pppimage(PSTricks(),4,2,par="showgrid=true") %>%
  psline(c(4,0,2),c(2,1,0),"linewidth=2pt,linearc=.25","->")
```

psovalbox

Put Stuff in an Oval Box

Description

Put Stuff in an Oval Box

Usage

```
psovalbox(p = NULL, stuff, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
stuff	The stuff to put in the box.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),16,9) %>%
  rput(8,4,paste0("\parbox{3.75cm}{At the introductory price of ",
    psovalbox("\$13.99","boxsep=false,linecolor=darkgray"),
    ", it pays to act now!}"))
```

pspicture	<i>Begin Picture Environment</i>
-----------	----------------------------------

Description

Begin Picture Environment

Usage

```
pspicture(p = NULL, x, y, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of upper right corner (and optionally lower left corner).
par	Parameters (see Voss' latest documentation).
star	Flag to indicate that objects should be clipped with respect to the boundaries.

Details

Available, but see pppicture().

Value

The updated PSTricks object.

Examples

```

PSTricks(engine="pdflatex") %>%
  psset("linecolor=red") %>%
  pspicture(1,1,"showgrid") %>%
  rput(0,0,
    paste(pspicture(,1,1,star=TRUE),
          psline(c(-1,2),c(-1,2)),
          endpspicture()),
    "lb") %>%
  endpspicture()
# Example found on the internet for clipping while showing labels

```

pspolygon

Draw PSTricks Polygon

Description

Draw PSTricks Polygon

Usage

```
pspolygon(p = NULL, x, y, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the line segment(s).
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```

pppicture(PSTricks(),4,2,par="showgrid=true") %>%
  pspolygon(c(0,1),c(2,2),"linewidth=1.5pt") %>%
  pspolygon(c(1,1,4,4),c(0,2,0,2),"linearc=.2", star=TRUE)

```

psscalebox	<i>Scale Box</i>
------------	------------------

Description

Scale Box

Usage

```
psscalebox(p = NULL, stuff, num1, num2)
```

Arguments

p	The PStricks object.
stuff	Stuff to scale.
num1, num2	Numbers to scale horizontally and vertically

Value

The updated PStricks object.

Examples

```
pppicture(PStricks(),16,9) %>%  
  rput(8,4,psscalebox("Big and long",4,2))
```

psscaleboxto	<i>Scale Box To</i>
--------------	---------------------

Description

Scale Box To

Usage

```
psscaleboxto(p = NULL, x, y, stuff)
```

Arguments

p	The PStricks object.
x, y	Width and height to scale to.
stuff	Stuff to rotate.

Value

The updated PStricks object.

Examples

```
pppicture(PSTricks(),16,9) %>%
  rput(8,4,psscaleboxto(,4,2,"Big and long"))
```

psset	<i>Set Any Native PSTricks Option</i>
-------	---------------------------------------

Description

Set Any Native PSTricks Option

Usage

```
psset(p = NULL, s)
```

Arguments

p	The PSTricks object.
s	A string with par=value specifications (comma separated).

Value

The updated PSTricks object.

Examples

```
psset(,"linewidth=0.1mm")
```

psshadowbox	<i>Put Stuff in a Box with a Frame and a Shadow</i>
-------------	---

Description

Put Stuff in a Box with a Frame and a Shadow

Usage

```
psshadowbox(p = NULL, stuff, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
stuff	The stuff to put in the box.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),16,9) %>%
  rput(8,4,"\\psshadowbox{\\textbf{Great Idea!!}}")
```

psTextFrame

Draw PSTricks Text Frame

Description

Draw PSTricks Text Frame

Usage

```
psTextFrame(p = NULL, x, y, text, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the frame.
text	Text to display in the frame.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),8,6,par="showgrid=true") %>%
  psTextFrame(c(0,4),c(0.5,1.5),"Hallo", "linecolor=lightgray,ref=1")
```

pstriangle	<i>Draw PSTricks Triangle</i>
------------	-------------------------------

Description

Draw PSTricks Triangle

Usage

```
pstriangle(p = NULL, x, y, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the triangle.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),4,2,par="showgrid=true") %>%
  pstriangle(c(2,4),c(.5,1),"gangle=10", star=TRUE)
```

pstribox	<i>Put Stuff in a Triangle Box</i>
----------	------------------------------------

Description

Put Stuff in a Triangle Box

Usage

```
pstribox(p = NULL, stuff, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
stuff	The stuff to put in the box.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),16,9) %>%
  rput(8,4,pstribox(,"\\Large\\textbf{Begin}", "trimode=R,framesep=5pt"))
```

PSTricks

Create a PSTricks Object

Description

Create a PSTricks Object

Usage

```
PSTricks(
  x = NULL,
  y = NULL,
  engine = c("default", "lualatex", "xelatex", "pdflatex", "latex"),
  paper = c("default", "a4", "letter"),
  landscape = FALSE,
  center = TRUE,
  packages = NULL,
  pstpkgs = NULL,
  familydefault = NULL,
  tmpdir = "."
)
```

Arguments

x	Width of paper (default A4).
y	Height of paper (default A4).
engine	Engine to produce a .pdf from the output .tex file. One of "lualatex" (default), "xelatex", "pdflatex", and "latex". No pdf will be produced if the engine name is not recognized.
paper	Paper size specification. One of "a4" (default) or "letter".
landscape	Flag to indicate landscape paper.
center	Flag to use LaTeX offsets to center pictures based on the first one.
packages	Font or other packages to load (default default).
pstpkgs	PSTricks packages in addition to pstricks itself (default none).
familydefault	Familydefault (default \sfdefault).
tmpdir	Temporary directory for the PSTtoEPS feature.

Value

An initial PSTricks object with attributes

- docOpened - A flag indicating that the LaTeX document has been opened (in the lines attribute).
- picOpened - A flag indicating that the pspicture PSTricks environment has been opened.
- paperx - The horizontal paper size in cm.
- papery - The vertical paper size in cm.
- x - The horizontal picture size in cm.
- y - The vertical picture size in cm.
- landscape - A flag indicating portrait or landscape output mode.
- center - A flag indicating that the pspicture will be centered on the paper.
- config - A list of configuration items (see below).
- lines - A list of LaTeX lines to be created.

The configuration list may consist of the following items:

- engine - The engine used to process the generated .tex file.
- familydefault - The default font family.
- packages - A list of additional LaTeX packages to be used.
- paper - The type of paper, for example "a4" or "letter".
- pstpkgs - A list of additional PSTricks packages (normally only "pstricks.sty").
- tmpdir - The temporary directory for the PSTtoEPS feature.
- gscmd - The name of the Ghostscript executable to use (default "gs").

Examples

```
names(PSTricks())
```

pswedge

Draw PSTricks Wedge

Description

Draw PSTricks Wedge

Usage

```

pswedge(
  p = NULL,
  x = NULL,
  y = NULL,
  radius,
  angle1,
  angle2,
  par,
  star = FALSE
)

```

Arguments

p	The PSTricks object.
x, y	Coordinates of the center of and the horizontal and vertical radii.
radius	Radius of the wedge.
angle1, angle2	End and start angles of the wedge.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```

pppicture(PSTricks(),2,2,par="showgrid=true") %>%
  pswedge(0,0,2,0,70,"linecolor=gray,linewidth=2pt,fillstyle=solid")

```

pszigzag

Draw PSTricks Zigzag

Description

Draw PSTricks Zigzag

Usage

```
pszigzag(p = NULL, x, y, par = NULL, arrows = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the zigzag.
par	PSTricks parameter string.
arrows	Arrows at the end of the zigzag.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-coil"),c(-1,5),c(-1,1),par="showgrid=true") %>%
  pszigzag(4,0,"coilarm=.5,linear=.1","<->")
# Note that the zigzag is drawn partly outside the pppicture.
```

qdisk

Draw PSTricks Disk

Description

Draw PSTricks Disk

Usage

```
qdisk(p = NULL, x, y, radius)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the center of the disk.
radius	Radius of the disk.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),4,6) %>%
  psset("linecolor=gray") %>%
  qdisk(2,3, 4*2.54/72)
```

qline	<i>Draw PSTricks Line Segment</i>
-------	-----------------------------------

Description

Draw PSTricks Line Segment

Usage

```
qline(p = NULL, x, y)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the line segment.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),2,1,par="showgrid=true") %>%
  qline(c(0,2),c(0,1))
```

Rnode	<i>Put Stuff in a Box at a Node</i>
-------	-------------------------------------

Description

Put Stuff in a Box at a Node

Usage

```
Rnode(p = NULL, name, stuff, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
name	The name of the node.
stuff	Stuff to put in a box at the node.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  rput(8,4,paste("\\Large",Rnode("A","sp"),"\\hskip 2cm",Rnode("B","Bit"))) %>%
  ncline("A","B")
```

rnode	<i>Put Stuff in a Box at a Node</i>
-------	-------------------------------------

Description

Put Stuff in a Box at a Node

Usage

```
rnode(p = NULL, name, stuff, refpoint = NULL)
```

Arguments

- `p` The PSTricks object.
- `name` The name of the node.
- `stuff` Stuff to put in a box at the node.
- `refpoint` The reference point (see [rput\(\)](#)).

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpkgs="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  rput(8,4,paste("\\Large",rnode("A","sp"),"\\hskip 2cm",rnode("B","Bit"))) %>%
  ncline("A","B")
```

rotatedown	<i>Rotate Box Down</i>
------------	------------------------

Description

Rotate Box Down

Usage

```
rotatedown(p = NULL, stuff)
```

Arguments

p	The PStricks object.
stuff	Stuff to rotate.

Value

The updated PStricks object.

See Also

[rotateleft\(\)](#) for an example.

rotateleft	<i>Rotate Box Left</i>
------------	------------------------

Description

Rotate Box Left

Usage

```
rotateleft(p = NULL, stuff)
```

Arguments

p	The PStricks object.
stuff	Stuff to rotate.

Value

The updated PStricks object.

Examples

```
pppicture(PSTricks(),16,9) %>%
  rput(8,4,paste("\\Large\\bfseries",
    rotateleft("Left"),rotatedown("Down"),rotateright("Right")))
```

rotateright	<i>Rotate Box Right</i>
-------------	-------------------------

Description

Rotate Box Right

Usage

```
rotateright(p = NULL, stuff)
```

Arguments

- p The PSTricks object.
- stuff Stuff to rotate.

Value

The updated PSTricks object.

See Also

[rotateleft\(\)](#) for an example.

rput	<i>Put Stuff at Refpoint</i>
------	------------------------------

Description

Put Stuff at Refpoint

Usage

```
rput(
  p = NULL,
  x = NULL,
  y = NULL,
  stuff,
  refpoint = NULL,
  rotation = NULL,
  star = FALSE
)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the stuff (may be omitted if rotation is present).
stuff	Stuff to put at the reference point.
refpoint	The reference point for the stuff.
rotation	Rotation to apply to the stuff.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),c(-1,4),c(-1,4)) %>%
  rput(stuff=paste0(psframe(c(-1,2),c(0,1)),
    rput(,2,1,"\\emph{stuff}", "br", "*0")),rotation=34)
```

sifelse

Conditional Object Selection

Description

Conditional Object Selection

Usage

```
sifelse(test, rt, rf)
```

Arguments

test	An object which can be coerced to logical mode.
rt	Return value if test is true.
rf	Return value if test is false.

Details

This is like ifelse, but for a scalar test, and any object may be returned.

Value

Appropriate return value.

startP2E	<i>Start PSTtoEPS Feature</i>
----------	-------------------------------

Description

Start PSTtoEPS Feature

Usage

```
startP2E(p, fileplot = FALSE)
```

Arguments

p	The PStricks object.
fileplot	Flag to indicate cated values will be used for fileplot.

Value

The updated PStricks object.

taput	<i>Put Stuff on Line</i>
-------	--------------------------

Description

Put Stuff on Line

Usage

```
taput(p = NULL, stuff, par = NULL, star = FALSE)
```

Arguments

p	The PStricks object.
stuff	The label to put on the line.
par	PStricks parameter string.
star	Flag to indicate starred version.

Value

The updated PStricks object.

See Also

[tlput\(\)](#) for an example.

tbput	<i>Put Stuff on Line</i>
-------	--------------------------

Description

Put Stuff on Line

Usage

```
tbput(p = NULL, stuff, par = NULL, star = FALSE)
```

Arguments

p	The PStricks object.
stuff	The label to put on the line.
par	PStricks parameter string.
star	Flag to indicate starred version.

Value

The updated PStricks object.

See Also

[tlput\(\)](#) for an example.

thput	<i>Put Stuff on Line</i>
-------	--------------------------

Description

Put Stuff on Line

Usage

```
thput(p = NULL, stuff, par = NULL, star = FALSE)
```

Arguments

p	The PStricks object.
stuff	The label to put on the line.
par	PStricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
PSTricks(engine="lualatex",pstpks="pst-node") %>%
  ppappend("\\[") %>%
  ppappend("\\setlength{\\arraycolsep}{1.1cm}") %>%
  ppappend("\\begin{array}{cc}") %>%
  ppappend(paste(Rnode("a", "(X-A)"), "&", Rnode("b", "A"), "\\[1.5cm]")) %>%
  ppappend(paste(Rnode("c", "x"), "&", Rnode("d", "\\tilde{X}"))) %>%
  ppappend("\\end{array}") %>%
  psset("nodesep=5pt,arrows=->") %>%
  everypsbox("\\scriptstyle") %>%
  ncline("a", "c") %>% thput("h") %>%
  ncline("a", "b") %>% thput("h") %>%
  ncline("b", "d") %>% tvput("v") %>%
  ncline("c", "d") %>% tvput("v") %>%
  ppappend("\\]")
```

ticks

Define Major and Minor Tickmarks at the Axes

Description

Define Major and Minor Tickmarks at the Axes

Usage

```
ticks(
  p,
  x = 0,
  y = 0,
  nolabels = FALSE,
  extlabs = FALSE,
  labels = NULL,
  rotation = 0,
  ticklength = 0.2,
  ticklengthi = NULL
)
```

Arguments

p	The PSTricks object.
x, y	Lists with number of major and minor tickmarks.
nolabels	Flag to indicate that no labels should be printed.

extlabs	Flag to indicate that labels at axis extrema should be printed (however labels cannot be used).
labels	List of labels instead of numbers to print at the tickmarks.
rotation	The rotation for the labels at the tickmarks.
ticklength	The length of the ticks.
ticklengthi	<ul style="list-style-type: none"> The inward length of the ticks (default same as outward).

Value

The updated PStricks object.

Examples

```
PStricks() %>%
  geom_dots(aes(x=wt,y=mpg),mtcars) %>%
  lims(c(1,6),c(10,35)) %>%
  ticks(c(6,0),c(6,1))
```

tlput	<i>Put Stuff on Line</i>
-------	--------------------------

Description

Put Stuff on Line

Usage

```
tlput(p = NULL, stuff, par = NULL, star = FALSE)
```

Arguments

p	The PStricks object.
stuff	The label to put on the line.
par	PStricks parameter string.
star	Flag to indicate starred version.

Value

The updated PStricks object.

Examples

```
PSTricks(engine="lualatex",pstpgks="pst-node") %>%
  ppappend("\\[") %>%
  ppappend("\\setlength{\\arraycolsep}{1.1cm}") %>%
  ppappend("\\begin{array}{cc}") %>%
  ppappend(paste(Rnode(", "a", "(X-A)", "&", Rnode(", "b", "A"), "\\[1.5cm]")) %>%
  ppappend(paste(Rnode(", "c", "x)", "&", Rnode(", "d", "\\tilde{X}"))) %>%
  ppappend("\\end{array}") %>%
  psset("nodesep=5pt,arrows=->") %>%
  everypsbox("\\scriptstyle") %>%
  ncline("a", "c") %>% tlput("r") %>%
  ncline("a", "b") %>% taput("u") %>%
  ncline("c", "d", "linestyle=dashed") %>% tbput("b") %>%
  ncline("b", "d") %>% trput("s") %>% ppappend("\\]")
# Note: no pppicture because of array
```

trinode	<i>Put Stuff in a Triangle</i>
---------	--------------------------------

Description

Put Stuff in a Triangle

Usage

```
trinode(p = NULL, name, stuff, par = NULL, star = FALSE)
```

Arguments

- p The PSTricks object.
- name The name of the node.
- stuff Stuff to put in a box at the node.
- par PSTricks parameter string.
- star Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(pstpgks="pst-node"),c(-2,14),c(-2,10),par="showgrid=true") %>%
  rput(0,3,dianode(", "A", "Diamond"), "tl") %>%
  rput(4,0,trinode(", "B", "Triangle", "trimode=L"), "br") %>%
  nccurve("A", "B", "angleA=-135,angleB=90")
```

trput	<i>Put Stuff on Line</i>
-------	--------------------------

Description

Put Stuff on Line

Usage

```
trput(p = NULL, stuff, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
stuff	The label to put on the line.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

See Also

[tlput\(\)](#) for an example.

tvput	<i>Put Stuff on Line</i>
-------	--------------------------

Description

Put Stuff on Line

Usage

```
tvput(p = NULL, stuff, par = NULL, star = FALSE)
```

Arguments

p	The PSTricks object.
stuff	The label to put on the line.
par	PSTricks parameter string.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

See Also

[thput\(\)](#) for an example.

uput	<i>Put Stuff as Label</i>
------	---------------------------

Description

Put Stuff as Label

Usage

```
uput(
  p = NULL,
  x = NULL,
  y = NULL,
  stuff,
  refangle = NULL,
  rotation = NULL,
  labelsep = NULL,
  star = FALSE
)
```

Arguments

p	The PSTricks object.
x, y	Coordinates of the stuff (may be omitted if rotation is present).
stuff	Stuff to put at the reference point.
refangle	The reference angle.
rotation	Rotation to apply to the stuff.
labelsep	Distance between coordinates and the stuff.
star	Flag to indicate starred version.

Value

The updated PSTricks object.

Examples

```
pppicture(PSTricks(),3,3) %>%
  qdisk(1,1,"1pt") %>%
  uput(1,1,"(1,1)",45)
```

xaspect	<i>Calculate x for pppicture given y to get $hy = aspect * hx$</i>
---------	---

Description

Calculate x for pppicture given y to get $hy = aspect * hx$

Usage

```
xaspect(
  y,
  aspect = 1,
  nx = 1,
  ny = 1,
  nxaxes = 1,
  nyaxes = 1,
  ntitle = 1,
  width = 1,
  height = 1,
  margin = 1
)
```

Arguments

y	Desired space in y direction.
aspect	Desired aspect ratio of axes.
nx	Number of plots in the x direction (if NULL, increment n automatically).
ny	Number of plots in the y direction.
nxaxes	Number of x axes to make space for.
nyaxes	Number of y axes to make space for.
ntitle	Number of title lines to make space for.
width	Number of subplots to occupy in the x direction.
height	Number of subplots to occupy in the y direction.
margin	Margin.

Value

The x value.

Examples

```
pppicture(PSTricks(), xaspect(12), 12, par="showgrid=true") %>%
  geom_dots(aes(x=wt, y=mpg), mtcars) %>%
  xticks(extlabs=TRUE) %>% yticks(extlabs=TRUE) %>%
  pptitle("\\Large mtcars")
```

<code>xlab</code>	<i>Set x Axis Label</i>
-------------------	-------------------------

Description

Set x Axis Label

Usage

`xlab(p, lab)`

Arguments

<code>p</code>	The PSTricks object.
<code>lab</code>	x axis label.

Value

The updated PSTricks object.

<code>xlim</code>	<i>Set x Axis Limits</i>
-------------------	--------------------------

Description

Set x Axis Limits

Usage

`xlim(p, xl = NULL, xu = NULL)`

Arguments

<code>p</code>	The PSTricks object.
<code>xl, xu</code>	Lower and upper axis limits.

Value

The updated PSTricks object.

See Also

See [geom_curve\(\)](#) for an example.

xyaspect

*Calculate x,y for pppicture given x,y (in p) to get $hy = aspect * hx$* **Description**

Calculate x,y for pppicture given x,y (in p) to get $hy = aspect * hx$

Usage

```
xyaspect(
  p,
  aspect = 1,
  nx = 1,
  ny = 1,
  nxaxes = 1,
  nyaxes = 1,
  ntitle = 1,
  width = 1,
  height = 1,
  margin = 1
)
```

Arguments

p	The PStricks object.
aspect	Desired aspect ratio of axes.
nx	Number of plots in the x direction (if NULL, increment n automatically).
ny	Number of plots in the y direction.
nxaxes	Number of x axes to make space for.
nyaxes	Number of y axes to make space for.
ntitle	Number of title lines to make space for.
width	Number of subplots to occupy in the x direction.
height	Number of subplots to occupy in the y direction.
margin	Margin.

Value

The updated PStricks object.

Examples

```
PStricks() %>% xyaspect(ntitle=0) %>% pppicture(par="showgrid=true") %>%
  geom_dots(aes(x=wt,y=mpg),mtcars)
```

yaspect	<i>Calculate y for pppicture given x to get $hy = aspect * hx$</i>
---------	---

Description

Calculate y for pppicture given x to get $hy = aspect * hx$

Usage

```
yaspect(
  x,
  aspect = 1,
  nx = 1,
  ny = 1,
  nxaxes = 1,
  nyaxes = 1,
  ntitle = 1,
  width = 1,
  height = 1,
  margin = 1
)
```

Arguments

x	Desired space in x direction.
aspect	Desired aspect ratio of axes.
nx	Number of plots in the x direction (if NULL, increment n automatically).
ny	Number of plots in the y direction.
nxaxes	Number of x axes to make space for.
nyaxes	Number of y axes to make space for.
ntitle	Number of title lines to make space for.
width	Number of subplots to occupy in the x direction.
height	Number of subplots to occupy in the y direction.
margin	Margin.

Value

The y value.

Examples

```
pppicture(PSTricks(),12,yaspect(12),par="showgrid=true") %>%
  geom_dots(aes(x=wt,y=mpg),mtcars) %>%
  xticks(extlabs=TRUE) %>% yticks(extlabs=TRUE) %>%
  pptitle("\\Large mtcars")
```

ylab	<i>Set y Axis Label</i>
------	-------------------------

Description

Set y Axis Label

Usage

```
ylab(p, lab)
```

Arguments

p	The PStricks object.
lab	y axis label.

Value

The updated PStricks object.

ylim	<i>Set y Axis Limits</i>
------	--------------------------

Description

Set y Axis Limits

Usage

```
ylim(p, yl = NULL, yu = NULL)
```

Arguments

p	The PStricks object.
yl, yu	Lower and upper axis limits.

Value

The updated PStricks object.

See Also

See [geom_curve\(\)](#) for an example.

`%>%`*Pipe PSTricks Object*

Description

Like dplyr, PSTricks also uses the pipe function, `%>%`, to pass information from one function to another. But this is unlike ggplot2, which uses the `+` operator.

Arguments

lhs, rhs A PSTricks object and a function to apply to it.

Examples

```
# Instead of
geom_dots(PSTricks(),aes(x=wt,y=mpg),mtcars)
# one may write
PSTricks() %>% geom_dots(aes(x=wt,y=mpg),mtcars)
```

Index

%>%, 138

adjx0y0, 6
adjx0y0(), 72
aes, 6

circlenode, 7
clipbox, 8
Cnode, 8
cnode, 9
cnode(), 63
cnodeput, 10
cput, 11
cx, 11
cy, 12

degrees, 12
degrees(), 80
dianode, 13
dotnode, 13

endP2E, 14
endpppicture, 14
endpspicture, 15
everypsbox, 15
everypsbox(), 22

fnode, 16

geom_abline, 16
geom_abline(), 19, 26, 33, 78
geom_ccurve, 17
geom_curve, 18
geom_curve(), 24, 27, 134, 137
geom_dots, 19
geom_ecurve, 20
geom_errorbar, 21
geom_everypsbox, 22
geom_frame, 22
geom_framebox, 23
geom_grid, 24

geom_hist, 25
geom_hline, 26
geom_legend, 26
geom_line, 27
geom_line(), 85, 110
geom_linewidth, 28
geom_polygon, 28
geom_rput, 29
geom_set, 30
geom_set(), 7, 22, 24, 28, 34, 71
geom_uput, 31
geom_vline, 32

icx, 33
icy, 33

labs, 34
lims, 34

MakeShortNab, 35
MakeShortNab(), 36
MakeShortTablr, 35
merge.list, 36
multirput, 37

naput, 38
nbput, 38
ncangle, 39
ncangles, 40
ncarc, 40
ncarcbox, 41
ncbar, 42
ncbox, 42
nccircle, 43
nccoil, 44
nccurve, 44
ncdiag, 45
ncdiag, 46
ncline, 46
ncloop, 47

ncpur, 48
 ncpur(), 38, 39
 nczigzag, 48
 newcmykcolor, 49
 newgray, 50
 newhsbcolor, 50
 newrgbcolor, 51
 nput, 51

 ovalnode, 52
 ovalnode(), 7

 parabola, 53
 pcangle, 54
 pcangles, 54
 pcarc, 55
 pcarcbox, 56
 pbar, 56
 pbox, 57
 pccoil, 58
 pccurve, 58
 pcdiag, 59
 pcdiagg, 60
 pcline, 60
 pclloop, 61
 pczigzag, 62
 pnode, 62
 ppappend, 63
 pparg, 63
 ppaxis, 64
 ppaxis(), 88
 ppbuild, 65
 ppbuild3D, 66
 ppclosedoc, 67
 ppcoords, 67
 ppcoords3D, 68
 ppdefpicture, 68
 ppgeoms, 69
 ppgeoms(), 83, 84
 ppgrid, 69
 ppgrid(), 24, 79
 pplegend, 70
 pplegend(), 27
 pplinewidth, 71
 pplinewidth(), 28
 ppmansubplot, 72
 ppmansubplot(), 89
 ppnewpage, 72
 ppnewrgbcolor, 73

 ppendoc, 74
 ppopt, 74
 pppicture, 75
 ppsetcartesian, 76
 ppsetcartesian(), 80
 ppsetlogx, 77
 ppsetlogy, 77
 ppsetlogxy, 77
 ppsetlogy, 78
 ppsetmargins, 78
 ppsetnologx, 79
 ppsetnologxy, 79
 ppsetnolog, 80
 ppsetpolar, 80
 ppsetpolar(), 12, 77
 ppsetprimary, 81
 ppsetprimaryx, 81
 ppsetprimaryy, 82
 ppsetpsttoeps, 82
 ppsetsecondary, 83
 ppsetsecondaryx, 83
 ppsetsecondaryy, 84
 ppsetxlabsep, 84
 ppsetxlabsep(), 85
 ppsetylabsep, 85
 ppsubplot, 86
 ppticks, 87
 pptitle, 88
 ppwrite, 89
 ppxlabelsep(ppsetxlabelsep), 84
 ppxticks, 90
 ppylabsep(ppsetylabsep), 85
 ppyticks, 91
 print.PSTricks, 92
 psarc, 93
 psarcn, 94
 psarcn(), 80
 psaxes, 95
 psbezier, 95
 pscurve, 96
 pscurve(), 18
 pscircle, 97
 pscirclebox, 97
 pscircleOA, 98
 psCoil, 99
 pscoil, 99
 pscurve, 100
 pscurve(), 18
 pscustom, 101

psdblframebox, 101
psdiabox, 102
psdiamond, 103
psdot, 103
psdots, 104
psdots(), 19
psecurve, 105
psecurve(), 20
psellipse, 105
psellipticarc, 106
psellipticarcn, 107
psframe, 108
psframe(), 23
psframebox, 108
psframebox(), 24
psgrid, 109
psline, 110
psline(), 27
psovalbox, 110
pspicture, 111
pspicture(), 15, 76
pspolygon, 112
pspolygon(), 29
psscalebox, 113
psscaleboxto, 113
psset, 114
psset(), 31
psshadowbox, 114
psTextFrame, 115
pstriangle, 116
pstribox, 116
PSTricks, 117
pswedge, 118
pszigzag, 119

qdisk, 120
qline, 121

Rnode, 121
rnode, 122
rotatedown, 123
rotateleft, 123
rotateleft(), 123, 124
rotateright, 124
rput, 124
rput(), 24, 30, 122

sifelse, 125
startP2E, 126

taput, 126
tbput, 127
thput, 127
thput(), 132
ticks, 128
tlput, 129
tlput(), 126, 127, 131
trinode, 130
trinode(), 13
trput, 131
tvput, 131
tvput(), 76

uput, 132
uput(), 32, 52

xaspect, 133
xlab, 134
xlim, 134
xticks (ppxticks), 90
xyaspect, 135

yaspect, 136
ylab, 137
ylim, 137
yticks (ppyticks), 91