



200

Oracle Public Cloud Workshop

Fusion Middleware Cloud Services

Contact: Dennis Foley dennis.foley@oracle.com

June 8, 2015

Introduction

In this lab, you will learn how to connect to the Database Cloud Service using SQL Developer, connect an IDE (JDeveloper) to your Java Cloud Service and connect to a Developer Cloud Service.

Please direct comments to: Dennis Foley (dennis.foley@oracle.com)

Objectives

- ☐ Connect SQL Developer to the Database Service
- ☐ Connect JDeveloper to the Java Service
- ☐ Explore the Developer Service
- ☐ Download Source from the Developer Service GIT Repository
- ☐ Build and Deploy an Application to the Java Service
- ☐ Test the Deployed Java Application

Required Artifacts

- ☐ The following labs assume that the steps outlined in lab guide 100 have been completed.

Outline


Introduction	2
Objectives	2
Required Artifacts	2
Outline	2
Connecting to the Java and Database Services	3
Connect to Database Cloud Service.....	3
Connect to Java Cloud Service	7
Exploring the Developer Cloud Service	13
Integrating with Developer Cloud Service	13
JDeveloper GIT Configuration.....	16
Explore Alpha Office Application Code	19
Deploying and Test the Java Application.....	26
Configure Weblogic	26
Deploy Application.....	34
Deleting Alpha01B-JCS	39
Freeing up Resources by Delete Alpha01B-JCS	39

Connecting to the Java and Database Services

Connect to Database Cloud Service

STEP 1: Create SSH tunnel to Database Cloud Service

- ☐ Using the **Consoles** drop down, select to the **Database Service Cloud** console. From the console click on the **Alpha01A-DBCS** Instance.



Oracle Database Cloud Service
Identity Domain: usoracle16033


As of May 28, 2015 7:40:54 PM UTC

Services	OCPUs	Memory	Storage	Public IPs
1	1	7.5 GB	90 GB	1

Services

Search by service name


[Create Service](#)

**Alpha01A-DBCS**
Version: 12.1.0.2
Edition: Enterprise Edition

Created On: May 28, 2015 1:51:05 PM UTC

OCPUs: 1
Memory: 7.5 GB
Storage: 90 GB

- ☐ Write down the Public IP Address for the **AlphaDBCS** Instance.



Alpha01A-DBCS
Public IP: 129.152.132.137

SQL *Net Port: 1521
SID: ORCL
PDB Name: PDB1

OCPUs: 1
Memory: 7.5 GB
Storage: 90 GB


- ☐ Click on the Virtual Box Terminal Window icon to load a Terminal Window.



- ☐ Enter the following command in the terminal window to create an SSH Tunnel on Port **1521**. This will allow SQL Developer running on your Virtual Box image to connect into the Database Cloud Service Image.

```
ssh -o ServerAliveInterval=60 -i ./lab/labkey oracle@<DB ip> -L 1521:<DB IP>:1521
```


- ☐ If prompted to accept the RSA key, **enter yes** and hit return



```
oracle@Alpha01A-DBCS:~  
File Edit View Search Terminal Help  
[oracle@oraclelinux6 OPCWorkshop]$ ssh -o ServerAliveInterval=60 -i ./lab/labkey oracle@129.152.132.137 -L 1521:129.152.132.137:1521  
The authenticity of host '129.152.132.137 (129.152.132.137)' can't be established.  
RSA key fingerprint is 1f:4b:1d:fd:04:cc:b7:ad:5f:c4:d3:b0:b9:54:cb:87.  
Are you sure you want to continue connecting (yes/no)? yes  
Warning: Permanently added '129.152.132.137' (RSA) to the list of known hosts.  
Authorized uses only. All activity may be monitored and reported.  
[oracle@Alpha01A-DBCS ~]$
```


STEP 2: Explore Alpha Office Schema with SQL Developer

- ☐ From the Desktop, Right click on **SQL Developer** and select **Open**



- ☐ Right click on **Connections** and select **New Connection**

Note: Cloud Connections are only used for the Database Cloud Service - Schema.



- ☐ Enter the following Connection Details

```
Connection Name = AlphaDBConnection
Username = alpha
Password = oracle
Click on the check box to Save Password
Select the Service Name radio button
Service name = PDB1.<Your ID Domain>.oraclecloud.internal
```

Connection Name: AlphaDBConnection

Username: alpha

Password: ••••••

☒ Save Password

Oracle

Connection Type: Basic Role: default

Hostname: localhost

Port: 1521


☐ SID: xe

☒ Service name: PDB1.usoracle16033.oraclecloud.internal

☐ OS Authentication ☐ Kerberos Authentication

- ☐ Click **Test** to confirm information is entered correctly. If you get a status of **Success** located in the bottom left corner of the dialog box, Click **Save** to store your connection information, and then Click **Connect** to exit the dialog

- ☐ Now from the Left hand Connections Panel expand the newly created **AlphaDBConnection** > **Tables** to view the tables that make up the Alpha Office schema.



- ☐ Select the **PRODUCTS** table to view column details.

AlphaDBConnection - PRODUCTS					
Columns Data Constraints Grants Statistics Triggers Flashback Dependencies Details Partitions Indexes SQL					
Actions...					
COLUMN_NAME	DATA_TYPE	NULLABLE	DATA_DEFAULT	COLUMN_ID	COMMENTS
1 PRODUCT_ID	NUMBER(15,0)	No	(null)	1 (null)	
2 PARENT_CATEGORY_ID	NUMBER(15,0)	Yes	(null)	2 (null)	
3 CATEGORY_ID	NUMBER(15,0)	Yes	(null)	3 (null)	
4 PRODUCT_NAME	VARCHAR2(150 BYTE)	No	(null)	4 (null)	
5 PRODUCT_STATUS	VARCHAR2(30 BYTE)	No	(null)	5 (null)	
6 COST_PRICE	NUMBER(8,2)	Yes	(null)	6 (null)	
7 LIST_PRICE	NUMBER(8,2)	No	(null)	7 (null)	
8 MIN_PRICE	NUMBER(8,2)	No	(null)	8 (null)	
9 WARRANTY_PERIOD_MONTHS	NUMBER(2,0)	Yes	(null)	9 (null)	
10 EXTERNAL_URL	VARCHAR2(200 BYTE)	Yes	(null)	10 (null)	
11 ATTRIBUTE_CATEGORY	VARCHAR2(30 BYTE)	Yes	(null)	11 (null)	
12 ATTRIBUTE1	VARCHAR2(150 BYTE)	Yes	(null)	12 (null)	
13 ATTRIBUTE2	VARCHAR2(150 BYTE)	Yes	(null)	13 (null)	
14 ATTRIBUTE3	VARCHAR2(150 BYTE)	Yes	(null)	14 (null)	
15 ATTRIBUTE4	VARCHAR2(150 BYTE)	Yes	(null)	15 (null)	
16 ATTRIBUTE5	VARCHAR2(150 BYTE)	Yes	(null)	16 (null)	
17 CREATED_BY	VARCHAR2(60 BYTE)	No	(null)	17 (null)	
18 CREATION_DATE	DATE	No	(null)	18 (null)	
19 LAST_UPDATED_BY	VARCHAR2(60 BYTE)	No	(null)	19 (null)	
20 LAST_UPDATE_DATE	DATE	No	(null)	20 (null)	
21 OBJECT_VERSION_ID	NUMBER(15,0)	No	(null)	21 (null)	

- ☐ Click on **Data** tab to view table data for all products.

PRODUCT_ID	PARENT_CATEGORY_ID	CATEGORY_ID	PRODUCT_NAME	PRODUCT_STATUS	COST_PRICE
1	1039	1002	1011 Crayola Original Markers - Broad Line, Classic Colors	AVAILABLE	3.19
2	1040	1002	1011 Expo Low Odor Chisel Tip Dry Erase Markers, 4 Colored Markers	AVAILABLE	4.99
3	1041	1003	1013 Scotch Magic Tape Deluxe Dispenser Value Pack	AVAILABLE	17.99
4	1042	1003	1013 Scotch Gift Wrap Tape in Handheld Dispenser 3/4" x 600" 2-pk.	AVAILABLE	6.29
5	1043	1003	1013 Scotch Chameleon Tape Dispenser with Scotch Magic Tape	AVAILABLE	9.25
6	1044	1004	1015 Bankers Box Stor/File Basic Strength Letter/Legal, 10-Pack	AVAILABLE	19.99
7	1045	1004	1015 Iris Open-Top Large File Bin	AVAILABLE	11.99
8	1046	1004	1015 Iris File-n-Stack Storage Box, Silver	AVAILABLE	14.79
9	1047	1004	1016 AT-A-GLANCE 2014 Recycled Monthly Academic Planner Black 6-7/8" X 8-3/4"	AVAILABLE	16.99

Connect to Java Cloud Service

STEP 3: Create an SSH tunnel to Java Cloud Service

- ☐ Go to **Java Cloud Service** instance page (you can get there from the Java Cloud Service Console and then selecting the **Alpha01A-JCS**). Make note of the IP for the Administration Server



Administration Server Domain: Alpha01A_domain

Managed Server: Alpha01A_server_1

Public IP: 129.152.134.239

OCPUs: 1

Memory: 7.5 GB

Storage: 52 GB


- ☐ Open a Terminal Window



- ☐ Create SSH Tunnel on Port 9001

Note: JCS by default creates a Channel configuration on 9001 for T3 traffic.

```
ssh -o ServerAliveInterval=60 -i ./lab/labkey opc@<Admin ip> -L
9001:<Admin ip>:9001
```




STEP 4: Create Connection to Weblogic Domain


- ☐ From the Desktop, Right click on **JDeveloper 12c** and select **Open**



- ☐ Select **Window -> Application Servers** to open Application Server Pane.



- ☐ Right click on **Application Servers** and select **New Application Server**



- ☐ If you receive the following screen, leave the default of **Standalone Server** for Step 1 and click **Next**



- ☐ Enter Connection Name of **AlphaJCSConnection** and click **Next**

Create Application Server Connection - Step 1 of 5

Name and Type

Specify a unique name and type for the connection identifier.

Create connection in: IDE Connections

Connection Name:
AlphaJCSConnection

Connection Type:
WebLogic 12.x

Help < Back Next >

- ☐ Enter Username = **weblogic** and Password = **Alpha2014_** and click **Next**

Create Application Server Connection - Step 2 of 5

Authentication

Specify a username and password to authenticate the connection.

Username:
weblogic

Password:
.....

Help < Back Next > Finish


- ☐ Enter Port = **9001**, leave the SSL Port blank, and WebLogic Domain = **Alpha01A_domain** and click **Next**. Note: localhost is used because the ssh tunnel will cause you to be connected to the WLS Admin server.

The screenshot shows a wizard window titled "Create Application Server Connection - S". The "Configuration" step is selected in the left-hand navigation pane, which also includes "Usage", "Name and Type", "Authentication", "Test", and "Finish". The main area displays the following configuration details:


- WebLogic Server connections use a host name and The Domain of the target will be verified
- WebLogic Hostname (Administration Server): localhost
- Port: 9001
- SSL Port: (blank)
- ☐ Always use SSL
- WebLogic Domain: Alpha01A_domain

At the bottom of the window, there are three buttons: "Help", "< Back", and "Next >".

- ☐ Click **Test Connection** to verify configuration. Once you get success click **Finish**



- ☐ Now From the **Application Servers** pane expand the newly create **AlphaJCSConnection**, and view both **Servers** and **Clusters**. Using JDeveloper, you also have the ability to view Log Files and Deployments for Weblogic Server running on the JCS.




Exploring the Developer Cloud Service

Integrating with Developer Cloud Service

STEP 5: Connect to a Developer Cloud Service

In this step we will log out of our Java Cloud Service Account, and we will log in using a different user account. This user has a Developer Cloud Service (DCS). For this lab a DCS has been created and source code has been loaded into the DCS's GIT repository. We will connect JDeveloper to that GIT repository and download the source code into our local copy of JDeveloper.

- ☐ If you are still logged into the JCS Dashboard, **Click** on **the drop down** for the JCS user, and **select Sign Out**



- ☐ In your browser, enter the following URL: <https://cloud.oracle.com>
- ☐ Click **Sign In** in the upper right hand Side
- ☐ Under My Services change Data Center to **US Commercial 2** and click on **Sign In to My Services**



For users with an active Oracle Cloud service:

- Administer cloud services
- Monitor utilization and uptime details

Select Data Center **US Commercial 2**

[Sign In to My Services >](#)

- ☐ Sign into the Oracle Cloud with the following credentials:

```
User Name = csbddemoteam_us@oracle.com
Password = <password to be supplied by instructor>
Identity Domain = usoracletrial92622
```

* User Name


* Password

* Identity Domain ?


[Forgot Password](#) | [Learn More](#)

Sign In


- ☐ Click on **Open Service Console** for the Oracle Developer Cloud Service



- ☐ From the Service Console you will view all the projects that have been checked into this developer Service. Click on the **Alpha01MobileApplication**.



- ☐ You are now looking at the Dashboard for the project you will checkout into your local JDeveloper Environment. **Explore each of the tabs** available for the project (Home, Code, Merge Requests, Issues, etc.)



- ☐ Return to the **Home** Tab. To copy the https URL used to access the Git repository, hover over and click on the **Hamburger menu** to the right of the **Hosted Repository** link found in the **Repositories** section.




- ☐ **Copy** the **https URL** displayed in the pop up window. You will use this URL when connecting JDeveloper to the Developer Service Git Repository.



JDeveloper GIT Configuration

STEP 6: JDeveloper GIT Configuration

- ☐ From the JDeveloper menu select **Team -> Git -> Clone**. This step accesses the DCS repository and checks the code into to your local JDeveloper.



- ☐ Click **Next** on the Clone Wizard dialog



- ☐ **Enter** the following into the dialog and **click** on **Next**


Remote Name = **Alpha01ProductCatalog**

Repository URL =


<Enter (or paste using cntl/v) the https URL coppied from the Developer Service>

User Name = **csbddemoteam_us@oracle.com**

Password = <password to be supplied by instructor>




- ☐ **Click Next** to select the Master Branch




- ☐ **Enter** the following in the dialog and **click** on **Next**


```
Destination = <Accept the default>  
Clone Name = AlphaProductCatalog  
Checkout Branch = master
```




- ☐ **Click** on **Finish** to download the source code




- ☐ To view the connection to the Git Repository, **click** on JDeveloper menu items **Team > Versions**



- ☐ Click on the **Applications** Tab.



- ☐ On the left side of the JDeveloper windows you will see a list of the Git repositories. Click on **AlphaProductCatalog** to Explore




Explore Alpha Office Application Code


STEP 7: Explore Alpha Office Application Code

In this step we'll explore the code checked out from the DBCS Git repository.

- In JDeveloper, click on the **Applications** tab, and expand **AlphaOfficeAccess > Application Sources > oracle.alpha**. Right click on **ProductAccess.java** and select **Open**



- **Review** the code for the Alpha Office application.




STEP 8: Modify and Check in Code

Now we will have you modify a file and commit the changes back to the GIT repository

- ☐ Double click or Right click and select open on the File **StudenXX.java**

Note: Student number XX will be assigned by the instructor



```
package oracle.alpha;

import ...;

@Path("/AlphaOfficeAccess/Student01")
public class Student01 {
    public Student01() {
        super();
    }

    @GET
    @Path("/sayHello")
    @Produces(MediaType.APPLICATION_JSON)
    public String sayHello() {
        String message;
        String firstName = "John";
        String lastName = "Smith";

        message = new String (firstName + " " + lastName + " - You have deployed a REST api to the Oracle Public Cloud");
        return message;
    }
}
```


- ☐ Modify the following lines:

```
String firstName = "<insert your first name>"
String lastName = "<insert your last name>"
```


```
public String sayHello() {
    String message;
    String firstName = "Dennis";
    String lastName = "Foley";
}
```

☐ Click Save All 

☐ Right click on file **StudentXX.java**, select **Versioning -> Commit**



☐ Click on the **Commit non-staged files**, and enter comment "**Modified firstName and lastName variables**" and click **Ok**




☐ Notice the GIT message in the log window for the commit to the local repository.


```
Build after save finished
git add /home/oracle/jdeveloper/mywork/AlphaProductCatalog/AlphaOfficeAccess/src/oracle/alpha/Student01.java
git commit -m Modified firstName and lastName variables /home/oracle/jdeveloper/mywork/AlphaProductCatalog/AlphaOfficeAccess/src/oracle/alpha/Student01.java
```

STEP 9: Push Changes to Developer Cloud Service


- ☐ Select the **AlphaOfficeAccess** Project




- ☐ From the JDeveloper menu select **Team -> Git -> Push**





- ☐ Click **Next** on Welcome Page. Leave defaults for Remote Repository and click **Next**



- ☐ Leave defaults for Local Branch and click **Next**




- ☐ Review summary page and click **Finish**




STEP 10: View updates in Developer Cloud Service

- ☐ Switch back to Firefox and the Developer Cloud Service. Click on **Code** icon/tab. Then click on the **Commits** button on the first right side of the page.




- ☐ Click on the Show Details link to list the changes for a given commit record.



- ☐ Click on one of the **Change Records** to view the modifications made to a given file.



- ☐ You can view the change you just made to your file




Deploying and Test the Java Application


Configure Weblogic

STEP 11: Reconnect to the Oracle Java Cloud Service

- ☐ If you are still logged into the **Developer Cloud** service, **Sign Out**. You will need to connect back into the **Java Cloud** Service



- ☐ From your browser, re-enter the URL **<http://cloud.oracle.com>**
- ☐ Click **Sign In** in the upper right hand Side
- ☐ Under My Services change Data Center **to Public Cloud Services - US** and click on **Sign In to My Services**



- ☐ Enter your **Username**, **Password** and **Identity Domain** then click **Sign In**

Sign In to Oracle Cloud

* User Name


* Password

* Identity Domain ?

[Forgot Password](#) | [Learn More](#)


Sign In

- ☐ Click on **Open Service Console** for the **Java Cloud Service**




Java Cloud Service
Category: Oracle Java Public Cloud Services
Subscription: Trial
Expires: 1-Feb-2016 5:59 PM CST

Suite VI OCPU Hours ?
(General Purpose)
no data
0

[Open Service Console](#) 

- ☐ Click on the  icon found on the far right of the **Alpha01A-JCS** Service listing. Select **Open WebLogic Server Console**.



Alpha01A-JCS
Version: 12.1.3.0.2
Edition: Enterprise Edition
JDK: 1.7.0_76

Nodes: 2
Load Balancer: Configured
Created On: May 8, 2015 2:41:35 PM UTC

[Open WebLogic Server Console](#)
[Open Fusion Middleware Control Console](#)
[Open Load Balancer Console](#)
[Delete](#)

- ☐ Log into the WebLogic Console

Username = **weblogic**
Password = **Alpha2014_**



A screenshot of the WebLogic Welcome screen. It has a blue border and a light blue background. At the top, it says "Welcome". Below that, it says "Log in to work with the WebLogic Server domain". There are two input fields: "Username:" with the text "weblogic" and "Password:" with a masked password ".....". A "Login" button is located to the right of the password field.


STEP 12: Load Required Libraries to WebLogic

Our test application uses the jersey libraries for the development of REST api's. We need to load the jersey library into WebLogic.


- ☐ Go to WebLogic Console and click on **Deployments**




- ☐ Before we can make changes to the configuration we need to go into Edit Mode. Click **Lock & Edit**




- ☐ On Deployment page click **Install**




- ☐ Click on **upload your file(s)** link




- ☐ Under **Deployment Archive** click **Browse**.
- ☐ Navigate to **/u01/OPCWorkshop/lab**. Select **jersey-bundle-1.9.war** and click **OPEN**



- ☐ Click **Next**. You will receive a message that the file was successfully uploaded.



- ☐ Click **Next** again to **Install the deployment as a library**



Install Application Assistant

Back Next Finish Cancel

Choose targeting style

Targets are the servers, clusters, and virtual hosts on which this deployment will run. There are several ways you can target an application.

☐ Install this deployment as an application

The application and its components will be targeted to the same locations. This is the most common usage.

☒ Install this deployment as a library

Application libraries are deployments that are available for other deployments to share. Libraries should be available on all of the targets running their referencing applications.

Back Next Finish Cancel

- ☐ Select **Alpha01A_cluster > All servers in the cluster**, then click **Next**

Clusters

☒ Alpha01A_cluster

☒ All servers in the cluster

☐ Part of the cluster

☐ Alpha01A_server_1

Back Next Finish Cancel

- ☐ Click **Finish**.

Install Application Assistant

Back Next Finish Cancel

- ☐ In the **Change Center** click **Activate Changes**.

Change Center

View changes and restarts

Pending changes exist. They must be activated to take effect.


☒ Activate Changes

Undo All Changes


STEP 13: Create required Data Source

In this step we will create a Data Source that will allow our application connectivity to the Database Cloud Service containing our demo data.


- ☐ In the WebLogic Console click **Lock & Edit** in Change Center



- ☐ In Domain Structure Expand **Services** and select **Data Sources**



- ☐ On the Data Sources screen, click **New -> Generic Data Source**



- ☐ Enter the following JDBC Details and click **Next**


```
Name = AlphaOfficeAccessDS
JNDI Name = jdbc/AlphaOfficeAccessDS
```

JDBC Data Source Properties

The following properties will be used to identify your new JDBC data source.

* Indicates required fields

What would you like to name your new JDBC data source?

 * Name:

What JNDI name would you like to assign to your new JDBC Data Source?

 JNDI Name:

- ☐ Click **Next** until prompted for Database Name, Host Name, Port, etc.
- ☐ Enter Data Source Details and click **Next**

```
Database Name = PDB1.<Domain ID>.oraclecloud.internal
Host Name = Alpha01A-DBCS
Port = 1521
Database User Name = alpha
Password = oracle
```

Create a New JDBC Data Source

Connection Properties

Define Connection Properties.

What is the name of the database you would like to connect to?

Database Name:

What is the name or IP address of the database server?

Host Name:

What is the port on the database server used to connect to the database?

Port:

What database account user name do you want to use to create database connections?

Database User Name:

What is the database account password to use to create database connections?


Password:

Confirm Password:

- ☐ Make the following correction to the URL Field. Change the ":" following the 1521 to a "/". It should read ":1521/". See the example below

```
URL = jdbc:oracle:thin:@Alpha01A-DBCS:1521/PDB1.<Your Domain Id>.oraclecloud.internal
```

- ☐ Click **Test.Configuration**. If the connection test succeeded, click **Next**.
- ☐ Select **Alpha01A_cluster** and click **Finish**



Clusters

☒ Alpha01A_cluster


☒ All servers in the cluster

☐ Part of the cluster

☐ Alpha01A_server_1

Back Next Finish Cancel

- ☐ In Change Center click **Activate Changes**.



Change Center

View changes and restarts

Pending changes exist. They must be activated to take effect.


☒ Activate Changes

Undo All Changes


Deploy Application

STEP 14: Deploy Application


- ☐ From JDeveloper 12c, right click on **AlphaOfficeAccess** project. Select **Deploy -> AlphaProductCatalog**




- ☐ Select **Deploy to Application Server** and click on **Next**




- ☐ Select **AlphaJCSConnection** as the Application Server and click **Next**




- ☐ Select **Deploy to selected instances in the domain. List Standalone Servers in the Cluster** and select **Alpha01A_cluster**. Click **Next**.




- ☐ Click on **Finish**



- ☐ **Monitor** the deployment in the log window. If the log window is not visible, from the top menu **select Window > Log**. Click on **Deployment** tab.




- ☐ To test the application, you will first need the **IP** of the Oracle Traffic Director (OTD) Server. If your Java Cloud Service Console is not already visible, navigate to it using either the console dropdown or from the main dashboard by clicking on **Open Service Console** for the **Java Cloud Service**



- ☐ Select the **Cloud icon** next to **Alpha01A-JCS** in the list of Services




- ☐ Write down the **Public IP Address** of **Load Balancer**. (Note: if the load balance is not visible, click on the refresh icon  until the Load Balancer is visible)



- ☐ Using the **Load Balance Public IP**, enter the following URL:

`https://<loadBalancerIp>/AlphaOffice/jersey/AlphaOfficeAccess/Products/getProducts`

- ☐ If you receive a message that the connection is Untrusted, as before, click on "I Understand the Risks," and add the Exception




```

- <ProductAPIList>
  - <products>
    <categoryId>1011</categoryId>
    <costPrice>3.19</costPrice>
    - <externalUrl>
      Images/OfficeSupplyProducts/Write/Write-Crayola_Markers.jpg
    </externalUrl>
    <listPrice>4</listPrice>
    <minPrice>2</minPrice>
    <parentCategoryId>1002</parentCategoryId>
    <productId>1039</productId>
    - <productName>
      Crayola Original Markers - Broad Line - Classic Colors


```

- ☐ If you receive an error, double check all previous steps especially ones where you need to click "Activate Changes" in weblogic. Drag this URL to your Browser's bookmark bar for later use



- ☐ You can also test out the Student code you modified, checked into the Developer Service and then deployed to the JCS. Enter the following URL from your browser, replacing **<Studentxx>** with the number you were assigned:

`https://<loadBalancerIp>/AlphaOffice/jersey/AlphaOfficeAccess/Studentxx/sayHello`



John Smith - You have deployed a REST api to the Oracle Public Cloud


Deleting Alpha01B-JCS


Freeing up Resources by Delete Alpha01B-JCS


STEP 15: Delete the JCS Instance created during lab 100

If you created a JCS Instance in Lab 100, and you desire to continue with the lab 300 (when you will “Scale Out” Alpha01A-JCS Server), then due to capacity restrictions placed on your Student Account Domains, you will need to delete the JCS Instance you created in Lab 100.

- ☐ If your Java Cloud Service Console is not already visible, navigate to it using either the console dropdown or from the main dashboard by clicking on **Open Service Console** for the **Java Cloud Service**



- ☐ From the list of JCS Instances, **click** on icon  located on the right for the **Alpha01B-JCS** instances that you created during lab 100. **Ensure** that you are **deleting the 01B instance**. Select **Delete Service**.



- ☐ Enter **sys** for the Database Administration user, and **Alpha2014_** for the password. **Select** the **Force Delete** check box, and **click** on the **Delete Service button**.

Delete Service

Deleting the instance Alpha01B-JCS will remove all of its servers and associated storage.

Provide the Database Administrator username and password.
This is the Database Administrator username and password provided for the Fusion Middleware schema when the service was created.



* Database Administrator Username

* Database Administrator Password

* Force Delete ☒ ?

Delete Cancel

- ☐ Your Alpha01B-JCS instance should now be in a Terminating state

Services			
Search by service name		Create Service	
 <p>Alpha01B-JCS Status: Terminating Version: 12.1.3.0.2 Edition: Enterprise Edition JDK: 1.7.0_76</p>	<p>Nodes: 2 Load Balancer: Configured Created On: May 28, 2015 7:14:43 PM UTC</p>	<p>OCPUs: 2 Memory: 15 GB Storage: 72 GB</p>	
 <p>Alpha01A-JCS Version: 12.1.3.0.2 Edition: Enterprise Edition JDK: 1.7.0_76</p>	<p>Nodes: 2 Load Balancer: Configured Created On: May 28, 2015 3:20:44 PM UTC</p>	<p>OCPUs: 2 Memory: 15 GB Storage: 72 GB</p>	

- ☐ This Lab is completed.