Lënda: Algoritmet dhe Strukturat e të Dhënave

Java 8 – String Sorts (LSD, MSD) and Tries

Detyra 1. Të sortohen stringjet e mëposhtme duke përdorur LSD String Sort:

TRUE, FEEL, DOWN, BLUE, GOOD, BYES, TREE, FIND, TRIE, FALL, KNIT, KNAP.

Detyra 2. Të sortohen stringjet e mëposhtme duke përdorur LSD String Sort:

dance, amber, zebra, flame, dealt, alive, zesty, fudge, dozen, arrow

Detyra 3: Të sortohen stringjet e mëposhtme duke përdorur LSD String Sort:

1406, 1998, 2211, 1997, 2503, 3664, 4567, 5321, 6427, 1312

Detyra 3. Të sortohen stringjet e mëposhtme duke përdorur MSD String Sort:

EDDIE, JOHN, MAYER, EDWARD, ED, MAYO, JORJA, SMITH, STALEY, DANIEL, CAESAR, DANNY, DIO, CHET

Detyra 4. Të sortohen stringjet e mëposhtme duke përdorur MSD String Sort:

APPLE, CARROT, STRAWBERRY, BANANA, CUCUMBER, SALMON, ASPARAGUS, TOMATO, ORANGE, SPINACH

Detyra 5. Të konstruktohen Trie dhe TST duke përdorur stringjet e mëposhtme:

HARRY, POTTER, KIT, HARRINGTON, WIZARDRY, HEDWIG, HAROLD, WITCH, HOGWARTS, KITKAT, POTTERHEAD, PORCH, WEASLEY, WIZARD, POTIONS

a) delete(“POTTER)

b) delete(“WIZARDRY”)

c) delete(“HOGWARTS”)

d) delete(“KITTEN”)

Detyra 6. Të konstruktohen Trie dhe TST duke përdorur stringjet e mëposhtme:

REARVIEW, NEVER, BETTER, MIND, RELEASE, MANNER, NEURON, BLOOD, NEUTRON, MINDFUL, MINNIE, RELATION, BLACK, BETTERMAN, REAR

a) delete(“NEVER”)

b) delete(“REARVIEW”)

c) delete(“MIND”)

d) delete(“MINDFUL”)

e) delete(“BETTERMAN”)