Stack Overflow requires external JavaScript from another domain, which is blocked or failed to load.

X

Facebook

Learn, Share, Build

Each month, over 50 million developers come to Stack Overflow to learn, share their knowledge, and build their careers.

Google

OR

Join the world's largest developer community.

Convert python list with None values to numpy array with nan values

I am trying to convert a list that contains numeric values and None values to numpy.array, such that None is replaces with numpy.nan.

For example:


```
my_list = [3,5,6,None,6,None]
# My desired result:
my_array = numpy.array([3,5,6,np.nan,6,np.nan])
```

Naive approach fails:

```
>>> my_list
[3, 5, 6, None, 6, None]
>>> np.array(my_list)
array([3, 5, 6, None, 6, None], dtype=object) # very limited
>>> _ * 2
Traceback (most recent call last):
    File "<stdin>", line 1, in <module>
TypeError: unsupported operand type(s) for *: 'NoneType' and 'int'
>>> my_array # normal array can handle these operations
array([ 3,  5,  6.,  nan,  6.,  nan])
>>> my_array * 2
array([ 6.,  10.,  12.,  nan,  12.,  nan])
```

What is the best way to solve this problem?

python numpy



2 Answers

You simply have to explicitly declare the data type:

```
>>> my_list = [3, 5, 6, None, 6, None]
>>> np.array(my_list, dtype=np.float)
array([ 3., 5., 6., nan, 6., nan])
```

answered Oct 18 '13 at 18:10



I had a feeling that I was missing something simple...Thank You - Akavall Oct 18 '13 at 18:12

The problem with this approach is that it only works for float for which nan is defined and not for dtype int. – Andrzej Pronobis May $20\,15$ at 2:14

Please see my question stackoverflow.com/questions/30339214/... on that problem exactly. – Andrzej Pronobis May 20 '15 at 2:35

Stack Overflow requires external JavaScript from another domain, which is blocked or failed to load.

What about

 $my_array = np.array(map(lambda x: numpy.nan if x==None else x, my_list))$

answered Oct 18 '13 at 18:07

