










 [googlesamples](#) / [android-ndk](#)Branch: **master** ▾[android-ndk](#) / [nn_sample](#) /[Create new file](#)[Upload files](#)[Find file](#)[History](#) **ggfan** Merge remote-tracking branch 'github/master' ...

Latest commit ecd28f0 on 19 Dec 2017

..


 app	Merge remote-tracking branch 'github/master'	3 months ago
 gradle/wrapper	Simple NN API code sample	3 months ago
 .gitignore	Simple NN API code sample	3 months ago
 README.md	Merge pull request #463 from miaowang14/master	3 months ago
 build.gradle	Simple NN API code sample	3 months ago
 gradle.properties	Simple NN API code sample	3 months ago
 gradlew	Simple NN API code sample	3 months ago
 gradlew.bat	Simple NN API code sample	3 months ago
 screenshot.png	Merge pull request #463 from miaowang14/master	3 months ago
 settings.gradle	Simple NN API code sample	3 months ago

 [README.md](#)

Android Neural Networks API Sample

Android Neural Networks API (NN API) Sample demonstrates basic usages of NN API with a simple model that consists of three operations: two additions and a multiplication.

The sums created by the additions are the inputs to the multiplication. In essence, we are creating a graph that computes: $(\text{tensor0} + \text{tensor1}) * (\text{tensor2} + \text{tensor3})$.



Two of the four tensors, tensor0 and tensor2 being added are constants, defined in the model. They represent the weights that would have been learned during a training process, loaded from `model_data.bin`.

The other two tensors, tensor1 and tensor3 will be inputs to the model. Their values will be provided when we execute the model. These values can change from execution to execution.

Besides the two input tensors, an optional fused activation function can also be defined for ADD and MUL. In this example, we'll simply set it to NONE.

The model then has 8 operands:

- 2 tensors that are inputs to the model. These are fed to the two ADD operations.
- 2 constant tensors that are the other two inputs to the ADD operations.
- 1 fuse activation operand reused for the ADD operations and the MUL operation.
- 2 intermediate tensors, representing outputs of the ADD operations and inputs to the MUL operation.
- 1 model output.

Pre-requisites


- Android Studio 3.0+.
- NDK r16+.
- Android API 27+.

Getting Started

1. [Download Android Studio](#)
2. Launch Android Studio.
3. Open the sample directory.
4. Click *Tools/Android/Sync Project with Gradle Files*.
5. Click *Run/Run 'app'*.

Screenshots





Support

If you've found an error in these samples, please [file an issue](#).

Patches are encouraged, and may be submitted by [forking this project](#) and submitting a pull request through GitHub. Please see [CONTRIBUTING.md](#) for more details.

- [Stack Overflow](#)
- [Google+ Community](#)
- [Android Tools Feedbacks](#)

License

Copyright 2017 Google, Inc.

Licensed to the Apache Software Foundation (ASF) under one or more contributor license agreements. See the NOTICE file distributed with this work for additional information regarding copyright ownership. The ASF licenses this file to you under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at

<http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.