You are reading documentation for the unreleased version of Matplotlib. Try searching for the released version of this page instead?



Fork me on GitHub

Version 2.1.1.post1118+gf867e21

home | examples | tutorials | pyplot | docs » modules | index

Plotting categorical variables

How to use categorical variables in Matplotlib.

Many times you want to create a plot that uses categorical variables in Matplotlib. Matplotlib allows you to pass categorical variables directly to many plotting functions, which we demonstrate below.


```
import matplotlib.pyplot as plt

data = {'apples': 10, 'oranges': 15, 'lemons': 5, 'limes': 20}
names = list(data.keys())
values = list(data.values())

fig, axs = plt.subplots(1, 3, figsize=(9, 3), sharey=True)
axs[0].bar(names, values)
axs[1].scatter(names, values)
axs[2].plot(names, values)
fig.suptitle('Categorical Plotting')
```

Related Topics
Documentation overview
This Page
Show Source
Quick search
Go

You are reading documentation for the unreleased version of Matplotlib. Try searching for the released version of this page instead?




This works on both axes:

```
cat = ["bored", "happy", "bored", "bored", "happy", "bored"]
dog = ["happy", "happy", "happy", "bored", "bored"]
activity = ["combing", "drinking", "feeding", "napping", "playing", "washing"]

fig, ax = plt.subplots()
ax.plot(activity, dog, label="dog")
ax.plot(activity, cat, label="cat")
ax.legend()

plt.show()
```

You are reading documentation for the unreleased version of Matplotlib. Try searching for the released version of this page instead?



© Copyright 2002 - 2012 John Hunter, Darren Dale, Eric Firing, Michael Droettboom and the Matplotlib development team; 2012 - 2017 The Matplotlib development team. Last updated on Jan 20, 2018. Created using Sphinx 1.6.6.