JEV ENGINEERING FOR CODING AGENTS

A Synthesis for Study

I. WHY YET ANOTHER AGENT

Coding agents inherit several architectural symptoms driven by model context limits and KV cache behaviour. Understanding these trade-offs is essential when designing explicit state mechanisms for informa?tion routing. The harness hands the decision layer the current state together with a predefined question.

Coding agents inherit several architectural symptoms driven by model context limits and KV cache behaviour. Understanding these trade-offs is essential when designing explicit state mechanisms for informa?tion routing. The harness hands the decision layer the current state together with a predefined question.

A. Routing Does Not Work

Coding agents inherit several architectural symptoms driven by model context limits and KV cache behaviour. Understanding these trade-offs is essential when designing explicit state mechanisms for informa?tion routing. The harness hands the decision layer the current state together with a predefined question.

Coding agents inherit several architectural symptoms driven by model context limits and KV cache behaviour. Understanding these trade-offs is essential when designing explicit state mechanisms for informa?tion routing. The harness hands the decision layer the current state together with a predefined question.

II. WHY YET ANOTHER AGENT

Coding agents inherit several architectural symptoms driven by model context limits and KV cache behaviour. Understanding these trade-offs is essential when designing explicit state mechanisms for informa?tion routing. The harness hands the decision layer the current state together with a predefined question.

Coding agents inherit several architectural symptoms driven by model context limits and KV cache behaviour. Understanding these trade-offs is essential when designing explicit state mechanisms for informa?tion routing. The harness hands the decision layer the current state together with a predefined question.

A. Routing Does Not Work

Coding agents inherit several architectural symptoms driven by model context limits and KV cache behaviour. Understanding these trade-offs is essential when designing explicit state mechanisms for informa?tion routing. The harness hands the decision layer the current state together with a predefined question.

Coding agents inherit several architectural symptoms driven by model context limits and KV cache behaviour. Understanding these trade-offs is essential when designing explicit state mechanisms for informa?tion routing. The harness hands the decision layer the current state together with a predefined question.

```
def route(state):
    chunks = score(state)
    return pick(chunks)
```

TABLE II Six design choices

Symptom	Why	Cost
Routing	KV cache	High
Compaction	Limits	Medium

III. WHY YET ANOTHER AGENT

Coding agents inherit several architectural symptoms driven by model context limits and KV cache behaviour. Understanding these trade-offs is essential when designing explicit state mechanisms for informa?tion routing. The harness hands the decision layer the current state together with a predefined question.

Coding agents inherit several architectural symptoms driven by model context limits and KV cache behaviour. Understanding these trade-offs is essential when designing explicit state mechanisms for informa?tion routing. The harness hands the decision layer the current state together with a predefined question.

A. Routing Does Not Work

Coding agents inherit several architectural symptoms driven by model context limits and KV cache behaviour. Understanding these trade-offs is essential when designing explicit state mechanisms for informa?tion routing. The harness hands the decision layer the current state together with a predefined question.

Coding agents inherit several architectural symptoms driven by model context limits and KV cache behaviour. Understanding these trade-offs is essential when designing explicit state mechanisms for informa?tion routing. The harness hands the decision layer the current state together with a predefined question.





Fig. 1. The harness overview

IV. WHY YET ANOTHER AGENT

Coding agents inherit several architectural symptoms driven by model context limits and KV cache behaviour. Understanding these trade-offs is essential when designing explicit state mechanisms for informa?tion routing. The harness hands the decision layer the current state together with a predefined question.

Coding agents inherit several architectural symptoms driven by model context limits and KV cache behaviour. Understanding these trade-offs is essential when designing explicit state mechanisms for informa?tion routing. The harness hands the decision layer the current state together with a predefined question.

A. Routing Does Not Work

Coding agents inherit several architectural symptoms driven by model context limits and KV cache behaviour. Understanding these trade-offs is essential when designing explicit state mechanisms for informa?tion routing. The harness hands the decision layer the current state together with a predefined question.

Coding agents inherit several architectural symptoms driven by model context limits and KV cache behaviour. Understanding these trade-offs is essential when designing explicit state mechanisms for informa?tion routing. The harness hands the decision layer the current state together with a predefined question.