

THE INVERSE PROBLEM

THE INVERSE PROBLEM

... and the use of Python-Implemented
Gradient Descent Techniques.

Tomás Gómez Álvarez-Arenas

OUTLINE

1. The Inverse Problem (IP):

Definition & examples

2. IP applications.

3. IP main elements.

4. IP optimization algorithms.

Gradient Descent algorithms (GDA) for IP.

5. A Python implementation of GDA for IP.

Examples.

Data



KNOWLEDGE

REGRESSION

INVERSE PROBLEM

MACHINE LEARNING

BAYESIAN INFERENCE

STATISTICAL ANALISYS

1. THE INVERSE PROBLEM: [IP] DEFINITION & EXAMPLES

DIRECT PROBLEM.

DIRECT PROBLEM

GIVEN:

Model parameters:

$$h_0 = 55 \text{ m}$$

$$g = 9.81 \text{ m/s}^2$$

&

Model (law):



$$h(t) = h_0 - \frac{1}{2} g t^2$$



PREDICT:

h at any t

BALL DROP





IP: DEFINITION.

INVERSE PROBLEM

EXTRACT:



Model parameters:
 h_0, g

GIVEN

Model (law):
 $h(t) = h_0 - 1/2 g t^2$ & h at some t




BALL DROP




IP EXAMPLE: GRAVITATIONAL WAVES

DIRECT PROBLEM





INVERSE PROBLEM

Parameters




IP EXAMPLE: ECHOGRAPHIC SIGNALS

DIRECT PROBLEM



INVERSE PROBLEM

Thicknesses (x2)
Densities (x2)
Elastic constant (x2)
Mechanical damping (x2)
Freq. dep. MD (x2)



2. IP APPLICATIONS

1. Obtention of model parameters .
2. Model confirmation.
3. Model selection.
Ockham's razor

3. IP MAIN ELEMENTS

INVERSE PROBLEM

MODEL (f):
 $y^*_i = f(\beta_j, x_i)$


ERROR FUNCTION
 ε

DATA
 x_i, y_i

**OPTIMIZATION
ALGORITHM**



$$\frac{\partial \varepsilon}{\partial \beta} = 0$$

$$\varepsilon_{min}$$



OUTPUT


MODEL PARAMETERS:
 β_j






IP vs ML

MACHINE LEARNING



INVERSE PROBLEM



INVERSE PROBLEM

Well-posed vs Ill-posed problems

Hadamard principles (Existence, uniqueness, stability)

"One can find the desired result to any degree of specified precision - provided one is prepared to work hard enough"*

*Working hard enough: making enough measurements with enough accuracy and then doing enough computations

4. IP OPTIMIZATION ALGORITHMS

OPTIMIZATION ALGORITHMS (just a few of them...)

NA: Newton algorithms.

GNA: Gauss-Newton algorithm.

BFGS: Broyden–Fletcher–Goldfarb–Shanno algorithm (1970).

NMA: Nelder-Mead algorithm (1965).

PA: Powell's algorithm (1964).

LMA: Levenberg–Marquardt algorithm (1944-1963).

GDA: Gradient Descent algorithms.

PYTHON IMPLEMENTATION OF OPTIMIZATION ALGORITHMS

(just a few of them...)

scipy.optimize

<http://docs.scipy.org/doc/scipy/reference/optimize.html>

Optimization and root finding

Sherpa

<http://cx.cfa.harvard.edu/contrib/sherpa47b/>

Levenberg-Marquardt, Nelder-Mead Simplex or Monte Carlo/Differential Evolution.

PyQt-Fit

<https://anaconda.org/pypi/pyqt-fit>

Regression toolbox and GUI

LMFIT

Non-Linear Least-Square Minimization and Curve-Fitting for Python

<https://lmfit.github.io/lmfit-py/>

High-level interface for scipy.optimize, extends LMA.

PYTHON IMPLEMENTATION OF OPTIMIZATION ALGORITHMS

(just a few of them...)

scipy.optimize

<http://docs.scipy.org/doc/scipy/reference/optimize.html>

Optimization and root finding

The `minimize` function supports the following methods:

- `minimize(method='Nelder-Mead')`
- `minimize(method='Powell')`
- `minimize(method='CG')`
- `minimize(method='BFGS')`
- `minimize(method='Newton-CG')`
- `minimize(method='L-BFGS-B')`
- `minimize(method='TNC')`
- `minimize(method='COBYLA')`
- `minimize(method='SLSQP')`
- `minimize(method='dogleg')`
- `minimize(method='trust-ncg')`

GRADIENT DESCENT ALGORITHMS FOR IPs.

PYTHON IMPLEMENTATION OF GRADIENT DESCENT ALGORITHMS

<https://github.com/mattnedrich/GradientDescentExample>

<http://tillbergmann.com/blog/articles/python-gradient-descent.html>

<http://scikit-learn.org/stable/modules/sgd.html>

<http://www.r-bloggers.com/r-and-python-gradient-descent/>

KEY ELEMENTS OF GDA FOR IP.

IP:

Data set: $y_i; x_i$

Model: $y = f([\beta_j], x)$

Error function

Optimization algorithm (GDA)

GDA:

Initial guess: β_j

Step size (constant / variable)

Constrains: $C_k(\beta^) = 0$*

The Gradient Descent approach for Inverse Problems.


1. Set initial guess

DATA

x_i, y_i

MODEL (f)

$y^*_i = f(\beta^0_j, x_i)$




$f(\{\beta^0_j, x_i\})$

$||y_i - f(\{\beta^0_j, x_i\})|| : \Delta\{\beta^0_j\}$: error is not minimum

The Gradient Descent approach for Inverse Problems.

2. Set a discrete
search volume
(DSV) around
IG



Set a discretization step: δ

DATA

x_i, y_i

MODEL (f)


$y^*_i = f(\beta_j \pm \delta, x_i)$

$f(\{\beta_j^0 \pm \delta, x_i\})$

$||y_i - f(\{\beta_j^0 \pm \delta, x_i\})|| : \Delta\{\beta_j^0 \pm \delta\}$: error

The Gradient Descent approach for Inverse Problems.

3. Search DSV.



DATA

x_i, y_i

MODEL (f)

$y_i^* = f(\beta_j \pm \delta, x_i)$


Dimension	Volume
N = 3:	27
N = 4:	81
N = 5:	243
N = 6:	729
N = 7:	2187
N = 8:	6561

$f(\{\beta_j^0 \pm \delta, x_i\})$

$||y_i - f(\{\beta_j^0 \pm \delta, x_i\})|| : \Delta\{\beta_j^0 \pm \delta\}$: error

The Gradient Descent approach for Inverse Problems.

4. Find next step



Systematic approach:

Search all points in V

Take $\{\beta_i\} / \Delta\{\beta_i\}_{\min}$

Stochastic approach:

Random search of V


Stop searching when:

$$\Delta\{\beta_i\} < \Delta\{\beta_0\}$$

	Systematic	Stochastic
Computational cost:	Cte. 3^N	Var. $1 \rightarrow 3^N$
Incremental improve:	Optimum	< Optimum
Avoid local minima:	??	May be
Same solution:	Yes	NO


The Gradient Descent approach for Inverse Problems.

5. Take a step.



Take a step: $2\vec{\delta} = 2(\vec{\beta}' - \vec{\beta}_0)$

$$\vec{\beta}_0 = \vec{\beta}_0 + 2\vec{\delta}$$



5. A PYTHON IMPLEMENTATION OF GDA FOR IPs.

... a simple code example built from scratch.

CODE DESCRIPTION

<https://github.com/PyDataMadrid2016/Conference-Info/>

[20160409 1530 The solution of inverse problems](#)

6. Examples.

Basic examples

Signals in time domain

Complex high dimensional problems

6. Examples (I)

Basic Examples.

Linear regression
Polynomial fitting

Example 1: Linear regression Run #1

Data:

$$y^* = a x + b + \text{noise}$$


$$a, b = (1.0, 10.0)$$

Model:

$$y = a x + b$$

Objective:

Find value of function parameters: (a, b)
that minimize the error (L2 norm) between
calculated (y) and data (y^*) .




Stochastic Gradient Descent (SGD)
Discretization step (DS): $\delta = 0.01$

Example 1: Linear regression Run #1

Path to fitting...
(in the parameters space)

Target value: (1.0, 10.0)

Initial guess: (1.5, 5.0)



```
GG.plot_pathN((GG2,GG3),(0,1),True,pa,pb)
```

Example 1: Linear regression Run #1

Target value: (1.0, 10.0)


Initial guess: (1.5, 5.0)

Run *GD*

Run *scipy.linregress*

Run *SGD* 200 times...

Only take $\text{Error} < \text{Error}_{\min} + 5\%$



`GG.plot_Bestcloud(tuple(GG_cloud),error_lim,(0,1),True,pa,pb)`

Example 1: Linear regression Run #1

Target value: (1.0, 10.0)


Initial guess: (1.5, 5.0)

Run *GD*

Run *scipy.linregress*

Run *SGD* 200 times...

Only take $\text{Error} < \text{Error}_{\min} + 0.5\%$



`GG.plot_Bestcloud(tuple(GG_cloud),error_lim,(0,1),True,pa,pb)`

Example 1: Linear regression Run #3

Target value: (1.0, 10.0)


Initial guess: (1.5, 5.0)

Run *GD*

Run *scipy.linregress*

Run *SGD* 200 times...

Only take $\text{Error} < \text{Error_min} + 0.5\%$



`GG.plot_Bestcloud(tuple(GG_cloud),error_lim,(0,1),True,pa,pb)`

Example 1: Linear regression Run #3

Target value: (1.0, 10.0)


Initial guess: (1.5, 5.0)

Run *GD*

Run *scipy.linregress*

Run *SGD* 200 times...

Only take $\text{Error} < \text{Error}_{\min} + 5\%$



`GG.plot_Bestcloud(tuple(GG_cloud),error_lim,(0,1),True,pa,pb)`

Example 2: Polynomial order 2

Data:


$$y^* = a x^2 + b x + c + \text{noise}$$

Model:

$$y = a x^2 + b x + c$$

Stochastic Gradient Descent (SGD)

$$\delta = 0.005$$



Example 2: Polynomial order 2

Path to fitting...
(in the parameters space)


Target value: (1.0, 3.0, 10.0)

Initial guess: (1.7, 2.7, 7.0)

Stochastic Gradient Descent (SGD)

$\delta = 0.005$

GG.plot_path2(GG2,(0,1),True,pa,pb)



Example 2: Polynomial order 2

Target value: (1.0, 3.0 10.0)


Initial guess: (1.7, 2.7, 7.0)

Run *GD*

Run *numpy.polyfit*

Run *SGD* 200 times...

Only take $\text{Error} < \text{Error}_{\min} + 10\%$



`GG.plot_Bestcloud(tuple(GG_cloud),error_lim,(0,1),True,pa,pb)`

Example 2: Polynomial order 2

Target value: (1.0, 3.0 10.0)


Initial guess: (1.7, 2.7, 7.0)

Run *GD*

Run *numpy.polyfit*

Run *SGD* 200 times...

Only take $\text{Error} < \text{Error_min} + 0.5\%$



`GG.plot_Bestcloud(tuple(GG_cloud),error_lim,(0,1),True,pa,pb)`

6. Examples (II)

Signals in the time domain.

Damped oscillator
Linear chirp
Linear-gained chirp

Example 3: Damped oscillator

Data:


$$y^* = (a \sin x + j b \cos x) \exp(-cx) + \text{noise}$$

Model:

$$y = (a \sin x + j b \cos x) \exp(-cx)$$

Stochastic Gradient Descent (SGD)

$$\delta = 0.005$$



Example 3: Damped oscillator

Target value: (2.0, 0.5, 0.1)

Initial guess: (1.5, 0.3, 0.2)


Run *GD*

Run *SGD* 50 times...

Stochastic Gradient Descent (SGD)

$\delta = 0.005$

`GG.plot_path2(GG2,(0,1),True,pa,pb)`



Example 4: Linear chirp

$$S(t) = w(t)\sin[\phi_0 + 2\pi f_1 t + \pi B/T t^2]$$

Initial guess error:


$$B/T \approx 10\%$$

$$f_1 \approx 20\%$$

$$\phi_0 \approx 0.4 \text{ rad}$$

Stochastic Gradient Descent (SGD)

$$\delta = 0.005$$



Example 4: Gained linear chirp

$$S(t) = w(t)\sin[\phi_0 + 2\pi f_1 t + \pi B/T t^2]$$

Initial guess error:


$$B/T \approx 10\%$$

$$f_1 \approx 20\%$$


$$\phi_0 \approx 0.4 \text{ rad}$$

Stochastic Gradient Descent (SGD)


$$\delta = 0.005$$




Path: 86 / 39 steps 0.05 / 0.05 s Error: 0.07 / Error: 0.09




Linear chirp



Path: 50 / 36 steps 0.02 / 0.07 s Error: 0.10 / Error: 0.10



Gained
linear chirp



Linear chirp

$$S(t) = w(t)\sin[\phi_0 + 2\pi f_1 t + \pi B/T t^2]$$

Initial guess error:

$B/T \approx 20\% \rightarrow$ trapped in loc. min.


$f_1 \approx 20\%$

$\phi_0 \approx 0.4$ rad


Increase δ : $0.005 \rightarrow 0.2$

Transform: FFT

Time domain \rightarrow frequency domain



Gained linear chirp



6. Examples (III)

Signals in the frequency domain.

Large dimensional problems

Echographic signal: single layer

Echographic signal: layered plate

Example 5: Ultrasonic transmission through a layer of tissue

$$S(t) = f(\beta, t) \xrightarrow{\text{FFT}} S^*(\omega) = f^*(\beta, \omega)$$

ω : frequency

$$\beta = \{t, \rho, v, \alpha, n\}$$

t : thickness


ρ : density

v : us velocity

α : us attenuation

n : variation of α with freq.

Dimension = 5 ($V_{\text{search}} = 242$ pts.)



Example 5: Ultrasonic transmission through a layer of tissue

$$S(t) = f(\beta, t) \xrightarrow{\text{FFT}} S^*(\omega) = f^*(M, L)$$

ω : frequency

$$\beta = \{t, \rho, v, \alpha, n\}$$

t : thickness


ρ : density

v : us velocity

α : us attenuation

n : variation of α with freq.

Dimension = 5 ($V_{\text{search}} = 242$ pts.)



Example 5: Ultrasonic transmission through a layer of tissue

$$S(t) = f(M, L) \xrightarrow{\text{FFT}} S^*(\omega) = f^*(M, L)$$

ω : frequency

M : medium: Z_m

L : layer of tissue t, ρ, v, α, n

t : thickness


ρ : density

v : us velocity

α : us attenuation

n : variation of α with freq

Dimension = 4 ($V_{\text{search}} = 81$ pts.)



Example 5: Ultrasonic transmission through a layer of tissue

$$S(t) = f(M, L) \xrightarrow{\text{FFT}} S^*(\omega) = f^*(M, L)$$

ω : frequency

M : medium: Z_m

L : layer of tissue t, ρ, v, α, n

t : thickness


ρ : density

v : us velocity



α : us attenuation

n : variation of α with freq

Dimension = 4 ($V_{\text{search}} = 81$ pts.)



Example 5: Ultrasonic transmission through a layer of tissue



`GG.plot_path2(GG2,(0,1),True,pa,pb)`

`GG.plot_Bestcloud(tuple(GG_cloud),error_lim,(0,1),True,pa,pb)`

Example 5: Ultrasonic transmission through a layer of tissue

$$S(t) = f(M, L) \xrightarrow{\text{FFT}} S^*(\omega) = f^*(M, L)$$

ω : frequency

M : medium: Z_m

L : layer of tissue t, ρ, v, α, n

t : thickness


ρ : density

v : us velocity



α : us attenuation

n : variation of α with freq

Dimension = 5 ($V_{\text{search}} = 242$ pts.)



Example 5: Ultrasonic transmission through a layer of tissue



`GG.plot_path2(GG2,(0,1),True,pa,pb)`

`GG.plot_Bestcloud(tuple(GG_cloud),error_lim,(0,1),True,pa,pb)`

Parameters separation/aggregation:

$$\beta_i, i = 1 \dots N; \quad 3^N - 1$$

P subsets of parameters (example P = 2):


$$\beta^1_i, i = 1 \dots K; \quad 3^K - 1$$

$$\beta^2_i, i = 1 \dots L; \quad 3^L - 1$$

$$M = K + L$$



Perform SGDA on β^1_i + early stop

Perform SGDA on β^2_i + early stop



Example 6: Ultrasonic transmission through a layered tissue

10 parameters in the model:
IG for them all
VS = 59049



Simplify the data set (reduction)



Simplify the model
(one layer: 5 params)

Apply parameters gathering
(3 + 2)

Solve the new IP (---)
early stop

Generate IG for whole IP
5 params → 10 params

Solve the whole IP



Solve the whole IP


Ill-posed problem
(infinite solutions)

Adding constrains:
(total thickness is know)
 $10 \rightarrow 9$

Ill-posed problem
(not unique solution).

IG

Further constrains.



Data



KNOWLEDGE

Q&A

BUT NOT: $IP[Q\&A] = A\&Q \rightarrow$ ILL-POSED