

<https://course.acciojob.com/idle?question=dbb19e7c-f100-4b90-9e98-b3c8916d3b29>

● EASY

● Max Score: 30 Points

-
-
-
-
-
-
-
-
-
-

Implement Queue using stack - Dequeue $O(1)$

Implement Queue using two stack s_1 and s_2 . You need to complete the push and pop function of Queue class. You are given 2 types of query 1 for push an integer into queue and 2 for enqueue the value from the queue and print.

Note: implement deQueue in $O(1)$

Input Format

First line contains q of queries.

Followed by q lines.

Query of type 1 is followed by an integer x to push element in the queue.

Query of type 2 is for dequeue the last value from the queue and print.

Output Format

Print the value for dequeue operations in the query given.

Example 1

Input

```
5
1 2
1 3
2
1 4
2
```

Output:

```
2 3
```

Explanation

First we push 2 , then for second query we push 3, for third query we dequeue 2 and print, for 4th query we push 4 and for 5th query we dequeue 3 and print.

Example 2

Input

```
3
2
1 2
2
```

Output:

```
-1 2
```

Explanation:

In the first query we don't have any element but we use dequeue query so we print -1, in the 2nd query we push 2 and in the 3rd we dequeue 2 and print 2.

Constraints

1 <= Total number of queries <= 100

1 <= value in each query <= 100

Topic Tags

- **Queues**
- **Stacks**

My code

```
// n java
```

```
import java.io.*;
```

```
import java.util.*;
```

```
class StackQueue
```

```
{
```

```
    Stack<Integer>st1;
```

```
    Stack<Integer>st2;
```

```
    public StackQueue()
```

```
    {
```

```
        st1=new Stack<>();
```

```
        st2=new Stack<>();
```

```
    }
```

```
//Function to push an element in queue by using 2 stacks.
```

```
void Push(int x)
```

```
{
```

```

        //Write your code here
        st1.add(x);
    }
    //Function to pop an element from queue by using 2 stacks.
    int Pop()
    {
        int t=-1;
        //Write your code here
        while(!st1.isEmpty())
            st2.add(st1.pop());
        if(!st2.isEmpty())
            t=st2.pop();
        while(!st2.isEmpty())
            st1.add(st2.pop());
        return t;
    }
}

public class Main {
    public static void main(String args[]) throws IOException {
        Scanner sc = new Scanner(System.in);
        StackQueue s = new StackQueue();
        int q = sc.nextInt();
        ArrayList<Integer> ans= new ArrayList<>();
        while(q>0)
        {
            int QueryType = sc.nextInt();
            if(QueryType == 1)
            {
                int a = sc.nextInt();
                s.Push(a);
            }
        }
    }
}

```

```
    }  
    else if(QueryType == 2)  
        ans.add(s.Pop());  
    q--;  
    }  
    for(int x:ans)  
        System.out.print(x+" ");  
    System.out.println();  
    }  
}
```