(f)	What is the use of subnet mask in I	Maria de la compania					
(g)	be 32 KB when a timeout occurs.				(d) 192.53.40.7 (e) 192.53.56.7		
	segment size used is 2 KB. Find the time taken (in msec) by the TCP connection to get back to 32 KB congestion window.					destination host over a fixed route. List and explain the delay components in the end-to-end delay. Which of these delays are constant and which are variable?	[4]
(h)							
(i)	Explain through an example the use of NAT (Network Address Translation) in a network. What would be the type for the Resource Record (RR) that contains the canonical host-name for a host?						5.47
				4.			[4]
(j)					(b)	What is the difference between centralized P2P	[4]
	SECTION-B					network and decentralized P2P network?	
(a)	How does TCP determine the time-out for implicit detection of packet loss? Be brief.		[4] 5.	(a)		[4]	
(b)	Sketch the flow of a typical email from Alice to Bob. Assume that Alice and Bob are on different "networks" (say, they are in different parts of the world). Identify the key components (both hardware and software) and protocols in the flow.		[4]			to the Internet (be precise).	
					(b)	What do you mean by congestion control and congestion avoidance? Briefly explain the different congestion control mechanisms used in the network.	[4]
(a)	A router has the following (CIDR) entries in its routing table:		[4]	6.	(a)	How long does it take a packet of length 1000 bytes to propagate over a link of distance 2,500 km, propagation speed 2.5x10 ⁸ m/s, and transmission rate 2 Mbps? More	[4]
	Address/mask	Next hop			(b)	generally, how long does it take a packet of length L to propagate over a link of distance d, propagation speed s, and transmission rate R bps? Does this delay depend on packet length? Does this delay depend on transmission rate? Suppose Alice, with a web-based e-mail account send a message to Bob, who accesses his mail from his mail	[4]
	135.46.56.0/22	Interface 0					
	135.46.60.0/22	Interface 1					
	192.53.40.0/23	Router 1					
	default	Router 2					
	For each of the following IP addresses, what does the router do if a packet with that address arrives? (a) 135.46.63.10					server using POP3. Discuss how the message gets from Alice's host to Bob's host.	
	(g) (h) (i) (j)	(g) Let the size of congestion window be 32 KB when a timeout occurs. of the connection is 100 msec segment size used is 2 KB. Find msec) by the TCP connection to congestion window. (h) Difference between Stop and Waselective Repeat. (i) Explain through an example the use Address Translation) in a network. (j) What would be the type for the Resthat contains the canonical host-names SECTION-B (a) How does TCP determine the time detection of packet loss? Be brief. (b) Sketch the flow of a typical email Assume that Alice and Bob are on (say, they are in different parts of the key components (both hardward protocols in the flow. (a) A router has the following (CIDR) table: Address/mask 135.46.56.0/22 135.46.60.0/22 192.53.40.0/23 default For each of the following IP address router do if a packet with that address	 (g) Let the size of congestion window of a TCP connection be 32 KB when a timeout occurs. The round-trip time of the connection is 100 msec and the maximum segment size used is 2 KB. Find the time taken (in msec) by the TCP connection to get back to 32 KB congestion window. (h) Difference between Stop and Wait, Go-Back-N and Selective Repeat. (i) Explain through an example the use of NAT (Network Address Translation) in a network. (j) What would be the type for the Resource Record (RR) that contains the canonical host-name for a host? SECTION-B (a) How does TCP determine the time-out for implicit detection of packet loss? Be brief. (b) Sketch the flow of a typical email from Alice to Bob. Assume that Alice and Bob are on different "networks" (say, they are in different parts of the world). Identify the key components (both hardware and software) and protocols in the flow. (a) A router has the following (CIDR) entries in its routing table: Address/mask Next hop 135.46.56.0/22 Interface 0 135.46.60.0/22 Interface 1 192.53.40.0/23 Router 1 default Router 2 For each of the following IP addresses, what does the router do if a packet with that address arrives? 	(g) Let the size of congestion window of a TCP connection be 32 KB when a timeout occurs. The round-trip time of the connection is 100 msec and the maximum segment size used is 2 KB. Find the time taken (in msec) by the TCP connection to get back to 32 KB congestion window. (h) Difference between Stop and Wait, Go-Back-N and Selective Repeat. (i) Explain through an example the use of NAT (Network Address Translation) in a network. (j) What would be the type for the Resource Record (RR) that contains the canonical host-name for a host? SECTION-B (a) How does TCP determine the time-out for implicit detection of packet loss? Be brief. (b) Sketch the flow of a typical email from Alice to Bob. Assume that Alice and Bob are on different "networks" (say, they are in different parts of the world). Identify the key components (both hardware and software) and protocols in the flow. (a) A router has the following (CIDR) entries in its routing table: Address/mask Next hop 135.46.56.0/22 Interface 0 135.46.60.0/22 Interface 1 192.53.40.0/23 Router 1 default Router 2 For each of the following IP addresses, what does the router do if a packet with that address arrives?	(g) Let the size of congestion window of a TCP connection be 32 KB when a timeout occurs. The round-trip time of the connection is 100 msec and the maximum segment size used is 2 KB. Find the time taken (in msec) by the TCP connection to get back to 32 KB congestion window. (h) Difference between Stop and Wait, Go-Back-N and Selective Repeat. (i) Explain through an example the use of NAT (Network Address Translation) in a network. (j) What would be the type for the Resource Record (RR) that contains the canonical host-name for a host? SECTION-B (a) How does TCP determine the time-out for implicit detection of packet loss? Be brief. (b) Sketch the flow of a typical email from Alice to Bob. Assume that Alice and Bob are on different "networks" (say, they are in different parts of the world). Identify the key components (both hardware and software) and protocols in the flow. (a) A router has the following (CIDR) entries in its routing table: Address/mask Next hop 135.46.56.0/22 Interface 0 135.46.60.0/22 Interface 1 192.53.40.0/23 Router 1 default Router 2 For each of the following IP addresses, what does the router do if a packet with that address arrives?	(g) Let the size of congestion window of a TCP connection be 32 KB when a timeout occurs. The round-trip time of the connection is 100 msec and the maximum segment size used is 2 KB. Find the time taken (in msec) by the TCP connection to get back to 32 KB congestion window. (h) Difference between Stop and Wait, Go-Back-N and Selective Repeat. (i) Explain through an example the use of NAT (Network Address Translation) in a network. (j) What would be the type for the Resource Record (RR) that contains the canonical host-name for a host? SECTION-B (a) How does TCP determine the time-out for implicit detection of packet loss? Be brief. (b) Sketch the flow of a typical email from Alice to Bob. Assume that Alice and Bob are on different "networks" (say, they are in different parts of the world). Identify the key components (both hardware and software) and protocols in the flow. (a) A router has the following (CIDR) entries in its routing table: Address/mask Next hop 135.46.56.0/22 Interface 0 135.46.60.0/22 Interface 1 192.53.40.0/23 Router 1 default Router 2 For each of the following IP addresses, what does the router do if a packet with that address arrives?	(g) Let the size of congestion window of a TCP connection be 32 KB when a timeout occurs. The round-trip time of the connection is 100 msec and the maximum segment size used is 2 KB. Find the time taken (in msec) by the TCP connection to get back to 32 KB congestion window. (h) Difference between Stop and Wait, Go-Back-N and Selective Repeat. (i) Explain through an example the use of NAT (Network Address Translation) in a network. (j) What would be the type for the Resource Record (RR) that contains the canonical host-name for a host? SECTION-B (a) How does TCP determine the time-out for implicit detection of packet loss? Be brief. (b) Sketch the flow of a typical email from Alice to Bob. Assume that Alice and Bob are on different "networks" (say, they are in different parts of the world). Identify the key components (both hardware and software) and protocols in the flow. (a) 135.46.50.022 Interface 0 135.46.50.0/22 Interface 1 135.46.50.0/22 Interface 1 135.46.50.0/22 Interface 1 157.46.50.0/23 Router 1 default Router 2 For each of the following IP addresses, what does the router do if a packet with that address arrives?

KIIT-DU/2019/SOT/Spring End Semester Examination-2019 (2)

KIIT-DU/2019/SOT/Spring End Semester Examination-2019

- 7_ (a) One class B network on the Internet has a subnet mask of 255.255.240.0. What is the maximum number of hosts per subnet?
 - (b) Consider a network with five nodes, N1 to N5, as shown below.

The network uses a Distance Vector Routing. Once the routes have stabilized, the distance vectors at different nodes are as following.



N1:(0, 1, 7, 8, 4)

N2:(1, 0, 6, 7, 3)

N3:(7, 6, 0, 2, 6) N4:(8, 7, 2, 0, 4)

N5:(4, 3, 6, 4, 0)

Each distance vector is the distance of the best known path at that instance to nodes, N1 to N5, where the distance to itself is 0. Also, all links are symmetric, and the cost is identical in both directions. In each round, all nodes exchange their distance vectors with their respective neighbors. Then all nodes update their distance vectors. In between two rounds, any change in cost of a link will cause the two incident nodes to

The cost of link N2-N3 reduces to 2 (in both directions). After the next round of update what will be the new distance vector at node, N3?

8. (a) What is the formula to calculate the number of redundancy bits required to correct a bit error in a given number of data bits? Explain an error correction technique on the following data: Data send 1001101 and data received 1000101.

change only that entry in their distance vectors.

(b) Why is it that voice and video traffic is often sent over TCP rather than UDP in today's internet?

[4]

[4]

[4]

[4]

6th Sem B. Tech & B. Tech Dual Deg. CN 173001/17-603 (CSE, IT CSCE, E&CSc)

SPRING END SEMESTER EXAMINATION-2019 6th Semester B.Tech & B.Tech Dual Degree

COMPUTER NETWORKS IT3001 / IT-603

(For 2017(L.E), 2016 & Previous Admitted Batches)

Time: 3 Hours

Full Marks: 60

Answer any SIX questions.

Question paper consists of four sections-A, B, C, D.

Section A is compulsory.

Attempt minimum one question each from Sections B, C, D.

The figures in the margin indicate full marks.

Candidates are required to give their answers in their own words as far as practicable and all parts of a question should be answered at one place only.

SECTION-A

1. Answer the following questions:

- $[2 \times 10]$
- (a) Why there is a need to establish the connection before the transmission of message? Briefly write the advantages and limitations of connectionorientedprotocol.
- (b) Distinguish between CSMA/CD and CSMA/CA.
- (c) What is the need of UDP? Would it not have been enough to just let user processes send raw IP packets? Explain in few sentences.
- Explain a way to do reassembly of IP fragments at the destination.
- (e) With non-persistent connection between browser and origin server, is it possible for a single TCP segment to carry two distinct HTTP request message? Explain your answer.

. .