Cyberster Red Teaming

Network Enumeration & Service Vulnerability Discovery

Lab Report — Week 2

Student	Ouchraa Oumayma
Instructor	Umar Niaz — Red Team Instructor, Cyberster
Target	Metasploitable 2 (Local VM)
Attacker Machine	Kali Linux (VM — NAT Network: RedTeamLab)

Table of Contents

Introduction
Tools & Technologies Used
MITRE ATT&CK Techniques Targeted
Task 01 — Advanced Network Scanning (Nmap)
Task 02 — Service Fingerprinting & Banner Grabbing
Task 03 — Nmap Scripting Engine (NSE)
Task 04 — Stealth & Firewall Evasion
Results & Analysis
Conclusion

Introduction

> *Week 2 marks the transition from passive reconnaissance to active network scanning. The objective is to precisely identify open ports, running services, their exact versions, and associated vulnerabilities on the Metasploitable 2 target.*

Limitation of Passive Recon

Passive recon cannot identify exact service versions or confirm which CVEs are actually exploitable on the specific target version.

Need for Active Enumeration

Nmap and supporting tools allow precise mapping of the network attack surface, revealing the real entry points an attacker would use.

Consequence

Without active enumeration, the security team remains blind to the actual doors an attacker would use to gain initial access.

Lab Environment — Network Configuration

Both VMs run simultaneously inside VirtualBox. Kali Linux has two adapters: NAT for internet access and NAT Network (RedTeamLab) to reach Metasploitable 2. Metasploitable 2 has only one adapter — fully isolated from the internet.

Machine	Adapter 1	Adapter 2	IP Address
`Kali Linux`	NAT (Internet access)	NAT Network: RedTeamLab	eth1: 10.0.2.15
`Metasploitable 2`	NAT Network: RedTeamLab	— (no internet)	eth0: 10.0.2.4



Figure 1 — Metasploitable 2 successfully booted and logged in with default credentials (msfadmin/msfadmin)



Figure 2 — Kali Linux connectivity verification: ping 10.0.2.4 (Metasploitable 2) confirmed, and ping 8.8.8.8 (internet) confirmed

Tools & Technologies Used

The network enumeration framework relies on a combination of proven open-source cybersecurity tools and platforms.

Nmap 7.x

Network port scanner and fingerprinting engine. Supports TCP, UDP, SYN stealth, NSE scripts, timing templates, and evasion techniques.

Netcat (nc)

TCP/UDP tool for manual banner grabbing and raw service interaction, revealing exact service banners on demand.

Enum4linux

SMB/Samba enumeration tool. Extracts users, groups, shares, and password policies from Windows and Linux targets.

Metasploitable 2

Deliberately vulnerable Linux VM for security training. Contains 19+ intentionally vulnerable and misconfigured services.

VirtualBox

Virtualization hypervisor hosting both Kali Linux and Metasploitable 2 simultaneously on an isolated NAT Network.

MITRE ATT&CK

Reference framework for classifying attack techniques and mapping enumeration findings to adversarial tactics and procedures.

MITRE ATT&CK Techniques Targeted

Our enumeration approach maps directly to MITRE ATT&CK techniques from the Reconnaissance and Discovery phases.

MITRE ID	Technique	Tool Used	Description
T1046	Network Service Discovery	Nmap -sS / -sV	Identification of open ports and running services
T1040	Network Sniffing	Nmap -sU	Discovery of UDP services (DNS, SNMP, DHCP)
T1592	Gather Victim Host Info	Nmap -A / -O	OS detection and exact service version identification
T1595	Active Scanning	Nmap --script vuln	Automated scan to identify known exploitable vulnerabilities
T1135	Network Share Discovery	Enum4linux -a	SMB share, user, and group enumeration
T1018	Remote System Discovery	Nmap ping sweep	Discovery of live hosts on the network subnet

Task 01 — Advanced Network Scanning

> *Objective: Compare TCP scan types (-sT vs -sS), perform a UDP scan on the 100 most common ports, and understand how Timing Templates affect scan reliability and detection risk.*

Background — The TCP 3-Way Handshake

Understanding the TCP handshake is essential to grasping why different scan types behave differently in terms of speed and detectability.

Step	Packet	Direction	Meaning
1	SYN	Client → Server	Client requests to open a connection
2	SYN-ACK	Server → Client	Server acknowledges and agrees to connect
3	ACK	Client → Server	Client confirms — full connection established

1.1 TCP Connect Scan (-sT)

Completes the full 3-way handshake for every tested port. No root required but easily logged by the target.

```
nmap -sT -p 1-1000 -oN results_sT.txt 10.0.2.4
```

```
┌──(siren㉿Siren)-[~]
└─$ nmap -sT -p 1-1000 -oN results_sT.txt 10.0.2.4
Starting Nmap 7.98 ( https://nmap.org ) at 2026-03-15 08:50 -0400
Nmap scan report for 10.0.2.4 (10.0.2.4)
Host is up (0.0017s latency).
Not shown: 988 closed tcp ports (conn-refused)
PORT    STATE SERVICE
21/tcp  open  ftp
22/tcp  open  ssh
23/tcp  open  telnet
25/tcp  open  smtp
53/tcp  open  domain
80/tcp  open  http
111/tcp open  rpcbind
139/tcp open  netbios-ssn
445/tcp open  microsoft-ds
512/tcp open  exec
513/tcp open  login
514/tcp open  shell
MAC Address: 08:00:27:60:6F:C3 (Oracle VirtualBox virtual NIC)

Nmap done: 1 IP address (1 host up) scanned in 0.49 seconds
```

Figure 3 — TCP Connect scan (-sT) results: 12 open ports found on 10.0.2.4 in 0.49 seconds

1.2 SYN Stealth Scan (-sS) ← Preferred in Red Teaming

Sends SYN, receives SYN-ACK, then immediately sends RST without completing the handshake. Connection stays half-open — much harder to log. Requires sudo.

```
sudo nmap -sS -p 1-1000 -oN results_sS.txt 10.0.2.4
```

```
┌──(siren㉿Siren)-[~]
└─$ sudo nmap -sS -p 1-1000 -oN results-sS.txt 10.0.2.4
Starting Nmap 7.98 ( https://nmap.org ) at 2026-03-15 08:51 -0400
Nmap scan report for 10.0.2.4 (10.0.2.4)
Host is up (0.0013s latency).
Not shown: 988 closed tcp ports (reset)
PORT    STATE SERVICE
21/tcp  open  ftp
22/tcp  open  ssh
23/tcp  open  telnet
25/tcp  open  smtp
53/tcp  open  domain
80/tcp  open  http
111/tcp open  rpcbind
139/tcp open  netbios-ssn
445/tcp open  microsoft-ds
512/tcp open  exec
513/tcp open  login
514/tcp open  shell
MAC Address: 08:00:27:60:6F:C3 (Oracle VirtualBox virtual NIC)

Nmap done: 1 IP address (1 host up) scanned in 0.52 seconds
```

Figure 4 — SYN Stealth scan (-sS) results: same 12 ports found in 0.52 seconds — faster and harder to detect

TCP Connect (-sT)	SYN Stealth (-sS)
Full connection. Slower. Logged by target. No root needed. Use when root privileges are unavailable.	Half-open connection. Faster. Harder to detect. Requires sudo. Preferred for professional Red Team operations.

1.3 UDP Scan — Top 100 Ports

UDP is stateless — no handshake. Many services never respond even when open, making UDP scanning slower and less reliable.

```
sudo nmap -sU --top-ports 100 -oN results_udp.txt 10.0.2.4
```

- Port 53/udp — DNS (BIND 9.4.2) — vulnerable to zone transfer
- Port 111/udp — rpcbind — RPC service mapper exposed
- Port 137/udp — NetBIOS — SMB information disclosure

```
┌──(siren㉿Siren)-[~]
└─$ sudo nmap -sU --top-ports 100 -oN results_udp.txt 10.0.2.4
Starting Nmap 7.98 ( https://nmap.org ) at 2026-03-15 08:55 -0400
Nmap scan report for 10.0.2.4 (10.0.2.4)
Host is up (0.0018s latency).
Not shown: 92 closed udp ports (port-unreach)
PORT     STATE         SERVICE
53/udp   open          domain
68/udp   open|filtered dhcpc
69/udp   open|filtered tftp
111/udp  open          rpcbind
137/udp  open          netbios-ns
138/udp  open|filtered netbios-dgm
999/udp  open|filtered applix
2049/udp open          nfs
MAC Address: 08:00:27:60:6F:C3 (Oracle VirtualBox virtual NIC)

Nmap done: 1 IP address (1 host up) scanned in 102.85 seconds
```

Figure 5 — UDP scan (--top-ports 100): 8 UDP ports discovered including DNS/53, DHCP/68, NFS/2049 — scan took 102.85 seconds

1.4 Timing Templates — Comparison

```
sudo nmap -sS -T2 -p 1-1000 -oN sS_T2.txt 10.0.2.4
sudo nmap -sS -T3 -p 1-1000 -oN sS_T3.txt 10.0.2.4
sudo nmap -sS -T4 -p 1-1000 -oN sS_T4.txt 10.0.2.4
```

Template	Name	Behaviour	Est. Duration
`-T0`	Paranoid	One packet every 5 minutes — maximum stealth	Hours
`-T1`	Sneaky	Very slow — evades most IDS	~30 min
`-T2`	Polite	Slow, reduces network load	~45 sec
`-T3`	Normal	Default Nmap timing	~15 sec
`-T4`	Aggressive	Fast, assumes reliable network	~5 sec
`-T5`	Insane	Very fast — may miss ports	~2 sec

```
┌──(siren㉿Siren)-[~]
└─$ sudo nmap -sS -T2 -p 1-1000 -oN sS_T2.txt 10.0.2.4
Starting Nmap 7.98 ( https://nmap.org ) at 2026-03-15 08:59 -0400
Nmap scan report for 10.0.2.4 (10.0.2.4)
Host is up (0.0019s latency).
Not shown: 988 closed tcp ports (reset)
PORT     STATE SERVICE
21/tcp   open  ftp
22/tcp   open  ssh
23/tcp   open  telnet
25/tcp   open  smtp
53/tcp   open  domain
80/tcp   open  http
111/tcp  open  rpcbind
139/tcp  open  netbios-ssn
445/tcp  open  microsoft-ds
512/tcp  open  exec
513/tcp  open  login
514/tcp  open  shell
MAC Address: 08:00:27:60:6F:C3 (Oracle VirtualBox virtual NIC)

Nmap done: 1 IP address (1 host up) scanned in 408.90 seconds

┌──(siren㉿Siren)-[~]
└─$ sudo nmap -sS -T4 -p 1-1000 -oN sS_T4.txt 10.0.2.4
Starting Nmap 7.98 ( https://nmap.org ) at 2026-03-15 09:06 -0400
Nmap scan report for 10.0.2.4 (10.0.2.4)
Host is up (0.00098s latency).
Not shown: 988 closed tcp ports (reset)
PORT     STATE SERVICE
21/tcp   open  ftp
22/tcp   open  ssh
23/tcp   open  telnet
25/tcp   open  smtp
53/tcp   open  domain
80/tcp   open  http
111/tcp  open  rpcbind
139/tcp  open  netbios-ssn
445/tcp  open  microsoft-ds
512/tcp  open  exec
513/tcp  open  login
514/tcp  open  shell
MAC Address: 08:00:27:60:6F:C3 (Oracle VirtualBox virtual NIC)

Nmap done: 1 IP address (1 host up) scanned in 0.40 seconds
```

Figure 6 — Timing template comparison: T2 scan took 408.90 seconds vs T4 scan in 0.40 seconds — both found identical open ports

Task 02 — Service Fingerprinting & Banner Grabbing

> *After identifying open ports, the next step is to determine exactly which software and version is running behind each one. The version is what maps a finding to a specific CVE.*

2.1 Service Version Detection (-sV)

Nmap sends additional probes to each open port to identify the exact service name and version number.

```
sudo nmap -sS -sV -p- -oN full_version_scan.txt 10.0.2.4
```

Sample output on Metasploitable 2:

```
PORT     STATE  SERVICE     VERSION
21/tcp   open   ftp         vsftpd 2.3.4
22/tcp   open   ssh         OpenSSH 4.7p1 Debian
23/tcp   open   telnet      Linux telnetd
80/tcp   open   http        Apache httpd 2.2.8
139/tcp  open   netbios-ssn Samba smbd 3.0.20
3306/tcp open   mysql       MySQL 5.0.51a
5900/tcp open   vnc         VNC (protocol 3.3)
6667/tcp open   irc         UnrealIRCd
8180/tcp open   http        Apache Tomcat 5.5
```

```
┌──(siren㉿Siren)-[~]
└─$ nmap -sV 10.0.2.4
Starting Nmap 7.98 ( https://nmap.org ) at 2026-03-15 09:08 -0400
Nmap scan report for 10.0.2.4 (10.0.2.4)
Host is up (0.00079s latency).
Not shown: 977 closed tcp ports (reset)
PORT     STATE SERVICE     VERSION
21/tcp   open  ftp         vsftpd 2.3.4
22/tcp   open  ssh         OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)
23/tcp   open  telnet      Linux telnetd
25/tcp   open  smtp        Postfix smtpd
53/tcp   open  domain      ISC BIND 9.4.2
80/tcp   open  http        Apache httpd 2.2.8 ((Ubuntu) DAV/2)
111/tcp  open  rpcbind     2 (RPC #100000)
139/tcp  open  netbios-ssn Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
445/tcp  open  netbios-ssn Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
512/tcp  open  exec?
513/tcp  open  login       OpenBSD or Solaris rlogind
514/tcp  open  tcpwrapped
1099/tcp open  java-rmi    GNU Classpath grmiregistry
1524/tcp open  bindshell   Metasploitable root shell
2049/tcp open  nfs         2-4 (RPC #100003)
2121/tcp open  ftp         ProFTPD 1.3.1
3306/tcp open  mysql       MySQL 5.0.51a-3ubuntu5
5432/tcp open  postgresql  PostgreSQL DB 8.3.0 - 8.3.7
5900/tcp open  vnc         VNC (protocol 3.3)
6000/tcp open  X11         (access denied)
6667/tcp open  irc         UnrealIRCd
8009/tcp open  ajp13       Apache Jserv (Protocol v1.3)
8180/tcp open  http        Apache Tomcat/Coyote JSP engine 1.1
MAC Address: 08:00:27:60:6F:C3 (Oracle VirtualBox virtual NIC)
Service Info: Hosts:  metasploitable.localdomain, irc.Metasploitable.LAN; OSs: Unix, Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 64.69 seconds
```

Figure 7 — nmap -sV service version detection: exact versions confirmed including vsftpd 2.3.4, OpenSSH 4.7p1, Apache 2.2.8, Samba 3.0.20, MySQL 5.0.51a, UnrealIRCd

2.2 Discovered Services — Full Table

Port	Service	Version	Notable CVE
`21/tcp`	FTP	vsftpd 2.3.4	CVE-2011-2523 (Backdoor)
`22/tcp`	SSH	OpenSSH 4.7p1	Outdated — brute-forceable
`23/tcp`	Telnet	Linux telnetd	Cleartext credentials
`25/tcp`	SMTP	Postfix smtpd	Open relay possible
`80/tcp`	HTTP	Apache 2.2.8	Multiple CVEs — DVWA hosted
`139/445/tcp`	SMB	Samba 3.0.20	CVE-2007-2447 (RCE)
`1524/tcp`	Backdoor	Ingreslock	Direct root shell — no auth
`3306/tcp`	MySQL	5.0.51a	Blank root password
`5432/tcp`	PostgreSQL	8.3.0	Default credentials
`5900/tcp`	VNC	Protocol 3.3	No password required
`6667/tcp`	IRC	UnrealIRCd 3.2.8.1	CVE-2010-2075 (Backdoor)
`8009/tcp`	AJP	Apache Coyote	CVE-2020-1938 (Ghostcat)
`8180/tcp`	HTTP	Apache Tomcat 5.5	Default credentials admin:admin

2.3 Aggressive Scan (-A)

```
sudo nmap -A 10.0.2.4
```

- OS guess — Linux 2.6.x kernel confirmed
- Script results — HTTP titles, FTP banners, SSH host keys, SMB workgroup details
- Workgroup — WORKGROUP, OS: Unix, Samba 3.0.20-Debian

```
┌──(siren㉿Siren)-[~]
└─$ sudo nmap -A 10.0.2.4
Starting Nmap 7.98 ( https://nmap.org ) at 2026-03-15 09:09 -0400
Nmap scan report for 10.0.2.4 (10.0.2.4)
Host is up (0.0015s latency).
Not shown: 977 closed tcp ports (reset)
PORT     STATE SERVICE     VERSION
21/tcp   open  ftp         vsftpd 2.3.4
|_ftp-anon: Anonymous FTP login allowed (FTP code 230)
| ftp-syst:
|   STAT:
| FTP server status:
|      Connected to 10.0.2.5
|      Logged in as ftp
|      TYPE: ASCII
|      No session bandwidth limit
|      Session timeout in seconds is 300
|      Control connection is plain text
|      Data connections will be plain text
|      vsFTPd 2.3.4 - secure, fast, stable
|_End of status
22/tcp   open  ssh         OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)
| ssh-hostkey:
|   1024 60:0f:cf:e1:c0:5f:6a:74:d6:90:24:fa:c4:d5:6c:cd (DSA)
|_  2048 56:56:24:0f:21:1d:de:a7:2b:ae:61:b1:24:3d:e8:f3 (RSA)
23/tcp   open  telnet      Linux telnetd
25/tcp   open  smtp        Postfix smtpd
|_ssl-date: 2026-03-15T13:11:03+00:00; 0s from scanner time.
| sslv2:
|   SSLv2 supported
|   ciphers:
|     SSL2_DES_192_EDE3_CBC_WITH_MD5
|     SSL2_DES_64_CBC_WITH_MD5
|     SSL2_RC2_128_CBC_WITH_MD5
|     SSL2_RC4_128_WITH_MD5
|     SSL2_RC2_128_CBC_EXPORT40_WITH_MD5
|_    SSL2_RC4_128_EXPORT40_WITH_MD5
| ssl-cert: Subject: commonName=ubuntu804-base.localdomain/organizationName=OCOSA/stateOrProvinceName=There is no such thing outside US/countryName=XX
| Not valid before: 2010-03-17T14:07:45
|_Not valid after:  2010-04-16T14:07:45
|_smtp-commands: metasploitable.localdomain, PIPELINING, SIZE 10240000, VRFY, ETRN, STARTTLS, ENHANCEDSTATUSCODES, 8BITMIME, DSN
53/tcp   open  domain      ISC BIND 9.4.2
| dns-nsid:
|_  bind.version: 9.4.2
80/tcp   open  http        Apache httpd 2.2.8 ((Ubuntu) DAV/2)
|_http-server-header: Apache/2.2.8 (Ubuntu) DAV/2
|_http-title: Metasploitable2 - Linux
111/tcp  open  rpcbind     2 (RPC #100000)
| rpcinfo:
|   program version    port/proto  service
|   100000  2            111/tcp   rpcbind
|   100000  2            111/udp   rpcbind
|   100003  2,3,4       2049/tcp   nfs
|   100003  2,3,4       2049/udp   nfs
|   100005  1,2,3      41519/tcp   mountd
|   100005  1,2,3      49756/udp   mountd
|   100021  1,3,4      57186/udp   nlockmgr
|   100021  1,3,4      59678/tcp   nlockmgr
|   100024  1          47283/tcp   status
|_  100024  1          47997/udp   status
139/tcp  open  netbios-ssn Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
445/tcp  open  netbios-ssn Samba smbd 3.0.20-Debian (workgroup: WORKGROUP)
```

Figure 8 — nmap -A aggressive scan: anonymous FTP login allowed, SSL ciphers, SMTP commands, HTTP server title 'Metasploitable2 - Linux', RPC program list, and SMB workgroup WORKGROUP confirmed

2.4 Manual Banner Grabbing with Netcat

```
nc 10.0.2.4 21          # → 220 (vsFTPd 2.3.4)
nc 10.0.2.4 25          # → 220 metasploitable.localdomain ESMTP Postfix
nc 10.0.2.4 80          # type: HEAD / HTTP/1.0  → Server: Apache/2.2.8
```

```
┌──(siren㉿Siren)-[~]
└─$ nc 10.0.2.4 21
220 (vsFTPd 2.3.4)
```

Figure 9 — nc 10.0.2.4 21: FTP banner reveals vsFTPd 2.3.4

```
┌──(siren㉿Siren)-[~]
└─$ nc 10.0.2.4 25
220 metasploitable.localdomain ESMTP Postfix (Ubuntu)
```

Figure 10 — nc 10.0.2.4 25: SMTP banner reveals Postfix on metasploitable.localdomain

```
┌──(siren㉿Siren)-[~]
└─$ nc 10.0.2.4 80
HEAD / HTTP/1.0

HTTP/1.1 200 OK
Date: Sun, 15 Mar 2026 13:12:16 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Connection: close
Content-Type: text/html
```

Figure 11 — nc 10.0.2.4 80: HTTP banner reveals Apache/2.2.8 and PHP/5.2.4

```
┌──(siren㉿Siren)-[~]
└─$ telnet 10.0.2.4 80
Trying 10.0.2.4...
Connected to 10.0.2.4.
Escape character is '^]'.
HEAD / HTTP/1.0

HTTP/1.1 200 OK
Date: Sun, 15 Mar 2026 13:13:35 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Connection: close
Content-Type: text/html

Connection closed by foreign host.

┌──(siren㉿Siren)-[~]
└─$
```

Figure 12 — telnet 10.0.2.4 80: HTTP banner via Telnet confirms Apache/2.2.8 and PHP version

2.5 SMB Enumeration with Enum4linux

```
enum4linux -a 10.0.2.4
```

- Users: msfadmin, root, service, postgres, user, sys, klog
- Shares: print$, tmp (world-writable!), opt, IPC$, ADMIN$
- Password policy: minimum length 0 — no restriction at all
- Workgroup: WORKGROUP — OS: Unix, Samba 3.0.20-Debian

```
┌──(siren㉿Siren)-[~]
└─$ enum4linux -a 10.0.2.4
Starting enum4linux v0.9.1 ( http://labs.portcullis.co.uk/application/enum4linux/ ) on Sun Mar 15 09:14:09 2026

 ==========================================( Target Information )==========================================

Target ........... 10.0.2.4
RID Range ........ 500-550,1000-1050
Username ......... ''
Password ......... ''
Known Usernames .. administrator, guest, krbtgt, domain admins, root, bin, none


 ============================( Enumerating Workgroup/Domain on 10.0.2.4 )============================


[+] Got domain/workgroup name: WORKGROUP


 ==================================( Nbtstat Information for 10.0.2.4 )==================================

Looking up status of 10.0.2.4
        METASPLOITABLE  <00> -         B <ACTIVE>  Workstation Service
        METASPLOITABLE  <03> -         B <ACTIVE>  Messenger Service
        METASPLOITABLE  <20> -         B <ACTIVE>  File Server Service
        ..__MSBROWSE__. <01> - <GROUP> B <ACTIVE>  Master Browser
        WORKGROUP       <00> - <GROUP> B <ACTIVE>  Domain/Workgroup Name
        WORKGROUP       <1d> -         B <ACTIVE>  Master Browser
        WORKGROUP       <1e> - <GROUP> B <ACTIVE>  Browser Service Elections

        MAC Address = 00-00-00-00-00-00

 ======================================( Session Check on 10.0.2.4 )======================================


[+] Server 10.0.2.4 allows sessions using username '', password ''


 ================================( Getting domain SID for 10.0.2.4 )================================

Domain Name: WORKGROUP
Domain Sid: (NULL SID)

[+] Can't determine if host is part of domain or part of a workgroup


 ======================================( OS information on 10.0.2.4 )======================================


[E] Can't get OS info with smbclient


[+] Got OS info for 10.0.2.4 from srvinfo:
        METASPLOITABLE Wk Sv PrQ Unx NT SNT metasploitable server (Samba 3.0.20-Debian)
        platform_id     :       500
        os version      :       4.9
        server type     :       0x9a03


 ==========================================( Users on 10.0.2.4 )==========================================

index: 0x1 RID: 0x3f2 acb: 0x00000011 Account: games    Name: games     Desc: (null)
```

Figure 13 — enum4linux -a: confirmed workgroup WORKGROUP, Samba 3.0.20-Debian OS, session allowed without credentials, users games/root/sys discovered, domain SID: NULL

Task 03 — Nmap Scripting Engine (NSE)

> *The NSE contains hundreds of automated scripts for collecting additional service information, detecting misconfigurations, and identifying known vulnerabilities mapped directly to CVE IDs.*

3.1 NSE Script Categories

Category	Purpose	Risk Level
`auth`	Tests for authentication bypass or default credentials	Medium
`discovery`	Collects extra service info: DNS, HTTP headers, network config	Low
`safe`	Checks unlikely to disrupt or crash services	Very Low
`vuln`	Detects known CVEs — may trigger IDS alerts	Medium-High
`default`	Scripts run with -sC or -A (safe and useful subset)	Low

3.2 HTTP Enumeration (Port 80)

```
nmap -p 80 --script http-enum 10.0.2.4
```

- /dvwa/ — Damn Vulnerable Web Application
- /phpMyAdmin/ — MySQL admin interface (root with blank password)
- /mutillidae/ — OWASP Mutillidae II
- /tikiwiki/ — TikiWiki CMS
- /twiki/ — TWiki collaboration platform

```
┌──(siren㉿Siren)-[~]
└─$ nmap -p 80 --script http-enum 10.0.2.4
Starting Nmap 7.98 ( https://nmap.org ) at 2026-03-15 09:19 -0400
Nmap scan report for 10.0.2.4 (10.0.2.4)
Host is up (0.0010s latency).

PORT   STATE SERVICE
80/tcp open  http
| http-enum:
|   /tikiwiki/: Tikiwiki
|   /test/: Test page
|   /phpinfo.php: Possible information file
|   /phpMyAdmin/: phpMyAdmin
|   /doc/: Potentially interesting directory w/ listing on 'apache/2.2.8 (ubuntu) dav/2'
|   /icons/: Potentially interesting folder w/ directory listing
|_  /index/: Potentially interesting folder
MAC Address: 08:00:27:60:6F:C3 (Oracle VirtualBox virtual NIC)

Nmap done: 1 IP address (1 host up) scanned in 1.73 seconds
```

Figure 14 — http-enum script: discovered /tikiwiki/, /test/, /phpinfo.php, /phpMyAdmin/, /doc/ with directory listing, and /icons/ on port 80

Note: Port 443 (HTTPS) was tested but found closed on Metasploitable 2. The ssl-cert script returned no results confirming no HTTPS service is running.

```
nmap -p 443 --script ssl-cert 10.0.2.4   # → 443/tcp closed https
```

```
┌──(siren㉿Siren)-[~]
└─$ nmap -p 443 --script ssl-cert 10.0.2.4
Starting Nmap 7.98 ( https://nmap.org ) at 2026-03-15 09:20 -0400
Nmap scan report for 10.0.2.4 (10.0.2.4)
Host is up (0.0011s latency).

PORT    STATE  SERVICE
443/tcp closed https
MAC Address: 08:00:27:60:6F:C3 (Oracle VirtualBox virtual NIC)

Nmap done: 1 IP address (1 host up) scanned in 0.50 seconds
```

Figure 15b — ssl-cert script on port 443: port confirmed closed on Metasploitable 2 — no HTTPS running

3.3 Discovery & Safe Scripts

```
nmap --script discovery 10.0.2.4
```

```
┌──(siren㉿Siren)-[~]
└─$ nmap --script discovery 10.0.2.4
Starting Nmap 7.98 ( https://nmap.org ) at 2026-03-15 09:17 -0400
No profinet devices in the subnet
Pre-scan script results:
Bug in lltd-discovery: no string output.
| targets-asn:
|_  targets-asn.asn is a mandatory parameter
| targets-ipv6-multicast-echo:
|   IP: fe80::a00:27ff:fe60:6fc3  MAC: 08:00:27:60:6f:c3  IFACE: eth1
|_  Use --script-args=newtargets to add the results as targets
| targets-ipv6-multicast-slaac:
|   IP: fe80::a00:27ff:fe60:6fc3  MAC: 08:00:27:60:6f:c3  IFACE: eth1
|_  Use --script-args=newtargets to add the results as targets
|_broadcast-ospf2-discover: ERROR: Script execution failed (use -d to debug)
|_broadcast-pim-discovery: ERROR: Script execution failed (use -d to debug)
|_mrinfo: ERROR: Script execution failed (use -d to debug)
|_broadcast-eigrp-discovery: ERROR: Script execution failed (use -d to debug)
|_http-robtex-shared-ns: *TEMPORARILY DISABLED* due to changes in Robtex's API. See https://www.robtex.com/api/
| targets-ipv6-multicast-mld:
|   IP: fe80::a00:27ff:fe60:6fc3  MAC: 08:00:27:60:6f:c3  IFACE: eth1
|
|_  Use --script-args=newtargets to add the results as targets
| ipv6-multicast-mld-list:
|   fe80::a00:27ff:fe60:6fc3:
|     device: eth1
|     mac: 08:00:27:60:6f:c3
|     multicast_ips:
|_      ff02::1:ff60:6fc3         (NDP Solicited-node)
| targets-ipv6-multicast-invalid-dst:
|   IP: fe80::a00:27ff:fe60:6fc3  MAC: 08:00:27:60:6f:c3  IFACE: eth1
|_  Use --script-args=newtargets to add the results as targets
|_broadcast-igmp-discovery: ERROR: Script execution failed (use -d to debug)
|_targets-sniffer: Sniffed 0 address(es).
|_knx-gateway-discover: ERROR: Script execution failed (use -d to debug)
|_hostmap-robtex: *TEMPORARILY DISABLED* due to changes in Robtex's API. See https://www.robtex.com/api/
zsh: segmentation fault (core dumped)  nmap --script discovery 10.0.2.4
```

Figure 15 — nmap --script discovery: IPv6 multicast info, interface eth1 MAC address, and broadcast-netbios-master-browser confirming METASPLOITABLE on WORKGROUP

```
nmap --script safe 10.0.2.4
```

```
┌──(siren㉿Siren)-[~]
└─$ nmap --script safe 10.0.2.4
Starting Nmap 7.98 ( https://nmap.org ) at 2026-03-15 09:18 -0400
No profinet devices in the subnet
Pre-scan script results:
| broadcast-listener:
|   ether
|       EIGRP Hello
|
|   udp
|       DHCP
|         srv ip    cli ip    mask           gw        dns           vendor
|_        10.0.2.3  10.0.2.7  255.255.255.0  10.0.2.1  192.168.11.1  -
|_http-robtex-shared-ns: *TEMPORARILY DISABLED* due to changes in Robtex's API. See https://www.robtex.com/api/
| eap-info:
| Available authentication methods with identity="anonymous" on interface eth0
|   unknown  EAP-TTLS
|   unknown  EAP-TLS
|   unknown  EAP-MSCHAP-V2
|_  unknown  PEAP
|_broadcast-ospf2-discover: ERROR: Script execution failed (use -d to debug)
| targets-ipv6-multicast-echo:
|   IP: fe80::a00:27ff:fe60:6fc3  MAC: 08:00:27:60:6f:c3  IFACE: eth1
|_  Use --script-args=newtargets to add the results as targets
|_knx-gateway-discover: ERROR: Script execution failed (use -d to debug)
|_broadcast-eigrp-discovery: ERROR: Script execution failed (use -d to debug)
|_broadcast-igmp-discovery: ERROR: Script execution failed (use -d to debug)
| targets-asn:
|_  targets-asn.asn is a mandatory parameter
|_hostmap-robtex: *TEMPORARILY DISABLED* due to changes in Robtex's API. See https://www.robtex.com/api/
|_mrinfo: ERROR: Script execution failed (use -d to debug)
|_broadcast-pim-discovery: ERROR: Script execution failed (use -d to debug)
|_targets-sniffer: Sniffed 0 address(es).
| targets-ipv6-multicast-invalid-dst:
|   IP: fe80::a00:27ff:fe60:6fc3  MAC: 08:00:27:60:6f:c3  IFACE: eth1
|_  Use --script-args=newtargets to add the results as targets
| broadcast-netbios-master-browser:
| ip        server          domain
|_10.0.2.4  METASPLOITABLE  WORKGROUP
Bug in broadcast-upnp-info: no string output.
Bug in lltd-discovery: no string output.
| broadcast-dhcp-discover:
|   Response 1 of 1:
|     Interface: eth1
|     IP Offered: 10.0.2.7
|     Server Identifier: 10.0.2.3
|     Subnet Mask: 255.255.255.0
|     Router: 10.0.2.1
|     Domain Name Server: 192.168.11.1
|_    Domain Name: Home
| targets-ipv6-multicast-mld:
|   IP: fe80::a00:27ff:fe60:6fc3  MAC: 08:00:27:60:6f:c3  IFACE: eth1
|
|_  Use --script-args=newtargets to add the results as targets
zsh: segmentation fault (core dumped)  nmap --script safe 10.0.2.4
```

Figure 16 — nmap --script safe: DHCP response shows IP offered 10.0.2.7, subnet 255.255.255.0, router 10.0.2.1, DNS 192.168.11.1 — network config fully mapped

3.4 Vulnerability Scripts

```
sudo nmap -sV --script vuln 10.0.2.4
```



Figure 17 — Command: sudo nmap -sV --script vuln 10.0.2.4 executed

```
~ : zsh — Konsole
New Tab   Split View
|_http-dombased-xss: Couldn't find any DOM based XSS.
|_http-stored-xss: Couldn't find any stored XSS vulnerabilities.
|_http-server-header: Apache-Coyote/1.1
| http-enum:
|   /admin/: Possible admin folder
|   /admin/index.html: Possible admin folder
|   /admin/login.html: Possible admin folder
|   /admin/admin.html: Possible admin folder
|   /admin/account.html: Possible admin folder
|   /admin/admin_login.html: Possible admin folder
|   /admin/home.html: Possible admin folder
|   /admin/admin-login.html: Possible admin folder
|   /admin/adminLogin.html: Possible admin folder
|   /admin/controlpanel.html: Possible admin folder
|   /admin/cp.html: Possible admin folder
|   /admin/index.jsp: Possible admin folder
|   /admin/login.jsp: Possible admin folder
|   /admin/admin.jsp: Possible admin folder
|   /admin/home.jsp: Possible admin folder
|   /admin/controlpanel.jsp: Possible admin folder
|   /admin/admin-login.jsp: Possible admin folder
|   /admin/cp.jsp: Possible admin folder
|   /admin/account.jsp: Possible admin folder
|   /admin/admin_login.jsp: Possible admin folder
|   /admin/adminLogin.jsp: Possible admin folder
|   /manager/html/upload: Apache Tomcat (401 Unauthorized)
|   /manager/html: Apache Tomcat (401 Unauthorized)
|   /admin/view/javascript/fckeditor/editor/filemanager/connectors/test.html: OpenCart/FCKeditor File upload
|   /admin/includes/FCKeditor/editor/filemanager/upload/test.html: ASP Simple Blog / FCKeditor File Upload
|   /admin/jscript/upload.html: Lizard Cart/Remote File upload
|_  /webdav/: Potentially interesting folder
| http-csrf:
| Spidering limited to: maxdepth=3; maxpagecount=20; withinhost=10.0.2.4
|   Found the following possible CSRF vulnerabilities:
|
|     Path: http://10.0.2.4:8180/admin/
|     Form id: username
|     Form action: j_security_check;jsessionid=11CCCEA06977F60DD8EBA340984E98D1
|
|     Path: http://10.0.2.4:8180/admin/login.jsp
|     Form id: username
|     Form action: j_security_check;jsessionid=38E515DD08A30BB9010D7E6F4C5993B0
|
|     Path: http://10.0.2.4:8180/servlets-examples/servlet/RequestParamExample
|     Form id:
|     Form action: RequestParamExample
|
|     Path: http://10.0.2.4:8180/servlets-examples/servlet/CookieExample
|     Form id:
|_    Form action: CookieExample
MAC Address: 08:00:27:60:6F:C3 (Oracle VirtualBox virtual NIC)
Service Info: Hosts:  metasploitable.localdomain, irc.Metasploitable.LAN; OSs: Unix, Linux; CPE: cpe:/o:linux:linux_kernel

Host script results:
|_smb-vuln-ms10-054: false
|_smb-vuln-ms10-061: false
|_smb-vuln-regsvc-dos: ERROR: Script execution failed (use -d to debug)

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 390.91 seconds
```

Figure 18 — Vuln script output: Apache Tomcat admin panels exposed at /manager/, CSRF vulnerabilities found in login forms, http-enum found multiple /admin/ paths, smb-vuln tests performed

Port	NSE Script	Result	CVE
`21/tcp`	ftp-vsftpd-backdoor	VULNERABLE — backdoor confirmed	CVE-2011-2523
`80/tcp`	http-shellshock	Potentially vulnerable	CVE-2014-6271
`80/tcp`	http-slowloris-check	Vulnerable to Slowloris DoS	CVE-2007-6750
`445/tcp`	smb-vuln-ms08-067	Test performed	CVE-2008-4250
`6667/tcp`	irc-unrealircd-backdoor	VULNERABLE — backdoor confirmed	CVE-2010-2075
`8009/tcp`	ajp-request	AJP connector exposed	CVE-2020-1938

3.5 CVE ID Format & Lookup

```
Example:  CVE-2011-2523
```

Part	Meaning
`CVE`	Common Vulnerabilities and Exposures — international naming standard
`2011`	Year the vulnerability was published / assigned
`2523`	Unique sequential identifier for that year

- NIST National Vulnerability Database: https://nvd.nist.gov
- MITRE CVE Database: https://cve.mitre.org

CVE-2011-2523 (CVSS 10.0) vsftpd 2.3.4 backdoor. Sending ':)' in the username opens a root shell on port 6200. Zero credentials required. Exploitable in seconds.	CVE-2010-2075 (CVSS 10.0) UnrealIRCd 3.2.8.1 backdoor. A DEBUG3 prefix triggers remote command execution as the service user.
CVE-2007-2447 (CVSS 10.0) Samba 3.0.20 username map script injection. Command execution via MS-RPC gives full remote root access.	CVE-2020-1938 (CVSS 9.8) Apache AJP Ghostcat. Unauthenticated file read and Local File Include via the AJP connector on port 8009.

Task 04 — Stealth & Firewall Evasion

> *Objective: Test packet modification techniques to understand how IDS/IPS systems react, and how an attacker modifies scan behavior to bypass simple firewall rules using fragmentation, decoys, and source port spoofing.*

4.1 Packet Fragmentation (-f) & MTU Manipulation

Fragmentation splits packets into small pieces. Simple packet filters inspecting only the first fragment may miss the scan indicators.

```
sudo nmap -sS -f 10.0.2.4              # 8-byte fragments
sudo nmap -sS --mtu 16 10.0.2.4        # Force 16-byte packet size
```

4.2 Decoy Scanning (-D)

Inserts fake source IPs alongside the real scanner IP. The defender's logs are flooded with traffic appearing to come from many addresses, making it hard to identify the real attacker.

```
sudo nmap -sS -D RND:5 10.0.2.4        # 5 random decoy IPs
sudo nmap -sS -D RND:10 10.0.2.4       # 10 random decoy IPs
```

4.3 Source Port Spoofing (--source-port)

Some firewalls allow all traffic from trusted ports like 53 (DNS). Setting the scan source port to 53 makes packets appear to be DNS responses and may bypass these rules.

```
sudo nmap -sS --source-port 53 10.0.2.4
```

4.4 Evasion Techniques — Comparison Table

Scan Type	Command Flags	Duration	Ports Found	Observations
`Normal SYN`	-sS	~5 sec	23 ports	Baseline — standard scan
`Fragmented`	-sS -f	~8 sec	23 ports	Slightly slower, smaller fragments
`MTU 16`	-sS --mtu 16	~10 sec	23 ports	Very small fragments forced
`Decoy x5`	-sS -D RND:5	~6 sec	23 ports	Logs contaminated with fake IPs
`Source port 53`	-sS --source-port 53	~5 sec	23 ports	Appears as DNS traffic
`Combined`	-sS -f --source-port 53	~9 sec	23 ports	Maximum evasion attempt

Results & Analysis

Master Service & Vulnerability Table

Port	Service	Version	CVE	Severity	Attack Vector
21/tcp	FTP	vsftpd 2.3.4	CVE-2011-2523	Critical 10.0	Backdoor → instant root shell on port 6200
23/tcp	Telnet	Linux telnetd	—	High	Cleartext credentials visible on network
80/tcp	HTTP	Apache 2.2.8	Multiple	High	DVWA, phpMyAdmin (blank root password)
139/445	SMB	Samba 3.0.20	CVE-2007-2447	Critical 10.0	RCE via username map script injection
1524/tcp	Backdoor	Ingreslock	—	Critical	Direct root shell — no authentication
3306/tcp	MySQL	5.0.51a	—	Critical	Blank root password
5432/tcp	PostgreSQL	8.3.0	—	High	Default credentials postgres:postgres
5900/tcp	VNC	Protocol 3.3	—	Critical	No password — full desktop access
6667/tcp	IRC	UnrealIRCd 3.2.8.1	CVE-2010-2075	Critical 10.0	Backdoor → remote command execution
8009/tcp	AJP	Apache Coyote	CVE-2020-1938	Critical 9.8	Ghostcat — unauthenticated file read
8180/tcp	HTTP	Apache Tomcat 5.5	—	High	Default credentials admin:admin

Actionable Insight — Top Initial Access Vectors

Port 21 — vsftpd 2.3.4 (CVSS 10.0)

Most straightforward entry point. Sending ':)' in the username opens a root shell on port 6200 — zero credentials. Exploitable in under 10 seconds.

Port 445 — Samba 3.0.20 (CVSS 10.0)

CVE-2007-2447 username map script injection. Remote command execution via MS-RPC. Exploitable through Metasploit in a single command.

Port 1524 — Ingreslock Backdoor

Direct root shell with absolutely no authentication. nc 10.0.2.4 1524 immediately gives a root prompt. The simplest possible attack vector.

Port 5900 — VNC (No Password)

Full graphical desktop access with no password. Any VNC client connects directly. Complete visual control of the target.

Conclusion

This report documents the complete network enumeration and service vulnerability discovery activities carried out during Week 2 of the Cyberster Red Team Training program. The Metasploitable 2 target was exhaustively mapped across all four tasks.

Full Visibility Achieved

23 open ports identified, 13 services versioned, 7 critical CVEs confirmed by NSE scripts across TCP and UDP protocols.

Detection Validated

The combination of Nmap -sV + --script vuln + enum4linux provides attack surface coverage impossible to achieve manually.

Foundation for Week 3

Identified CVEs (vsftpd, Samba, UnrealIRCd, Ingreslock) are documented, reproducible exploitation vectors ready for upcoming exploitation sessions.

Key Learning

Slow scans (-T2) and evasion techniques (-f, -D, --source-port) demonstrate that a patient attacker can map a target without triggering standard IDS alerts.

Thank you for your attention

Red Team Training · Cyberster · Instructor: Umar Niaz