ESM-2 650M base
ESM-C 600M base
guess from other AA usage

5% = blind guessing, 1 amino acid in 20

Influenza viruses
Influenza A polymerase PB1
Influenza A haemagglutinin HA
Influenza A polymerase PB2
Influenza A neuraminidase NA
Influenza B haemagglutinin
Influenza C haemagglutinin HEF
Influenza A matrix M2
Influenza A matrix M1
Influenza A NS1
Influenza A nucleoprotein NP
Influenza A polymerase PA

Coronaviruses
SARS-CoV-2 nucleoprotein
HCoV-229E spike
HCoV-OC43 spike
SARS-CoV-2 spike
MERS-CoV spike

Other viruses
HIV-1 envelope gp160
HTLV-1 gp62
parvovirus B19 VP2
HSV-1 glycoprotein B
RSV fusion F
Ebola glycoprotein
rabies glycoprotein G
mumps HN
VZV glycoprotein E
Nipah glycoprotein G
HBV surface antigen
rotavirus VP7
adenovirus hexon
Lassa glycoprotein
HPV major capsid L1
measles haemagglutinin

Eukaryotes
yeast ADH1
human p53
jellyfish GFP

Bacteria
M. tuberculosis KatG
E. coli OmpA
Taq polymerase

Phages
phage lambda CI
phage T7 RNA pol
phage T4 capsid gp23

5%
10%
20%
40%
80%

Average probability the model gave the true amino acid at a masked position