



AUDIO JACKS: STX-353K7A Series

3.5mm, Audio Jacks, Through Hole, Vertical High-Temp

Product Features

Contoured face

4-Pole

Used in Devices Such as Audio Equipment, Cell Phones, or Digital Still Camera

Complies with EIA Standards

Performance Specifications

Materials and Finish

Housing

High Temperature Thermoplastic, UL 94V-0 Rated

Color: Black

Contact Material

Contact #4: Stainless Steel

All other Contacts: Copper Alloy

Contact Plating: Gold Flash Over Nickel Underplate

Electrical Characteristics

Insulation Resistance

100 Megohms Min. at 500V DC

Contact Resistance

50 milliohms Max.(Initial)

100 milliohms Max.(Final)

Dielectric Withstanding Voltage

250V AC for 1 Minute

Mechanical Characteristics

Insertion Force: 0.3kg - 3.0kg

Withdrawal Force: 0.3kg - 3.0kg

Durability: 5000 Mating Cycles Min.

Operating Temperature

-40°C to +85°C

Process Temperature:

260°C Lead-Free Reflow Soldering

2D Drawing

IGES

STEP

3D PDF

Solder Profile

CofC RoHS Compliant

CofC REACH Compliant

UL Plastic File

Certificate of Origin

Check Stock

Request a Sample

Send Us An Email

Generated Part Number

Part Number Builder

	-			
Series		Number of Pins	Threading Option	Packaging

Series

STX-353K7A - 3.5mm Audio Jack

Number of Pins

6 - Pins

Threading Option

N - Non-Threaded Barrel

Packaging

KTTR - Tape and Reel

Contact Kycon for other options

STX-353K7A

Dimensions in mm

