

MICCAI Doctoral Consortium 2025



Data-Efficient Learning for Generalizable Surgical Video Understanding

Department of Information Technology (ITEC), University of Klagenfurt

Research Problem and Motivation

The Challenge: Operating rooms are becoming intelligent, data-driven environments through computer-assisted systems that recognize surgical workflows and enable procedural indexing, performance evaluation, and report generation. While deep learning powers automated phase/action recognition and semantic segmentation.

- Data Scarcity: Expert annotation is costly and time-consuming
- Visual Complexity: Motion blur, occlusions, smoke, blood degrade video quality Domain Gaps: Variations across institutions prevent reliable model generalization

- How can we reduce reliance on large-scale expert annotations?
- How can we leverage abundant unlabeled surgical video data to improve intra-domain performance?
- How can we design data-efficient, temporally-aware, and generalizable models that perform reliably across diverse

Special Harman to Surgest Van Harra

Proposed Approaches


☐ Supervised Action and Phase Recognition

CNN-RNN Architecture:

- Integrates spatial feature extractors with stacked recurrent layers
- Captures temporal dependencies for short, variable actions
- Frame sampling strategy enhances temporal diversity and robustness to surgeon-specific

CNN-Transformer Framework for Critical Events:

- Addresses critical event detection (bleeding, abdominal access, needle passing, coagulation)
- Transformer encoders model long-range temporal dependencies
- Multi-head self-attention processes spatial features for complex temporal reasoning



☐ Semi-Supervised Learning

❖ Dual Invariance Self-Training for Surgical Phase Recognition.

Two-Stage Framework:

Stage 1: Teacher model generates pseudo-labels for unlabeled clips → Student training Stage 2: Student becomes teacher - process repeats

- Pseudo Supervision: Reliability estimation: Uses predictions from 3 checkpoints (T(n/3), T(2n/3), T(n)) - retains
- top 50% consistent labels

Colubeled data (D*)

- II. Dual Invariance Constraints: Temporal invariance across frame sampling strategies
 - Transformation invariance under strong augmentations


DEST AND 1

 $M_2(\cdot,\theta_3)$

Dataset Curation

Cynecology laparoscopy surgery (CynSurg):

- Actions: 152 videos (Actions and side-effects)
- Semantic Segmentation: 12362 frames (surgical instruments and anatomical structures)
- Cataract surgery (Cataract-Ik)
- Phases: 56 videos (12 phases)
- Semantic Segmentation, 2256 fames (surgical instruments and anatomical



Results and Contributions

Our models were evaluated on six diverse surgical datasets (CynLaps, CynSurg, Cataraca 1K, RAMIE, Cholec80, EndoVis) spanning action/phase recognition and instrument and anatomy segmentation tasks.

Dateset	Model	1/16		1/22		Detained	Mode		
				1	Fi	Course W	AS-MT	78-85	但為
Cataract-1K	CMF1	53.26	29.82	DE.	\$6.28		AL-MIT-ENCORS	製工	1
				ない		Detaut	Model		
	DEST Stage 1	87.28 N.D.		延 数		Cataract-CR	3-52	6.34	# # # # # # # # # # # # # # # # # # #
		1/16		1/22			Samin-ENCORE	热液	
Detroot					F2		The second secon	3.5	
	SyFuener	TL34	200	54.35 74.03	90.35 73.44	EndoVis	Dallach-EWIEL	8.3	-
	DEST_Stage1	79.55	2157	72.66	74.8				

As shown in this table. DIST achieves strong results on challenging low-label splits leg. the art baselines on the 85.97% accuracy with only one labeled 04-858 50 TS video in the 1/32 split) on both Cataract-1K