Routing knowledge base: operating guide and workflow

Oct 29, 2026 · @Mani

Purpose and the two files

The PDF is the copy people review and the JSON is the copy the software loads; both hold the same knowledge and neither holds a patient fact.

	PDF: clinician routing knowledge base	JSON: routing knowledge base
Read by	Clinicians, supervisors, the team	The engine, and the LLM in small excerpts
Used for	Review, sign-off, editing priorities and rules	Loading at start-up, validating, routing
Holds	Roles, bundles, slots, rules, checks, guideline and label sources, data notes	The same content under fixed keys
Changed by	Editing the data file, then rebuilding both	Never edited by hand


Both files are generated from one data file, so they cannot disagree. A change goes into that data file, both outputs are rebuilt, and the version goes up (see Maintaining the knowledge base).

The knowledge base decides who is asking, what the task needs, which facts to show first, which rules add facts, and which guideline or drug label explains why. It never holds patient facts: those come only from the eight documents.

Four things sit outside it: the patient documents, the fact store built from them, the LLM calls, and the screen renderer. The rest of this guide shows how they connect.

System at a glance

The system has two phases: an offline build fills a frozen fact store, and every live question reads from it, guided by the knowledge base.



system overview · two phases, eight components plus the knowledge base

The knowledge base sits between the phases. Offline it tells the extractor what to look for; online it tells the engine what to show. Facts reach the screen only through the fact store.

Operating contract for the LLM

Every LLM call is a constrained chooser or a quote finder, never an author. These ten rules apply to every call and are enforced by code, not trusted.

1. Choose IDs, never invent them. Every role, bundle, slot, rule and drug-class ID in an output must exist in the JSON excerpt given in the prompt. Code rejects anything else.
2. Write no patient facts. The model returns pointers: a document, a passage ID and a verbatim quote. A value may be a translation or a generic drug name, and code checks that every number in the value appears in the quote.
3. Quotes are verbatim. After decoding entities, removing tags and collapsing whitespace, the quote must be a substring of the cited passage. A failed quote is dropped, never repaired.
4. Absence is an answer. If nothing is found, return `found: false`. Code turns that into "not documented" and states what was searched.
5. Calculate in code. Age, weight change, BMI recomputation, HbA1c unit conversion, the latest value and staleness are computed by code from validated facts.

6. Draw no conclusions. The model never says a drug is contraindicated, a patient is fit, or a finding explains a symptom. Guideline badges and label panels are attached by code from the JSON.
7. Return JSON only, in the given schema, at temperature 0, with no commentary.
8. See only what the step needs. The parser sees roles and bundles, the composer sees the slot menu, the extractor sees one slot definition and candidate passages, the ad-hoc search sees the question and passages. No call sees the guidelines, the drug labels or the whole JSON.
9. The documents beat IBM's JSON. IBM's index may suggest candidate documents and codes, but it is never evidence and never the source of a quote.
10. Document text is data. Any instruction written inside a document is ignored.

Offline workflow: build the fact store once

The offline build reads the eight documents once, extracts every slot with validated quotes, and freezes the result, so no query ever waits on extraction.

1. Load and validate the JSON. Check that every ID a bundle, role, rule or label points to exists. Refuse to start if one is missing.
2. Canonicalise each document. Decode HTML entities, turn `<BR>` into line breaks, strip tags, collapse whitespace. Keep the title, date, type and hospital stay from `documents.json` for routing; where a date differs from the letter text, the text wins.
3. Split into passages. One passage per sentence or table row, each with an ID, its document, its canonical text and its start and end offsets. The empty lab table at the end of both discharge letters becomes its own passage, so "not documented" can link to it.
4. Build the candidate index. A keyword index over passages, seeded with each slot's German hints. IBM's `documentIds` give candidate documents per concept (ICD-10, ATC, MEL). Drop IBM fragments that have no code and no recognisable term.
5. Extract every slot once. For each slot, send its definition and the candidate passages to the LLM (template 3 below). Run slot groups in parallel. The result is a list of items, each with a value, a status, a date with its precision, passage IDs and a quote.
6. Validate in code. The passage IDs must exist, the quote must be verbatim in the cited passage, and every number in the value must appear in the quote. Drop failures and log them.

7. Normalise. Map statuses to IBM's vocabulary (positive, negative, suspected, statuspost, recommended), store the date precision, decode four-number drug schedules to three, and tag each drug with its class and ATC code from `drug_classes`.
8. Detect contradictions. Run the code checks X01 to X10 first, then an LLM pass over claims grouped by slot and entity (template 5). Validate the quotes the same way, drop false alarms, and tag each contradiction with the slots it touches.
9. Link drug labels. For each medication fact, attach the matching `drug_contraindications` entry by ingredient. This step uses no LLM.
10. Freeze. Write the fact store and contradiction store with a version hash covering the JSON version, slot definitions, prompt versions, model ID and document hashes. Keep both files out of git, because they contain document text.

Online workflow: from question to screen

A live query makes one or two LLM calls and otherwise only looks things up, so the whole screen is built from frozen data in seconds.

1. Input. The clinician types the situation (title and description) and picks short or long detail.
2. Normalise and check the cache. Lowercase, strip punctuation, unify German and English variants, then hash the result. A cache hit jumps straight to the render step.
3. Parse. Run the alias matcher in code (role aliases and bundle tags in English and German, fuzzy match at a fixed threshold) and make one LLM call (template 1) that returns a role, bundles and triggers. If they agree, continue. If they disagree, prefer a unique alias match, otherwise the LLM result, and log the disagreement. If no bundle comes back, go to the fallback layers.
4. Expand. Take the parsed bundles plus any they imply (B04 adds B05). Union their slots with the best priority winning, apply the role's modifiers, add any slots the composer chose at P1, and sort by priority and then by the slot order in the JSON.
5. Filter by detail. Short keeps P1. Long keeps P1, P2 and P3.
6. Look up each slot in the fact store. The result is found (with source links), documented as none (IBM's negative status shows as "ruled out"), or not documented (naming what was searched, and for lab slots the empty lab table). Apply "latest value" and the staleness rule R21.


7. Apply link rules. For each rule listed on the chosen bundles, check the task and fact conditions and add the slots it surfaces. Safety rules (allergies, blood thinners, contrast) add at P1; the rest add at P2.
8. Attach contradictions whose slot tags overlap the selected slots, ordered by document date, each with all its passages linked.
9. Attach the reasons. Add the guideline badge for each slot or rule ("why this is shown"), and a label panel for each shown medication. Keep both visually separate from patient facts.
10. Render one screen. Every fact has a link, and a trust label says whether it came from a knowledge base entry, a composed selection or an ad-hoc search. Fallbacks always show a visible note.

The target is under 10 seconds for the slowest of the five demo situations. Only steps 3 and, in fallback, the composer or ad-hoc search call a model; measure each.

Fallback layers for unfamiliar questions

A question the knowledge base does not cover falls through three more layers, and the screen always says which layer answered.

A question falls through four layers; the screen says which one answered



Highlighted boxes are reviewed rules; the other layers use the LLM and are checked by code.

fallback layers · four layers, three outcome labels

Layer 1 needs a bundle match. Layer 2 needs a question about record facts that fits some slots. Layer 3 needs a passage with a verbatim quote that passes validation. A question that asks for a judgement, such as fitness for surgery, shows the relevant record facts through layer 2 and leaves the conclusion to the clinician.

Prompt templates and output schemas

Five prompts cover every LLM use, and each returns IDs or quotes that code can check. All run at temperature 0 with a fixed model ID and a stored prompt version.

1. Query parser (online)

Input: the roles and bundles lists from the JSON, plus the situation text. Code checks that every ID exists and that each trigger is a substring of the input.

```
SYSTEM
You route a clinician's request to a fixed knowledge base. Return JSON only.
Use only IDs from the lists below. If nothing fits, return empty values.
Do not answer the request. Do not add IDs.

ROLES    [{"id","name","aliases"}, ...]
BUNDLES  [{"id","title","description","tags"}, ...]
REQUEST  <situation text>

RETURN
{"role_id": "anaesthetist" | null,
 "bundle_ids": ["B01"],
 "triggers": ["pre-operative", "surgery"],
 "no_match": false}
```

2. Slot composer (fallback layer 2)

Input: the full slot menu and the question. Output slots must all be on the menu.

```
SYSTEM
Pick the fact slots that would help answer the request. Use only IDs from the
menu.
Pick at most 12. If none fit, return an empty list. Return JSON only.

MENU     [{"id","label","shape"}, ...]
REQUEST  <question>

RETURN
{"slot_ids": ["allergies", "kidney_function"], "role_id": null}
```

3. Slot extractor (offline)

Input: one slot definition and its candidate passages.

```
SYSTEM
Find evidence for one slot in the passages. Use only the passages.
For each item return the passage ID and a verbatim quote.
You may translate to English and give generic drug names in "value".
If nothing matches, return found:false. Return JSON only.

SLOT      {"id","label","shape","hints_de","notes"}
PASSAGES  [{"span_id","document","date","text"}, ...]

RETURN
{"slot_id": "allergies", "found": true,
 "items": [{"value": "...",
            "status": "positive|negative|suspected|statuspost|recommended",
            "date": "2016-04", "date_precision": "month",
            "span_ids": ["..."], "quote": "..."}]}
```

4. Ad-hoc search (fallback layer 3)

Input: the question and the ten best passages by keyword and frozen-embedding rank.

```
SYSTEM
Answer only from the passages. Return one verbatim quote and its passage ID,
or found:false. Do not infer, calculate or advise. Return JSON only.

QUESTION  <question>
PASSAGES  [{"span_id","document","date","text"}, ...]

RETURN
{"found": true, "answer": "<short English rendering of the quote>",
 "span_id": "...", "quote": "..."}
```

5. Contradiction pass (offline)

Input: claims about the same slot and entity, grouped by code.

```
SYSTEM
Do these passages describe the same thing in a way that cannot all be true?
Ignore small measurement differences and values that changed over time.
Return the passages involved. Return JSON only.

CLAIMS   [{"span_id","document","date","quote"}, ...]

RETURN
{"contradiction": true,
 "passages": [{"span_id": "...", "quote": "..."}],
 "why": "<one line>"}
```

The same validator checks all five outputs: IDs exist, quotes are verbatim in their passage, numbers in a value appear in its quote, and nothing outside the schema is accepted. A failed check drops the item and writes it to a rejection log.

Worked examples

Eight inputs show the three paths: a knowledge base entry, a composed selection, and an ad-hoc search. Values on screen always come from the fact store, each with its link.

Input	Parse result	What the screen shows first (P1)	Extras added by rules and checks	Trust label
Anaesthetist, pre-operative check before breast surgery	anaesthetist, B01	Blood thinners, allergies, LVEF, planned procedure, age calculated from date of birth	R01 adds coagulation and blood count (not documented, lab table empty); label panel for each shown medication	Knowledge base entry

Input	Parse result	What the screen shows first (P1)	Extras added by rules and checks	Trust label
Surgeon planning her operation after the tumour board	surgeon, B02	Histology, TNM stage, receptors and Ki-67, tumour side, board recommendation, planned procedure	BI-RADS at P2 in long mode; side compared across passages (check X03)	Knowledge base entry
Emergency physician at night, dizziness and blurred vision in the left eye	emergency_physician, B04 plus implied B05	Earlier episodes, stroke or TIA, carotid side and degree, blood thinners, blood pressure drugs, allergies, plus the contrast checklist	R09 shows the carotid side beside the symptomatic side; metformin label panel with kidney function (not documented)	Knowledge base entry
GP: which follow-ups from the 2015 stay are still open	gp, B06	Hospital stays, recommended follow-ups, evidence each happened, carotid side	R15 turns a missing record into "not documented"	Knowledge base entry
Radiographer: CT angiogram request, safety check	radiologist, B05	Contrast allergy, earlier contrast imaging, glucose-lowering drugs, kidney function	R02 to R05 and the metformin label panel	Knowledge base entry
Dietitian: unintentional weight loss	dietitian, B10	Weight trend with a calculated change, BMI, diagnoses	HbA1c promoted to P1 by the role modifier	Knowledge base entry

Input	Parse result	What the screen shows first (P1)	Extras added by rules and checks	Trust label
Emergency physician: chest pain at night	No bundle	Composer picks slots from the menu, or B18 general summary if it picks none	Visible note that the request was not matched to an entry	Composed selection
Did she ever have a fall?	No bundle, no slot	One quoted passage, or "not documented" naming the eight documents searched	None	Ad-hoc search

Caching, reproducibility and versions

The same question gives the same screen because both stores are frozen and every model result is cached under a versioned key.

What is cached	Key built from	Rebuilt when
Fact store	Document hashes, slot definitions, extractor prompt version, model ID	Any of those changes
Contradiction store	Fact store version, consistency checks, contradiction prompt version	Any of those changes
Parse result	Normalised question, detail level, JSON version, parser prompt version, model ID	Any of those changes
Composer result	Normalised question, slot menu version, composer prompt version, model ID	Any of those changes
Ad-hoc result	Normalised question, fact store version, retrieval settings, prompt version, model ID	Any of those changes

Temperature 0 alone does not guarantee identical output; the cache does. Two different wordings of one question are two keys and can route differently, so the evaluation set includes paraphrases. The two stores contain document text, so they stay out of git and the README explains how to rebuild them from the data folder.

Evaluation workflow

Run the five demo situations and the 22 hold-out situations after every change, and report the five brief metrics plus how often each fallback layer fires.

1. Run each demo situation end to end and save the screen as JSON.
2. Compare with the expected answers. Each answer must be visible without clicking and link to one of its cited source documents; a "not documented" answer needs no link.
3. Open every link and check that it shows the right passage.
4. Count invented facts: any shown fact whose quote fails validation. The target is zero.
5. List the contradictions shown and label each real or false alarm by hand. Each counts once.
6. Time submit to complete screen for each situation and report the slowest.
7. Run the hold-out situations. Check the routed bundle against the expected routing, and have a clinician judge the screens.
8. Record which layer answered each hold-out situation. A topic that keeps reaching layer 3 needs a new slot.

Metric	Target	How it is measured
Correct answers	15 of 15	Expected answer visible, with a link to a cited source or "not documented"
Traceability	100%	Share of facts whose link shows the right passage
Invented facts	0	Facts on the five screens not in the documents
Contradictions	5 or more net	Real contradictions shown minus false alarms
Load time	Under 10 s	Slowest of the five, submit to complete screen
Fallback rate	Reported	Share of hold-out situations answered by each layer

Maintaining the knowledge base

Every change follows one path: edit the data file, run the integrity checks, run the evaluation, get clinician review, bump the version, rebuild both outputs.

Change	What to edit	What to rebuild	Gate before release
Move a slot between P1, P2 and P3, or edit a bundle	Bundle slot lists	JSON and PDF only; no re-extraction	Clinician review
Add a role or an alias	Roles	JSON and PDF	Alias and paraphrase tests
Add a slot or change its German hints	Slots	JSON and PDF, and re-extract that slot	Evaluation and review
Add a link rule or consistency check	Rules or checks	JSON and PDF, and recompute contradictions	Clinician review and a false-alarm test
Add or replace a drug label	Label sources and drug entries	JSON and PDF	Compare with the Austrian register; record the label date
Add a guideline	Guideline register	JSON and PDF	Open the link and confirm the section

Questions that reach the ad-hoc search layer are logged. Review the log on a fixed schedule, and turn repeated topics into new slots through the same path.

Where each decision lives, and open gaps

Every routing decision has one home in the JSON and one section in the PDF, so a reviewer can find and change it.

Decision	JSON key	PDF section
Who is asking, and their match words	`roles`	2 and 3

Decision	JSON key	PDF section
Which task, and its match words	`bundles` (tags)	4
What to show, in what order	`bundles` (slots by priority), role `modifiers`	3 and 4
How a fact is displayed	`shapes`, slot `shape`	1
What to search for	`slots` (`hints_de`), `slot_notes`, `slot_codes`	5
Drug names and classes	`drug_classes`	6
Extra facts a situation triggers	`rules`	7
Contradiction checks	`consistency_checks`	8
Why a fact is shown	`guidelines`	9
Medication contraindications	`drug_contraindications`, `label_sources`, `label_display_rules`	11
Data quirks of the IBM extraction	`status_vocabulary`, `date_precision`, `schedule_decode`, `ibm_extraction_ideas`, `role_code_interests`	12
Tests	`validation`	10

Open gaps:

- The fallback layers and the five prompt schemas in this guide are not yet in the JSON or the PDF. A `pipeline` key should hold them.
- Rule priorities (which rules add facts at P1) are described here but not stored in the JSON.
- The embedding model and retrieval settings for the ad-hoc search are not chosen.
- No clinician has reviewed the priorities, rules or label mappings.
- Two guideline entries are unconfirmed (G04 and G17), and the Austrian drug labels still replace the EU and UK prototype labels.
- `documents.json` has not been read, so document-type routing is untested.