

FROM LINEAR ALGEBRA TO MACHINE LEARNING

Omar Gutiérrez

September 7, 2018

@trinogz

OVERVIEW

Motivation

Tensors

Vectors

Matrices

Examples

Conclusions

MOTIVATION

MOTIVATION

- **Linear algebra** is important to understand machine learning.
- As well as **calculus**, **probability theory**, and **statistics**.
- It is rewarding to take the **hard path** to learn machine learning (IMHO).

TENSORS

VECTORS - RANK-1 TENSORS

- A vector is a collection of numbers

$$\vec{a} = \mathbf{a} = \begin{bmatrix} a_1 \\ a_2 \\ \vdots \\ a_n \end{bmatrix}$$

$$||\mathbf{x}||_p = \left(\sum_{i=1}^n |x_i|^p \right)^{\frac{1}{p}}$$

NumPy

```
np.linalg.norm(a)
```

TensorFlow

```
tf.linalg.norm(a, ord=1)  
tf.norm(a)
```

LENGTH OF A VECTOR - L^2 NORM

$$|a| = \sqrt{\sum_{i=0}^n a_i^2}$$

NumPy

```
np.linalg.norm(a)
```

TensorFlow

```
tf.linalg.norm(a)  
tf.norm(a)
```


DISTANCE BETWEEN VECTORS - L^2 NORM

$$d(a, b) = ||a - b||$$

$$= \sqrt{\sum_{i=0}^n (a_i - b_i)^2}$$

NumPy

```
np.linalg.norm(a-b)
```

TensorFlow

```
# Manhattan  
tf.norm(a-b, ord=1)  
# Euclidean  
tf.norm(a-b, ord="euclidean")  
tf.norm(a-b, ord=2)
```

$$d(a, b) = ||a - b||$$
$$= \sqrt{\sum_{i=0}^n (a_i - b_i)^2}$$

NumPy

```
np.linalg.norm(a-b)
```

TensorFlow

```
# Manhattan  
tf.norm(a-b, ord=1)  
# Euclidean  
tf.norm(a-b, ord="euclidean")  
tf.norm(a-b, ord=2)
```

DOT PRODUCT

$$\begin{aligned} a \cdot b &= \sum_{i=0}^n a_i b_i \\ &= a_0 b_0 + a_1 b_1 + \dots + a_n b_n \end{aligned}$$

NumPy

```
# do not confuse with np.multiply
np.dot(a, b)
# or with complex-conjugation
np.vdot(a, b)
# or
np.sum(np.multiply(a, b))
```

TensorFlow

```
tf.tensordot(a, b, 1)
# or
tf.matmul(tf.transpose(a), b)
# or
tf.matmul(a, b, transpose_a=True)
```

DOT PRODUCT

So,


$$\begin{aligned} \mathbf{a} \cdot \mathbf{a} &= a_0a_0 + a_1a_1 + \dots + a_na_n \\ &= a_0^2 + a_1^2 + \dots + a_n^2 \\ &= |\mathbf{a}|^2 \end{aligned}$$

```
np.linalg.norm(a) ** 2  
# or  
np.vdot(a, a)
```

MATRIX - RANK-2 TENSORS

- Matrices are sometimes used to represent **vector** transformations.

MATRIX - RANK-2 TENSORS



NumPy

`np.matmul(a, b)`


TensorFlow

`tf.matmul(a, b)`

- Matrix multiplication is not commutative. $AB \neq BA$ in general.

EXAMPLES

LINEAR REGRESSION



- Linear regression is the Swiss Army Knife of Data Science.

$$\arg \min_{a,b} \sum_i (y_i - (ax_i + b))^2 = \arg \min_w ||Xw - y||^2$$

- We want to calculate the w coefficients

$$\begin{pmatrix} y_1 \\ y_2 \\ \dots \\ y_n \end{pmatrix} = \begin{pmatrix} 1 & x_1 \\ 1 & x_2 \\ 1 & \dots \\ 1 & x_n \end{pmatrix} \bullet \begin{pmatrix} w_0 \\ w_1 \end{pmatrix}$$

LINEAR REGRESSION


- In the simplest case we want to calculate the intercept a and the slope b .

$$\begin{pmatrix} y_1 \\ y_2 \\ \dots \\ y_n \end{pmatrix} = \begin{pmatrix} 1 & x_1 \\ 1 & x_2 \\ 1 & \dots \\ 1 & x_n \end{pmatrix} \bullet \begin{pmatrix} a \\ b \end{pmatrix}$$

- The solution to this optimization problem is:

$$w^* = (X^T X)^{-1} X^T y .$$

SIMPLE PERCEPTRON



x_0	x_1	Σ	$f(x)$
1	1	$1 \times 0.5 + 1 \times -1 = -0.5$	0
1	0	$1 \times 0.5 + 0 \times -1 = 0.5$	1

- ToDo.

- This **matrix decomposition** technique is the base of dimensionality reduction.

$$\mathbf{A}\mathbf{v} = \lambda\mathbf{v}$$

- \mathbf{A} (with dimension $N \times N$) is a square matrix
- \mathbf{v} (with dimension N) is the eigenvector
- λ is a scalar value

- ToDo.

CONCLUSIONS

MORE TOPICS WE SHOULD CHECK

- **Gradient descent** is a beautiful optimization algorithm, basically, we multiply matrices to many times.
- Be aware that **numerical instabilities** can happen, and avoid these ones.

REFERENCES

- **Mathematics for Machine Learning: Linear Algebra** by Coursera.
- **The Math of Intelligence** by Siraj Raval.
- **Deep Learning Book** by Bengio and Goodfellow, has a chapter summarizing which linear algebra topics you need to learn neural networks.

Thank you.

Questions?

Comments?