

GENERICS

// class
class Box<T> {}
// variable
Box<String> b = new Box<String>();
// method
public <T> void doStuff(T value) {}

JAVA BEING STUPID

T obj = new T(); // error
obj instanceof T; // error
T heh = (T) "asdf"; // no typechecking
var s = Stack<int>(); // no primitive types
private static T x; // static no workkey
Node<Number> s = new Node<Integer>; // error
class IThrowAnErrorBecauseWhyNot {
 void m(List<String> list) {}
 void m(List<Integer> list) {}
} // error because of type erasure & identifiability

ITERATOR

for (String s : stringList) {} // ==
for (Iterator<String> i = stringList.iterator();
 i.hasNext();) {
 String s = i.next();
}

ITERABLE

interface Iterable<T> {
 Iterator<T> iterator();
}
interface Iterator<E> {
 boolean hasNext();
 E next();
}

COMPARABLE

TODO:
Type signature?

static <T extends Comparable> T doStuff(T a, T b) {
 // compareTo is possible with all types
 return a.compareTo("b") > 0 ? a : b;
}
static <T extends Comparable<T>> T doStuff(T a, T b)
{
 // compareTo is possible only with T
 return a.compareTo(b) > 0 ? a : b;
}

EXAMPLE

class Graphic {
 public void draw() {}
}
class Rectangle extends Graphic {
}
class Circle extends Graphic {
}
class GraphicStack<T extends Graphic> {
 extends Stack<T> {
 public void drawAll() {
 for (T item : this) item.draw();
 }
 }
}

BYTECODE

TODO:

TYPE ERASURE

- Introduced because of "bAcKwArDs CoMpAtAbIlItY"
- No type information at runtime (Non-Reifiable Type)

class MyStack<T> {
 Entry<T> top;
 int push(T value) {}
}
// becomes
class MyStack {
 Entry top;
 int push(Object value) {}
}
/* with bounds */
class MyStack<T extends Comparable<T>> {
 Entry<T> top;
 int push(T value) {}
}
// becomes
class MyStack {

Entry top;
int push(Comparable value) {}
}
/* what happens at/before runtime */
MyStack<String> s = new MyStack<String>();
s.push("Eh");
String x = s.pop();
// becomes
MyStack s = new MyStack();
s.push("Eh");
String x = (String) s.pop();

WILDCARDS

void printGs(List<Graphic> gs) {}
List<Graphic> gs1 = new ArrayList<>();
printGs(gs1); // ok
List<Circle> gs2 = new ArrayList<>();
printGs(gs2); // error
/* solution */
void printGs(List<? extends Graphic> gs) {}

GENERIC VARIANCE

	Type	Compatible Type-Args	R	W
Invariance	C<T>	T	✓	✓
Covariance	C<? extends T>	T and sub-types	✓	✗
Contravariance	C<? super T>	T and basis-types	✗	✓
Bivariance	C<?>	All	✗	✗

INVARIANCE

static <T> void move(Stack<T>, from, Stack<T> to) {
 while(!from.isEmpty()) to.push(from.pop());
}
var rectS = new Stack<Rectangle>();
var graphS = new Stack<Graphic>();
graphS.push(new Rectangle()); // ok
move(rectS, graphS); // error
Stack<Object> objS = graphS; // error
/* anotherone */
String[] strA = new String[10];
Object[] objA = strA; // ok
objA[0] = Integer.valueOf(2); // runtime err

TODO:

// compiles?
List<Graphic> list = new ArrayList<Rectangle>();
// compiles?
Rectangle[] rectangleStack = new Rectangle[10];
Graphic[] graphicStack = new Graphic[10];
graphicStack = rectangleStack;
// compiles?
Stack<Rectangle> rectangleStack = new Stack<>();
Stack<Graphic> graphicStack = new Stack<>();
graphicStack = rectangleStack;
// compiles?
Stack<Rectangle> rectangleStack = new Stack<>();
Stack<Graphic> graphicStack = new Stack<>();
for (Rectangle r : rectangleStack) {
 graphicStack.push(r);
}

COVARIANCE

public class Stack<E> {
 public void pushAll(Iterable<? extends E> src) {}
}
Stack<? extends Graphic> graphS;
graphS = new Stack<Rectangle>(); // ok
graphS = new Stack<Circle>(); // ok
graphS = new Stack<Object>(); // error (duh)
/* read only */
Stack<? extends Graphic> stack = new
Stack<Rectangle>();
stack.push(new Graphic()); // error
stack.push(new Rectangle()); // error
stack.push(new Triangle()); // error

CONTRAVARIANCE

static <T> void addToC(List<? super T> list, T e) {
 list.add(e);
}
addToC(new ArrayList<Number>(), 3); // ok
addToC(new ArrayList<Object>(), 3); // ok
/* shenanigans */

Stack<? super Graphic> s = new Stack<Object>();
s.add(new Graphic()); // ok
s.add(new Rectangle()); // ok
Graphic g = s.pop(); // error
Object g = s.pop(); // ok

BIVARIANCE

static void printList(List<?> list) {
 for (Object elem : list)
 System.out.print(elem + " ");
}
/* more shenanigans */
static void appendNewObject(List<?> list) {
 list.add(new Object()); // error
}

PRODUCER / CONSUMER

TODO:

MISC

<T extends Comparable & Collection> // multiple type
bounds

GENERIC STREAM TOMFOOLERY

List<? extends Media> mediaList;
public <S extends T> List<S>
 filterBySubtype(Class<S> subtype) {
 return mediaList.stream()
 .filter(subtype::isInstance)
 .map(subtype::cast)
 .collect(Collectors.toList());
 }
}

ANNOTATIONS

- Metadata
- Not actually part of the code

TODO:
slides 10

- @Override
- @Test
- @Json...

DEFINING

@Target(ElementType.TYPE)
@Retention(RetentionPolicy.RUNTIME)
public @interface Author {
 String name();
 String date() default "N/A";
}

@Author(name = "UwU", date = "idon't validate input")
public class WeeOoo {}

REFLECTION

- Information of Class (private and public): Methods, Attrib-
utes, Parent class, Implemented interfaces
- Calling methods possible
- Usages: Debugger, Serialization, Frameworks, Remote
Procedure Call, ORM
// all of these `throws SecurityException`
public Field[] getDeclaredFields()
public Method[] getDeclaredMethods()
public Constructor<?>[] getDeclaredConstructors()

System.out.println(dump(new Student("a", "b"), 0));
// {
// firstName = a
// lastName = b
// }
Class c = "s".getClass(); // java.lang.String

TODO:
Diagram (slides 26)

METHOD

// @Target(ElementType.METHOD)

public String getName()
public boolean isAnnotationPresent(
 Class<? extends Annotation> annotationClass)
public Object invoke(Object obj, Object... args)
 throws IllegalAccessException,

IllegalArgumentException,
InvocationTargetException

public class Profiler {
 public static void main(String[] args) {
 var testFunctions = new ProfileFunctions();
 int[] array = {5, 2, 8, 1, 93, 3, 33, 1, 333};
 var methods = ProfileFunctions.class
 .getDeclaredMethods();
 for (var m : methods) {
 if(m.isAnnotationPresent(Profile.class)) {
 m.setAccessible(true); // best practice or
 sth, idk, i write code in actually good languages
 Profiler.profileMethod(testFunctions, m,
 new Object[] {array});
 }
 }
 }
}

CLASS

TODO:

// @Target(ElementType.TYPE)

getDeclaredConstructor().newInstance()
...
ATTRIBUTE

TODO:

// @Target(ElementType.FIELD)

...
VALIDATION

@Min(value = 18, message = "Age must be ≥ 18")
@Max(value = 99, message = "Age must be ≤ 99")
private int age;
@NotNull(message = "Name cannot be null")
private String name;

ALGORITHMS

- Brute-force
- Greedy
- Take best option each step (optimize locally)
- Fast
- Backtracking
- Trial and error
- Best overall option
- Higher compute costs
- Divide and conquer
- Binary search
- Dynamic programming
- Recursion optimization?
- Tabulation

BACKTRACKING

TODO:
slides 87

BIG O NOTATION

- Worst case scenario
- Atomic operations = constant time
- Runtime measured as sum of primitive operations

Notation

Algorithm $\tilde{f}$ $\left(\underbrace{n}_{\text{Size of problem}} \right)$ = Number of steps

 g = complexity class

TODO:
diagram $f \leq cg$

$f(n)$ is $O(g(n))$ if $c > 0 \wedge n_0 \geq 1$
 $f(n) \leq cg(n)$ for $n \geq n_0$

f in order g :

Let $f, g : \mathbb{N} \rightarrow \mathbb{N}$
 $n_0, c \in \mathbb{N} \wedge \forall n \geq n_0 : f(n) \leq c \cdot g(n)$
 $\Rightarrow f \in O(g) \Leftrightarrow f = O(g)$

Big O

$\tilde{O} \left(\underbrace{n}_{\text{Size of problem}} \right) = \text{Complexity class}$

RULES

If $f(n)$ is polynomial of degree d , then $f(n) \in O(n^d)$
- ignore lower powers
- ignore constants

Use most optimal function (lowest power)
- $2n$ is $O(n)$ better than $2n$ is $O(n^2)$

Simplify as far as possible
- $3n + 5$ is $O(n)$ instead of $3n + 5$ is $O(3n)$

COMPLEXITY CLASSES

Name	Class	Example
Constant	1	Array read
Logarithmic	$\log n$	Binary search
Linear	n	Linear search
Log-linear	$n \log n$	Merge+Quick sort
Quadratic	n^2	Bubble+Insertion sort
Cubic	n^3	Solve equation
Polynomial	n^k	Various algorithms
Exponential	2^n	Calculate all subsets
Factorial	$n!$	Calculate all permutations

$O(1)$
 $O(\log n)$
 $O(n)$
 $O(n \log n)$
 $O(n^2)$
 $O(n^3)$
 $O(2^n)$

TODO:
Counting primitive operations (slides 55)

SORTING ALGORITHMS

SELECTION SORT

- Search for smallest elem in unsorted part and move in front

- Less mutations in array
- Same performance even if list almost sorted

```
public static void selectionSort(int[] a) {
    int n = a.length;
    for (int i = 0; i < n - 1; i++) {
        int minimum = i;
        for (int j = i + 1; j < n; j++)
            if (a[j] < a[minimum])
                minimum = j;
        swap(a, i, minimum);
    }
}
```

$$(n-1) + (n-2) + \dots + 1 = \sum_{i=1}^{n-1} i = \frac{n(n-1)}{2} = \frac{n^2-n}{2} \sim O(n^2)$$

- INSERTION SORT**
- Take elem and put into correct place in sorted part
 - Good for already partially sorted arrays

```
public static void insertionSort(int[] a) {
    int n = a.length;
    for (int i = 1; i < n; i++)
        for (int j = i; j > 0 && a[j] < a[j - 1]; j--)
            swap(a, j, j - 1);
}
```

$$1 + \dots + (n-1) + n = \sum_{i=1}^n i = \frac{n(n+1)}{2} = \frac{n^2+n}{2} \sim O(n^2)$$

- BUBBLE SORT**
- Compare neighboring elems and swap if needed

```
public static void bubbleSort(int[] a) {
    for (n = a.length; n > 1; n--)
        for (i = 0; i < n - 1; i++)
            if (a[i] > a[i + 1])
                swap(a, i, i + 1);
}
```

$$(n-1) + (n-2) + \dots + 1 = \sum_{i=1}^{n-1} i = \frac{n(n-1)}{2} = \frac{n^2-n}{2} \sim O(n^2)$$

```
public static void countingSort(int[] a) {
    int k = Arrays.stream(arr).max().getAsInt();
    int[] c = new int[k + 1];
    for (int i : a) c[i] += 1;
    int pos = 0;
    for (int i = 0; i < k; i++)
        for (int j = 0; j < c[i]; j++) {
            a[pos] = i;
            pos++;
        }
}
```

$$n + n + k + n = 3n + k \sim O(n + k)$$

- SHELL SORT**
- Sort pairs of far away elems
 - Sort the partially sorted array through insertion sort

```
public static void shellSort(int[] a) {
    int n = a.length;
    int h = 1;
    while (h < n/3) h = 3 * h + 1;
    while (h >= 1) {
        for (int i = h; i < n; i++)
            for (int j = i; j >= h && a[j] < a[j - h]; j = j - h) swap(a, j, j - h);
        h /= 3;
    }
}
```

BINARY SEARCH

```
public static <T extends Comparable<T>> boolean bs(
    List<T> data, T target, int low, int high) {
    if (low > high) return false;
    int pivot = low + ((high - low) / 2);
    if (target.equals(data.get(pivot)))
        return true;
    else if (target.compareTo(data.get(pivot)) < 0)
        return searchBinary(data, target, low, pivot - 1);
    else
        return searchBinary(data, target, pivot + 1, high);
}
```

```
return searchBinary(data, target, pivot + 1, high);
}
```

$$O(\log n)$$

RECURSION

When a function calls itself

LINEAR RECURSION

Recursive call starts **at most one** further recursive call

TODO:

recursive → iterative (slides 61)

TAIL RECURSION

Linear recursion where the recursive call is **last**

TODO:

recursive → iterative (slides 69 – nice)

BINARY RECURSION

All non-terminal calls have **two** recursive calls

TODO:

example (slides 76,77,78)

TODO:



$O(n)$ (slides 84)

DATA STRUCTURES

ADT: Abstract Data Type (e.g. Interface)

TODO:

diagram



PRIORITY QUEUE




Method	Unsorted List	Sorted List
insert	$O(1)$	$O(n)$
min	$O(n)$	$O(1)$
removeMin	$O(n)$	$O(1)$

HEAP

- Binary tree
- Layers 0, ..., $h-1$ fully populated, layer h filled from left
- Operations always lowest RHS so that tree stays consistent

Min-Heap: Keys of nodes are **smaller** or equal than children's


Max-Heap: Keys of nodes are **larger** or equal than children's



HEAP SORT

Dequeue elems from head into list, resorting tree on each iter

- TODO:**
- BINARY SEARCH TREE (BST)**
- All subnodes of **left** subtree are **smaller** than root
 - All subnodes of **right** subtree are **larger** than root



TODO: