

INFORMATION SECURITY (IS)

Information: Data that has been processed in a way that gives it meaning and value

Information security: Protection of the integrity, confidentiality and availability of information

Non-repudiation: Prevents parties from denying their actions

Accountability: Ability to trace actions back to a person

Authentication: Verifies the identity of a user or system

Authorization: Determines actions an entity is allowed to do

Access control: Restrict access to resources based on roles

Security policy: A rule/expectation for protecting information

Compliance: Adherence to laws, regulations, and standards

Types of information: Personal, business, financial, intellectual, system

Components of an Information System (IS): Software, Hardware, Data, People, Procedures, Networks

Bottom-Up: Implementations happen before policies

Top-Down: Initiated by management, more effective

McCumber cube: x: CIA (what), y: Information states (where), z: Control (how)

(C)onfidentiality: Prevent unauthorized access to info

(I)ntegrity: Protect reliability and correctness of information

(A)vailability: Ensure uninterrupted access to information

Information states: In storage, in transit, in use

Control: A measure designed to reduce the potential risk of an attack by eg. **Policy, Education, Technology**

(S)poofing: Pretending to be someone else

(T)ampering: Unauthorized data modification or altering

(R)epudiation: Denying actions without proof

(I)nformation disclosure: Exposing sensitive information

(D)enial of service: Making systems or services unavailable

(E)levation of privilege: Gaining unauthorized rights

THREAT CATEGORIZATION

SOCIAL ENGINEERING

Manipulating people to reveal confidential information

Phishing: Forged emails impersonating legitimate entities

Spear Phishing: Targeted phishing to specific individuals

Vishing: Voice-based phishing over phone or video calls

Smishing: SMS / Text-based phishing

SOFTWARE ATTACKS

Exploiting vulnerabilities in software to gain access to a system or steal data

Virus: Malware that attaches to programs and spreads

Worms: Self-replicating malware that spreads over a network

Trojan Horse: Malicious sw disguised as legitimate apps

Ransomware: Encrypts victim data, asks payment to restore

Rootkits: Stealthy tools that hide malicious activity and maintain privileged access

DENIAL OF SERVICE

Overloading one or multiple systems to make it unavailable

DoS: Single source denial of service attacks

DDoS: DoS performed by multiple attackers/devices

Botnet: Network of compromised devices controlled by an attacker and used to together to flood a target with traffic

SYN-Flood Attack: Sending many TCP connection requests without completing them

Reflection Attack: Attacker spoofs victim's IP, sends requests to a service so that it sends (many) replies to victim

WEB APPLICATION ATTACKS

Exploiting vulnerabilities in websites/servers hosting websites

SQL Injection: Insert malicious SQL commands into an input

Cross-Site Scripting (XSS): Inject malicious scripts into website that execute in users' browsers to steal data

Cross-Site Request Forgery (CSRF): Trick logged-in user's browser into sending reqs to a webapp on attacker's behalf

Broken Authentication: Weak auth mechanisms allow attackers to gain unauthorized access (password/session)

PASSWORD / AUTHENTICATION ATTACKS

Attempting to bypass or compromise login systems to gain unauthorized access

Rainbow Table Attacks: Precomputed hash lookup tables to reverse weakly hashed passwords back into plaintext

Password Spraying: Trying a few common passwords like "password" across many accounts to avoid lock-timeouts

Credential Stuffing: Using leaked credentials from previous breaches to attempt logins on other services

Brute Force Attack: Repeatedly try many username & password combinations until they gain access to an account

PHYSICAL ATTACKS

Bypassing technical controls by accessing physical infrastructure directly

Theft of devices: Physically steal hardware to gain direct access to stored data, credential, internal systems, ...

Hardware tampering: Modify/implant malicious components in to intercept data, bypass security, or disrupt operations

Power disruption: Interrupt or manipulate power supply impacting availability and business continuity

Environmental damage: Environmental events that damage infrastructure, causing data loss, downtime, ...

INFORMATION SECURITY MANAGEMENT (ISM)

TODO:
notes 12

Information security governance: System by which IS strategy is controlled to ensure that it supports business objectives, manages risk appropriately, and complies with legal and other regulatory requirements. (what)

Information Security Management System (ISMS): Framework used to manage and protect assets through policies, processes and controls (how)

Enterprise Information Security Policy (EISP): Information security policy that sets the strategic direction and scope for all an organization's security efforts

Risk Management Process: Definition of processes to identify assets, analyze threats and evaluate risk

Security Awareness and Training: Educational programs to ensure employees understand their security responsibilities

Monitoring, Measurement and Audits: Ongoing evaluation of control effectiveness and ISMS performance

POLICY

Practices: Ex. actions that illustrate compliance with policies

Policy: Instructions that dictate certain behavior within an org

Standard: Details of what must be done to comply with policy

Guidelines: Non-mandatory recommendations (reference)

Procedures: Step-by-step instructions designed to assist employees in following policies

De jure standard: Formally evaluated and approved by a formal standards organization

De facto standard: Widely adopted/accepted by public group

TODO:
notes 14,15

RISK ANALYSIS

Identify Assets → Identify Threats → Identify Vulnerabilities → Assess Likelihood → Assess Impact → Determine Risk Level

Asset: Item of value belonging to an organization, eg: Information: Customer data, intellectual property, code

Technical: Services, applications, databases, networks

Physical: Servers, devices, facilities, infrastructure

Human: Employees, administrators, contractors

Business Process: Critical operational workflows

Threat: An event or action with the potential to cause harm by exploiting a vulnerability, eg: power outage, vishing

CLASSIFYING ASSETS

Public: Information that can be shared without risk

Internal: Information for organization internal use only

Confidential: Sensitive info, could cause harm if disclosed

Restricted: Highly sensitive, strictly limited, strongly protected

SECURITY CONTROLS

Administrative/Management Controls: Policies, procedures, security training, security governance

Technical / Logical Controls: Firewalls, encryption, access control systems, system hardening

Physical Controls: Physical locks, surveillance cameras, secure access badges, turnstiles

Preventive Controls: Stop incidents before they occur. eg. Firewalls, access control, encryption

Detective Controls: Identify incidents when they occur. eg. Intrusion detection, log monitoring, SIEM, CCTV

Corrective Controls: Limit damage, restore systems after an incident. eg. Backups, system restore, incident response

Deterrent Controls: Discourage malicious behavior. eg. Warning banners, monitoring notices, disciplinary policies

Compensating Controls: Reduce risk when a primary control cannot be implemented. eg. Network isolation, layered security, alternative safeguards

Business continuity: Ensures critical operations continue during disruptions. Objectives: maintain operations, minimize impact, protect assets, recover fast

SECURITY AND AWARENESS TRAINING

1) **Awareness:** basic information, what

2) **Training:** detailed knowledge, how

3) **Education:** depth of knowledge, why

GAP ANALYSIS

Define target framework → Assess curr state → Identify gaps, assess risk → Eval, prioritize gaps → Create remediation plan

SECURITY FRAMEWORK

NIST Cybersecurity Framework: Framework for managing cyber risk: Identify, Protect, Detect, Respond, Recover

CIS Controls: Defines 18 practical technical security controls

THREATS

Attack: Act that intends to damage, steal or degrade assets

Vulnerability: A weakness in a system that can be abused

Exploit: A method used to take advantage of a vulnerability

Risk: The likelihood of a threat exploiting a vulnerability and the potential harm that could cause = Vulnerability + Threat

Threat vector: Path, method, or delivery mechanism that a threat uses to reach an asset and exploit a vulnerability

Attack surface: Sum of threat vectors that hackers can use to carry out a cyberattack.

RISK MANAGEMENT (RM)

The process of identifying, assessing, prioritizing and mitigating threats to an asset from an organisation.

Risk management process: Implementation, analysis, evaluation of the risk management framework (doing).

Risk assessment: The identification, analysis, and evaluation of risk as initial parts of risk management.

Risk treatment & Risk Owner: The application of safeguards or controls to reduce the risks to an organization's information assets to an acceptable level.

1) **Risk identification:** Where and what is the risk?

2) **Risk analysis:** How severe is the current level of risk?

3) **Risk evaluation:** Is the current level of risk acceptable?

4) **Risk treatment:** What do I need to do to bring the risk to an acceptable level?

Risk management framework: Structure of the strategic planning and design of risk management efforts (planning).

1) **Executive Governance & Support:** Support from management and users.

2) **Framework Design:** Defining the methods and risk appetite strategy.

3) **Framework Implementation:** Rollout of the plan (through → RM process).

4) **Monitoring & Review:** How effective is the entire system?

5) **Continuous Improvement:** Continuous adaption to new, or existing threats.

Risk appetite (strategic): The quantity of risk that organizations are willing to accept, to achieve their goals

Risk tolerance (specific): The acceptable risk organizations are willing to accept for a specific asset

Residual risk: Remaining risk after controls were applied

TODO:
slides 17,19 (notes 19,20), risk identification, risk analysis

Common Vulnerabilities and Exposures (CVE): Standard identification number for vulnerabilities

Common Vulnerability Scoring System (CVSS): Severity scores for vulnerabilities based on CIA (14d 2b remediated)

QUANTITATIVE RISK ANALYSIS

1) Assign Asset Value (AV)

1) Identify the organization's information assets.

2) Classify them.

3) Categorize them into useful groups.

4) Prioritize them by overall importance.

2) Calculate Exposure Factor (EF)

– percentage of loss that an organization would experience if a specific asset is violated by a realized risk

3) Calculate single loss expectancy (SLE)

– Exact amount of loss if an asset were harmed by a threat

– $SLE = AV \times EF$

4) Assess the annualized rate of occurrence (ARO)

– Expected occurrence frequency of a threat within a year

5) Derive the annualized loss expectancy (ALE)

– possible yearly cost of all instances of a realized threat against an asset

– $ALE = SLE \times ARO$

6) Perform cost/benefit analysis of countermeasures

TODO:
ALE with safeguards, risk evaluation, risk treatment, mitigation (notes 22,23)

IDENTITY & ACCESS MANAGEMENT (IAM)

Provisioning and protecting digital ids & access permissions

Subject: Active entity that accesses a passive object. users, programs, processes, services, computers

Object: Passive entity that provides information to subjects. files, databases, computers, programs, services, printers

Physical controls: To prevent, monitor, or detect direct contact with systems: guards, fences, motion detectors

Technical or logical controls: To manage access and provide protection for resources. auth, encryption, ACL

Administrative controls: Policies and procedures. hiring practices, background checks, security training

Identification: Claiming an identity, eg. typing a username

Authentication: Verifying validity of claimed id, eg. password

1) Something you know, eg. password

2) Something you have, eg. smartcard

3) Something you are/something you do, eg. biometrics

4) Somewhere you are / aren't (secondary factor)

Basic Authentication: Username/pw transmitted in the clear

One Time Passwords: Basic auth but used only once

Challenge / Response: Password and one-time challenge

Anonymous Key Exchange: Exchange credentials over unauthenticated secure channel, eg. diffie-hellmann

Zero-Knowledge Password Proofs: Does not permit offline-based password attacks


Server Certificates + User Authentication: Transmit user password over unilaterally authenticated secure channel

Mutual Public Key Authentication: Bilateral use of public key signatures

Multifactor Auth: Using two or more factors

KERBEROS

Uses symmetric key encryption (DES)



Principal: A Kerberos participant

Principal's Master Key: Long-term secret between the principal and KDC. Used to en-/decrypt authentication tickets.

Kerberos Ticket: Temporary credential for network services

Authentication Server (AS): Verifies client, gives TGT

Ticket Granting Server (TGS): Grants services, gives ST

Ticket Granting Ticket (TGT): Given by the AS

Service Ticket (ST): Given by the TGS

Key Distribution Center (KDC): Verifies & manages auth credentials, distributes session keys to users and services

RADIUS

Remote Authentication Dial-In User Service provides centralized Authentication, Authorization and Accounting (AAA)

1) User requests access from Network Access Server (NAS)


2) NAS prompts the RADIUS server for credentials

3) RADIUS server evaluates the request and returns one of:

- Access-Accept: User authenticated, NAS grants access
- Access-Reject: Invalid credentials, NAS denies access
- Access-Challenge: Server requires more info (MFA)

4) Connected: NAS sends Accounting-Request (log session)

Attack	Kerberos	RADIUS
Passive Password Sniffing		
Offline Brute Force Password Attack	X	X
Active Man-in-the-Middle Attack		X
Identity Theft on Server		
CA Compromise		X



Discretionary access control (DAC): Every object has an owner, the owner can grant or deny access (sharing drive)

Nondiscretionary access control (NDAC): Access controls that are implemented by a central authority (HIPAA/DSG)

Lattice-based access control (LBAC): Assigns users a matrix of authorizations for particular areas

Mandatory access control (MAC): Labels applied to both subjects and objects (classified documents ↔ glowies)

Role-based access control (RBAC): Privileges are tied to a role or job (project info ↔ project manager)

Task-based (TBAC) access control: Privileges are tied to a task (access to server room ↔ technician's time slot)

Auditing: A subject's actions are tracked and recorded

Accounting: Consumption of resources by a subject is measured, metered, and collected.

TODO:
shorten all this below

Salting: Adds unique random value password before hashing, prevents same passwords from producing same hash

Access Aggregation Attacks (passive attack): Aggregating nonsensitive information to learn sensitive information (Reconnaissance attack)

Password Attacks (brute-force attack): Online vs Offline: steal account database and then crack the passwords

Dictionary Attack (brute-force attack): Discover passwords by using every possible password in a predefined database

Birthday Attack (brute-force attack): Finding collisions. MD5 is not collision free, SHA-3 is safe against birthday attacks and collisions

Sniffer Attacks: Application that captures traffic traveling over the network. Encrypt all sensitive data, Use OTP.

CRYPTOGRAPHY

Ciphertext/Cryptogram: Encrypted message

Cipher: Encryption algorithm. Set of rules for en-/deciphering Key/Cryptovariable: Usually a very large binary number

Key space: Range of numbers from 0 to 2ⁿ, where n is the bit size of the key. A 128-bit key is $\in \{0, \dots, 2^{128}\}$

One-Way Functions: Easily produces output values but makes it impossible to retrieve the input values

Reversability: Being able to undo the operation of encryption

Nonce: Must be a unique number each time it is used. Used to make sure that a key is not re-used twice. The nonce is public, whereas the (shared) key is private

Initialization vector (IV): Random bit string, same length as the block size and is XORed with the message to create unique ciphertext every time same message is encrypted

Steganography: Embedding secret messages within content

Objectives: Confidentiality (Privacy), Integrity, Authentication, Non-repudiation

Kerckhoff's Principle: Security stems from the secrecy of the key and not the secrecy of the algorithm

Shannon's Principles:

- Confusion:** Relationship between the plaintext and the key is complicated. **S-Box, substitution**
- Diffusion:** Change in plaintext results in multiple changes spread throughout the ciphertext. **P-Box, permutation**
- SP-Network:** Repeated **substitution** and **permutation**
- One-Time-Pad (OTP):** XORing all bytes with same size OTP
- Hashing:** Maps data to fixed-size output. Should be: random, diffused, fast, deterministic, irreversible, collisionless
- Password storage:** Prefer slow hash functions (SHA-256)
- Summarizing data:** Prefer fast hash functions (argon2)
- HMAC:** Hash based MAC, splits a key in two and hashes twice, not vulnerable to length extension attack
- SHA-1:** Insecure, fast
- SHA-2:** 256/512-bit variants, current standard, secure
- SHA-3:** (KECCAK), flexible
- KMAC 128/256:** SHA-3 based KECCAK MAC
- bcrypt:** Salted, GPU-resistant
- Argon2:** Highly secure, configurable
- AES:** Advanced Encryption Standard (SP-Net). XOR, Sub-Bytes, ShiftRows, MixColumns (128 bit block size)

SYMMETRIC CRYPTOGRAPHY

Relies on shared secret key, distributed to all members participating in the communications

- Stream ciphers:** Approximate a one-time pad by generating an infinite pseudo-random keystream, work on messages of any length, nonce guarantees uniqueness, fast, no guaranteed integrity
- Block ciphers:** Take an input of a fixed size and return an output of the same size, use confusion and diffusion (SP-Network) $\Rightarrow$ AES

TODO:
S-Box, P-Box (slides 39)

Electronic Code Block (ECB):

TODO:

Cipher Block Chaining (CBC):

TODO:

Counter Mode (CTR):

TODO:

ASYMMETRIC CRYPTOGRAPHY

Relies on mathematically linked key pairs. $n \in \mathbb{N} \setminus \{0\}, z \in \mathbb{Z}$

Public-key enc: $\text{pubk}(e, n)$ encrypt, $\text{privk}(d)$ decrypt

Digital signing: $\text{privk}(d)$ sign, $\text{pubk}(e, n)$ verify

Discrete logarithm: $f(g, a, p) = g^a \bmod p$ (Diffie-Hellman)

Primitive root:

TODO:

Factoring: $f(p, q) = p \cdot q$ (RSA)

Euler's Theorem: $\text{gcd}(z, n) = 1 \Rightarrow z^{\varphi(n)} \equiv 1 \bmod n$

Totent:

$$\begin{aligned} \mathbb{Z}_n^* &= \{x \in \mathbb{Z}_n \mid x \text{ has a multiplicative inverse in } \mathbb{Z}_n\} \\ \varphi(n) &= \text{Nr. of elements in } \mathbb{Z}_n^* \text{ with mult. inv.} \\ &= \text{Amount of Numbers } 1 \leq q \leq n \text{ with } \text{gcd}(q, n) = 1 \\ &= |\mathbb{Z}_n^*| \end{aligned}$$

- 1) $n \in \mathbb{N}$ prime $\Rightarrow \varphi(n) = n - 1$

- 2) $n \in \mathbb{N}$ prime, $p \in \mathbb{N} \setminus \{0\} \Rightarrow \varphi(n^p) = n^{p-1} \cdot (n - 1)$
- 3) $m, n \in \mathbb{N} \setminus \{0\}, \text{gcd}(m, n) = 1 \Rightarrow \varphi(n \cdot m) = \varphi(n) \cdot \varphi(m)$
- RSA:** Rivest–Shamir–Adleman: Signing, use DH for Encryption. Weak for short messages, add OAEP
- 1) Choose two prime numbers p, q
 - 2) Calculate $n = p \cdot q$
 - 3) Calculate $\varphi(n) = (p - 1)(q - 1)$
 - 4) Choose a, b , so that $a \cdot b \equiv 1 \bmod \varphi(n)$
 - 5) Forget $p, q, \varphi(p \cdot q)$

Public key is now n, b , private key is n, a

- Encrypt: $z = e^a \bmod n$
- Decrypt: $c = z^b \bmod n = c^{a^b} \bmod n$

OAEP: Padding, introduces IV and hashes it


PSS: Probabilistic Signature Scheme: Hash, Salt, Pad, RSA

DSA: Digital Signature Algorithm

DSS: Digital Signature Standard

DH: Diffie Hellman, share secret over insecure channel

- 1) Agree on **public parameters** (prime and generator)
- 2) Combine **private key** with the **parameters**
- 3) Send resulting **public keys** to each other
- 4) Combine other **pubkey** with **priv key** to get shared **secret**



ECC: Elliptic Curve Cryptography

TODO:

ECDSA: Elliptic Curve Digital Signature Algorithm

ECDH: Elliptic-Curve Diffie Hellman

ECDSA: Elliptic Curve Diffie-Hellmann Ephemeral

Perfect forward secrecy: Ephemeral DH KEX, forces new key exchange for every new session (refreshing website)

TRANSPORT LAYER SECURITY (TLS)

TODO:
handshake

AEAD: Authenticated Encryption with associated data



GCM: Galois Counter Mode $\Rightarrow$ Message Authentication Code

PUBLIC KEY INFRASTRUCTURE (PKI)

A set of roles, policies, hardware and software needed to manage digital certificates and public-key encryption

TODO:
explanations

Subscriber $\xrightarrow{\text{CSR}}$ RA $\rightarrow$ CA $\rightarrow$ VA

RA: Registration Authority, validates CSR

CP: Certificate Policies

CPS: Certificate Practice Statements

CA: Certificate Authority, trusted certificate issuer

CSR: Certificate Signing Request (creates)

CRL: Certificate Revocation List (signs)

VA: Validation Authority, validates integrity of certificates

TSA: Time Stamp Authority

Subscriber: Client / Certificate holder

HPKP: Certificate pinning

Truststore: Central (private) storage for certificates

Keystore: Central (private) storage for private keys

Hybrid cryptosystem: Var. methods for optimal use-cases

- Hashing: Digital fingerprint
- Symmetric cryptography: Bulk encryption

– Asymmetric cryptography: Signing/exchanging keys

Cipher suites: **enc_kex_signature_WITH_bulk-enc_mac**

TLS_DHE_RSA_WITH_AES_128_GCM_SHA256

OCSP: Certificate Status Protocol

CT: Certificate Transparency

TODO:
illustrate CSR procedure

E-MAIL

MIME: Multipurpose Internet Mail Extensions

SMIME: Secure MIME (signatures + encryption)

TODO:
notes 50-55

TODO:
Web

CYBER KILL CHAIN

A model developed by Lockheed Martin in 2011, adapted from a military concept.

- 1) Reconnaissance: Gather information on the target
 - Social media, DNS Lookup, Legal info
- 2) Weaponization: Construct custom weapon to attack target
 - Exploit: Office macro execution, malicious PDF
 - Payload: Remote Access Tool, Ransomware, Spyware
 - Weapon: Phishing Email, Crafted Network Request
- 3) Delivery: Transmit the weapon to the target
 - USB Drops, drive-by downloads, phishing mails
- 4) Exploitation: Vulnerability is triggered or the target tricked
- 5) Installation: Establish persistence, install backdoors
 - Scheduled tasks, startup folders
- 6) Command & Control (C2): Compromised host connects to the attacker
 - DNS tunneling, HTTPS to legitimate-looking domain
- 7) Actions on Objectives: Exfiltration, encryption, sabotage, lateral movement

Beaconing: Most C2 traffic beacons: small periodic check-ins, often jittered, tiny in volume but constant in rhythm

TODO:
breaking the chain

MITRE ATT&CK: Matrix of 14 tactics, hundreds of techniques

INCIDENT RESPONSE

ESCALATION PATH

Event: Any observable occurrence in a system. A user logs in, a file is created, a packet arrives. Most events are routine

Alert: Automated notification from a security tool that an event matched a detection rule and may warrant investigation

False positive: An alert or suspected adverse event that turns out to be benign

Adverse event: An event with possibly negative consequences, worth investigating

Incident: A confirmed adverse event that threatens the confidentiality, integrity, or availability of information assets

Data breach: An incident resulting in unauthorised access to or disclosure of protected data

PIPKIN'S INDICATORS

Possible: Weak signals, worth logging but not acting on alone

Probable: Strong signals, typically trigger investigation

Definite: Confirmed incidents, activate the IR plan

True Positive	False Positive
False Negative	True Negative

Classifier's dilemma:

DETECT AND RESPOND

"Prevent Everything": If the perimeter holds, we are safe

"Assume Breach" Mindset: Design for fast detection and fast containment, not just for prevention.

MTTD (Mean Time to Detect): Initial compromise - first alert

MTTR (Mean Time to Resp.): First alert - incident contained

Dwell Time (MTTD + MTTR): Total time attacker was active

SOC (Security Operations Centre): The always-on monitoring function. Runs the SIEM, triages alerts, drives day-to-day detection. (T1 triage, T2 investigation, T3 engineering).

CSIRT (Computer Security Incident Response Team): Handles confirmed incidents end-to-end. Often virtual, pulled together when needed: IT, legal, comm, mgmt

CERT (Computer Emergency Response Team): National or sector-level coordination bodies (e.g., GovCERT.ch)

In-House vs. Managed: Many organisations outsource SOC functions to an MSSP (Managed Security Service Provider). CSIRT responsibilities usually stay in-house.

NIST IR PROCESS

- 1) Preparation: Policy, plan, team, tools, training
- 2) Detection & Analysis: Spot signals, classify them
- 3) Containment, Eradication & Recovery: Stop the bleeding, remove the attacker, restore services. Short/Long-Term
- 4) Post-Incident Activity: Lessons learned, feed back to Prep

COMMON IR MISTAKES

Unclear Chain of Command: Attacker uses the confusion

No Central operations center: Decisions are undocumented

Containing too slowly: Fear of "making it worse"

Wiping evidence b4 Forensics: Rebuilding infected server

Skipping after-action Review: Same mistakes next year

No tested Backups: Everyone assumes the backups work

INTRUSION DETECTION SYSTEMS (IDS)

IDS: Monitors systems, flags activity, raises alerts

Intrusion Prevention System (IPS): IDS that takes action

Signature-based detection: Match traffic w/ known pattern

Anomaly-based detection: Alert on deviations from "normal"

Stateful Protocol Analysis: IDS understands net protocols

Heuristic & Behavioral Rules: Rules describing sus seq.

AI-Assisted Classification: ML trained on labelled samples

Hybrid in Practice: Real-world products blend all the above

SECURITY INFORMATION AND EVENT MANAGEMENT

TODO:
SIEM correlation, SOC

SIEM: Collect, normalize, correlate, alert. Human response.

Security Orchestration, Automation and Response (SOAR): On top of SIEM. Runs playbooks: isolate, disable

Extended Detection and Response (XDR): Vendor-bundled detection. Lighter alt. to SIEM+SOAR, vendor lock-in.

In real enterprises: SIEM + SOAR is the classic stack

Volume Problem: Avg company produces 20+GB logs/day

Correlation Problem: Attacks touch several systems

Retention Problem: Forensics need logs from 90+ days ago

Compliance Problem: PCI-DSS, ISO 27001, FINMA, NIS2

- 1) Sources: Endpoints, firewalls, servers, identity providers
- 2) Collectors: Agents, syslog receivers, API, log forwarders
- 3) Parse & Normalize: Map every log into a common schema
- 4) Correlate & Store: Detection rules, ML, search index
- 5) Consume: Alerts to the SOC, dashboards, search, reports

TODO:
Why SIEM projects fail

OPEN-SOURCE INTELLIGENCE (OSINT)

Collecting, analyzing, decisions based on public information

Cyber Threat Intelligence (CTI): Proactive collection, processing, and analysis of information about threats

External sources: CI vendors, Subscription service

Internal sources: Logs, Alerts, Dedicated teams

- 1) Strategic Level for Executives & Management: Who is attacking and why?
- 2) Operational Level for SOC Teams & Analysts: How does a specific attack unfold?
- 3) Tactical Level for SIEM systems & Firewalls: Which concrete indicators do I need to block?

Advanced Persistent Threat (APT) Attack: Attacker gains access to network, stays there, undetected, for long time

TODO:
APT lifecycle

ETHICAL HACKING

Validate, audit and report on system/software vulnerabilities

Black Hat: Malicious, destructive hacker, anonymous

Grey Hat: Possess Black hat skills, focus on offense+defense

White Hat: Possess Black hat skills, focus on defense

Script Kiddie: Use tools without knowing what they are doing

Cyber Terrorist: Skilled attacker with ideological purpose

State Sponsored: Hackers employed by the government

Hacktivist: Hacking in order to pursue a political or social aim

Pentesting: Manual process, in-depth analysis

Vulnerability scanning: Automated, periodic

Penetration Testing Execution Standard (PTES): Community-driven industry standard, e2e pentesting methodology

NIST 800-115: Technical Guide, Government-oriented

EC-Council: Global organization providing cysec certs

Black-box Testing: No internal info, Attacker's perspective

Gray-box Testing: Limited knowledge, Realistic auth, Insider-based threat modeling

White-box Testing: Full internal knowledge, Deep analysis

TODO:
PurpleSec risk rating

MALICIOUS CODE

User-Dependent Malware: Most malware rely on user interaction or unsafe behavior to propagate

Self-Replication Threats: Worms: spread autonomously, no human involvement

Computer Viruses: Propagation and payload execution

Drive-by downloads: Unintentional dl of malicious code

MBR infection: Read MBR $\rightarrow$ Exec malware $\rightarrow$ Start OS

File infection: Infect exe files, self-contained, easily detected

Service injection: Inject into trusted runtime processes

Macro infection: Written in embedded macro lang (Excel)

Fileless techniques: RAM, resistant to signature-based det.

Multipartite Viruses: Use > than one propagation technique

Stealth Viruses: Hide themselves, trick antivirus

Polymorphic Viruses: Modify their code as they travel. Signature differs, antivirus vendors cracked the code of many

Encrypted Viruses: Use cryptographic techniques, include decryption routine segment, use different keys (polymorph)

Logic Bombs: Lie dormant until some event triggers them

Trojan Horses: Appears "kind", carries hidden (mal) payload

Keystroke logging: Record the keys struck on a keyboard

Ransomware: Encrypts files with key known only to hacker

Worms: Propagate themselves without human intervention

Spy-/Adware: windows

ANTIVIRUS & ENDPOINT SECURITY

Signature-based: Database of characteristics of viruses

Heuristic-based: Analyze the behavior of software

Data integrity: Detect Unauthorized file modifications (hash)

Endpoint Security: EDR tools capture all sys events. Behavioral Analysis, Automated Response and Remediation

POST-QUANTUM CRYPTOGRAPHY

Quantum Computer: Factoring, Discrete Log, Hashing, Asymmetric Crypto (RSA), Symmetric Crypto (HMAC)

IoT

Feature	IT (Office/IT)	IoT (Connected)	OT (Industrial)
CIA Prio	C > I > A	I > C > A	A > I > C
Asset Focus	Servers, Laptops, Databases	Smart Dev, Trackers, Cams	Motors, Robots, Sensors
OS Type	Windows, MacOS	Linux, Embedded / Lightweight Linux	Real-time (RTOS) Proprietary
Lifecycle	3-5 Years (Short-lived)	2-7 Years (Fast-paced)	15-30 Years (Legacy Systems)
Patching	Regular (e.g. "Patch Tuesday")	OTA (Over-the-Air) targeted	Rare (only during downtime)
Failure Impact	Data loss, Reputation damage	Mass manipulation, Botnets	Physical damage, Risk to life

TODO:
p. 79+

TODO:
iso

This summary was created thanks to the motivation provided
by [turnstile](#) , [wisdom in chains](#) and [hands of god](#)