

```
GENERICSEntry top;class Box<T> {}// variableBox<String> b = new Box<String>();// methodpublic <T> void doStuff(T value) {}
```

```
JAVA BEING STUPIDT obj = new T(); // errorobj instanceof T; // errorT heh = (T) "asdf"; // no typecheckingvar s = Stack<int>(); // no primitive typesprivate static T x; // static no workeyNode<Number> s = new Node<Integer>; // errorclass IThrowAnErrorBecauseWhyNot {void m(List<String> list) {}void m(List<Integer> list) {}// error because of type erasure & identifiabilityInteger[] c = set.toArray(new Integer[0]);}
```

```
ITERATORfor (String s : stringList) {} // ==for (Iterator<String> i = stringList.iterator(); i.hasNext();) {String s = i.next();}
```

```
ITERABLEinterface Iterable<T> {Iterator<T> iterator();}
```

```
interface Iterator<E> {boolean hasNext();E next();}
```

```
COMPARABLETODO:Type signature?
```

```
static <T extends Comparable> T doStuff(T a, T b) { // compareTo is possible with all typesreturn a.compareTo("b") > 0 ? a : b;}
```

```
static <T extends Comparable<T>> T doStuff(T a, T b) { // compareTo is possible only with Treturn a.compareTo(b) > 0 ? a : b;}
```

```
EXAMPLEclass Graphic {public void draw() {}class Rectangle extends Graphic {}class Circle extends Graphic {}class GraphicStack<T extends Graphic> extends Stack<T> {public void drawAll() {for (T item : this) item.draw();}}
```

```
BYTECODETODO:
```

```
TYPE ERASURE– Introduced because of “bAcKwArDs CoMpAtAbIlItY”– No type information at runtime (Non-Reifiable Type)
```

```
class MyStack<T> {Entry<T> top;int push(T value) {}// becomesclass MyStack {Entry top;int push(Object value) {}/* with bounds */class MyStack<T extends Comparable<T>> {Entry<T> top;int push(T value) {}// becomes
```

```
class MyStack {Entry top;int push(Comparable value) {}/* what happens at/before runtime */MyStack<String> s = new MyStack<String>();s.push("Eh");String x = s.pop();// becomesMyStack s = new MyStack();s.push("Eh");String x = (String) s.pop();
```

```
WILDCARDSvoid printGs(List<Graphic> gs) {}List<Graphic> gs1 = new ArrayList<>();printGs(gs1); // okList<Circle> gs2 = new ArrayList<>();printGs(gs2); // error/* solution */void printGs(List<? extends Graphic> gs) {}
```

	Type	Compatible Type-Args	R	W
Invariance	C<T>	T	✓	✓
Covariance	C<? extends T>	T and sub-types	✓	✓
Contravariance	C<? super T>	T and basis-types	✗	✗
Bivariance	C<?>	All	✗	✗

```
INVARIANCEstatic <T> void move(Stack<T>, from, Stack<T> to) {while(!from.isEmpty()) to.push(from.pop());}
```

```
var rectS = new Stack<Rectangle>();var graphS = new Stack<Graphic>();graphS.push(new Rectangle()); // okmove(rectS, graphS); // errorStack<Object> objS = graphS; // error/* anotherone */String[] strA = new String[10];Object[] objA = strA; // okobjA[0] = Integer.valueOf(2); // runtime err
```

```
TODO:// compiles?List<Graphic> list = new ArrayList<Rectangle>();// compiles?Rectangle[] rectangleStack = new Rectangle[10];Graphic[] graphicStack = new Graphic[10];graphicStack = rectangleStack; // compiles?Stack<Rectangle> rectangleStack = new Stack<>();Stack<Graphic> graphicStack = new Stack<>();graphicStack = rectangleStack; // compiles?Stack<Rectangle> rectangleStack = new Stack<>();Stack<Graphic> graphicStack = new Stack<>();graphicStack = rectangleStack;for (Rectangle r : rectangleStack) {graphicStack.push(r);}
```

```
COVARIANCEpublic class Stack<E> {public void pushAll(Iterable<? extends E> src) {}Stack<? extends Graphic> graphS;graphS = new Stack<Rectangle>(); // okgraphS = new Stack<Circle>(); // okgraphS = new Stack<Object>(); // error (duh)/* read only */Stack<? extends Graphic> stack = new Stack<Rectangle>();stack.push(new Graphic()); // errorstack.push(new Rectangle()); // errorstack.push(new Triangle()); // errorCONTRAVARIANCEstatic <T> void addToC(List<? super T> list, T e) {list.add(e);}addToC(new ArrayList<Number>(), 3); // okaddToC(new ArrayList<Object>(), 3); // ok
```

```
/* shenanigans */Stack<? super Graphic> s = new Stack<Object>();s.add(new Graphic()); // ok s.add(new Rectangle()); // ok Graphic g = s.pop(); // error Object g = s.pop(); // okBIVARIANCEstatic void printList(List<?> list) {for (Object elem : list) System.out.print(elem + " ");}/* more shenanigans */static void appendNewObject(List<?> list) {list.add(new Object()); // error}
```

PRODUCER / CONSUMER

TODO:

MISC

<T extends Comparable & Collection> // multiple type bounds

GENERIC STREAM TOMFOOLERY

```
List<? extends Media> medialis;public <S extends T> List<S> filterBySubtype(Class<S> subtype) {return medialis.stream().filter(subtype::isInstance).map(subtype::cast).collect(Collectors.toList());}
```

ANNOTATIONS

- Metadata
- Not actually part of the code

TODO:slides 10

- @Override
- @Test
- @Json...

DEFINING

```
@Target(ElementType.TYPE)@Retention(RetentionPolicy.RUNTIME)public @interface Author {String name();String date() default "N/A";}
```

```
@Author(name = "UwU", date = "idon't validate input")public class WeeDoo {}
```

REFLECTON

- Information of Class (private and public): Methods, Attribs, Parent class, Implemented interfaces
- Calling methods possible
- Usages: Debugger, Serialization, Frameworks, Remote Procedure Call, ORM

```
// all of these `throws SecurityException`public Field[] getDeclaredFields()public Method[] getDeclaredMethods()public Constructor<?>[] getDeclaredConstructors()
```

```
System.out.println(dump(new Student("a", "b"), 0));// { // firstName = a // lastName = b // }Class c = "s".getClass(); // java.lang.String
```

TODO:Diagram (slides 26)

METHOD

// @Target(ElementType.METHOD)

```
public String getName()public boolean isAnnotationPresent(Class<? extends Annotation> annotationClass)public Object invoke(Object obj, Object... args)
```

```
throws IllegalAccessException, IllegalArgumentException, InvocationTargetExceptionpublic class Profiler {public static void main(String[] args) {var testFunctions = new ProfileFunctions();int[] array = {5, 2, 8, 1, 93, 3, 33, 1, 333};var methods = ProfileFunctions.class.getDeclaredMethods();for (var m : methods) {if (m.isAnnotationPresent(Profile.class)) {m.setAccessible(true); // best practice orsth, idk, i write code in actually good languagesProfiler.profileMethod(testFunctions, m, new Object[] {array});}}}
```

CLASS

TODO:

// @Target(ElementType.TYPE)

```
getDeclaredConstructor().newInstance()...
```

ATTRIBUTE

TODO:

// @Target(ElementType.FIELD)

...

VALIDATION

```
@Min(value = 18, message = "Age must be ≥ 18")@Max(value = 99, message = "Age must be ≤ 99")private int age;@NotNull(message = "Name cannot be null")private String name;
```

ALGORITHMS

- Brute-force
- Greedy
 - Take best option each step (optimize locally)
 - Fast
- Backtracking
 - Trial and error
 - Best overall option
 - Higher compute costs
- Divide and conquer
 - Binary search
- Dynamic programming
 - Recursion optimization?
 - Tabulation

BACKTRACKING

TODO:slides 87

BIG O NOTATION


- Worst case scenario
- Atomic operations = constant time
- Runtime measured as sum of primitive operations

Notation

$$\widetilde{f} \left(\underbrace{n}_{\text{Size of problem}} \right) = \text{Number of steps}$$

g = complexity class

TODO:diagram $f \leq cg$



$f(n)$ is $O(g(n))$ if $c > 0 \wedge n_0 \geq 1$
 $f(n) \leq cg(n)$ for $n \geq n_0$

f in order g :

$$\text{Let } f, g : \mathbb{N} \rightarrow \mathbb{N} \\ n_0, c \in \mathbb{N} \wedge \forall n \geq n_0 : f(n) \leq c \cdot g(n) \\ \Rightarrow f \in O(g) \Leftrightarrow f = O(g)$$

Big O

$$\overset{\text{Big O}}{\sim} \left(\underbrace{n}_{\text{Size of problem}} \right) = \text{Complexity class}$$

RULES


- If $f(n)$ is polynomial of degree d , then $f(n) \in O(n^d)$
- ignore lower powers
- ignore constants

Use most optimal function (lowest power)
– $2n$ is $O(n)$ better than $2n$ is $O(n^2)$

Simplify as far as possible
– $3n + 5$ is $O(n)$ instead of $3n + 5$ is $O(3n)$

COMPLEXITY CLASSES

Name	Class	Example
Constant	1	Array read
Logarithmic	$\log n$	Binary search
Linear	n	Linear search
Log-linear	$n \log n$	Merge+Quick sort
Quadratic	n^2	Bubble+Insertion sort
Cubic	n^3	Solve equation
Polynomial	n^k	Various algorithms
Exponential	2^n	Calculate all subsets
Factorial	$n!$	Calculate all permutations



TODO:Counting primitive operations (slides 55)

SORTING ALGORITHMS

SELECTION SORT

- Search for smallest elem in unsorted part and move in front

Georgiy Shevoroashkin

- Less mutations in array
- Same performance even if list almost sorted

```
public static void selectionSort(int[] a) {
    int n = a.length;
    for (int i = 0; i < n - 1; i++) {
        int minimum = i;
        for (int j = i + 1; j < n; j++)
            if (a[j] < a[minimum])
                minimum = j;
        swap(a, i, minimum);
    }
}
```

$$(n-1) + (n-2) + \dots + 1 = \sum_{i=1}^{n-1} i = \frac{n(n-1)}{2} = \frac{n^2 - n}{2} \sim O(n^2)$$

INSERTION SORT

- Take elem and put into correct place in sorted part
- Good for already partially sorted arrays

```
public static void insertionSort(int[] a) {
    int n = a.length;
    for (int i = 1; i < n; i++)
        for (int j = i; j > 0 && a[j] < a[j - 1]; j--)
            swap(a, j, j - 1);
}
```

$$1 + \dots + (n-1) + n = \sum_{i=1}^n i = \frac{n(n+1)}{2} = \frac{n^2 + n}{2} \sim O(n^2)$$

BUBBLE SORT

- Compare neighboring elems and swap if needed

```
public static void bubbleSort(int[] a) {
    for (n = a.length; n > 1; n--)
        for (i = 0; i < n - 1; i++)
            if (a[i] > a[i + 1])
                swap(a, i, i + 1);
}
```

$$(n-1) + (n-2) + \dots + 1 = \sum_{i=1}^{n-1} i = \frac{n(n-1)}{2} = \frac{n^2 - n}{2} \sim O(n^2)$$

COUNTING SORT

```
public static void countingSort(int[] a) {
    int k = Arrays.stream(arr).max().getAsInt();
    int[] c = new int[k + 1];
    for (int i : a) c[i] += 1;
    int pos = 0;
    for (int i = 0; i < k; i++)
        for (int j = 0; j < c[i]; j++) {
            a[pos] = i;
            pos++;
        }
}
```

$$n + n + k + n = 3n + k \sim O(n + k)$$

SHELL SORT

- Sort pairs of far away elems
- Sort the partially sorted array through insertion sort

```
public static void shellSort(int[] a) {
    int n = a.length;
    int h = 1;
    while (h < n/3) h = 3 * h + 1;
    while (h >= 1) {
        for (int i = h; i < n; i++)
            for (int j = i; j >= h && a[j] < a[j - h]; j = j - h) swap(a, j, j - h);
        h /= 3;
    }
}
```

BINARY SEARCH

```
public static <T> extends Comparable<T>> boolean bs(
    List<T> data, T target, int low, int high) {
    if (low > high) return false;
    int pivot = low + ((high - low) / 2);
    if (target.equals(data.get(pivot)))
        return true;
    else if (target.compareTo(data.get(pivot)) < 0)
        return searchBinary(data, target, low, pivot - 1);
    else
```

```
return searchBinary(data, target, pivot + 1, high);
}
```

$$O(\log n)$$

RECURSION

When a function calls itself

LINEAR RECURSIONRecursive call starts **at most one** further recursive call**TODO:**

recursive → iterative (slides 61)

TAIL RECURSIONLinear recursion where the recursive call is **last****TODO:**

recursive → iterative (slides 69 – nice)

BINARY RECURSIONAll non-terminal calls have **two** recursive calls**TODO:**

example (slides 76,77,78)

TODO: $O(n)$ (slides 84)**DATA STRUCTURES**


ADT: Abstract Data Type (e.g. Interface)

TODO:



diagram

ARRAY**LINKED LIST****DOUBLY LINKED LIST****STACK**

LIFO

**QUEUE**

FIFO




**TREE****RING BUFFER****PRIORITY QUEUE**

Method	Unsorted List	Sorted List
insert	$O(1)$	$O(n)$
min	$O(n)$	$O(1)$
removeMin	$O(n)$	$O(1)$

HEAP

- Binary tree
- Layers 0, ..., $h-1$ fully populated, layer h filled from left
- Operations always lowest RHS so that tree stays consistent


Min-Heap: Keys of nodes are **smaller** or equal than children's
Max-Heap: Keys of nodes are **larger** or equal than children's

**HEAP SORT**

Dequeue elems from head into list, resorting tree on each iter

TODO:**BINARY SEARCH TREE (BST)**

- All subnodes of **left** subtree are **smaller** than root
- All subnodes of **right** subtree are **larger** than root

TRAVERSING**TODO:****MORE DATA STRUCTURES**

Set: Elements of same type, no duplicates, without order
Multiset: Set with duplicates
Map: KV-pairs with unique keys
Multimap: Key can have multiple values

HASHINGHash-function h maps e onto $[0, n-1]$. $h(e)$ = position of e

$$e \xrightarrow{\text{hash code}} \mathbb{Z} \xrightarrow{\text{compression function}} \text{Index} \rightarrow [0, n-1]$$

Properties of good hash functions:

- Equal distribution
- Fast computation
- Constant time complexity
- Deterministic
- Incorporates as much information from key as possible

HASH FUNCTIONS

- Modulo primes
- Memory address (Object.hashCode() default)
- Byte/Integer cast ByteBuffer.wrap(b).getInt()
- Component sum (eg. sum string char codepoints)
- Polynomial accumulation $a_0 + a_1z + a_2z^2 + \dots + a_{n-1}z^{n-1}$
- $z = 33$ for strings
- Horner-Schema (identical, but easier to compute):
 $- a_0 + z \cdot (a_1 + z \cdot (a_2 + \dots + z \cdot a_{n-1}))$

EQUALITY

It is generally necessary to override hashCode whenever equals is overridden

```
x.equals(y) => x.hashCode() == y.hashCode()
```

HASHING OBJECTS

```
// when to rehash
// Horner schema with z = 31 and start = 17
@Override
public int hashCode() {
    int result = 17;
    for (Object field : fields) result = 31 * result
        + (field == null ? 0 : field.hashCode());
    return result;
}
```

ANOMALIES


- Empty spaces
- Collisions
- Overflow

MANAGING HASH COLLISIONS**CLOSED ADDRESSING/SEPARATE CHAINING**

Each bucket is a list.

Search: $O(\text{entries}/\text{buckets})$

- Larger storage overhead
- Acceptable performance under high load

**OPEN ADDRESSING**

e "overflows" into next empty bucket
 → Must probe **2** times in example

**TODO:**

Problem: Primary Clustering

Linear probing: $s(k, i) = h(k) + i$ **Linear probing backwards:** $s(k, i) = h(k) - i$ **Quadratic probing:** $s(k, i) = h(k) + i^2$ **TODO:**

diagram, slides 10,11

TODO:

deletion (slides 16-21)

- Only mark as "deleted"
- Move next best candidate to deleted position

TODO:

access (slides 22-27)

Probability for finding free spot:

$$n = \text{entries} \quad N = \text{buckets}$$

$$a = \frac{n}{N} = \text{probability: occupied} \quad p = \text{probing steps}$$

$$P(X = p) = a^{p-1}(1-a)$$

$$E(X) = \sum_{x=1}^{\infty} p \cdot P(X = p) = \frac{1}{1-a} = \text{Nr. accesses}$$


- Resize/Rehash compute intensive
- No storage overhead
- Bad performance under high load

CUCKOO-HASHING

$$h_1(x) = x \bmod 5 \quad h_2(x) = x/5 \bmod 5$$

Insert: If $h_1(x) = \text{null} \Rightarrow T_1$, else push y into T_2
 If no cycle $\rightarrow O(1)$, if rehash is needed $\rightarrow O(n)$

(MAX_CYCLE)

Search: $O(1) \Rightarrow$ only has to check 2 positions**Rehashing:** $x \bmod n \Rightarrow x \bmod (n+m)$ **TODO:****EXTENSIBLE HASHING****TODO:**

- Resize/Rehash easier
- Larger storage overhead
- Good performance under high load

```
// getting index
int idx = key.hashCode() & ((1 << globalDepth) - 1);
```

```
// when to rehash
if (bucket.getLocalDepth() == globalDepth)
    growHashTable();
else
    splitBlock();
// splitting block
int highBit = 1 << localDepth;
for (Entry e : page.entries) {
    int h = e.key.hashCode();
    Page newPage = (h & highBit) == 0 ? p1 : p0;
    newPage.put(e.key, e.value);
}
```

TODO:

slides 64

