

MISC

```
<T extends Comparable & Collection> // multiple type bounds

Set<Integer> set = new Set<>();
Integer[] c = set.toArray(new Integer[0]);

RECORDS
public record Person (String name, String address) {}

GENERICS STREAM TOMFOOLERY
List<? extends Media> medialist;
public <S extends T> List<S>
    filterBySubtype(Class<S> subtype) {
        return medialist.stream()
            .filter(subtype::isInstance)
            .map(subtype::cast)
            .collect(Collectors.toList());
    }

GENERICS
// class
class Box<T> {}
// variable
Box<String> b = new Box<String>();
// method
public <T> void doStuff(T value) {}
```

Example 1:

```
class OrderedPair<T, U> {
    T first;
    U second;
    public OrderedPair(T t, U u) {
        this.first = f;
        this.second = s;
    }
    public T getFirst() { return first; }
    public U getSecond() { return second; }
    @Override
    public int hashCode() {
        return Objects.hash(first.hashCode(),
                               second.hashCode());
    }
    @Override
    public boolean equals(Object obj) {
        if (obj == null ||
            obj.getClass() != getClass()) return false;
        @SuppressWarnings("unchecked")
        var other = (OrderedPair<T, U>)obj;
        return Objects.equals(first, other.first) &&
            Objects.equals(second, other.second);
    }
}

public class Employee
    implements Comparable<Employee> {
    // ...
    @Override
    public int compareTo(Employee other) {
        return Double.compare(salary, other.salary);
    }
}
```

Example 2:

```
class Graphic {
    public void draw() {}
}

class Rectangle extends Graphic { }
class Circle extends Graphic { }
class GraphicStack<T extends Graphic>
    extends Stack<T> {
    public void drawAll() {
        for (T item : this) item.draw();
    }
}
```

JAVA BEING STUPID

```
T obj = new T(); // error
obj instanceof T; // error
T heh = (T) "asdf"; // no typechecking
var s = Stack<int>(); // no primitive types
private static T x; // static no workey
Node<Number> s = new Node<Integer>; // error
class IThrowAnErrorBecauseWhyNot {
```

```
void m(List<String> list) { }
void m(List<Integer> list) { }
} // error because of type erasure & identifiability
static <T extends Comparable<T>> T m(T x, T y, T z) {
    return x > y ? z : x;
}

Integer n = m(1, 3.141, 0); // error
Number n = m(1, 3.141, 0); // ok

COMPARABLE
interface Comparable<T> { int compareTo(T o); }
static <T extends Comparable> T doStuff(T a, T b) {
    // compareTo is possible with all types
    return a.compareTo("b") > 0 ? a : b;
}

static <T extends Comparable<T>> T doStuff(T a, T b) {
    // compareTo is possible only with T
    return a.compareTo(b) > 0 ? a : b;
}

BYTECODE
JVM Architecture:
– Operand Stack (LIFO op vals)
– Local variables (op results)
– Constant pool (runtime refs)

TYPE ERASURE
– Introduced because of "bAcKwArDs CoMpAtAbIlItY"
– No type information at runtime (Non-Reifiable Type)
```

Example 3:

```
class MyStack<T> {
    Entry<T> top;
    int push(T value) { }
}

class MyStack { // becomes this when compiling
    Entry top;
    int push(Object value) { }
}
```

Example 4: With bounds

```
class MyStack<T extends Comparable<T>> {
    Entry<T> top;
    int push(T value) { }
}

class MyStack { // becomes this when compiling
    Entry top;
    int push(Comparable value) { }
}
```

Example 5: Casts

```
MyStack<String> s = new MyStack<String>();
s.push("Eh");
String x = s.pop();
// becomes this when compiling
MyStack s = new MyStack();
s.push("Eh");
String x = (String) s.pop();
```

GENERIC VARIANCE

```
void printGs(List<Graphic> gs) {}
List<Graphic> gs1 = new ArrayList<>();
printGs(gs1); // ok
List<Circle> gs2 = new ArrayList<>();
printGs(gs2); // error
/* solution */
void printGs(List<? extends Graphic> gs) {}
```

	Type	Compatible Type-Args	R	W
Invariance	C<T>	T	✓	✓
Covariance	C<? extends T>	T and sub-types	✓	✓
Contravariance	C<? super T>	T and basis-types	✗	✓
Bivariate	C<?>	All	✗	✗

INVARIANCE

```
static <T> void move(Stack<T>, from, Stack<T> to) {
    while(!from.isEmpty()) to.push(from.pop());
}
```

Example 6:

```
var rectS = new Stack<Rectangle>();
var graphS = new Stack<Graphic>();
graphS.push(new Rectangle()); // ok
move(rectS, graphS); // error
Stack<Object> objS = graphS; // error
```

Example 7: Runtime errors

```
String[] strA = new String[10];
Object[] objA = strA; // ok
objA[0] = Integer.valueOf(2); // runtime err
```

Example 8: Even more

```
ArrayList<String> sA = new ArrayList<>();
ArrayList<Object> oA = sA; // error
// error
List<Graphic> l = new ArrayList<Rectangle>(); // ok
Rectangle[] rectangleStack = new Rectangle[10];
Graphic[] graphicStack = new Graphic[10];
graphicStack = rectangleStack; // ok
Stack<Rectangle> rectangleStack = new Stack<>();
Stack<Graphic> graphicStack = new Stack<>();
for (Rectangle r : rectangleStack)
    graphicStack.push(r);
```

COVARIANCE

– Allows a subtype to be treated as a supertype. Eg. List<Dog> can be used where a List<Animal> is expected.

```
public class Stack<E> {
    public void pushAll(Iterable<? extends E> src) { }
```

Example 9:

```
Stack<? extends Graphic> graphS;
graphS = new Stack<Rectangle>(); // ok
graphS = new Stack<Circle>(); // ok
graphS = new Stack<Object>(); // error (duh)
```

Example 10: Read-only

```
graphS.push(new Graphic()); // error
graphS.push(new Rectangle()); // error
graphS.push(new Triangle()); // error
```

CONTRAVARIANCE

– Allows a supertype to be treated as a subtype. Eg. List<Animal> can be used where a List<Dog> is expected.

```
static <T> void addToC(List<? super T> list, T e) {
    list.add(e);
}
```

Example 11: Ok

```
addToC(new ArrayList<Number>(), 3); // ok
addToC(new ArrayList<Object>(), 3); // ok
```

Example 12: Shenanigans

```
Stack<? super Graphic> s = new Stack<Object>();
s.add(new Graphic()); // ok
s.add(new Rectangle()); // ok
Graphic g = s.pop(); // error
Object g = s.pop(); // ok
```

BIVARIANCE

– If concrete type doesn't matter

```
static void printList(List<?> list) {
    for (Object elem : list)
        System.out.print(elem + " "); // ok
}
```

Example 13: Shenanigans

```
static void appendNewObject(List<?> list) {
    list.add(new Object()); // error
}
```

TYPICAL "DOES THIS COMPIL MR. LINTER?" QUESTIONS

```
public class GenericsSyntax<T extends Iterable<T>> {
    public void fun(Iterable<? super T> i) { } // ok
}

// ok
List<? extends Object> v = new ArrayList<String>();
```

Example 14: Complete example

```
public class VarianceExamples {
    public static double sum(
        Collection<? extends Number> numbers) {
        double sum = 0;
        for (Number num : numbers)
            sum += num.doubleValue();
        return sum;
    }

    public static void addNrs(List<? super Integer>
        list, Collection<? extends Integer> source) {
        list.addAll(source);
    }

    public static <T extends Comparable<T>> T
        findMax(Collection<T> coll) {
        return coll.stream()
            .max(Comparator.naturalOrder())
            .orElse(null);
    }

    public static <T> List<T> filterByType(
        Collection<?> source, Class<T> clazz) {
        List<T> result = new ArrayList<>();
        for (Object obj : source)
            if (clazz.isInstance(obj))
                result.add(clazz.cast(obj));
        return result;
    }
}
```

ANNOTATIONS

– Metadata
– Macros for the poor people forced to work corporate
– @Override, @Test, @Json...

DEFINING

```
@Target(ElementType.TYPE)
@Retention(RetentionPolicy.RUNTIME)
public @interface Author {
    String name();
    String date() default "N/A";
}
```

```
@Author(name = "UwU", date = "idon't validate input")
public class Wee0oo { }
```

REFLECTION

– Information of Class (private and public): Methods, Attributes, Parent class, Implemented interfaces
– Calling methods possible
– Usages: Debugger, Serialization, Frameworks, Remote Procedure Call, ORM

```
// all of these 'throws SecurityException'
public Field[] getDeclaredFields()
public Method[] getDeclaredMethods()
public Constructor<>[] getDeclaredConstructors()
```

```
System.out.println(dump(new Student("a", "b"), 0));
// {
//     firstName = a
//     lastName = b
// }
Class c = "s".getClass(); // java.lang.String
```

METHOD

```
@Retention(RetentionPolicy.RUNTIME)
@Target(ElementType.METHOD)
public @interface Init { }

// ...
public class User {
    private String needsInit;
    @Init
    private void initObj() {
        this.needsInit = "wowie";
    }
}
```

CLASS

```
@Retention(RetentionPolicy.RUNTIME)
@Target(ElementType.TYPE)
public @interface JsonSerializable { }
// ...
@JsonSerializable
public class User { }
```

Also, this is a thing:

```
Class z = Class.forName("Test");
Test c = z.getDeclaredConstructor().newInstance();
// ==
Test c = new Test();
```

ATTRIBUTE

```
@Retention(RetentionPolicy.RUNTIME)
@Target({ ElementType.FIELD })
public @interface JsonElement {
    public String key() default "";
}

// ...
public class User {
    @JsonElement
    private String firstName;
}
```

VALIDATION

```
@Min(value = 18, message = "Age must be ≥ 18")
@Max(value = 99, message = "Age must be ≤ 99")
private int age;
@NotNull(message = "Name cannot be null")
private String name;
```

Example 15: Complete example

```
@Target(ElementType.TYPE)
@Retention(RetentionPolicy.RUNTIME)
public @interface WebController { }
// ...
@Retention(RetentionPolicy.RUNTIME)
@Target(ElementType.METHOD)
public @interface Get {
    String path();
    String contentType() default "application/json";
}

// ...
@WebController
public class Controller {
    private User user = new User("frank", "meier");
    @Get(path = "/user")
    public String user() {
        return new ObjectToJsonConverter()
            .convertToJson(user);
    }
}

// ...
public class WebFramework {
    public void addCtrl(Class<?> controllerClass)
        throws Exception {
        if (!controllerClass
            .isAnnotationPresent(WebController.class))
            throw new Exception("Is not a WebController");

        for (Method method : controllerClass
            .getDeclaredMethods())
            if (method.isAccessible(true); // best practice
                or sth, idk, i write code in actually good languages
                var annot = method.getAnnotation(Get.class);
                routeHandlers.put(
                    annot.path(),
                    new WebHandler<>(method,
                                    controllerClass
                                        .getDeclaredConstructor()
                                            .newInstance(),
                                        annot.contentType())
                );
    }
}
```

ALGORITHMS

Brute-force: slow, stupid, go shame yourself
Greedy: Take best option each step (optimize locally). Fast.
Not necessarily global optimum
Backtracking: Trial and error. Best overall option. Higher compute costs
Divide and conquer: Binary search
Dynamic programming: Recursion optimization? Tabulation. Iterative reuse of previous results

BACKTRACKING

1) Choose one of the possible paths to solution
2) If path leads to goal → done
3) Else → backtrack to previous decision
4) Choose next path, iterate further from Step 1)

Example 16: Sudoku

```
boolean checkRow(int row, int num) {
    for (int c : arr[row])
        if (c == num) return false;
    return true;
}
boolean checkCol(int col, int num) {
    for (int row : arr)
        if (row[col] == num) return false;
    return true;
}
boolean checkBox(int row, int col, int num) {
    row = (row / 3) * 3;
    col = (col / 3) * 3;
    for (int i = row; i < row + 3; i++)
        for (int j = col; j < col + 3; j++)
            if (arr[i][j] == num) return false;
    return true;
}
boolean solve(int row, int col) {
    if (row == 8 && col == 9) return true;
    if (col == 9) {
        row++;
        col = 0;
    }
    if (arr[row][col] != 0) {
        return solve(row, col + 1);
    } else {
        for (int num = 1; num < 10; num++) {
            if (checkRow(row, num) && checkCol(col, num)
                && checkBox(row, col, num)) {
                arr[row][col] = num;
                if (solve(row, col + 1)) return true;
            }
        }
        arr[row][col] = 0;
        return false;
    }
}
```

Example 17: KnightsTour

1	6	15	10	21
14	9	20	5	16
19	2	7	14	11
8	13	24	17	4
H	18	3	12	23

```
boolean tour(int[][] visited, int x, int y, int pos) {
    visited[x][y] = pos;
    if (pos >= N * N) return true;
    for (int k = 0; k < 8; k++) {
        int newX = x + row[k];
        int newY = y + col[k];
        if (isValid(newX, newY)
            && visited[newX][newY] == 0
            && tour(visited, newX, newY, pos + 1))
            return true;
    }
    visited[x][y] = 0;
    return false;
}
```

BIG O NOTATION

– Upper bound of f
– Worst case scenario
– Atomic operations = constant time
– Runtime measured as sum of primitive operations

Notation

f Algorithm

n Size of Problem

g Complexity Class

$c > 0$

$n_0 \geq 1$

$f(n)$ = Number of steps
 g = complexity class

$f(n)$ is $O(g(n))$ if $c > 0 \wedge n_0 \geq 1$
 $f(n) \leq cg(n)$ for $n \geq n_0$
 f in order g :
 $f, g : \mathbb{N} \rightarrow \mathbb{N}$
 $n_0, c \in \mathbb{N} \wedge \forall n \geq n_0. (f(n) \leq c \cdot g(n))$
 $\Rightarrow f \in O(g) \Leftrightarrow f = O(g)$
 $O(n)$ = Complexity class

RULES

If $f(n)$ is polynomial of degree d , then $f(n) \in O(n^d)$
– ignore lower powers
– ignore constants

Use most optimal function (lowest power)
– $2n$ is $O(n)$ better than $2n$ is $O(n^2)$

Simplify as far as possible
– $3n + 5$ is $O(n)$ instead of $3n + 5$ is $O(3n)$

COMPLEXITY CLASSES

Name	Class	Example
Constant	1	Array read
Logarithmic	$\log n$	Binary search
Linear	n	Linear search
Log-linear	$n \log n$	Merge+Quick sort
Quadratic	n^2	Bubble+Insertion sort
Cubic	n^3	Solve equation
Polynomial	n^k	Various algorithms
Exponential	2^n	Calculate all subsets
Factorial	$n!$	Calculate all permutations

MAFS

$$1 + 2 + \dots + n = \sum_{k=1}^n = \frac{n(n+1)}{2}$$
$$1 + q + q^2 + \dots + q^n = \sum_{k=0}^n q^k = \frac{1 - q^{n+1}}{1 - q}$$
$$q=2, n=\log_2(n) \Rightarrow 2n - 1$$

SORTING ALGORITHMS

BODYSORT

The best sorting algorithm

STALINSORT

The most efficient sorting algorithm

MIRACLE SORT

The most magical sorting algorithm

SELECTION SORT

– Search for smallest elem in unsorted part and move in front
– Less mutations in array
– Same performance even if list almost sorted

$$(n-1) + (n-2) + \dots + 1 = \sum_{i=1}^{n-1} i = \frac{n(n-1)}{2} = \frac{n^2 - n}{2} \sim O(n^2)$$

Example 18:

```
public static void selectionSort(int[] a) {
    int n = a.length;
    for (int i = 0; i < n - 1; i++) {
        int minimum = i;
        for (int j = i + 1; j < n; j++)
            if (a[j] < a[minimum])
                minimum = j;
        swap(a, i, minimum);
    }
}
```

INSERTION SORT

– Take elem and put into correct place in sorted part
– Good for already partially sorted arrays

$$1 + \dots + (n-1) + n = \sum_{i=1}^n i = \frac{n(n+1)}{2} = \frac{n^2 + n}{2} \sim O(n^2)$$

```
public static void insertionSort(int[] a) {
    int n = a.length;
    for (int i = 1; i < n; i++)
        for (int j = i; j > 0 && a[j] < a[j - 1]; j--)
            swap(a, j, j - 1);
}
```

BUBBLE SORT

– Compare neighboring elems and swap if needed

```
public static void bubbleSort(int[] a) {
    for (n = a.length; n > 1; n--)
        for (i = 0; i < n - 1; i++)
            if (a[i] > a[i + 1])
                swap(a, i, i + 1);
}
```

$$(n-1) + (n-2) + \dots + 1 = \sum_{i=1}^{n-1} i = \frac{n(n-1)}{2} = \frac{n^2 - n}{2} \sim O(n^2)$$

COUNTING SORT

– For int-like data only i guess
– Count how often (n) values of index i appear in array, then insert i n times in new array

```
public static void countingSort(int[] a) {
    int k = Arrays.stream(arr).max().getAsInt();
    int[] c = new int[k + 1];
    for (int i : a) c[i] += 1;
    int pos = 0;
    for (int i = 0; i < k; i++)
        for (int j = 0; j < c[i]; j++) {
            a[pos] = i;
            pos++;
        }
}
```

$$n + n + k + n = 3n + k \sim O(n + k)$$

SHELL SORT

– Sort pairs of far away elems
– Sort the partially sorted array through insertion sort

```
public static void shellSort(int[] a) {
    int n = a.length;
    int h = 1;
    while (h < n/3) h = 3 * h + 1;
    while (h >= 1) {
        for (int i = h; i < n; i++)
            for (int j = i; j >= h && a[j] < a[j - h];
                j = j - h) swap(a, j, j - h);
        h /= 3;
    }
}
```

$$O(n^2)$$

BINARY SEARCH

// recursive

```
static <T extends Comparable<T>> int bsRec(
    List<T> data, T target, int low, int high) {
    if (low > high) return -1;
    int pivot = low + ((high - low) / 2);
    if (target.equals(data.get(pivot)))
        return pivot;
    else if (target.compareTo(data.get(pivot)) < 0)
        return bsRec(data, target, low, pivot - 1);
    else
        return bsRec(data, target, pivot + 1, high);
}
```

// iterative

```
static <T extends Comparable<T>> int bsIter(
    List<T> data, T target) {
    int low = 0;
    int high = list.size() - 1;
    while (low <= high) {
        int pivot = low + ((high - low) / 2);
        int res = target.compareTo(data.get(pivot));
        if (res > 0)
            low = pivot + 1;
        else if (res < 0)
            high = pivot - 1;
        else
            return pivot;
    }
    return -1;
}
```

$$O(\log n)$$

RECURSION

When a function calls itself. FP <3

LINEAR RECURSION

Recursive call starts at **most one** further recursive call

RECURSIVE → ITERATIVE

```
static int[] reverseArrRec(int[] a, int i, int j) {
    if (i >= j) return a;
    int temp = a[j];
    a[j] = a[i];
    a[i] = temp;
    return reverseArrRec(a, i + 1, j - 1);
}
static int[] reverseArrIter(int[] a, int i, int j) {
    while (i < j) {
        int temp = a[j];
        a[j] = a[i];
        a[i] = temp;
        i = i + 1;
        j = j - 1;
    }
    return a;
}
```

TAIL RECURSION

Linear recursion where the recursive call is **last**

```
static int recsum(int x) {
    if (x == 0) return 0;
    else return x + recsum(x - 1);
    // no tail recursion because "+" is evaluated last
}
static int tailrecsum(int x, int total) {
    if (x == 0) return total;
    else return tailrecsum(x - 1, total + x);
}
```

BINARY RECURSION

All non-terminal calls have **two** recursive calls

```
static int binsum(int low, int high) {
    if (low > high)
        return 0;
    else if (low == high)
        return low;
    else {
        int mid = (low + high) / 2;
        return binsum(low, mid) + binsum(mid + 1, high);
    }
}
```

DATA STRUCTURES

ADT: Abstract Data Type (e.g. Interface)
– Describes "What", not "How"
– Describes Attributes, Operations and Exceptions
– Doesn't provide implementation details, that is done by the concrete data type

Data structure	Access	Search	Insertion	Deletion
Array	$O(1)$	$O(n)$	$O(n)$	$O(n)$
Linked list	$O(n)$	$O(n)$	$O(n)$	$O(n)$
Doubly Linked List	$O(n)$	$O(n)$	$O(1)$	$O(1)$
Stack	$O(n)$	$O(n)$	$O(1)$	$O(1)$
Queue	$O(n)$	$O(n)$	$O(1)$	$O(1)$
Binary Tree	$O(n)$	$O(n)$	$O(n)$	$O(n)$
Binary Search Tree	$O(n)$	$O(n)$	$O(n)$	$O(n)$
Hash Table	$O(n)$	$O(n)$	$O(n)$	$O(n)$

ARRAY

```
int[] aAaAhrrray = {69, 420, 1337};
```

00P2 | FS26


Page 2

LINKED LIST



```
class LinkedList<T> {
    Node head;
    static class Node {
        T data;
        Node next;
        Node(T d) { data = d; }
    }
    public T insert(T data) {
        Node n = new Node(data);
        if (list.head == null)
            list.head = n;
        else {
            Node last = list.head;
            while (last.next != null)
                last = last.next;
            last.next = n;
        }
        return data;
    }
}
```

DOUBLY LINKED LIST



```
class DoublyLinkedList<T> {
    Node head;
    static class Node {
        T data;
        Node next, prev;
        Node(T d) { data = d; }
    }
    public T insert(T data) {
        Node n = new Node(data);
        if (list.head == null)
            list.head = n;
        else {
            Node last = list.head;
            while (last.next != null)
                last = last.next;
            n.prev = last;
            last.next = n;
        }
        return data;
    }
}
```

STACK


LIFO



```
class Stack<T> {
    private int maxSize;
    private T[] arr;
    private int top;
    public Stack(int size) {
        maxSize = size;
        arr = (T[]) new Object[maxSize];
        top = -1;
    }
    public void push(T value) {
        if (top == maxSize - 1)
            throw new StackOverflowError();
        arr[++top] = value;
    }
    public T pop() {
        if (top == -1)
            throw new StackUnderflowError();
        return arr[top--];
    }
}
```


QUEUE

FIFO



```
class Queue<T> {
    private int maxSize;
    private T[] arr;
    private int front, rear;
    public Queue(int size) {
        maxSize = size;
        arr = (T[]) new Object[maxSize];
        front = rear = -1;
    }
    public T front() {
        if (front == -1)
            throw new StackUnderflowError();
        return arr[front];
    }
    public T rear() {
        if (rear == -1)
            throw new StackUnderflowError();
        return arr[rear];
    }
    public void enqueue(T value) {
        if (this.empty()) {
            front = 0;
            rear = 0;
            arr[front] = value;
        } else {
            front++;
            if (front < maxSize) arr[front] = value;
            else // rebuild array
                return;
        }
    }
    public T dequeue() {
        if (this.empty())
            throw new StackUnderflowError();
        T ret = arr[rear];
        if (front == rear) front = rear = -1;
        else rear++;
        return ret;
    }
    boolean empty() {
        return front == -1 && rear == -1;
    }
}
```

TREE




```
public class Tree<T> {
    private Node<T> root;
    public Tree(T rootData) {
        root = new Node<T>();
        root.data = rootData;
    }
    public static class Node<T> {
        private T data;
        private Node<T> left, right;
    }
}
```

REVERSING BINARY TREE

```
public static void swap(Node root) {
    if (root == null) return;
    Node tmp = root.left;
    root.left = root.right;
    root.right = tmp;
}

public static void mirror(Node root) {
    if (root == null) return;
    mirror(root.left);
    mirror(root.right);
    swap(root);
}
```

RING BUFFER



```
class RingBuffer {
    private int[] buffer;
    private int size;
    private int start;
    private int end;
    private boolean isFull;

    public RingBuffer(int size) {
        if (size <= 0)
            throw new IllegalArgumentException("size > 0");
        this.size = size;
        this.buffer = new int[size];
        this.start = 0;
        this.end = 0;
        this.isFull = false;
    }

    public void append(int item) {
        buffer[end] = item;
        end = (end + 1) % size;
        if (isFull)
            start = (start + 1) % size;
        if (end == start)
            isFull = true;
    }


    public List<Integer> getData() {
        List<Integer> items = new ArrayList<>();
        if (!isFull)
            for (int i = 0; i < end; i++)
                items.add(buffer[i]);
        else {
            for (int i = start; i < size; i++)
                items.add(buffer[i]);
            for (int i = 0; i < end; i++)
                items.add(buffer[i]);
        }
        return items;
    }
}
```

HEAP

- Binary tree
- Layers 0,...,h-1 fully populated, layer h filled from left
- Operations always lowest RHS so that tree stays consistent


Min-Heap: Keys of nodes are **smaller** or equal than children's

Max-Heap: Keys of nodes are **larger** or equal than children's




ENQUEUE

- Insert into lowest RHS
- Compare inserted elem recursively with parent
- Swap if parent is larger, stop when parent is smaller



DEQUEUE

- Remove root
- Put lowest RHS into root pos
- Compare moved elem recursively with smaller child
- Swap if child is smaller, stop when no child is smaller
- Tree is now heapified again, repeat at step 1



HEAP SORT

Dequeue elems from head into list, resorting tree on each iter

```
public class HeapSort {
    private static <T> int getLargest(T[] array, int n,
        int parent, Comparator<T> comparator) {
        int left = 2 * parent + 1;
        int right = 2 * parent + 2;
        int largest = parent;
        if (left < n && comparator.compare(array[left],
            array[largest]) < 0)
            largest = left;
        if (right < n && comparator.compare(array[right],
            array[largest]) < 0)
            largest = right;
        return largest;
    }

    static <T> void heapify(T[] arr,
        Comparator<T> comparator) {
        int n = arr.length;
        for (int i = n / 2 - 1; i >= 0; i--)
            heapify(arr, i, comparator);
    }

    public static <T> void heapify(T[] array,
        int parent, Comparator<T> comparator) {
        int largest = getLargest(array, array.length,
            parent, comparator);
        if (largest == parent) return;
        T temp = array[parent];
        array[parent] = array[largest];
        array[largest] = temp;
        heapify(array, largest, comparator);
    }

    static <T> void percolate(T[] array, int parent,
        int n, Comparator<T> comparator) {
        int largest = getLargest(array, n,
            parent, comparator);
        if (largest == parent) return;
        T temp = array[parent];
        array[parent] = array[largest];
        array[largest] = temp;
        percolate(array, largest, n, comparator);
    }


    static <T> void sort(T[] arr,
        Comparator<T> comparator) {
        int n = arr.length;
        heapify(arr, comparator.reversed());
        while (n > 1) {
            T temp = arr[0];
            arr[0] = arr[n - 1];
            arr[n - 1] = temp;
            n = n - 1;
            percolate(arr, 0, n, comparator.reversed());
        }
    }
}
```

BINARY SEARCH TREE (BST)

TODO:
impl

- All subnodes of **left** subtree are **smaller** than root
- All subnodes of **right** subtree are **larger** than root

TRAVERSING



Preorder (W-L-R) 

Postorder (L-R-W) 

Inorder (L-W-R) 

Breadth-First/
Level-Order 

MORE DATA STRUCTURES

Set: Elements of same type, no duplicates, without order

Multiset: Set with duplicates

Map: KV-pairs with unique keys (put, get, remove O(n))

Multimap: Key can have multiple values

00P2 | FS26

Page 3

ITERATORS

```
Iterator<String> it = stringList.iterator();
while (it.hasNext()) {
    String s = it.next();
    System.out.println(s);
}
```

Mutating Collection while iterating over it: ConcurrentModificationException

EXCEPTIONS

Error	Exception
Critical, don't handle	Runtime, handleable
OutOfMemoryError, StackOverflowError, AssertionError	IOException
Checked	Unchecked
Must be handled (or throws-declaration)	Not necessary
Checked by compiler	Compiler doesn't check
Exception, not RuntimeException	RuntimeException, Error

Child Exception gets caught in catch clause with parent class

```
void test() throws ExceptionA, ExceptionB {
    String c = cliP("asdf");
    throw new ExceptionB("wack");
}

// finally ALWAYS executes, even on unhandled Exc.
try {
    test();
} catch (ExceptionA | ExceptionB e) {
    // ...
} finally { }
```


```
try { ... } catch(NullPointerException e) {
    throw e; // →leaves blocks→
} catch (Exception e) {
    // above e won't get caught!
} finally {
    // will still get executed
}

1 / 0; // ArithmeticException div by zero

String s = "";
s = null;
s.toUpperCase(); // NullPointerException

int[] arr = new int[] {1, 2, 3};
int elem = arr[8]; // ArrayIndexOutOfBoundsException
```

Unchecked



IMPORTANT STUFF

- Hashing should be added to equals fn's for strict equality
- Check if input == null
- Check if array.length == 0
- IllegalArgumentException("reason")
- try/catch finally block always executes

```
try (var fr = new FileReader("text.txt")) {
    int input = fr.read();
    while (input >= 0) {
        if (input == ';') { /* do something */ }
        input = fr.read();
    }
}

try (FileWriter writer = new FileWriter("out.txt",
    StandardCharsets.UTF_8, true)) { // append
    writer.write("weooo\n");
}

try {
    var input = new FileInputStream("text.txt");
    int i = input.read();
    while(i != -1) {
        System.out.print((char)i);
        i = input.read();
    }
    input.close();
} catch (Exception e) {
    e.printStackTrace();
}

try (BufferedReader reader = new BufferedReader(
    new FileReader("text.txt",
        StandardCharsets.UTF_8))) {
    String line;
    while ((line = reader.readLine()) != null) {
        System.out.println(line);
    }
}

try (
    FileReader reader = new FileReader("in.txt");
    FileWriter writer = new FileWriter("out.txt")
) {
    int i = input.read();
    while(i >= 0) {
        writer.write(i);
        i = input.read();
    }
}
```

TRY WITH

```
try (var output = new FileOutputStream("f.txt")) {
    output.write("Hello".getBytes());
} catch (IOException e) {
    System.out.println("Error writing file");
} finally {
    System.out.println("Done");
}
```

SERIALIZING

```
class X implements Serializable { }
// Serializing
try (var stream = new ObjectOutputStream(
    new FileOutputStream("s.bin"))) {
    stream.writeObject(new X());
}
// Deserializing
try (var stream = new ObjectInputStream(
    new FileInputStream("s.bin"))) {
    X x = (X) stream.readObject();
}
```

FUNCTION

```
public interface Function<T, R> {
    R apply(T t);

    @FunctionalInterface
    public interface ShortToByteFunction {
        byte applyAsByte(short s);
    }

    <V> Function<T, V> andThen(
        Function<? super R, ? extends V> after);

    <V> Function<V, R> compose(
        Function<? super V, ? extends T> before);
}
```

PREDICATE

```
public interface Predicate<T> {
    boolean test(T t);
}

static void removeAll(Collection<Person> collection,
    Predicate criterion) {
    var it = collection.iterator();
    while (it.hasNext())
        if (criterion.test(it.next()))
            it.remove();
}
```

COMPARABLE

```
public interface Comparable<T> {
    int compareTo(T obj);
}
```

```
var l = new ArrayList<Integer>(asList(3,2,4,5,1));
l.sort((a, b) -> a > b ? 1 : -1); // =
l.sort((a, b) -> a - b); // 1,2,3,4,5
```

```
class Person implements Comparable<Person> {
    private final String firstName, lastName;
    @Override
    public int compareTo(Person other) {
        int result = lastName.compareTo(other.lastName);
        if (result == 0)
            result = firstName.compareTo(other.firstName);
        return result;
    }
}
```

```
static int compareByAge(Person a, Person b) {
    return Integer.compare(a.getAge(), b.getAge());
}
```

```
List<Person> people = ...;
Collections.sort(people);
people.sort(Person::compareByAge);
```

COMPARATOR

```
class AgeComparator implements Comparator<Person> {
    @Override
    public int compare(Person a, Person b) {
        return Integer.compare(a.getAge(), b.getAge());
    }
}
```

```
Collections.sort(people, new AgeComparator());
people.sort(new AgeComparator());
```

```
people.sort(Comparator
    .comparing(Person::getAge)
    .thenComparing(Person::getFirstName)
    .reversed())
```

```
Comparator.comparing(Person::getName,
    (s1, s2) -> s2.compareTo(s1));
// =
Comparator.comparing(Person::getName).reversed();
```

```
Comparator<T> nullsLast(Comparator<T> c);
Comparator<T> nullsFirst(Comparator<T> c);
Comparator<T> comparing(Function<T,U> keyExtractor,
    Comparator<U> c);
Comparator<T> comparingInt(ToIntFunction<T,U> f);
```

FUNCTIONALINTERFACE

Any interface with a single abstract method is a functional interface

```
@FunctionalInterface
public interface ShortToByteFunction {
    byte applyAsByte(short s);
}

@FunctionalInterface
public interface PersonStringifier {
    String getNameAndAge(Person p);
}
```

COLLECTION

```
boolean add(E e);
boolean remove(Object o);
boolean equals(Object o);
int hashCode();
int size();
boolean isEmpty();
Object[] toArray();
void clear();
boolean contains(Object o);
boolean addAll(Collection<? extends E> c);
boolean containsAll(Collection<?> c);
boolean removeAll(Collection<?> c);
boolean retainAll(Collection<?> c);
```

```
Set<String> noDup = new HashSet<>();
```

COLLECTION IMPLEMENTATIONS

```
// List
int indexOf(Object o);
int lastIndexOf(Object o);
E get(int index);
subList(int from, int to);
void sort(Comparator<? super E> c);

// Stack
E peek();
E pop();
E push(E item);
boolean empty();
int search(Object o);
```

```
// Queue
E element(); // throws → peek(); doesn't
E remove(); // throws → poll(); doesn't
boolean add(E e); // throws → offer(E e); doesn't
```

```
// Set
// (I) SortedSet → (C) TreeSet
// (C) HashSet, (C) LinkedHashSet
```

```
// Map
// HashMap
boolean containsKey(Object key);
boolean containsValue(Object value);
Set<Map.Entry<K, V>>> entrySet();
V get(Object key);
V put(K key, V value);
V putIfAbsent(K key, V value);
V replace(K key, V value);
V remove(Object key);
V getOrDefault(Object key, V defaultValue);
Set<K> keySet();
Collection<V> values();
```

LAMBDAS

```
String pattern = readFromConsole();
// vvv not final → Error
while (pattern.length() == 0)
    pattern = readFromConsole();
Utils.removeAll(people, p ->
    p.getLastName().contains(pattern));
// Local variable ... referenced from a lambda
expression must be final or effectively final
```

```
// Predicate :: a → boolean
Predicate<Integer> isLarge = (v) -> v > 69420;
// Function :: a → b
Function<Integer, String> str = (v) -> "" + v;
// Supplier :: a
Supplier<String> hello = () -> "Hello, World!";
// Consumer :: a → void
Consumer<Integer> consommer = (v) -> log(v);
// UnaryOperator :: a → a
UnaryOperator<Integer> more = (v) -> v * v;
// BinaryOperator :: a → a → a
BinaryOperator<Integer> less = (a, b) -> a - b;
```

STREAMS

```
import java.util.stream.*;

people
    .stream()
    .distinct()
    .filter(p -> p.getAge() >= 18)
    .skip(5)
    .limit(10)
    .map(p -> p.getLastName())
    .sorted()
    .forEach(System.out::println);

people
    .stream()
    .reduce(0, (acc, cur) -> acc + cur.getAge());
```

```
list.stream().mapToInt(Integer::intValue);
list.stream().mapToInt(Integer::parseInt);
```

OPTIONAL (HASKELL / RUST IN BLOAT)

```
T get(); // NoSuchElementException
boolean isPresent();
void ifPresent(Consumer<T> consumer);
T orElse(T other);
static Optional<T> empty();
static Optional<T> of(T value);
```

METHODS

```
boolean allMatch(Predicate<T> predicate);
boolean anyMatch(Predicate<T> predicate);
boolean noneMatch(Predicate<T> predicate);
static Stream<T> concat(Stream<T> a, Stream<T> b);
Stream<T> distinct();
Stream<R> flatMap(Function<T, R> mapper);
Stream<T> limit(long maxSize);
Stream<T> skip(long maxSize);
Stream<T> sorted(Comparator<T> comparator);
```

TERMINAL OPERATIONS

```
Optional<T> min(Comparator<T> comparator);
Optional<T> max(Comparator<T> comparator);
Optional<T> findAny();
Optional<T> findFirst();
void forEach(Consumer<T> action);
void forEachOrdered(Consumer<T> action);
// IntStream
average();
sum();
```

COLLECTORS

```
// List
s.collect(Collectors.toList());
// TreeSet
s.collect(Collectors.toCollection(TreeSet::new));
// String
s.collect(Collectors.joining(", "));
// Integer
s.collect(Collectors.summingInt(Person::getAge));
// Map<String, Person>
s.collect(Collectors.groupingBy(Person::getCity));
// Map<String, Integer>
s.collect(Collectors.groupingBy(Person::getCity,
    Collectors.summingInt(Person::getSalary));
// Map<boolean, List<Person>>
s.collect(Collectors.partitioningBy(s ->
    s.getAge() > 18))
```

MORE API'S WE "SHOULD" BE PROVIDED WITH

```
Yes I'm salty, thanks for pointing that out

// Integer
static int parseInt(String s);
// System
arraycopy(Object src, int srcPos, Object dest,
    int destPos, int length);
// Arrays
static <T> List<T> asList(T... a);
// example usage
String[] B = new String[4];
HashSet<String> H = new HashSet<>(Arrays.asList(B));
```