

strrev():~ (Reverse)

It is a sdf present within <string.h>. It will take one parameter as an argument (string) and will always return reverse of a string as a string value.

strcat():~ (Concatenate)

It is a sdf within <string.h>. It will take ^{two} ~~one~~ parameter as an argument. 2nd parameter destination array i.e string and 1st parameter source array (string). This func. is used to concatenate or merge two string that means through this func. content of the second array will be merged to the end of the 1st array and it will return merge string as a return value.

strstr():~ (string string)

It is a sdf within <string.h>. It will take 2 parameter as an argument. 1st parameter the entire string and 2nd parameter the word which we want to search. This func. is used to check a substring within a given string and will always return character pointer that is NULL and not null value. If the substring is found then it will return not NULL value and if the substring is not found it will return NULL value.

strupr():~ (Upper)

It is a sdf within <string.h>. It will take one parameter as an argument (string) and will always return uppercase of the string as a value.

strlwr():~ (Lower)

It is a sdf within <string.h>. It will take one parameter as an argument (string) and will always return lowercase of the string as a value.

String handling:-

P-109

<string.h> headerfile is used to implement string program. There are few inbuilt string ~~about~~ function present within <string.h> headerfile.

1. strlen()
2. strcpy()
3. strcmp()
4. strcmp()
5. strcat()
6. strstr()

1. strlen() :- (string length)

It is a system define function (sdf) present within <string.h>. It will take one parameter as an argument that is string and will always return integers as a value of count the length of a string.

2. strcpy() :- (string copy)

It is a system define function (sdf) present within <string.h>. It will take two parameter as an argument. First parameter destination array (string) second parameter source array (string). Content of 1st array will be copied within the second array. That is (i.e) it will return string value.

3. strcmp() :- (string compare)

It is a sdf present within <string.h>. It will take two parameter as an argument. It is not mandatory to take source or destination array as first or second parameter. This func. is used to check whether 2 strings are equal or not. If both the strings are same then it will return One other wise it will return 0.

- * zero means conditions is satisfied i.e true
- * One means conditions is dissatisfied i.e false

strdup():- (Duplicate)

P-60

It is a sdf within <string.h>. It will take one parameter as an argument (string) and will always return duplicate of the string as a value.

stricmp():-

It is a sdf within <string.h>. It ~~will take~~ is same as a strcmp(), but this func. negotiates case i.e 'A' and 'a' treated as same.

strchr():-

It is a sdf within <string.h> It will take two Parameter as an argument the entire string and second the letter (character) which we want to search. It will return character pointer where the specific letter is pointed.

//WAP to count length of a string