

# CodeForces Round 1037 Div. 3E

omeganot

July 18, 2025

Trying to build the original  $a$  felt like the most promising path. Given  $p_i$  and  $s_i$ ,  $a_i$  would definitely need to be a multiple of both. This me think of the LCM of  $p_i$  and  $s_i$ . We may theorize that if there is exist some valid  $a$ , then one such  $a$  must consist of  $a_i = \text{lcm}(p_i, s_i)$ .

Let's assume there exists some valid  $a$  given  $p$  and  $s$ .  $p_1 = a_1$  must be true as well as  $s_n = a_n$ , meaning that if  $p$  and  $s$  are good,  $p_1$  is a multiple of  $s_1$  and  $s_n$  is a multiple of  $p_n$ . Then, for 1 and  $n$ , the condition  $a_i = \text{lcm}(p_i, s_i)$  would be satisfied. Now, take some arbitrary  $a_i$  where  $1 < i < n$ . We know that

$$\gcd(p_{i-1}, a_i) = p_i$$

and

$$\gcd(s_{i+1}, a_i) = s_i$$

If we were to change  $a_i$  into  $\text{lcm}(p_i, s_i)$ ,  $p_1 \dots p_{i-1}$  wouldn't change and  $s_{i+1} \dots s_n$  would also be the same. Furthermore,  $\gcd(p_{i-1}, a_i) = p_i$  would imply  $\gcd(p_{i-1}, \text{lcm}(p_i, s_i)) = p_i$ , as  $a_i$  being a multiple of  $p_i$  and  $s_i$  would mean it is a multiple of  $\text{lcm}(p_i, s_i)$ . Thus,  $\gcd(p_{i-1}, a_i)$  must be a multiple of  $\gcd(p_{i-1}, \text{lcm}(p_i, s_i))$ , and since  $\gcd(p_{i-1}, a_i) = p_i$ ,  $\gcd(p_{i-1}, \text{lcm}(p_i, s_i)) = p_i$  as  $\text{lcm}(p_i, s_i)$  is still a multiple of  $p_i$ . Similar logic would hold for  $s_i$ . Since the rest of  $a$ , remains the same, if  $p_i$  and  $s_i$  remain the same so do  $p_{i+1} \dots p_n$  and  $s_1 \dots s_{i-1}$ . We could repeat this process until  $a_i = \text{lcm}(p_i, s_i)$  for all  $i$ .

Now that we have a greedy method to find a valid  $a$ , we can just create  $a$  based on our rule and then check if the resulting  $p'$  and  $s'$  match the inputs. Since we would need to use lcm and gcd  $O(n)$  times, our solution is  $O(n \log a_i)$ .