

Id

Body

Title

<p>What tools beside Visual Studio's Cider do you use?

Have you succeed in using something from Microsoft Expression product family?
</p>

<p>EDIT:

Here are revealed tools:</p>

Snoop
Mole debugger visualizer
Perforator suggested by Matt Hamilton
The Expression Blend 2.5 Preview suggested by Anthony Conyers
Kaxaml suggested by Anthony Conyers & Brad Leach
Xaml Export suggested by Artur Carvalho

<p>Some other related questions:</p>

Tools to develop WPF or Silverlight applications
How to speed up WPF programs? - has a list of related tools

<p>Some of the work we do at my company is slowly edging towards a product family with different products in the same family and different flavours (or feature sets) in each product. I am looking for some product line engineering techniques that might help us. Web search leads to a lot of resources and a lot of different sources of information and differing methodologies. Before plugging into any of these in depth I thought it would be useful to get some practical advice from someone who has done something similar to this before. Anyone have any pointers/nuggets of wisdom in this area? I am particularly looking for better ways to do the following in a product line environment: </p>

configuration and build management
ease of development cycle
testing

305423

Product Line Engineering

<p>I think I'm approaching this the wrong way, which is why I can't seem to figure out an easy solution. I'm relatively new to Rails, so bear with me.</p>

<p>I have a layout, "store," that contains all of the common visual elements for the other controllers. In this layout, I need to dynamically create the sidebar with data from two models, Product and ProductFamily. I want it to output like so:
</p>

```
<pre><code>Product Family
---- Product1
---- Product2
</code></pre>
```

<p>And continue on through all relevant records.</p>

<p>I just can't figure out where to start writing the logic for this. Does it go in the layout? In a controller?</p>

<p>Please, point me in the right direction!</p>

1105476

Logic in Rails Layout?

I have a list of Product objects (as rows), each object has several data fields (like product id, product family, etc) - as columns. I managed to create a table model subclassing QAbstractTableModel, and display the datas in a QTableView.

What i want is provide a "grouped" view of the model in a tree-like structure. For example I want to group the products by their family id, so the tree should contain in the first level the groups (family id) and their childs are the product's having that family id.

Any ideas?

PS:

The need of multiple groupings (group by family id, and group them by another column, and so on) shows me that the model should be a tree. The root nodes indicates the groups, and then the childs are the group members. The multiple grouping can be achieved by multi-level trees.

Then my transformed question is the following: How can I implement a special QTableView class that displays only the tree's leafs (at a given level)? Because actually leafs are the real objects we would like to see in a grid

I can use setRootIndex in the tableview, but it doesn't solve anything, other leafs are not displayed.

I was digging a little bit, and found that in QTableView::paintEvent, when displaying each row and column, the actual item is fetched like :

```
const QModelIndex index = d->model->index(row, col, d->root);
```

where d->root() is the root node given by setRootIndex(). This should be embedded in a tree-traversal code, and everything would be fine. But how could I avoid to reimplement the whole paintEvent method ?

<p>I want to upgrade my product via msi setup.
The Upgrade Code of both msi remains the same because it's the same product family. Even if I change Version/Product Code of the msi for updating it just tells me the product is already installed or asks me to repair it. it doesn't ever provide an update option that replaces the current installation.</p>

<p>I'm using Visual Studio 2008 Pro to generate the msi setup</p>

2028425

How to upgrade via msi

<p>I'm building an asp.net cutom control inside which I have two dropdownlists: companyIdSelection and productFamilySelection. I populate the companyIdSelection at Page_Load and in order to populate the productFamilySelection depending on the selected item in companyIdSelection. I'm using UpdatePanels to achieve this, but for some reason every time I update companyIdSelection Page_Load is being called (which as far as I know should happen only when the entire page is reloaded), the list is being reloaded again and the item the user selected is lost(the selected item is always the top one). Here's the code</p>

<p></p>

```
<pre><code> <asp:UpdatePanel ID="updateFamilies"
    runat="server"
    UpdateMode="Always">
    <ContentTemplate>
        Company ID:<br>
        <br>
        <asp:DropDownList ID="companyIdSelection"
            runat="server"
            AutoPostBack="True"
            OnSelectedIndexChanged="
companyIdSelection_SelectedIndexChanged">
            </asp:DropDownList>
            <br>
            Product Family:
            <br>
            <asp:DropDownList ID="productFamilySelection" runat="server"
                AutoPostBack="True"
                onselectedindexchanged="
productFamilySelection_SelectedIndexChanged">
            </asp:DropDownList>
            <br>
        </ContentTemplate>
    </asp:UpdatePanel>
```

```
protected void Page_Load(object sender, EventArgs e)
{
    this.companyIdSelection.DataSource = companyIds(); //companyId returns
the object containing the initial data items
    this.companyIdSelection.DataBind();
}
```

<p>I want to disable the background window when clicking the button. In my project I am using update panel and progress bar. when I click the button the background window is fully visible= false. I want to disable the background window and the progress bar should be displayed. Here is the code:</p>

```
<pre><code>&lt;%@ Page Language="VB" MasterPageFile="~/MasterPage.master" AutoEventWireup="false" CodeFile="fp_t012stk.aspx.vb" Inherits="fp_t012stk" title="Current Stock Report" %&gt;
```

```
&lt;%@ Register Assembly="CrystalDecisions.Web, Version=10.2.3600.0, Culture=neutral, PublicKeyToken=692fba5521e1304"
```

```
Namespace="CrystalDecisions.Web" TagPrefix="CR" %&gt;
```

```
&lt;%@ Register Assembly="AjaxControlToolkit" Namespace="AjaxControlToolkit" TagPrefix="cc1" %&gt;
```

```
&lt;asp:Content ID="Content1" ContentPlaceHolderID="ContentPlaceHolder1" Runat="Server"&gt;
```

```
&lt;script type="text/JavaScript" language="JavaScript"&gt;
```

```
function ShowProgress()
```

```
{
```

```
document.getElementById ('MainDiv').style.display="";
```

```
document.getElementById ('MainDiv').style.visibility='visible';
```

```
document.getElementById ('MainDiv').style.position='absolute';
```

```
document.getElementById ('MainDiv').style.top='0px';
```

```
document.getElementById ('MainDiv').style.left='0px';
```

```
document.getElementById ('MainDiv').style.width= '100%';
```

<p>I work on a device that uses Embedded Linux. In the near future this device is going to probably turn into a product family and a few more devices (i.e. hardware platforms) are going to added to the mix. These devices will be similar but may have processors, hardware peripherals (and device drivers), user space applications and kernel settings. In addition to compiling distributions for different devices, I'd also like to build debug distributions for development.</p>

<p>What are some of the more common ways to assemble and manage Embedded Linux systems? I have been playing around with Jenkins some and see some potential there.</p>

6553409

Build Systems for Embedded Linux

I am writing my first WCF service. I am trying to understand how Datacontracts work. I have read the [MSDN Article](http://msdn.microsoft.com/en-us/library/ms733811.aspx) that describes how custom types should be marked up to create a data contract but I cannot get my example to work.

I have a simple DTO object that I have placed in a shared library because I want the client and the service to know about this type (right?) it looks like this:

```
<pre><code> using System.Collections.Generic;
using System.Runtime.Serialization;

namespace org.healthwise.gatewayinterfaces.mocks
{
    [DataContract]
    public class MockCheckInDTO : ICheckInDTO
    {
        [DataMember]
        private string _testPackageFilePath = "testpackages\\973eb455-6acc-486b-
a1dd-2cf527872b1e.zip";
        [DataMember]
        private IDictionary<string, string> _testMetaData;

        public MockCheckInDTO()
        {
            _testMetaData = MakeTestMetaDataDictionary();
        }

        private IDictionary<string, string> MakeTestMetaDataDictionary()
        {
            IDictionary<string, string> testMetaData = new Dictionary<string,
string>();
            testMetaData.Add("Version", "9.0.1");
            testMetaData.Add("Product Family", "Learning Modules");
            return testMetaData;
        }

        [DataMember]
        public string PackageFileLocation
        {
            get { return _testPackageFilePath; }
            set { _testPackageFilePath = value; }
        }
    }
}
```

<p>How does Find control method works if i need to find any control which is inside gridview template, more specifically Item Template??</p>

<p>I have a hyperlink but it is not able to find the same.</p>

<p>Question updated with code</p>

<p>Gridview Code is below:</p>

```
<pre><code>&lt;asp:GridView ID="grvYourOpportunities" runat="server"
AllowPaging="True" AutoGenerateColumns="False"
    DataKeyNames="ID#,B,H" PageSize="20" CellPadding="4" ForeColor="
#333333" GridLines="Both"
    OnRowDataBound="grvYourOpt_RowDataBound"&gt;
    &lt;HeaderStyle BackColor="#5D7B9D" Font-Bold="True" ForeColor="White"
/&gt;
    &lt;RowStyle BackColor="#F7F6F3" ForeColor="#333333" /&gt;
    &lt;Columns&gt;
        &lt;asp:TemplateField&gt;
            &lt;HeaderTemplate&gt;
                i
            &lt;/HeaderTemplate&gt;
            &lt;ItemTemplate&gt;
                &lt;%# Eval("i") %&gt;
            &lt;/ItemTemplate&gt;
            &lt;/asp:TemplateField&gt;

        &lt;asp:TemplateField&gt;
            &lt;HeaderTemplate&gt;
                H
            &lt;/HeaderTemplate&gt;
            &lt;ItemTemplate&gt;

                &lt;%;--&lt;a href="javascript:ShowChildGrid('div&lt;%;# Eval("ID#") %
&gt;');" &gt;
                &lt;img id="imgdiv&lt;%;# Eval("ID#") %&gt;" alt="Click" border="0"
src="plus.gif" runat="server" /&gt; &lt;a&gt; --%&gt;

                &lt;asp:HyperLink runat="server" ID="hIPlus" ImageUrl="~/plus.gif"
&gt;&lt;/asp:HyperLink&gt;
```

I am trying to pass a static resource URL, via the apex:param tag. The code I have so far is:

VisualForce:

```
<code><apex:selectList value="{!SelectedFamily}" onchange="
renderGallery();" size="1" label="Product Family">
    <apex:actionFunction name="renderGallery" rerender="gallery"
oncomplete="renderScripts();">
        <apex:param value="{!URLFOR($Resource.NoImage)}" assignTo="{!
noImage}"/>
        <apex:param value="{!URLFOR($Resource.NoImageThumb)}" assignTo="{!
noImageThumb}"/>
    </apex:actionFunction>
    <apex:actionFunction name="renderScripts" rerender="scriptPanel">
    </apex:actionFunction>
    <apex:selectOptions value="{!Family}" />
</apex:selectList>
</code>
```

Controller:

```
<code>public string noImage{ get; set; };
public string noImageThumb { get; set; }
</code>
```

My understanding of apex:param was that I would now be able to call the controller variables after the re-render had occurred and they would be populated with the static resource URL. But unfortunately I keep getting null.

Anyone have any idea why it isn't working?

<p>We have a rather flexible application written in C# (.net 4.0) that copies data to different ERP systems around the company. It uses an XML file to determine the from and to ERP systems, the data source, credentials, and the columns to copy.</p>

<p>What we are seeing is that there is an interest in transforming the data as it is copied. So a part number with a product family, gets converted to just a product family. For example to do the following transformation 564-8911277 ==> 564 using SSRS functions this would be </p>

```
<pre><code>=Left("564-8911277", instr(564-8911277, "-" ) - 1))
</code></pre>
```

<p>The thought is to put the expression in the XML file and have the system interpret the expression and transform the data.</p>

<p>I'm researching and working on a cost estimate to develop this feature, and wondering if there is anything out there that already exists that can be integrated into a .net application? </p>

<p>I've found a few things (scripting.net from 2001), but thought I'd reach out to the community to see what else is out there.</p>

<p>Thanks, Tim</p>

<p>I've the following unordered list:</p>

```
<pre><code>&lt;ul class="primary"&gt;
  &lt;li id="1"&gt;&lt;span&gt;Product Family A&lt;/span&gt;
    &lt;ul class="secondary"&gt;
      &lt;li&gt;&lt;span&gt;A.1&lt;/span&gt;&lt;/li&gt;
      &lt;li&gt;&lt;span&gt;A.2&lt;/span&gt;&lt;/li&gt;
    &lt;/ul&gt;
  &lt;/li&gt;
  &lt;li id="2"&gt;&lt;span&gt;Product Family B&lt;/span&gt;
    &lt;ul class="secondary"&gt;
      &lt;li&gt;&lt;span&gt;B.1&lt;/span&gt;&lt;/li&gt;
    &lt;/ul&gt;
  &lt;/li&gt;
  etc...
&lt;/ul&gt;
</code></pre>
```

<p>I'd like to generate the output below with jQuery. Can someone help?</p>

```
<pre><code>product_family:[{
  id:1,
  products:[{
    model: A1,
    model: A2
  }],
  product_family:[{
    id:2,
    products:[{
      model: B1
    }]
  }
]</code></pre>
```

<p>THanks!</p>

<p>I need some help figuring out the best way to sctructure content using Expression Engine. I've red the documentation, looked at all information I could find but I haven't found the answer. I hope someone here could help.</p>

<p>What I want to create is a product catalogue that would look like this:</p>

<p><code>/bikes</code> (product category, displays the product families, two-wheelers, three wheelers etc.)</p>

<p><code>/bikes/two-wheelers</code> (product family, displays the products in the family)</p>


<p><code>/bikes/two-wheelers/red-bike</code> (product)</p>


<p><code>/bikes/two-wheelers/red-bike/wheels</code> (optional product details page)</p>

<p>I understand that EE URI's are template-group/template based and that the content is in channels. I'm not yet sure how categories can be used in this. Essentially I would like to create "simple" parent-child relationships between the entries and I found a plug-in called Structure that does something like that. Unfortunately, this project needs to be done without additional (payed) plug-ins.</p>

<p>Is it possible for the <code>product</code> to be the channel, and <code>product-family</code> and <code>product-category</code> to be attributes of the <code>product</code> in EE? Would that work? Is there a better way to structure that?</p>

<p>I realise that this isn't a straight-forward question, but I'm still hoping to be pointed in the right direction.
Thanks for reading!</p>

Lets say I have following DB structure:

and my application needs to show the list of articles with all the details (model, product family, brand, producer). For that I would need to make more JOINS to get needed data.

Is it OK if I increase application's performance by creating redundant FKs to the Article table like follow? Does it actually increase the performance?


12004210

DB design and performance: Is it OK to use redundant Fk

I have a list of products that has two columns, product and product family.

I want to create another list that uses this first list as a lookup for one of the columns. This I can do, i.e. I create a custom column and then use the "Add from existing site columns" linko the "List Settings" page of the second list.

However, what I'd really like is that the custom column only proposes products that belong to a specific product family. I can create a View in the first list which allows me to display only the products in a specific family. However I don't see any way to specify only this view when I create the custom column.

Anyone have any ideas ?

Best regards,

Colm

12974739

Is it possible to create a Custom Column that will take va

Not sure if this is possible. In my example I am using json as the source but this could be any size. In my example on <http://jsfiddle.net/jqIndy/ZPUr4/3/> I would use this data in a shared fashion by only binding two columns ProductFamily (xAxis) and Value (yAxis) but I would like to be able to group the columns by using an aggregate.

In this example without the grouping it shows multiple columns for FamilyA.
Can this be grouped into ONE column and the values aggregated regardless of the amount of data?

So the result will show one column for FamilyA of Value $4850 + 4860 = 9710$ etc.?

A problem with all examples online is that there is always the correct amount of data for each category. Not sure if this makes sense?

<http://jsfiddle.net/jqIndy/ZPUr4/3/>

```
<pre><code>//Sample data (see fiddle for complete sample)
```

```
{
  "Client":"","
  "Date":"2011-06-01",
  "ProductNumber":"5K190",
  "ProductName":"CABLE USB",
  "ProductFamily":"FamilyC",
  "Status":"OPEN",
  "Units":5000,
  "Value":5150.0,
  "ShippedToDestination":"CHINA"
}
```

```
var productDataSource = new kendo.data.DataSource({
  data: dr,
  //group: {
  // field: "ProductFamily",
  //},
  sort: {
    field: "ProductFamily",
    dir: "asc"
  },
  ,
}
```


I have downloaded opensource delphi twain component (TDelphiTwain). The interesting thing is, that when placed and saved on the form it creates bad dfm entry for itself.

```
object DelphiTwain: TDelphiTwain
  OnSourceDisable = DelphiTwainSourceDisable
  OnSourceSetupFileXfer = DelphiTwainSourceSetupFileXfer
  TransferMode = ttmMemory
  SourceCount = 0
  Info.MajorVersion = 1
  Info.MinorVersion = 0
  Info.Language = tlDanish
  Info.CountryCode = 1
  Info.Groups = [tgControl, tgImage, tgAudio, MinorVersion]
  Info.VersionInfo = 'Application name'
  Info.Manufacturer = 'Application manufacturer'
  Info.ProductFamily = 'App product family'
  Info.ProductName = 'App product name'
  LibraryLoaded = False
  SourceManagerLoaded = False
  Left = 520
  Top = 136
end
```

The problem is with the line:

```
Info.Groups = [tgControl, tgImage, tgAudio, MinorVersion]
```

There are only three possible elements:

```
tgControl, tgImage and tgAudio
```

It adds MinorVersion everytime I Save the form. When the app is run I get the error that there is invalid property for Info.Groups. When i remove the bad part manually and without leaving dfm file the app starts ok.

I looked in the internet and there was one inquire regarding these strange

<p>As part of our installation procedure we have to install Adobe Acrobat XI. According to Adobe:</p>

<blockquote>

<p>The basic formula for constructing and decoding the GUID is as follows:</p>

<p>Acrobat: Example: AC76BA86-1033-F400-7760-100000000002</p>

<p>[product family]-[language code]-[additional languages]-[product type]-[license type][major version][major minor version]</p></blockquote>

<p>Since I know the key is located in <code>HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\Uninstall</code> and I know the key starts with <code>{AC76BA86-</code> I would like to simply search for the key(s) that begin with that sequence so I can inspect it to determine if we need to install Acrobat.</p>

<p>Is there a way to do a partial registry key search in InstallShield's install script?</p>

14712484

Search for partial registry key in InstallShield

<p>So, I bought into the dream in the form of a surface pro and then I installed Visual Studio 2010 in the hopes of coding on the toilet. However, I cannot get SP1 to install (from this link: here). Has anyone successfully installed SP1 on the surface?</p>

<p>The error I get is:</p>

<blockquote>

<p>KB2736182 does not apply, or is blocked by another condition on your computer. Please see http://go.microsoft.com/fwlink/?LinkId=225649 for more details.</p>

</blockquote>

<p>If you follow the link you'll see this gem:</p>

<p>"Product of the product family Visual Studio 2010 or Team Foundation Server 2010 with Service Pack 1 applied"</p>

15216123

Visual Studio on Surface Pro SP1

I have two low-level questions about how memory interleaving across channels works on Sandy Bridge processors. I've poured through technical documents from Intel, and I still cannot find the answers. Can you help?

Multi-channel memory controllers in modern CPUs stripe data across the memory channels. This allows reads and writes to be carried out in parallel, thus increasing performance.

Question #1: What is the chunk size Sandy Bridge uses for interleaving? I've found some information that suggests that it is the cache-line size. On the other hand, others have suggested that it is <http://stackoverflow.com/questions/4183461/nehalem-memory-architecture-address-mapping> configurable (at least in older Intel architectures). Which is it? Can you point to an Intel document?

Some CPUs allow interleaving to be disabled. This is confirmed by BIOS settings of some high-end systems such as HP's ProLiant and Fujitsu's Primergy. The closest documentation from Intel that I can find on this is section 4.4.4.3 in this <http://www.intel.com/content/dam/www/public/us/en/documents/datasheets/xeon-e5-1600-2600-vol-2-datasheet.pdf> [E5 Product Family Data Sheet](#). I have gone as far as contacting HP about how their ProLiant systems work when interleaving is disabled, but even on a conference call, they were unable to answer my question.

Question #2: How is memory mapped across the channels when interleaving is disabled? Presumably, it is different from sparse or mirror mode configurations.

15836309

SandyBridge: How does physical memory map across channels?

<p>I have the below table:</p>

```
<pre><code>&lt;table class="authors-list" border=0 id="ordertable"&gt;
  &lt;tr&gt;
    &lt;td &gt;&lt;input type="text" id="product_1" name="product_1" class="
rounded"/&gt;&lt;/td&gt;
    &lt;td &gt;&lt;input type="text" size='5' id="qty_1" name="qty_1" class="
rounded"/&gt;&lt;/td&gt;
    &lt;td class="tdcheckbox"&gt;&lt;input type="checkbox" id="h09_1" name="
h09_1" class="rounded"/&gt;
    &lt;input type="text" id="line_1_09" name="line_1_09" value=""&gt;&lt;
/td&gt;
    &lt;td class="tdcheckbox"&gt;&lt;input type="checkbox" id="h12_1" name="
h12_1" class="rounded"/&gt;
    &lt;input type="text" id="line_1_12" name="line_1_12" value=""&gt;&lt;
/td&gt;
    &lt;td class="tdcheckbox"&gt;&lt;input type="checkbox" id="h15_1" name="
h15_1" class="rounded"/&gt;
    &lt;input type="text" id="line_1_15" name="line_1_15" value=""&gt;&lt;
/td&gt;
    &lt;td&gt;&lt;input type="text" name="cubespercheck_1" id="
cubespercheck_1" value="0" size=5&gt;&lt;/td&gt;
  &lt;/tr&gt;
&lt;/table&gt;
</code></pre>
```

<p>you can see the fiddle here:

http://jsfiddle.
net/3Befc/7/</p>

<p>My main goal is to be able to post each checkbox as an individual product.
the product field is populated with a product family. example is 38114CR. the
checkboxes represent the lengths of the product. the code for a 1.8 meter length
of 38114CR is 3811418CR where 18 is the length (1.8)</p>

<p>In the end, I want to be able to post each checked checkbox as its unique
product code. so if 0.9 is checked for product 38114CR post the value
3811409CR.</p>

<p>My ultimate goal is to insert the following into a database:
(this is as per the fiddles desired result)</p>

<p>I have two relationships.
product family.</p>

<p>a family can have several products. a product belongs to one family.</p>

<p>Taking a product like you can remove the family relationship. ie how could leave a product without family?</p>

<p>I tried this:</p>

```
<pre><code>$product-&gt;getFamily()-&gt;remove();  
$product-&gt;setFamily(null);  
</code></pre>
```

<p>but not working.
must be an instance of my\myBundle\Entity\Family
thanks.</p>

16239733

Removing Associations doctrine symfony2

<p>I'm having a wired issue, I'm using protobuf-net for C# to generate a file which based on Google Protocol Buffer message and then upload it to one of my company's servers.</p>

<p>I created a tool in C# that generates a .proto file to .cs, then I'm using its classes (from .cs file) to fill all the required fields in the message and after that I called to Serializer.Serialize() function and its creates for me the requested file.</p>

<p>BUT, and this is the problem, I have another file (same file) which created in another tool that wrote in C++ (uses the same .proto file that I used), but when I'm trying to upload my file to our servers I'm getting an error that something is wrong.</p>

<p>I compared the 2 files with "Win Merge" software and I noticed a very little differences in 3 different lines (out of 7000+ lines in each file) compared to the file that generated in the C++ tool.</p>

<p>Here is example of 2 line captured from Win Merge tool (on the Left the C++, on the right C#):</p>

<p></p>


<p></p>

<p>I notice that the differences is in the rectangulars (which I don't understand what is there meaning) with the bytes inside them...</p>

<p>Here is the .proto file that I'm using:</p>

```
<pre><code>message Package {  
  
message ArchDepend {  
  
    message Arch {  
        required string version = 1;  
        required string description = 2;  
    }  
}
```

i am developing a software using Visual C++ 2008 Express Edition. after build in release mode, i have made a setup file with latest redistributable 2008. the software is running in my PC fine. in my PC this redistributable are installed :



in my friends PC, the same redistributable are installed. but the software is crashing on my friends PC.




from the event log it shows:



as you can see, it is demanding 9.0.21022.8 version of redistributable whether there is previously installed latest version of redistributable(9.0.30729.17). so, i go for a google. from the internet, i edit my `C:\Program Files\Microsoft Visual Studio 9.0\VC\include\crtassem.h`



but it didn't help. then i check my project manifest. and i saw :



but i don't know how to edit manifest (i am new in VC++). and i also check `C:\Program Files\Microsoft Visual Studio 9.0\VC\redist\x86\Microsoft.VC90.CRT\Microsoft.VC90.CRT.manifest`. i shows:



i have tried to find out 9.0.21022.8 version of redistributable in the internet. but i have failed. from my VCExpress installer there is a file named `vc90distmin_x86.exe` :

I am an Android developer, I have to create a generic component for parsing xml using sax parser. For any kind of schema I should create a common component through which we can parse the xml and save that into a data file (bean or model object).

Is this possible with SAX, if so can you please assist me?

For ex,

```
<code><?xml version="1.0" encoding="UTF-8" ?>
<ns:multiStockDataDownloadResponse xmlns:ns="http://service.
tcs.web" >
  <ns:return>
    <StockList>
      <Stock changeData="-0.10" companyData="Sprint Nextel Corporation"
lastData="5.21" marketCapData="15586.73" percChangeData="-1.88" tkr="S"
      >
        <customerProfile value="false" name="isNWCustomer" />
        <customerProfile value="English" name="custLangPref" />
        <customerProfile value="karthi.muthusamy@bankofamerica.com"
          name="fullEmailAddress" />
      </Stock>
      <Stock changeData="+0.43" companyData="Vodafone Group Plc (ADR)"
lastData="26.43" marketCapData="135649.83" percChangeData="2.05" tkr="
VOD" >
        <customerProfile value="false" name="isNWCustomer" />
        <customerProfile value="English" name="custLangPref" />
      </Stock>
      <Stock changeData="+0.12" companyData="Verizon Communications Inc."
lastData="35.24" marketCapData="98672.00" percChangeData="0.34" tkr="VZ"
      >
        <customerProfile value="false" name="isNWCustomer" />
      </Stock>
      <Stock changeData="+0.08" companyData="AT&T Inc." lastData="
30.43" marketCapData="180206.46" percChangeData="0.26" tkr="T" />
      <Stock changeData="-0.22" companyData="Telefonica S.A. (ADR)" lastData="
23.47" marketCapData="107117.00" percChangeData="-0.93" tkr="TEF" />
    </StockList>
  </ns:return>
</ns:multiStockDataDownloadResponse>
```

<p>I am binding Multiselect jquery through code behind</p>

<p>and on button click i am rebinding with different values</p>

<p>it shows the changed list,</p>

<p>I have to disabled some items in second list if it is available in first list</p>

<p>suppose
Old list1 is </p>

<p>Date</p>

<p>Revenue</p>

<p>New list1 is</p>

<p>productName</p>

<p>new second list is</p>

<p>Date</p>

<p>Product Family</p>

<p>so as Date was in oldlist1
its disabling in list2</p>

<p>but date is not in newlist1 so it should not disabled in list2</p>

<p>when i look in firebug i saw the date is avaibale in List1 like this</p>

<p></p>

<p>its keep storing old list, but its not visible in list on GUI</p>

<p>The code is like this</p>

<p>I have modified this line in jquery plugin </p>

<p>How can we cluster customers from transaction data in R ? For e.g., we have customer name,product code,product family,product modules and units they boughtnow i want to find some pattern via clustering. I have looked over k-means and som in R but not getting the right approach to do it. kindly help</p>

<p>PS: My data is not numeric data,they are categorical</p>

19157556

clustering customers in R with transactional data

<p>I'm trying to learn C# (and Linq-to-Xml) for handling of XML files, yet having some troubles. </p>

<p>I can get the elements and values, but my output is missing the information I need for logic decisions (id and state attributes in the transaction and target elements). </p>

<p>I think it has to do with the Descendants, but not sure how to grab them.</p>

<p>A little nudge in the right direction?</p>

<p>My XML File</p>

```
<pre><code>&lt;?xml version="1.0"?&gt;
&lt;xliff version="1.2"&gt;
  &lt;file source-language="en-US" datatype="plaintext" category="framework"
&gt;
    &lt;body&gt;
      &lt;transaction approved="no" id="1"&gt;
        &lt;source xml:lang="en-US"&gt;Product Family&lt;/source&gt;
        &lt;target state="translated" xml:lang="en-US"&gt;Product Family&lt;
/target&gt;
      &lt;/transaction&gt;
    &lt;/body&gt;
  &lt;/file&gt;
&lt;/xliff&gt;
</code></pre>
```

<p>C# Code</p>

```
<pre><code>private void btnOpen_Click(object sender, EventArgs e)
{
    // Show the dialog, using defaults, and get result
    OpenFileDialog ofdResult = new OpenFileDialog();

    if (ofdResult.ShowDialog() == DialogResult.OK)
    {
        try
        {
            if (ofdResult.OpenFile() != null)
            {
                // File opened successfully
            }
        }
        catch { }
    }
}
```

<p>I have two XML files i am trying to merge some elements using xsl.</p>

<p>XML1:</p>

```
<pre><code>&lt;ALL xmlns:a="http://example.com/ns1" xmlns:xsi="http://www.
w3.org/2001/XMLSchema-instance">
&lt;a:BusinessUnit>
  &lt;a:businessUnitCode>SGS&lt;/a:businessUnitCode>
  &lt;a:longName>Singapore Global Sourcing&lt;/a:longName>
  &lt;a:parentBusinessUnitCode>CGS&lt;/a:parentBusinessUnitCode>
&lt;/a:BusinessUnit>
&lt;a:BusinessUnit>
  &lt;a:businessUnitCode>EGH&lt;/a:businessUnitCode>
  &lt;a:longName>EMS Global HQ&lt;/a:longName>
  &lt;a:parentBusinessUnitCode xsi:nil="true"/>
&lt;/a:BusinessUnit>
</code></pre>
```

<p></p>

<p>XML2:</p>

```
<pre><code>&lt;Get_ProductFamily xmlns:aa="http://example.com/ns2">
&lt;aa:ProductFamily>
  &lt;aa:integrationId>2323&lt;/aa:integrationId>
  &lt;aa:parentBusinessUnitCode>EGH&lt;/aa:
parentBusinessUnitCode>
&lt;/aa:ProductFamily>
&lt;aa:ProductFamily>
  &lt;aa:integrationId>3434&lt;/aa:integrationId>
  &lt;aa:parentBusinessUnitCode>CGS&lt;/aa:
parentBusinessUnitCode>
&lt;/aa:ProductFamily>
&lt;aa:ProductFamily>
  &lt;aa:integrationId>4545&lt;/aa:integrationId>
  &lt;aa:parentBusinessUnitCode>CDD&lt;/aa:
parentBusinessUnitCode>
&lt;/aa:ProductFamily>
&lt;/Get_ProductFamily>
</code></pre>
```

I am working on a highcharts stacked column with column drilldown graph. I based what I am doing in this example: <http://jsfiddle.net/NULTY/753/>

```
var chart;
$(document).ready(function() {

var colors = Highcharts.getOptions().colors,
    categories = ['MSIE', 'Firefox', 'Chrome', 'Safari', 'Opera'],
    name = 'Browser brands',
    level = 0,
    data = [{
        y: 55.11,
        color: colors[0],
        drilldown: {
            type: 'pie',
            name: 'MSIE versions',
            categories: ['MSIE 8.0', 'MSIE 6.0', 'MSIE 7.0', 'MSIE 9.0'],
            level: 1,
            data: [11,10.85, 7.35, 2.41],
            color: colors[0]
        }
    }, {
        y: 21.63,
        color: colors[1],
        drilldown: {
            type: 'pie',
            name: 'Firefox versions',
            categories: ['Firefox 3.6', 'Firefox 4.0', 'Firefox 3.5', 'Firefox 3.0', 'Firefox 2.0'],
            data: [13.52, 5.43, 1.58, 0.83, 0.20],
            color: colors[1]
        }
    }, {
        y: 11.94,
        color: colors[2],
        drilldown: {
            type: 'pie',
            name: 'Chrome versions',
            categories: ['Chrome 10.0', 'Chrome 11.0', 'Chrome 8.0', 'Chrome 9.0', 'Chrome 12.0', 'Chrome 7.0', 'Chrome 6.0', 'Chrome 5.0', 'Chrome 4.0', 'Chrome 3.0', 'Chrome 2.0', 'Chrome 1.0']
        }
    }
    ],
    chart = new Highcharts.Chart({
        chart: {
            type: 'column',
            height: 400
        },
        title: {
            text: 'Browser brands'
        },
        xAxis: {
            categories: categories,
            type: 'category'
        },
        yAxis: {
            title: 'Percentage'
        },
        series: data
    })
});
```

I get the following error compiling my new universal app for Windows Phone and Desktop version 8.1:

```
The SDK "MSAdvertisingXaml, Version=8.1" cannot be referenced alongside SDK(s) "MSAdvertisingXaml, Version=6.1", as they all belong to the same SDK product Family "Microsoft.Advertising". Please consider removing references to other SDKs of the same product family.
```

They both use the same tool, AdControl, and it was running fine while I built the Windows Phone side of the app. Once I dropped the same control into the Windows Desktop side of the app, I get this error. I can't get ANYTHING to return when I Google the error message. What is the problem???

25649947

Windows 8.1 AdControl for Universal Apps (Phone and Desktop)

I'm processing a data.frame of products called "`all`" whose first variable `all$V1` is a product family. There are several rows per product family, i.e. `length(levels(all$V1))` < `length(all$V1)`.

I want to traverse the data.frame and process by product family "`p`". I'm new to R, so I haven't fully grasped when I can do something vectorially, or when to loop. At the moment, I can traverse and get subsets by:

```
for (i in levels (all$V1)){
  p = all[which(all[, 'V1'] == i), ];
  calculateStuff(p);
}
```

Is this the way to do this, or is there a groovy vectorial way of doing this with `apply` or something? There are only a few thousand rows, so performance gain is probably negligible, but I'd like to develop good habits for larger data sets.

26163209

R - traverse data.frame levels in loop or vectorially?

<p>I've got a page with 3 GridViews.</p>

```
<pre><code>&lt;div id="Export" runat="server" class="headeropt noprint"&gt;
```

```
    &lt;asp:LinkButton runat="server" ID="buttonexport" OnClick="
buttonexport_Click" OnClientClick="Javascript:Noshow();" CssClass="btn btn-
default"&gt;
```

```
    &lt;asp:Image runat="server" ImageUrl="/images/Excel-16.gif" /&gt;
```

```
    &lt;asp:Label runat="server" Text="Export" /&gt;
```

```
    &lt;/asp:LinkButton&gt;
```

```
    &lt;/div&gt;
```

```
&lt;div class="col-md-12"&gt;
```

```
    &lt;asp:GridView ID="grid1" runat="server" CellPadding="0" CssClass="
table" CellSpacing="0" OnRowDataBound="grid1_RowDataBound"
AutoGenerateColumns="false" GridLines="Vertical" BorderStyle="Solid"
ShowFooter="true" OnRowEditing="grid1_RowEditing" datakeynames="grid1"
&gt;
```

```
    &lt;Columns&gt;
```

```
        &lt;asp:TemplateField HeaderText="Name"&gt;
```

```
            &lt;ItemTemplate&gt;
```

```
                &lt;asp:LinkButton ID="Inkname" runat="server"
```

```
CausesValidation="false" CommandName="Edit" CommandArgument='&lt;##
Eval("name") %&gt;' Text='&lt;## Eval("name") %&gt;';&lt;/asp:
```

```
LinkButton&gt;
```

```
            &lt;/ItemTemplate&gt;
```

```
        &lt;/asp:TemplateField&gt;
```

```
        &lt;asp:TemplateField HeaderText="Company"&gt;
```

```
            &lt;ItemTemplate&gt;
```

```
                &lt;asp:Label ID="Label2" runat="server" Text='&lt;## Eval
("company") %&gt;';&lt;/asp:Label&gt;
```

```
            &lt;/ItemTemplate&gt;
```

```
            &lt;ItemStyle CssClass="alinha-direita" /&gt;
```

```
            &lt;FooterStyle CssClass="alinha-direita" /&gt;
```

```
        &lt;/asp:TemplateField&gt;
```

```
    &lt;/Columns&gt;
```

```
    &lt;/asp:GridView&gt;
```

```
    &lt;asp:GridView ID="grid2" runat="server" CellPadding="0" CssClass="
table" CellSpacing="0" OnRowDataBound="grid2_RowDataBound"
AutoGenerateColumns="false" GridLines="Vertical" BorderStyle="Solid"
ShowFooter="true" OnRowEditing="grid2_RowEditing" datakeynames="grid2"
```


<p>I know that SandDisk Micro SD cards have bad block detection and re-mapping capability. The default mode for an SD card is the 4 bit SD interface. When using the SPI interface does anyone know if the SD card will still do this automatic bad block detection and re-mapping? Based on my reading the SanDisk OEM Product Manual</p>

<p>"The SPI Mode is a secondary communication protocol for cards in the SanDisk microSD Card Product Family. This mode is a subset of the SD Protocol, designed to communicate with an SPI channel, commonly found in Motorola and other vendors' microcontrollers. Detailed information about SPI Mode can be found in Section 7 or the SDA Physical Layer Specification, Version 3.01."</p>

<p>This does not seem to clarify my doubt. Does anyone know the answer?</p>

26984152

Bad block detection in SD card using SPI interface?

I'm building a shopping cart. In my shopping cart an item can be composed of other items. I need to display a set of items with their corresponding associated parts in a single template. I know how to show a single item with its corresponding parts in a template, but I can't seem to figure out how to show more than one item, each with its own list of included parts.

I have fiddled with every permutation of tags in the template file:

```
# checkout.html
```

```
{% for item in cart_items %}
    <tr>
        <td class="left">
            {{ item.name }}
            <ul>
                {% for part in item.product.buildpart.part_set.all %}
                    <li>{{ part.name }}
                {% endfor %}
            </ul>

        </td>
        <td>${{ item.price }}</td>
        <td>{{ item.quantity }}</td>
        <td class="right">${{ item.lineItemTotal }}</td>
    </tr>
{% endfor %}
</code></pre>
```

Here is the view that generates the template:

```
# views.py
```

```
def checkout(request):
    cart_items = get_cart_items(request)

    <snip>

    return render(request, 'checkout.html', locals())
</code></pre>
```

And here's the `get_cart_items()` function that returns all the items in the

<p>I modified the Product entity form for a particular CRM environment in 2015. However, I don't see a + sign to add Bundle Products to it.</p>

<p>However, in my trial environment, I'm easily able to do so.</p>

<p>Not sure what went wrong. I checked for both Draft bundle and Active Bundle.</p>

<p>PS: I'm not using Product Family.</p>

28046951

Can't add Bundle Products to a created Bundle in CRM

<p>I am in desperate need of help. I have been stuck on this problem for days now and have been looking all over the internet, you are my last hope.</p>

<p>I've been trying to create a Windows Installer using WIX and all seems well until I try to customize the standard UI's (minimal to be specific).</p>

<p>I am trying to create a custom dialog that will go into the Minimal UI set that will allow the user to choose to different kinds of install - this seems to be an impossible task.</p>

<p>When I do attempt the customization the compile brings an error. Please help.</p>

<p>Product.wxs</p>

```
<pre><code>&lt;?xml version="1.0" encoding="UTF-8"?&gt;
```

```
&lt;Wix xmlns="http://schemas.microsoft.com/wix/2006/wi"
    xmlns:util="http://schemas.microsoft.com/wix/UtilExtension"&gt;
```

```
&lt;?define vendor="Vendor" ?&gt;
&lt;?define productName="Product Name" ?&gt;
&lt;?define vendorAndProductName="$ (var.vendor) $ (var.productName)" ?&gt;
```

```
&lt;!--
The language 1033 and codepage 1252 refer to 'English, US'
See:
http://msdn.microsoft.com/library/default.asp?url=/library/en-us/msi/setup/localizing\_the\_error\_and\_actiontext\_tables.asp
--&gt;
```

```
&lt;Product Id="*"
    Name="$ (var.vendorAndProductName)"
    Language="1033"
    Codepage="1252"
    Version="$ (var.version)"
    Manufacturer="$ (var.vendor)"
    UpgradeCode="c338cb1c-8a1d-44e4-9aff-b2ad82f095fb"&gt;
&lt;!--GUID defines product family, installed newer product versions
in the same family will replace older versions--&gt;
```

I am currently programming a CPLEX/OPL model using IBM ILOG CPLEX Optimization Studio.

I have a problem with using sums or indexes which contain a subset and depend on another parameter/variable, e.g. check the following constraints: NB 2,3,4,8).

Can anyone help me with incorporating these constraints properly?

Please find the source code attached:

```
//Parameter
```

```
int maxblock=...;      //number of blocks (I)
int maxprodfam=...;    //number of product families (J)
int maxprod=...;       //number of products (P)
int maxdemand=...;     //number of demand elements (K)
```

```
range blocks=1..maxblock;
range prodfam=1..maxprodfam;
range products=1..maxprod;
range demandelements=1..maxdemand;
```

```
int startalpha[blocks]=...; //earliest start time of block i
int endalpha[blocks]=...;   //latest completion time of block i
int prodtime[products]=...; //unit production time for product p (a)
int minorsetup[products]=...; //minor setup time per sub-lot of product p (s)
int majorsetup[prodfam]=...; //major setup time for product family j (S)
int demand[products]=...;   //demand elements (d)
```

```
//Variablen
```

```
dvar int+ x[blocks][demandelements]; //quantity of demand element k satisfied
from production in block i (x)
dvar boolean y[blocks][prodfam];      //product family assessment to blocks (y)
dvar boolean q[blocks][products];     //product assessment to blocks
dvar boolean o[blocks];               //activation of blocks (e.g. if a prodfam is assigned
to it)
dvar int+ alpha[blocks];               //start time block
dvar int+ duration[blocks];           //duration of block
```

```
//Modell
```

<p>I have a excel as below:

</p>

<p>For each Sales level3 we have a set of "product family" and a set of "country", now I wish to get a output as:</p>

<p></p>

<p>Each country to have all product families against it. Tried with Vlookup/Index/Match, however I was not able to get the desired output, I would need the output for all countries and sales level3</p>

30451273

Creating a table in excel based on column values

<p>I'm using XCTU to test sending packets. My xbee radio is configured as a Coordinator API-2 (product family XB24-ZB, firmware version 21A7, MAC address 0013A20040BCE8CB). I'm send the following transmit request frame bytes:</p>

<blockquote>
<p>7E 00 12 10 01 00 00 00 00 00 00 00 FF FE 00 00 01 02 03 04 E7</p>
</blockquote>

<p>The receive packet frame has the following bytes in the frame detail panel:
</p>

<blockquote>
<p>7E 00 10 90 00 7D 33 A2 00 40 BC E8 CB 00 00 01 01 02 03 04 00</p>
</blockquote>

<p>My problem are the bytes in bold text (the sender's 64 bit address).</p>

<p>The correct bytes, as I understand it, should be:</p>

<blockquote>
<p>00 13 A2 00 40 BC E8 CB</p>
</blockquote>

<p>The checksum for the bytes as I receive them are wrong (0x9C).</p>

<p>However, if I substitute the correct bytes (i.e., I replace 00 7D 33 with 00 13, the checksum value is correct (0xFF).
</p>

<p>I see this behavior in my Arduino code as well. I thought it was me, but I get the exact same behavior there (and in a C# project as well) as I get in the XCTU application. (Specifically, the 64 bit address always has 00 7D 33 where I'm expecting 00 13. What am I missing?</p>

<p>Thanx</p>

<p>I have a C# .Net collection of solutions which started as a proof of concept, and has grown to almost 15 different projects. I am currently in the process of rewriting the whole product family, and trying to maintain best practices to the best of my abilities, with future-proof organisation. </p>

<p>I have done some research, and I am still unclear on the best place to keep delegates in a multi-project product to minimise the likelihood of a need for refactoring in the future. </p>

<p>I would assume the general consensus is that you place them anywhere that makes sense for the use case, but in general I feel there is a best way to structure everything in a solution to minimise problems, promote positive modularity, and ease maintenance. </p>

<p>In many cases it is recommended that they travel with where they are used; presumably declared in the namespace above the class file, which in my case would translate to my common library with the common interfaces which mandate the events. I currently have delegates in their own file, in a 'delegate' namespace. Is there an oversight I am making by doing so, or am I overcomplicating the use case for delegates - or is this inline with current usage expectations?</p>

<p>I have done the typical searches, but haven't found anything credible nor substantial; however this could be a consequence of poor keyword selection. </p>

30587714

Where to put Delgates in .Net Solution

I need to limit the choices in a Django Admin form but cannot come up with a solution. Given these models:

```
class ProductFamily(models.Model):
    name = models.CharField(max_length=250)
    default_product_to_display = models.OneToOneField('Product',
limit_choices_to={'product_family': ???})
    # Enclosing Product reference in quotes is necessary since the Product
    declaration is below ProductFamily declaration

class Product(models.Model):
    name = models.CharField(max_length=250)
    image = models.ImageField(upload_to='images/', blank=True, null=True)
    product_family = models.ForeignKey(ProductFamily)

```

What should be placed in the ???'s in class ProductFamily? I've tried everything I can think of including name, 'name' ProductFamily, 'Product Family', self, self.id. The options with self return an Internal Server Error. The quoted options return: 'invalid literal for int()'. When "name" is used unquoted, it returns:

int() argument must be a string or a number, not 'CharField'.
If I put a hard-coded integer value in to test it, then it works fine, so it is obviously looking for an integer value.
I also tried, without success, placing both
id = models.AutoField(primary_key=True)
in the declaration with id at the ???'s as well as defining a function that returns self.id, but none of this works.

So - how do I limit the selection of products by showing only those whose product_family id's match those of the current ProductFamily?

30689964

How to fill value in a limit_choices_to option in OneToOr

<p>This program takes input from user product name, product class and product family and then stores it into a file. But after giving inputs and pressing enter program crashes saying product.exe has stopped working.</p>

<p>Here's the code-</p>

```
<pre><code>#include &lt;stdio.h&gt;
#include &lt;conio.h&gt;
```

```
void add_new_product(void);
struct product
{
    char P_name;
    char P_class;
    char P_family;
}P[100];
FILE *fp;
void add_new_product()
{
    char ch;
    int i=0;
    fp=fopen("product.txt","w+");
    do
    {
        clrscr();
        printf("\t\t\t Add New Product");
        printf("\n User:");
        printf("\n\n \t\t\t 1.Product Name  :");
        printf("\n\n \t\t\t 2.Product Class  :");
        printf("\n\n \t\t\t 3.Product Family :");
        gotoxy(44,5);
        scanf("%s",&P[i].P_name);
        gotoxy(44,7);
        scanf("%s",&P[i].P_class);
        gotoxy(44,9);
        scanf("%s",&P[i].P_family);
        fprintf(fp,"%s %s %s %s %s %s",P[i].P_family,"|",P[i].P_class,"|",P[i].
P_name,"");
        printf("\n \t\t\t Do you want to add another product?(Y/N) :");
        scanf("%s",&ch);
        i++;
    } while (ch=='Y' || ch=='y');
```

<p>I've a table with documents in the format of </p>

```
<pre><code>{
  "_id" : ObjectId("55867f3bfe2b0bea9c634ded"),
  "Best Site CR GU Party ID" : 14783,
  "Best Site CR GU Party Name" : "AUTOMOBILE INSURANCE COMPANY",
  "Product ID" : "C5500",
  "Product Family" : "C5000",
  "Product Description" : "5500 Chassis",
  "Best Site CR Party ID" : 45714558,
  "Best Site CR Party Name" : "INSURANCE COMPANY",
  "LDoS" : "4/27/2008",
  "LDoS FY" : 2008,
  "List Price $" : 3495,
  "Collector View" : "No"
}
</code></pre>
```

<p>and I'm using mongodb java driver 3.0.2. The intention is to aggregate the prices and number of documents for each month of every year in the collection. I've created the following function for map, which works on MongoVUE and fails with the java driver:</p>

```
<pre><code>function Map() {
  var currentYr = new Date().getFullYear();
  var ldoMonth = this['LDoS'].split(/[/-]/)[0].replace(/^0+/, '');
  var key = {partyId: this['Best Site CR GU Party ID'], year: this['LDoS FY'], month:
parseInt(ldoMonth)};

  emit(key, {price: this['List Price $'], count: 1});
}</pre>
```

Exception in thread "main" com.mongodb.MongoCommandException: Command failed with error 16722: 'exception: TypeError: Object 42582 has no method 'split'

at Map (_funcs1:1:99) near '['LDoS'].split(/[/-]/)[0].replace(/^0+/' ' on server localhost:27017. The full response is { "errmsg" : "exception: TypeError: Object 42582 has no method 'split'\n at Map (_funcs1:1:99) near '['LDoS'].split(/[/-]/)[0].replace(/^0+/' ", "code" : 16722, "ok" : 0.0 }

at com.mongodb.connection.ProtocolHelper.getCommandFailureException (ProtocolHelper.java:77)

<p>First of all sorry as I may sound quite stupid while asking this.</p>

<p>I want to understand the practical usage of abstract design pattern. Which all APIs have implemented this pattern and under what all use case. </p>

<p>One of the use case which strikes me immediately is the DI of objects which need to be created using run time information.</p>

<p>I have the understanding that this pattern is used to create object of various product families. But for every new product family we have to change the existing factories. Also if there is an addition implementation of any product family we have to provide a new factory for this new implementation.</p>

<p>For example </p>

<p>I have products Frame and TextBox for two types of OS (Windows and MAC). Now we will have two factories one for each Window and Mac so that WindowFactory returns textbox and frame for Windows and MacFactory return the same objects for MAC. Now say I want to add another OS say Solar then in this case I need to write a new factory which returns the corresponding objects for solar.</p>

<p>How API use this patterns in real world?</p>

31569817

Abstract Factory method practice or usage of abstract fa

<p>I'm trying to build a code that will filter a table by product type, of which there might be multiple items. I need the table to filter through each of the product types to build a hierarchy for each product family.</p>

<p>I'm thinking it should be something like:</p>

```
<pre><code>Sub familyfilter()
```

```
With ActiveSheet.ListObjects(1)
```

```
For Each Item In .Columns(1)
```

```
.AutoFilter.ShowAllData
```

```
.Columns(1).autofilterrange.AutoFilter Field:=3, Criteria1:=Item
```

```
'[insert sub call here for hierarchy]
```

```
Next Item
```

```
End With
```

```
End Sub
```

```
</code></pre>
```

<p>I won't know the values in the family column, so I can't set a list of values to cycle through.</p>

<p>So if anyone knows how to do this for all the items in the column, I'd appreciate it!!</p>

<p>Thanks</p>

31748777

Loop filters for all items in table column of excel

I want to create a new variant group in Akeneo with some fixed attributes to "simulate" the behaviour of a product family. Unfortunately I don't know how to get a `ProductTemplate` with some attributes with empty values.

When I tried my code below, I get an error after opening the created variant group in the Akeneo GUI:

```
Error: Option "attributes" must only contains instances of
"Pim\Bundle\CatalogBundle\Entity\Attribute", got
"Pim\Bundle\EnrichBundle\Form\Type\AvailableAttributesType"
```

My code looks like this:

```
<code> $groupType = $this->groupManager
    ->getGroupTypeRepository()
    ->findOneBy(['code' => 'VARIANT']);
    $group = $this->groupFactory->createGroup($groupType);
    $group->setCode('MY_VARIANT_GROUP');

    $attributes = array($this->attributeRepository->findOneByIdentifier
('AXIS_ATTRIBUTE'));
    $group->setAxisAttributes($attributes);

    // ??? How can I create a new product value?
    $productValue1 = new ProductValue();
    $productValue1->setId('PREDEFINED_ATTRIBUTE1');
    $productValue1->setAttribute($this->attributeRepository->
findOneByIdentifier('PREDEFINED_ATTRIBUTE1'));

    $productTemplate = new ProductTemplate();
    $productTemplate->setValuesData(array($productValue1));

    $group->setProductTemplate($productTemplate);
    $this->groupSaver->save($group);
</code>
```

<p>Following is the code which i am trying to search WT part </p>

```
<pre><code>public static WtSet searchWtPart(String partNumber, String type,
boolean exactMatch ,String productfamilyforjsp,String ordertypeformjsp) throws
WtException {
```

```
    System.out.println("Method partNumber "+partNumber);
    long branchId = 0;
    int iPartMaster, iPart;
    String criteria;
    QueryResult qr = null;
```

```

    //wt.pds.PartialResultException qr1 = new PartialResultException(arg0);
    QuerySpec qs= new QuerySpec();
    iPartMaster = qs.addClassList(WtPartMaster.class,true);
```

```
    int defindex = qs.addClassList(StringDefinition.class, false);
    int valueindex = qs.addClassList(StringValue.class, false);
```

```

    // search product Family as per jsp product family Input
```

```
    if(productfamilyforjsp.equalsIgnoreCase("Helical/Emill"))
    {
        productfamilyforjsp="Helical";
    }
```

```
    if(productfamilyforjsp.equalsIgnoreCase("Fluid Coupling"))
    {
        productfamilyforjsp="Fluid Coupling";
    }
```

```
    if(productfamilyforjsp.equalsIgnoreCase("Worm/Altra"))
    {
        productfamilyforjsp="Worm";
    }
```

```
    if(productfamilyforjsp.equalsIgnoreCase("Gear Motor"))
    {
        productfamilyforjsp="Geared motor";
    }
}
```

I have a `GridView` control, and inside of this control I have defined a link button using `GridView.ItemTemplate`.

I am using this to open a new window on click. When I click on the link button, however, the page refreshes before opening the new window.

How can I stop the page from refreshing after the link button is clicked?

HTML

```
<pre><code>    <asp:UpdatePanel ID="UpdatePanel4" runat="server">
        <ContentTemplate>

            <asp:GridView ID="DataGrid1" style="visibility:visible"
runat="server" AlternatingRowStyle-BackColor="#E9EDF5" Font-Names="Arial"
                ForeColor="#09538A" Font-Size="12px" BackColor="#ffffff"
BorderColor="DarkGray" Font-Bold="true"
                HeaderStyle-BackColor="#298DC7" EnableViewState="
false" CellSpacing="20"
                CellPadding="10" HeaderStyle-Font-Bold="true"
AutoGenerateColumns="False" OnRowCommand="DataGrid1__RowCommand"
OnRowDataBound="DataGrid1__RowDataBound" >
                <HeaderStyle Font-Names="Arial;" CssClass="
MyHeaderStyle" Font-Size="13px" ForeColor="White" Font-Bold="True" Height="
20" BackColor="#298DC7" ></HeaderStyle>
                <asp:templatefield headertext="NDC" ItemStyle-CssClass="col" ItemStyle-
HorizontalAlign="Justify" HeaderStyle-Width="10%" ItemStyle-Width="10%">
                <Columns>
                    <itemtemplate>
                        <asp:linkbutton id="productcode" ForeColor="#09538A" runat="
server" text='&lt;%=Eval("product code")%>'></asp:linkbutton>

                    </itemtemplate>
                </asp:templatefield>
            </asp:GridView>
        </ContentTemplate>
    </asp:UpdatePanel>

    <AjaxToolkit:ModalPopupExtender ID="
ModalPopupExtender1" BackgroundCssClass="modalBackground"
    </code></pre>
```


I have a `GridView` control, and inside of this control I have defined a link button using `GridView.ItemTemplate`.

I am using this to open a new window on click. When I click on the link button, however, the page refreshes before opening the new window.

How can I stop the page from refreshing after the link button is clicked?

Pop up is not displaying when i add Update panel to first grid

if i remove Update panel from first grid, grid is refreshing and popup is displaying

I need to open a popup without refreshing my grid

PLEASE FIND ME THE SOLUTION FOR THIS AS I WAS WORKING ON THIS FROM PAST 2 DAYS

HTML

```
<code>&lt;%@ Page Language="c#" AutoEventWireup="false" CodeFile="ViewData1.aspx.cs" Inherits="ablesas.ViewDataUI1" EnableEventValidation="false"%>
```

```
&lt;asp:UpdatePanel ID="UpdatePanel4" runat="server"&gt;
    &lt;ContentTemplate&gt;
```

```
        &lt;asp:GridView ID="DataGrid1" style="visibility:visible"
runat="server" AlternatingRowStyle-BackColor="#E9EDF5" Font-Names="Arial"
        ForeColor="#09538A" Font-Size="12px" BackColor="
#ffffff" BorderColor="DarkGray" Font-Bold="true"
        HeaderStyle-BackColor="#298DC7" EnableViewState="
false" CellSpacing="20"
        CellPadding="10" HeaderStyle-Font-Bold="true"
AutoGenerateColumns="False" OnRowCommand="DataGrid1__RowCommand"
OnRowDataBound="DataGrid1__RowDataBound" &gt;
        &lt;HeaderStyle Font-Names="Arial;" CssClass="
MyHeaderStyle" Font-Size="13px" ForeColor="White" Font-Bold="True" Height="
20" BackColor="#298DC7" &gt;&lt;/HeaderStyle&gt;
        &lt;asp:templatefield headertext="NDC" ItemStyle-CssClass="col" ItemStyle-
```

I have a `GridView` control, and inside of this control I have defined a link button using `GridView.ItemTemplate`.

I am using this to open a new window on click. When I click on the link button, however, the page refreshes before opening the new window.

How can I stop the page from refreshing after the link button is clicked?

Pop up is not displaying when i add Update panel to first grid

if i remove Update panel from first grid, grid is refreshing and popup is displaying

I need to open a popup without refreshing my grid

PLEASE FIND ME THE SOLUTION FOR THIS AS I WAS WORKING ON THIS FROM PAST 2 DAYS

HTML

```
<code>&lt;%@ Page Language="c#" AutoEventWireup="false" CodeFile="ViewData1.aspx.cs" Inherits="ablesas.ViewDataUI1" EnableEventValidation="false"%>
```

```
&lt;asp:UpdatePanel ID="UpdatePanel4" runat="server"&gt;
    &lt;ContentTemplate&gt;
```

```
        &lt;asp:GridView ID="DataGrid1" style="visibility:visible"
runat="server" AlternatingRowStyle-BackColor="#E9EDF5" Font-Names="Arial"
        ForeColor="#09538A" Font-Size="12px" BackColor="
#ffffff" BorderColor="DarkGray" Font-Bold="true"
        HeaderStyle-BackColor="#298DC7" EnableViewState="
false" CellSpacing="20"
        CellPadding="10" HeaderStyle-Font-Bold="true"
AutoGenerateColumns="False" OnRowCommand="DataGrid1__RowCommand"
OnRowDataBound="DataGrid1__RowDataBound" &gt;
        &lt;HeaderStyle Font-Names="Arial;" CssClass="
MyHeaderStyle" Font-Size="13px" ForeColor="White" Font-Bold="True" Height="
20" BackColor="#298DC7" &gt;&lt;/HeaderStyle&gt;
        &lt;asp:templatefield headertext="NDC" ItemStyle-CssClass="col" ItemStyle-
```

<p>I'm working with our IT group to develop an optimizer for logistics operations. The basic design is that it will look at shipments, run a search for additional shipments originating within XX miles of the previous shipments destination, and link them together in a loop. It will continue to do this until it hits a user defined set of shipment legs where the loop ends at or close to 1st shipment origin.</p>

<p>The issue we are facing is that the materials we ship are chemicals, which can have interactions if placed in a tank that contained XX chemical before it. The obvious solution is to use a different tank or wash it out, but we also need it to compute solutions prior to that.</p>

<p>My problem is, currently, there is no way on the market to do that prior product optimization. </p>

<p>The question is: Is there some kind of logic table function I can write that will allow the optimizer to see an element in the data set (say, Product Family of 1) that will pull from a product database containing predefined product families (i.e. PF 1 = Chemicals A1-B7, PF 2 = Chemical B8-J8, etc.) and then ping off of a logic table that defines a do not ship with list (i.e. PF 1 cannot ship if PF 2 was on the previous leg.</p>

33001749

Using an element in a data set to drive If/Then logic deci

<p>tnis is a long function but the key problem is in the char* variables..
**the function was working fine before i have trasformed it to store the data
instead of print to console.</p>

<p>i have tried to use <code>char[]</code> instead of <code>char*</code>
that's when i got some buffer overrun error, so now as it is allocated, it shows
??? all over the console.
what is the correct way to concat and use <code>char*</code> on <code>puts();
</code></p>

```
<pre><code>MySystemInfo Msi;  
puts(Msi.getOsInfo());
```

```
char* MySystemInfo::getOsInfo()  
{  
    OSVERSIONINFOEX osver;  
    BOOL bOsVersionInfoEx;  
    HKEY hKey;  
    LONG lRet;  
    char* RtTmpOsInfo= (char *) malloc(sizeof(char)*70);  
    char* s1=(char *) malloc(sizeof(char)*20);  
    char* s2=(char *) malloc(sizeof(char)*50);  
  
    // Try calling GetVersionEx() using the OSVERSIONINFOEX structure.  
    // If that fails, try using the OSVERSIONINFO structure.  
    ZeroMemory(&osver, sizeof(OSVERSIONINFOEX));  
    osver.dwOSVersionInfoSize = sizeof(OSVERSIONINFOEX);  
    if(!bOsVersionInfoEx = GetVersionEx((OSVERSIONINFO *) &osver))  
    {  
        osver.dwOSVersionInfoSize = sizeof(OSVERSIONINFO);  
        if(!GetVersionEx((OSVERSIONINFO *) &osver))  
            return "";  
    }  
  
    switch (osver.dwPlatformId)  
    {  
        //Test for the Windows NT product family.  
        case VER_PLATFORM_WIN32_NT:
```

<p>I have controller actions which have AuthorizeAttribute on them</p>

<p>Often someone will try an old url which will take them (forms authentication) to the logon page and then redirect to the url, but it may be for whatever reason that they are no longer allowed to access to that page</p>

<p>Is there any way of testing the url before redirecting?</p>

<p>I can decompose the url into the area/controller/action and test it but it feels clumsy to do that</p>

<p>(Extra info)</p>

<p>Our site is part of a product family, in the desktop app we can determine who has access to what parts. e.g. we may have a clocking page, a user accesses it and keeps the url. In the main product we remove their access to this page, the authorizeattribute now says they don't have access to it.</p>

<p>So we get</p>

<p>they try to access the url</p>

<p>forms authentication says they don't have access and reroutes to the logon page</p>

they logon, however they still don't have access to this page and they are redirected again to the logon page.

33367382

AuthorizeAttribute, anyway of checking in advance if thi:

<p>I have a created a macro for my spreadsheet which can sent out emails successfully. </p>

<p>However, it can only send e-mails of each individual part numbers which are over the due date. Which means if I have 100 over the due date part numbers, there will be 100 emails being sent out.</p>

<p>I would like my macro to send the email by a range of cells which are of similar product (eg. printer) and are over the due date. There can be other products like laptop, camera, webcam as well. I need to do this as i don't want to spam the receiver's inbox.</p>

<p>How do I do that?</p>

```
<pre><code>Sub LabelArtworkRelease()
```

```
    Dim OutApp As Object
    Dim Message1 As Object
    Dim cell As Range
    Dim emailBody As String
    Dim Signature As String
```

```
    'GET DEFAULT EMAIL SIGNATURE
```

```
    Signature = Environ("appdata") & "& "\Microsoft\Signatures\"
```

```
    If Dir(Signature, vbDirectory) <& vbNullString Then
```

```
        Signature = Signature & Dir$(Signature & "*.htm")
```

```
    Else:
```

```
        Signature = ""
```

```
    End If
```

```
    Signature = CreateObject("Scripting.FileSystemObject").GetFile(Signature).
```

```
    OpenAsTextStream(1, -2).ReadAll
```

```
    'End
```

```
    Application.ScreenUpdating = False
```

```
    'Create a new Outlook session
```

```
    Set appOutlook = CreateObject("Outlook.Application")
```

```
    On Error GoTo cleanup
```

```
    'Declare header variables
```

<p>Product family: XBP24-ZB
Function set: ZigBee Coordinator API
Firmware version: 21A7</p>

<p>Hello, I am currently using Digi's XBee Java Library with API (AP=1) and it works properly.

However, another node of my network is associated with an Arduino and I want to use 'Arduino Library for communicating with XBee in API mode' (https://github.com/andrewrapp/xbee-arduino).

That Arduino Library requires API Escaped operating mode (API 2). It was not supposed to be a problem, since XBee Java Library supports API 2. Nevertheless, I got an error when trying to open the serial connection with the XBee.</p>

<pre><code>package com.digi.xbee.example;

import com.digi.xbee.api.XBeeDevice;
import com.digi.xbee.api.exceptions.XBeeException;

```
public class MainApp {  
    /* Constants */  
    // TODO Replace with the port where your sender module is connected to.  
    private static final String PORT = "COM4";  
    // TODO Replace with the baud rate of your sender module.  
    private static final int BAUD_RATE = 9600;  
  
    private static final String DATA_TO_SEND = "Hello XBee World!";  
  
    public static void main(String[] args) {  
        XBeeDevice myDevice = new XBeeDevice(PORT, BAUD_RATE);  
        byte[] dataToSend = DATA_TO_SEND.getBytes();  
  
        try {  
            myDevice.open();  
  
            System.out.format("Sending broadcast data: '%s'", new String  
(dataToSend));  
  
            myDevice.sendBroadcastData(dataToSend);  
  
            System.out.println(" &gt;&gt; Success");  
        }  
    }  
}
```

I know `PowerPivot` is not programming, but I wanted to see if I could get help or a recommendation on how to get the total rows to correctly calculate the sum of Absolute Values at a higher aggregation level than the detailed data in a `PowerPivot` data model.

Here is my example: This is detailed data format. There are 2 hierarchies:

```
1. Product Group\Product Family\**Material**  '3 columns'
2. Region\**Plant**\SalesMgr\Employee\Customer  '5 columns'
```

Hierarchy represents 8 columns in my data model

All data in the data model is at the lowest level (i.e. Material/Customer). However I want to calculate Forecast Accuracy at Material/Plant Level (a higher aggregation level).

```
DataModel Column9: Sales 'Sales at the detailed
Material/Customer'
DataModel Column10: Forecast 'Forecast at the detailed Material/Customer'
Calculated Column11: AbsoluteError = ABS(Forecast - Sales) 'calcd at Mat/Cust'
```

```
PowerPivot DAX formulas/measures, shortened for simplicity
TotalSales:=SUM(Sales)
TotalAbsError:=SUM(AbsoluteError)
MAPE:= TotalAbsError/TotalSales
ForecastAccuracy:= 1 - MAPE (Mean Absolute Percentage Error)
```

This calculates the data correctly at the Material/Plant level when I create my Pivot Table. However the Total values in the Pivot Table are incorrect.

For example, the Total of AbsError is the Sum of 20 rows of Material/Customer Combinations. I need the Total of only the 5 Material/Plant Combinations. The 20 rows of detailed Material/Customer data aggregates up to only 5 rows of Material/Plant Combinations.

I have a sample spreadsheet I can share. Thanks Dimitry for updating the question!

<p>I am using X-CTU v6.3 in Mac OS X El Capitan with XBee S2C</p>

<p>In XCTU, the device is detected as</p>

<p>Function: ZIGBEE TH Reg</p>

<p>Product Family: XB24C</p>

<p>Firmware version: 4059</p>

<p></p>

<p>How do I configure it as a Coordinator at AT mode?</p>

<p>The update firmware button doesn't show anything beyond the function and product family mentioned above. </p>

<p></p>

<p>What am I missing?</p>

36671556

Xbee S2C setting as a Coordinator AT mode

I want to use columns of the i table in a data.table join for both calculations and for grouping. There appears to be some limitation in the syntax for this. Can you suggest a cleaner way of doing this?

```
require(data.table)
set.seed(1)
```

Table 1

```
DT1 <- data.table(loc = c("L1", "L2"), product = c("P1", "P2", "P3"),
  qty = runif(12))
```

Table 2

```
DT2 <- data.table(product = c("P1", "P2", "P3"), family = c("A", "A", "B"), price = c(5, 7, 10))
```

A straight join on the tables is fine: [not the issue here, but the requirement to use quoted column names in the `on` clause seems to be inconsistent for data.table]

```
DT1[DT2, on = "product"]
#   loc product    qty family price
# 1: L1   P1 0.1297134    A     5
# 2: L2   P1 0.2423550    A     5
# 3: L1   P1 0.3421633    A     5
# 4: L2   P1 0.6537663    A     5
# 5: L2   P2 0.9822407    A     7
# 6: L1   P2 0.8568853    A     7
# 7: L2   P2 0.7062672    A     7
# 8: L1   P2 0.9224086    A     7
# 9: L1   P3 0.8267184    B    10
#10: L2   P3 0.8408788    B    10
#11: L1   P3 0.6212432    B    10
#12: L2   P3 0.5363538    B    10
```

Calculation using columns of both tables is fine:

<p>(my english is not too good)

I need extract in web pages from icecat(I know they have xml files), But I need extract data with php from html.

I try some codes but I not understand how can extract all data, example:

</p>

```
<pre><code>    brand | Product family | product name | short description
```

```
    hp    |    200    |    250 g4    | HP 200 250 G4.....
```

```
        |
```

```
        without: "Short summary description HP 200 250 G4:"
```

```
    .
```

```
    .
```

```
    Category feature | key          | value
```

```
    processor        | processor frequency | 1.9Ghz
```

```
    processor        | processor cores    | 2
```

```
    memory           | Internal memory    | 4Gb
```

```
    memory           | Memory clock speed | 1600Mhz
```

```
    Display          | Display diagonal   | 39.6 cm (15.6")
```

```
    .
```

```
</code></pre>
```

<p>i need put "brand","Product family" etc in db like columns and value in the tuple

For features need 2 columns key and value:

Processor frequency(key), 1.9 GHz(value).

And the problem is each page have something different, for example some pages have more ean or/and more product code and so on.

but in html have something like this in features:
</p>

```
<pre><code>    &lt;div class="table"&gt;
```

```
        &lt;div class="tableRowHead"&gt;
```

```
            &lt;span class="ds_bold_header " title="Processore Apple iPad Pro  
128GB 3G 4G Grigio"&gt;Processore&lt;/span&gt;
```

```
        &lt;/div&gt;
```

```
        &lt;div class="tableRow"&gt;
```

```
            &lt;div class="ds_label"&gt;
```

```
                &lt;span class="tip-anchor tip-anchor-text line 1_text none_float"
```

```
&gt; Famiglia processore&lt;/span&gt;
```

```
            &lt;/div&gt;
```

```
        &lt;div class="ds_data"&gt;
```

<p>I written few lines code..</p>

```
<pre><code>book = xlwt.Workbook()
sheet = book.add_sheet('Section details', cell_overwrite_ok=True)
style_detail = xlwt.easyxf('font: name Calibri, height 180,colour_index black;align:
wrap on, vert center, horiz center; border : bottom thin,right thin,top thin,left
thin;')
sheet.write_merge(0, 0, 0, 0, 'Product Family')
sheet.write_merge(1, 1, 0, 0, 'Product Category')
sheet.write_merge(0, 0, 1, 1, 'Product')
.
.
sheet.write_merge(n, n, n, n, 'Product') //n is just dynamic number..
</code></pre>
```

<p>Now, After completing all my writing work. Want to apply style for specific cells only(depending on requirement).</p>

```
<pre><code>rw = sheet.row(1)
rw.set_style(style_detail)
</code></pre>
```

<p>If i apply style for specific row then it apply for entire row of sheet(for column A to endless columns). How can i apply style for specific cell of any row only?</p>

<p>Please let us know if any more code or info require to get idea.</p>

<p>Thanks in-advance.</p>

37114641

Apply easyxf style for specific cell or row range only: xlw

<p>We have a large product catalog with products grouped under product families.

This is great as we can easily see the products hierarchy.</p>

<p>The problem is that when we create an opportunity it is very difficult to just search for a list of products that fall under one product family.</p>

<p>On the Opportunities form is there a way to modify the Price List Items "Look Up Records" search form to allow the user to filter the price list items by a product family?</p>

<p>Currently the Search form says</p>

```
<pre><code>Look for: Price List Items
Look in: Price List Items in Entity Price List
Search:
</code></pre>
```

<p>Is there a way to add another search field such as Product Family to the filter?</p>

37784151

In Dynamics CRM Online How do I add the Family Hierarchy

I'm doing simple test application to explore Morphia capabilities. At the moment I'm trying to make a simple aggregation query on `SaleStatistics` collection.

The query is Filter by product description and grouping by product family and subFamily and sum quantity and amount.

The issue is that while Morphia was doing a correct replacement of property names on the \$match phase according to the @Property mappings defined in the classes, it wasn't doing the same replacement in the \$group phase. In that case it was using directly the property strings used in the aggregation definition, as you can see in this code snippet from the logging console:

```
2016-06-16 10:09:22 DEBUG AggregationPipelineImpl:36 - stages =
[{"$match": {"Producto.Denominacion": "MAGNA"}}, {"$group": {"_id": {"productFamily": "$product.productFamily", "productSubfamily": "$product.productSubFamily"}, "saleStatisticsQuantity": {"$sum": "$quantity"}, "saleStatisticsAmount": {"$sum": "$amount"}}}]
```

Here is my Entity mapping:

```
@SuppressWarnings("serial")
@Entity(value="EstadisticaDeVentas", noClassnameStored=true)
public class SaleStatistics extends FactTableEntity {

    @Embedded(value="Gasolinera", concreteClass=GasStationEmbedded.class)
    private GasStationEmbedded gasStation;

    @Embedded(value="Producto", concreteClass=ProductEmbedded.class)
    private ProductEmbedded product;

    @Embedded(value="Cliente", concreteClass=ClientEmbedded.class)
    private ClientEmbedded client;

    @Embedded(value="Turno", concreteClass=ShiftEmbedded.class)
    private ShiftEmbedded shift;

    @Embedded(value="Responsable", concreteClass=ResponsibleEmbedded.class)
    private ResponsibleEmbedded responsible;

    @Embedded(value="Isla", concreteClass=IslandEmbedded.class)
```

I'm new to Ruby on Rails and I was working on a catalog website which consists of two frames: the first one contains product families and the second one dynamically shows the list of machines within those families as you click them on the first frame. This happens since form target is that frame's name:

I have already inspected <http://stackoverflow.com/questions/28416002/opening-a-new-tab-in-capybara-poltergeist> but there is an important difference: I want to iteratively click through the product family links in the first frame by working "within_frame ('families_frame')" and get the list of machines in the second frame. However "switch_to_frame" and similar solutions do not work and I get the following error:

```
switch_to_window is not supposed to be invoked from
within's, within_frame's or
within_window's' block. (Capybara::ScopeError)
```

Because my iterator runs from "within_frame". How can I switch to the resulting frame, reach the content and then switch back to the working frame? The HTML structure is:

```
<HTML>
<FRAME NAME="families_frame" SRC="../../../productfamily.jsp">
<FRAME NAME="machines_frame" SRC="../../../blank.jsp">
</HTML>
```

Thank you a lot.

38546028

How to switch to a frame from within another frame in C

<p>Morning all, </p>

<p>We would like to release our app via Apples Ad Hoc distribution. We "can register up to 100 devices per product family per year that your team uses for development and testing." Our developer account is up for renewal on 20th January, but we want to release on 1st September. Does this mean that the app will stop working for testers on 20th January or will it run for 12 months from 1st September? We need it to run for 12 months from the initial release date, is there anything we need to be aware of to ensure this happens?</p>

<p>Huge thanks in anticipation of your help!</p>

38566173

iOS Ad Hoc Distribution - starting 12 months testing peri

<p>I need to show the number of units for a product type in my reports. I'm using a custom formula and this is what I have so far:</p>

<p>IF(ISPICKVAL(Family ,"Specific Product Category"),1,0) * Units_c</p>

<p>the syntax seems to work until I * units_c</p>

38646762

How do I create a custom Salesforce field to show units l

<p>I'm trying to add a column at a specific index based on the content of a different column:</p>

```
<pre><code>df.insert(10, 'Escalation Status', np.where(df['Reasons for escalation'] == '', 'FALSE', 'TRUE'))</code></pre>
```

<p>So, when Column "Reasons for escalation" is empty, write "FALSE", if not, write "TRUE" in the newly created "Escalation Status" column.</p>

<p>My problem: The content is always "TRUE", no matter if there is anything in the "Reasons for escalation" field.</p>

<p>example output:</p>

```
<pre><code>Country,Date,Vendor,Product Family,Case number,Reseller Name, OpeningDate,Closing Date,Case Status,Topic,Escalation Reason,Reasons for escalation
DEU,28.10.2016,VENDOR,,201610281078864,,28.10.2016,28.10.2016,closed, Software issue,TRUE,Software
DEU,28.10.2016,VENDOR,,201610281078862,,28.10.2016,28.10.2016,closed, Config help,TRUE,</code></pre>
```

<p>The first row is correct (Reasons for escalation is not empty, it contains "Software"), but the second row should be "FALSE", as the Reasons for escalation is empty</p>

<p>thanks</p>

40706073

python pandas add column content based on conditiona

I am very new to the single sign-on options available to me. I currently have a requirement to secure multiple application sets within the same product family and have no idea where to start.

Some of the base requirements would be

User should be able to authenticate once, and based on the credentials user would be redirected to the required application

A central management console should be available for administrators to simplify role assignments as well as grant access to the various applications as required

Users can register for certain applications but certain sensitive applications require administrator approval before the user can successfully log in.

This SSO should also secure an API with some sort of permission logic e.g. only supervisor roles can delete a record

Users should be able to register with OAuth providers such as Facebook, Twitter, Google & Windows live.

The SSO provider should be simple to implement into multitude of platforms such as Windows Apps, Web Apps, Mobile & services

I have no idea where to start, I have done a quick read through of something like ADFS https://msdn.microsoft.com/en-us/library/bb897402.aspx, but NO IDEA if this would meet all the listed requirements above.

Any help of pointing me in the right direction would be greatly appreciated!!

40845570

Single Sign-On ASP Identity Securing Multiple application

<p>I'm using Antlr's string template capabilities and am seeing the following error:</p>

```
<pre><code>Antlr4.StringTemplate.Compiler.TemplateException was unhandled
HResult=-2146233088
Message=Exception of type 'Antlr4.StringTemplate.Compiler.
TemplateException' was thrown.
Source=Antlr4.StringTemplate
</code></pre>
```

<p>With the code:</p>

```
<pre><code>class Program
{
    static void Main(string[] args)
    {
        var messageTemplate = "&lt;table style='border-collapse: collapse; width:
100%' dir='ltr' cellspacing='0'&gt;&lt;tr style='background-color: #f8f8f9;
border: thin #e8eae8 solid'&gt;&lt;td style='font-family: Verdana; font-size:
12pt; background-color: #f8f8f9; border: thin #e8eae8 solid; padding: 20px 20px
20px 20px'&gt;&lt;strong style='font-family: Verdana;
font-size: 12pt;'&gt;%VendorName%&lt;/strong&gt;&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;&lt;/td&gt;&lt;/tr&gt;&lt;tr style='background-color: #f8f8f9;
border: thin #e8eae8 solid'&gt;&lt;td style='font-family: Verdana; font-size:
12pt; background-color: #f8f8f9; border: thin #e8eae8 solid; padding: 20px 20px
20px 20px'&gt;&lt;table&gt;&lt;tr&gt;&lt;td style='font-family: Verdana; font-
size: 12pt;'&gt;Order Number: &lt;/td&gt;&lt;td width='2px'&gt;&lt;/td&gt;
&lt;td style='font-family: Verdana; font-size: 12pt;'&gt;%OrderNumber%&lt;
/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td style='font-family: Verdana; font-size: 12pt;
'&gt;State: &lt;/td&gt;&lt;td width='2px'&gt;&lt;/td&gt;&lt;td style='font-
family: Verdana; font-size: 12pt;'&gt;%CustomerAddressState%&lt;/td&gt;&lt;
/tr&gt;&lt;tr&gt;&lt;td style='font-family: Verdana; font-size: 12pt;'&gt;County:
&lt;/td&gt;&lt;td width='2px'&gt;&lt;/td&gt;&lt;td style='font-family:
Verdana; font-size: 12pt;'&gt;%CustomerAddressCounty%&lt;/td&gt;&lt;/tr&gt;
&lt;tr&gt;&lt;td style='font-family: Verdana; font-size: 12pt;'&gt;Municipality:
&lt;/td&gt;&lt;td width='2px'&gt;&lt;/td&gt;&lt;td style='font-family:
Verdana; font-size: 12pt;'&gt;%VendorCity%&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td
style='font-family: Verdana; font-size: 12pt;'&gt;Borrower:&lt;/td&gt;&lt;td
width='2px'&gt;&lt;/td&gt;&lt;td style='font-family: Verdana; font-size: 12pt;
'&gt;%Borrowers%&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td style='font-family:
Verdana; font-size: 12pt;'&gt;Product Family:&lt;/td&gt;&lt;td width='2px'&gt;&lt;
/td&gt;&lt;td style='font-family: Verdana; font-size: 12pt;'&gt;%ProductFamily%
&lt;/td&gt;&lt;/tr&gt;&lt;/table&gt;&lt;/code></pre>
```

<p>I am looking for an data analysis tool that can visualize the data from different sensors in my place. These sensors are all light sensors but from different companies and different product families. I need to compare them and therefore I have to analyze the data that my program stores in text files specified by sensor producer and product family.</p>

<p>Do you have any suggestions?</p>

42032592

Data analysis tool needed

I've created a website for my friends company a few months ago while i was a complete newbie and all the stuff i knew about creating websites i learned on Codecademy. The site is pretty big, it's in 2 languages and has about 25 html pages per language. What Codecademy didn't teach me is the SEO importance of a good website folder structure and SEO friendly links, so now i'm trying to correct my mistakes and i've encountered some problems to which i cannot find a solution to.

So, the problem is i'm using .htaccess to remove the .html extensions from my URL's, so when i write the link in to my html i write it without the .html extension.

I have a products folder with a single index file as the starting products page, and that same folder has a few more folders for each of the product families, and each of those product family folders has an index file + a few more html files for each specific product in that product family.

So when the visitor is on a specific product page the link should look like this:

`www.mywebsite.com/products/product-family-name/product-name`

When i link to a product family from the products page i type in just the product family name without any slashes and it would go to that product family folder and shows the index file from that folder. The problem appears when i try to create a link like shown above, when i try to reach an html file which is in the same folder as the index file from which i'm linking to. It won't work without the .html extension, instead the page is not found.

I type it like this:

`/product-family-name/product-name` (this doesnt work)

`/product-family-name/product-name.html` (this works)

I also tried typing in only the product name, but that doesn't work without the .html either.

I could solve this by just creating a new folder for each specific product inside of the product family folder and name them index, but i don't know if that is a good practice, coz it doesn't seem like it is. I just want to know if there is another

<p>I need some help doing the following. I have a file in which column M is a measure. For the exercise, Column M - Measure "Forecast, appears every 17 lines under a product.

From columns N -> CG would be that forecast over a long period of time driven by a formula.</p>

<p>In column M there is a also a measure, "locked forecast", I would like a toggle button that allows the user to take the forecast measure -> N134:CG134 to around 4000. This could expand or minimize it products are added or deleted but for now there are around 4000 rows.</p>

<p>When the press the button I would like to see those variable forecasts locked within the "locked forecast" measures

The "locked forecast" measure starts at N140:CG140 and just like the forecast it repeats itself within every product family.</p>

<p>I try to do visible copy paste but I get multiple selection errors, I assume I need some kind of loop.</p>

42255369

Excel VBA cut and paste hard coded value