

Id	Body	Title
38642	<p><p>What tools beside Visual Studio's Cider do you use?
Have you succeed in using something from Microsoft Expression product family?</p></p> <p><p>EDIT:
Here are revealed tools:</p></p> <p></p> <p>Snoop</p> <p>Mole debugger visualizer</p> <p>Perforator suggested by Matt Hamilton</p> <p>The Expression Blend 2.5 Preview suggested by Anthony Conyers</p> <p>Kaxaml suggested by Anthony Conyers & Brad Leach</p> <p>Xaml Export suggested by Artur Carvalho</p> <p></p> <p><p>Some other related questions:</p></p> <p></p> <p>Tools to develop WPF or Silverlight applications</p> <p>How to speed up WPF programs? - has a list of related tools</p> <p></p>	What tools do you use for WPF development

<p>On JavaFX's
Wikipedia</p>

<blockquote>

<p>In May 2008 (...) Sun Also announced a
multi-year agreement with On2
Technologies to bring comprehensive
video capabilities to the JavaFX
product family using the company's
TrueMotion Video codec.</p>

</blockquote>

<p>Do you know if it will include encoding capabilities for webcam video like Flash or just
playback/streaming?</p>

<p>Thanks</p>

44516

JavaFX video encoding

<p>Some of the work we do at my company is slowly edging towards a product family with different
products in the same family and different flavours (or feature sets) in each product. I am looking for
some product line engineering techniques that might help us. Web search leads to a lot of resources
and a lot of different sources of information and differing methodologies. Before plugging into any of
these in depth I thought it would be useful to get some practical advice from someone who has done
something similar to this before. Anyone have any pointers/nuggets of wisdom in this area? I am
particularly looking for better ways to do the following in a product line environment: </p>

configuration and build management

ease of development cycle

testing

305423

Product Line Engineering

<p>I think I'm approaching this the wrong way, which is why I can't seem to figure out an easy solution. I'm relatively new to Rails, so bear with me.</p>

<p>I have a layout, "store," that contains all of the common visual elements for the other controllers. In this layout, I need to dynamically create the sidebar with data from two models, Product and ProductFamily. I want it to output like so:</p>

```
<pre><code>Product Family
---- Product1
---- Product2
</code></pre>
```

<p>And continue on through all relevant records.</p>

<p>I just can't figure out where to start writing the logic for this. Does it go in the layout? In a controller?</p>

<p>Please, point me in the right direction!</p>

1105476

Logic in Rails Layout?

<p>Here's the basics of the system we have in place today. We have a SQL 2005/2008 table defined as:</p>

```
<pre><code>CREATE TABLE [dbo].[Profiles] (  
    [Firm] [char] (4) NULL ,  
    [Account] [char] (10) NOT NULL ,  
    [UndSym] [char] (24) NOT NULL ,  
    [Updated] [timestamp] NOT NULL ,  
    [Data] [image] NOT NULL  
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]  
</code></pre>
```

<p>The Data field is a BLOB. It is where virtually all the goodies are. The data in the BLOB is compressed text which looks very similar to an INI file, with key-value pairs within sections. The internal layout of this INI file is quite complex however with much inter-related data.</p>

<p>We also have another product family which is completely different in design, implementation, and target audience. But now we have a client coming online who wants to integrate the two systems at the database level.</p>

<p>My system is MSSQL. The other system is MySQL. Between the two sits a custom middleware solution of our own design. I don't want to connect to MySQL directly, and they don't want to connect directly to me, for various reasons which are sound and are beyond the scope of this conversation, so don't worry about that.</p>

<p>The concept is simple. When a row in my Profiles table is touched, I need to rip thru the BLOB and look for a few bits of data. If those bits of data has changed, I need to send just those bits of data (not the whole BLOB) to the middleware piece. I must only do this when there are changes I'm interested in, and the only way I can do that is to process both blobs (the original and the replacement).</p>

<p>I quickly concluded that using T-SQL to process the BLOB is not the road I want to go down. I need to write custom code, and I am constrained to using either unmanaged C++, managed C++ or C# to do it.</p>

<p>There are a couple questions here.</p>

<p>FIRST: Should I use an INSTEAD OF trigger to, well, trigger the code which will compare the BLOBs and send interesting data? I know there are some extremist schools of thought on triggers: some people think they are pure Evil, others think they are awesome. The truth is somewhere in between. If I don't use a trigger, how can I trigger processing the BLOBs?</p>

<p>I have a list of Product objects (as rows), each object has several data fields (like product id, product family, etc) - as columns. I managed to create a table model subclassing QAbstractTableModel, and display the datas in a QTableView.</p>

<p>What i want is provide a "grouped" view of the model in a tree-like structure. For example I want to group the products by their family id, so the tree should contain in the first level the groups (family id) and their childs are the product's having that family id.</p>

<p>Any ideas?</p>

<p>PS:

The need of multiple groupings (group by family id, and group them by another column, and so on) shows me that the model should be a tree. The root nodes indicates the groups, and then the childs are the group members. The multiple grouping can be achieved by multi-level trees.</p>

<p>Then my transformed question is the following: How can I implement a special QTableView class that displays only the tree's leafs (at a given level)? (Because actually leafs are the real objects we would like to see in a grid)</p>

<p>I can use setRootIndex in the tableview, but it doesn't solve anything, other leafs are not displayed.</p>

<p>I was digging a little bit, and found that in QTableView::paintEvent, when displaying each row and column, the actual item is fetched like :</p>

<p>const QModelIndex index = d->model->index(row, col, d->root);</p>

<p>where d->root() is the root node given by setRootIndex(). This should be embedded in a tree-traversal code, and everything would be fine. But how could I avoid to reimplement the whole paintEvent method ?</p>

<p>I want to upgrade my product via msi setup.
The Upgrade Code of both msi remains the same because it's the same product family. Even if I change Version/Product Code of the msi for updating it just tells me the product is already installed or asks me to repair it. it doesn't ever provide an update option that replaces the current installation.</p>

<p>I'm using Visual Studio 2008 Pro to generate the msi setup</p>

2028425

How to upgrade via msi

I have this MDX query (based on the Foodmart sample database):

```
SELECT
{[Measures].[Profit]} ON COLUMNS,
{CROSSJOIN([Product].[All Products].Children, [Time].[1997].Children)} ON ROWS
FROM [Sales]
```

This generates a result like this:

```
[Product].[Product Family] [Time].[Year] [Time].[Quarter] [Measures].[Profit]
-----+-----+-----+-----
Drink      | 1997    | Q3      | 7203.3445
Drink      | 1997    | Q4      | 8005.2245
Food       | 1997    | Q1      | 60814.47140000001
Food       | 1997    | Q2      | 57323.3736
```

What I would like to have, is this:

```
[Product Family],[Year],[Quarter] [Measures].[Profit]
-----+-----
Drink, 1997, Q3      | 7203.3445
Drink, 1997, Q4      | 8005.2245
Food, 1997, Q1       | 60814.47140000001
Food, 1997, Q2       | 57323.3736
```

I know I can use `SetToStr()` to serialize the row headers to one string. So now I would like to use that result as rowheader: basically turning each tuple from the original multi-member tuples on the ROW axis into a tuple with just one member, whose value is a concatenation of the original member names. So basically this:

```
SELECT
{[Measures].[Profit]} ON COLUMNS,
SetToStr(
  {CROSSJOIN([Product].[All Products].Children, [Time].[1997].Children)}
) ON ROWS
FROM [Sales]
```

<p>I'm building an asp.net cutom control inside which I have two dropdownlists: companyIdSelection and productFamilySelection.I populate the companyIdSelection at Page_Load and in order to populate the productFamilySelection depending on the selected item in companyIdSelection.I'm using UpdatePanels to achieve this, but for some reason every time I update companyIdSelection Page_Load is being called (which as far as I know should happen only when the entire page is reloaded), the list is being reloaded again and the item the user selected is lost(the selected item is always the top one).Here's the code</p>

<p></p>

```
<pre><code> <asp:UpdatePanel ID="updateFamilies"
    runat="server"
    UpdateMode="Always">
    <ContentTemplate>
        Company ID:<br>
        <br></br>
        <asp:DropDownList ID="companyIdSelection"
            runat="server"
            AutoPostBack="True"
            OnSelectedIndexChanged="companyIdSelection_SelectedIndexChanged">
        </asp:DropDownList>
        <br></br>
        Product Family:
        <br></br>
        <asp:DropDownList ID="productFamilySelection" runat="server"
            AutoPostBack="True"
            onselectedindexchanged="productFamilySelection_SelectedIndexChanged">
        </asp:DropDownList>
        <br>
    </ContentTemplate>
</asp:UpdatePanel>
```

```
protected void Page_Load(object sender, EventArgs e)
{
    this.companyIdSelection.DataSource = companyIds(); //companyIds returns the object containing
the initial data items
    this.companyIdSelection.DataBind();
}
```

```
protected void companyIdSelection_SelectedIndexChanged(object sender, EventArgs e)
{
    //Populate the productFamilySelection from the selected item in companyIdSelection
```


<p>This is an SQL efficiency question. </p>

<p>A while back I had to write a collection of queries to pull data from an ERP system. Most of these were simple enough but one of them resulted in a rather inefficient query and it's been bugging me ever since as there's got to be a better way. </p>

<p>The problem is not complex. You have rows of sales data. In each row you have quantity, sales price and the salesman code, among other information.</p>

<p>Commission is paid based on a stepped sliding scale. The more they sell, the better the commission. Steps might be 1000, 10000, 10000\$ and so forth. The real world problem is more complex but that's essentially it.</p>

<p>The only way I found of doing this was to do something like this (obviously not the real query) </p>

```
<pre><code>select qty, price, salesman,
(select top 1 percentage from comisiones
 where comisiones.salesman = saleslines.salesman
 and saleslines.qty > comisiones.qty
 order by comisiones.qty desc
 ) percentage
from saleslines
</code></pre>
```

<p>this results in the correct commission but is horrendously heavy. </p>

<p>Is there a better way of doing this? I'm not looking for someone to rewrite my sql, more 'take a look at foobar queries' and I can take it from there.</p>

<p>The real life commission structure can be specified for different salesmen, articles and clients and even sales dates. It also changes from time to time, so everything has to be driven by the data in the tables... i.e I can't put fixed ranges in the sql. The current query returns some 3-400000 rows and takes around 20-30 secs. Luckily it's only used monthly but the slowness is kinda bugging me.</p>

<p>This is on mssql.</p>

<p>lan</p>

<p>edit:</p>

<p>I am trying to run a query similar to this one:</p>

```
<pre><code>SELECT s.custno,
      s.prodno,
      IF(daycode = 1, (SELECT avg(sell)
        FROM sales ss
        JOIN (SELECT DISTINCT `prodno`
          FROM `familycode`
          WHERE prodfamily = 101) f2
        ON f2.prodno = ss.prodno
      WHERE ss.CUSTNO = 800
        AND ss.weekno = s.weekno - 1), (SELECT avg(sell)
        FROM sales ss
        JOIN (SELECT DISTINCT `prodno`
          FROM `familycode`
          WHERE prodfam = 101) f3
        ON f3.prodno = ss.prodno
      WHERE ss.CUSTNO = 800
        AND ss.weekno = s.weekno)) AS weekavg
FROM sales s
      JOIN product p
      ON p.prodno = s.prodno
      JOIN (SELECT DISTINCT `prodno`
        FROM `familycode`
        WHERE prodfamily = 101) f
      ON f.prodno = s.prodno
WHERE s.CUSTNO = 800
ORDER BY ardate8n ASC,
      s.CUSTNO,
      s.prodno
</code></pre>
```

<p>In this query I would like to get the products week average based on the daycode param for a product family.</p>

<p>A product belongs to a product family.</p>

If daycode = 1 I want to get for the same product family the average of the previous week.

else I want to get average on the current week for the same product family.

I want to disable the background window when clicking the button. In my project I am using update panel and progress bar. when I click the button the background window is fully visible= false. I want to disable the background window and the progress bar should be displayed. Here is the code:

```
<code><? Page Language="VB" MasterPageFile="~/MasterPage.master"
AutoEventWireup="false" CodeFile="fp_t012stk.aspx.vb" Inherits="fp_t012stk" title="Current Stock
Report" %>
```

```
<? Register Assembly="CrystalDecisions.Web, Version=10.2.3600.0, Culture=neutral,
PublicKeyToken=692fba5521e1304"
```

```
Namespace="CrystalDecisions.Web" TagPrefix="CR" %>
```

```
<? Register Assembly="AjaxControlToolkit" Namespace="AjaxControlToolkit" TagPrefix="cc1" %
>
```

```
<asp:Content ID="Content1" ContentPlaceHolderID="ContentPlaceHolder1" Runat="Server">
```

```
<script type="text/JavaScript" language="JavaScript">
```

```
function ShowProgress()
```

```
{
```

```
document.getElementById ('MainDiv').style.display="";
```

```
document.getElementById ('MainDiv').style.visibility='visible';
```

```
document.getElementById ('MainDiv').style.position='absolute';
```

```
document.getElementById ('MainDiv').style.top='0px';
```

```
document.getElementById ('MainDiv').style.left='0px';
```

```
document.getElementById ('MainDiv').style.width= '100%';
```


I am writing my first WCF service. I am trying to understand how Datacontracts work. I have read the [MSDN Article](http://msdn.microsoft.com/en-us/library/ms733811.aspx) that describes how custom types should be marked up to create a data contract but I cannot get my example to work.

I have a simple DTO object that I have placed in a shared library because I want the client and the service to know about this type (right?) it looks like this:

```
<pre><code> using System.Collections.Generic;
using System.Runtime.Serialization;

namespace org.healthwise.gatewayinterfaces.mocks
{
    [DataContract]
    public class MockCheckInDTO : ICheckInDTO
    {
        [DataMember]
        private string _testPackageFilePath = "testpackages\\973eb455-6acc-486b-a1dd-2cf527872b1e.
zip";
        [DataMember]
        private IDictionary<string, string> _testMetaData;

        public MockCheckInDTO()
        {
            _testMetaData = MakeTestMetaDataDictionary();
        }

        private IDictionary<string, string> MakeTestMetaDataDictionary()
        {
            IDictionary<string, string> testMetaData = new Dictionary<string, string>();
            testMetaData.Add("Version", "9.0.1");
            testMetaData.Add("Product Family", "Learning Modules");
            return testMetaData;
        }

        [DataMember]
        public string PackageFileLocation
        {
            get { return _testPackageFilePath; }
            set { _testPackageFilePath = value; }
        }
    }
}
```

<p>How does Find control method works if i need to find any control which is inside gridview template, more specifically Item Template??</p>

<p>I have a hyperlink but it is not able to find the same.</p>

<p>Question updated with code</p>

<p>Gridview Code is below:</p>

```
<pre><code>&lt;asp:GridView ID="grvYourOpportunities" runat="server" AllowPaging="True"
AutoGenerateColumns="False"
    DataKeyNames="ID#,B,H" PageSize="20" CellPadding="4" ForeColor="#333333" GridLines="
Both"
    OnRowDataBound="grvYourOpt_RowDataBound"&gt;
        &lt;HeaderStyle BackColor="#5D7B9D" Font-Bold="True" ForeColor="White" /&gt;
        &lt;RowStyle BackColor="#F7F6F3" ForeColor="#333333" /&gt;
        &lt;Columns&gt;
            &lt;asp:TemplateField&gt;
                &lt;HeaderTemplate&gt;
                    i
                &lt;/HeaderTemplate&gt;
                &lt;ItemTemplate&gt;
                    &lt;:## Eval("i") %&gt;
                &lt;/ItemTemplate&gt;
            &lt;/asp:TemplateField&gt;

            &lt;asp:TemplateField&gt;
                &lt;HeaderTemplate&gt;
                    H
                &lt;/HeaderTemplate&gt;
                &lt;ItemTemplate&gt;

                    &lt;:## Eval("ID#") %&gt;
                    &lt;img id="imgdiv&lt;:## Eval("ID#") %&gt;" alt="Click" border="0" src="plus.gif" runat="
server" /&gt; &lt;/a&gt; --%&gt;

                    &lt;asp:HyperLink runat="server" ID="hlPlus" ImageUrl="~/plus.gif"&gt;&lt;/asp:
HyperLink&gt;

                &lt;/ItemTemplate&gt;
            &lt;/asp:TemplateField&gt;
        &lt;/Columns&gt;
    &lt;/asp:GridView&gt;
```

<p>I'm looking for best solution for this issue:</p>

<p>I've a Model like this:</p>

```
<pre><code>class annotation(models.Model):  
    product = models.ForeignKey(Product, ... )  
    annotation = models.TextField( ...  
</code></pre>
```

<p>A form for this Model may be:</p>

```
<pre><code>product: [ a select to chose a product ]  
annotations: [ a input type text ]  
</code></pre>
```

<p>But, because product table is big, I show a previous select to user:</p>

```
<pre><code>product family: [ a select to chose a product family ]  
product: [ a select to chose a product in selected product family ]  
annotations: [ a input type text ]  
</code></pre>
```

<p>(Product family is another model and product has a foreign key to it)</p>

<p>My first solution was to write a new widget called SelectAjax and use it on ModelChoiceField. It works fine, but is not an elegant solution for me. </p>

<p>Can someone propose an alternative?</p>

7068807

django - model form with 'helper select'

<p>I am trying to pass a static resource URL, via the apex:param tag. The code I have so far is:</p>

<p>VisualForce:</p>

```
<pre><code>&lt;apex:selectList value="{!SelectedFamily}" onchange="renderGallery();" size="1"
label="Product Family"&gt;
    &lt;apex:actionFunction name="renderGallery" rerender="gallery" oncomplete="renderScripts();"
&gt;
    &lt;apex:param value="{!URLFOR($Resource.NoImage)}" assignTo="{!noImage}"/&gt;
    &lt;apex:param value="{!URLFOR($Resource.NoImageThumb)}" assignTo="{!noImageThumb}"
/&gt;
    &lt;/apex:actionFunction&gt;
    &lt;apex:actionFunction name="renderScripts" rerender="scriptPanel"&gt;
    &lt;/apex:actionFunction&gt;
    &lt;apex:selectOptions value="{!Family}" /&gt;
&lt;/apex:selectList&gt;
</code></pre>
```

<p>Controller:</p>

```
<pre><code>public string noImage{ get; set; };
public string noImageThumb { get; set; }
</code></pre>
```

<p>My understanding of apex:param was that I would now be able to call the controller variables after the re-render had occurred and they would be populated with the static resource URL. But unfortunately I keep getting null.</p>

<p>Anyone have any idea why it isn't working?</p>

9710523

Visualforce passing static resource URL to Ap

<p>We have a rather flexible application written in C# (.net 4.0) that copies data to different ERP systems around the company. It uses an XML file to determine the from and to ERP systems, the data source, credentials, and the columns to copy.</p>

<p>What we are seeing is that there is an interest in transforming the data as it is copied. So a part number with a product family, gets converted to just a product family. For example to do the following transformation 564-8911277 ==> 564 using SSRS functions this would be </p>

```
<pre><code>=Left("564-8911277", instr(564-8911277, "-" ) - 1))  
</code></pre>
```

<p>The thought is to put the expression in the XML file and have the system interpret the expression and transform the data.</p>

<p>I'm researching and working on a cost estimate to develop this feature, and wondering if there is anything out there that already exists that can be integrated into a .net application? </p>

<p>I've found a few things (scripting.net from 2001), but thought I'd reach out to the community to see what else is out there.</p>

<p>Thanks, Tim</p>

10105603

Creating SSRS style expressions (functions) in

<p>I've the following unordered list:</p>

```
<pre><code>&lt;ul class="primary"&gt;
  &lt;li id="1"&gt;&lt;span&gt;Product Family A&lt;/span&gt;
    &lt;ul class="secondary"&gt;
      &lt;li&gt;&lt;span&gt;A.1&lt;/span&gt;&lt;/li&gt;
      &lt;li&gt;&lt;span&gt;A.2&lt;/span&gt;&lt;/li&gt;
    &lt;/ul&gt;
  &lt;/li&gt;
  &lt;li id="2"&gt;&lt;span&gt;Product Family B&lt;/span&gt;
    &lt;ul class="secondary"&gt;
      &lt;li&gt;&lt;span&gt;B.1&lt;/span&gt;&lt;/li&gt;
    &lt;/ul&gt;
  &lt;/li&gt;
  etc...
&lt;/ul&gt;
</code></pre>
```

<p>I'd like to generate the output below with jQuery. Can someone help?</p>

```
<pre><code>product_family:[{
  id:1,
  products:[{
    model: A1,
    model: A2
  }],
  product_family:[{
    id:2,
    products:[{
      model: B1
    }]
  }
]</code></pre>
```

<p>THanks!</p>

<p>I need some help figuring out the best way to structure content using Expression Engine. I've read the documentation, looked at all information I could find but I haven't found the answer. I hope someone here could help.</p>

<p>What I want to create is a product catalogue that would look like this:</p>

<p><code>/bikes</code> (product category, displays the product families, two-wheelers, three wheelers etc.)</p>

<p><code>/bikes/two-wheelers</code> (product family, displays the products in the family)</p>

<p><code>/bikes/two-wheelers/red-bike</code> (product)</p>

<p><code>/bikes/two-wheelers/red-bike/wheels</code> (optional product details page)</p>

<p>I understand that EE URI's are template-group/template based and that the content is in channels. I'm not yet sure how categories can be used in this. Essentially I would like to create "simple" parent-child relationships between the entries and I found a plug-in called Structure that does something like that. Unfortunately, this project needs to be done without additional (paid) plug-ins.</p>

<p>Is it possible for the <code>product</code> to be the channel, and <code>product-family</code> and <code>product-category</code> to be attributes of the <code>product</code> in EE? Would that work? Is there a better way to structure that?</p>

<p>I realise that this isn't a straight-forward question, but I'm still hoping to be pointed in the right direction.

Thanks for reading!</p>

<p>I have a text file which contains some data.</p>

<p>I m particularly interested in finding the count of the number of items in v_dims</p>

<p>v_dims pattern in my text file looks like this :</p>

```
<pre><code>v_dims={  
"Sales",  
"Product Family",  
"Sales Organization",  
"Region",  
"Sales Area",  
"Sales office",  
"Sales Division",  
"Sales Person",  
"Sales Channel",  
"Sales Order Type",  
"Sales Number",  
"Sales Person",  
"Sales Quantity",  
"Sales Amount"  
}  
</code></pre>
```

<p>So I m thinking of getting all the elements in v_dims and dumping them out in a Python list. Then compute the len(mylist) to get the count of the items.</p>

<p>The challenge is in getting all the elements of v_dims from my text file and putting them in an empty list.</p>

<p>I m particularly interested in items in v_dims in my text file. The text file has data in the form of v_dims pattern i showed in my original post. Some data has nested patterns of v_dims. Thanks.</p>

<p>Here's what I have tried and failed. Any help is appreciated. TIA.</p>

```
<pre><code>import re
```

```
fname = "C:\Users\XXXX\Test.mrk"  
with open(fname, "r") as fo:  
    content_as_string = fo.read()
```

<p>Lets say I have following DB structure:

and my application needs to show the list of articles with all the details (model, product family, brand, producer). For that I would need to make more JOINS to get needed data.</p>

<p>Is it OK if I increase application's performance by creating redundant FKs to the Article table like follow? Does it actually increase the performance?

</p>

12004210

DB design and performance: Is it OK to use re

I wish to have a table something as follows:

```
CREATE TABLE ProductFamilies (  
  ID varchar,  
  PriceLow int,  
  PriceHigh int,  
  MassLow int,  
  MassHigh int,  
  MnfGeo int,  
  MnfID bigint,  
  Data varchar,  
  PRIMARY KEY (ID)  
);
```

There are 13 fields in total. Most of these represent buckets. Data is a JSON of product family IDs, which are then used in a subsequent query. Given how Cassandra works, the column names under the hood will be the values. I wish to filter these.

I wish to run queries as follows:

```
SELECT Data FROM MyApp.ProductFamilies WHERE ID IN (?, ?, ?) AND PriceLow >= ?  
AND PriceHigh <= ? AND MassLow >= ? AND MassHigh <= ? and MnfGeo >= ? AND  
MnfGeo <= ?
```


I read that Cassandra can only execute WHERE predicates against composite row keys or indexed columns. Is this still true? If so, I would have to make the columns & Data part of the PK.

Is it still the case that one has to include all columns from left to right and cannot skip any?

Are there any non-optimum points in my design?

I would like to add a column "Materials", which is an array of possible materials in a product family. Think pizza toppings, and querying "WHERE Materials IN ('Pineapple')". Without creating a separate inverted index of materials and then performing a manual intersection against the above query, is there any other [more elegant] way of handling this in Cassandra?

<p>I have a list of products that has two columns, product and product family.</p>

<p>I want to create another list that uses this first list as a lookup for one of the columns. This I can do, i.e. I create a custom column and then use the "Add from existing site columns" link on the "List Settings" page of the second list.</p>

<p>However, what I'd really like is that the custom column only proposes products that belong to a specific product family. I can create a View in the first list which allows me to display only the products in a specific family. However I don't see any way to specify only this view when I create the custom column.</p>

<p>Anyone have any ideas ?</p>

<p>Best regards,</p>

<p>Colm</p>

12974739

Is it possible to create a Custom Column that

Not sure if this is possible. In my example I am using json as the source but this could be any size. In my example on <http://jsfiddle.net/jqIndy/ZPUr4/3/> I would use this data in a shared fashion by only binding two columns ProductFamily (xAxis) and Value (yAxis) but I would like to be able to group the columns by using an aggregate.

In this example without the grouping it shows multiple columns for FamilyA. **Can this be grouped into ONE column and the values aggregated regardless of the amount of data?**

So the result will show one column for FamilyA of Value $4850 + 4860 = 9710$ etc.?

A problem with all examples online is that there is always the correct amount of data for each category. Not sure if this makes sense?

<http://jsfiddle.net/jqIndy/ZPUr4/3/>

```
<code>//Sample data (see fiddle for complete sample)
```

```
[{
  "Client": "",
  "Date": "2011-06-01",
  "ProductNumber": "5K190",
  "ProductName": "CABLE USB",
  "ProductFamily": "FamilyC",
  "Status": "OPEN",
  "Units": 5000,
  "Value": 5150.0,
  "ShippedToDestination": "CHINA"
}]
```

```
var productDataSource = new kendo.data.DataSource({
  data: dr,
  //group: {
  // field: "ProductFamily",
  //},
  sort: {
    field: "ProductFamily",
    dir: "asc"
  },
  //aggregate: [
    // { field: "ProductFamily", aggregate: "sum", type: "Value" }
  ]
});
```

<p>Hurting my brain trying to get this to work, maybe someone can help me out.</p>

<p>I have products, each product has a family. The path-auto url is {product family}/{product name}
</p>

<p>Each product has a family relation, meaning you can select its' parent via a taxonomy term.</p>

<p>On the product family page I'd like a rundown of the available products. I've tried to use contextual filters but every Google result's method isn't working, so I finally came here looking for help.</p>

<p>Any ideas?</p>

13808396

Drupal 7: Contextual Filter for Second URL Ar

I have downloaded opensource delphi twain component (TDelphiTwain).
The interesting thing is, that when placed and saved on the form it creates bad dfm entry for itself.

```
object DelphiTwain: TDelphiTwain
  OnSourceDisable = DelphiTwainSourceDisable
  OnSourceSetupFileXfer = DelphiTwainSourceSetupFileXfer
  TransferMode = ttmMemory
  SourceCount = 0
  Info.MajorVersion = 1
  Info.MinorVersion = 0
  Info.Language = tlDanish
  Info.CountryCode = 1
  Info.Groups = [tgControl, tgImage, tgAudio, MinorVersion]
  Info.VersionInfo = 'Application name'
  Info.Manufacturer = 'Application manufacturer'
  Info.ProductFamily = 'App product family'
  Info.ProductName = 'App product name'
  LibraryLoaded = False
  SourceManagerLoaded = False
  Left = 520
  Top = 136
end
```

The problem is with the line:

```
Info.Groups = [tgControl, tgImage, tgAudio, MinorVersion]
```

There are only three possible elements:

```
tgControl, tgImage and tgAudio
```

It adds MinorVersion everytime I Save the form.
When the app is run I get the error that there is invalid property for Info.Groups.
When i remove the bad part manually and without leaving dfm file the app starts ok.

I looked in the internet and there was one inquire regarding these strange issue, unfortunately it hasn't been resolved.

<p>As part of our installation procedure we have to install Adobe Acrobat XI. According to Adobe:</p>

<blockquote>

<p>The basic formula for constructing and decoding the GUID is as follows:</p>

<p>Acrobat: Example: AC76BA86-1033-F400-7760-100000000002</p>

<p>[product family]-[language code]-[additional languages]-[product type]-
[license type][major version][major minor version]</p>

</blockquote>

<p>Since I know the key is located in

<code>HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\Uninstall</code> and I know the key starts with <code>{AC76BA86-</code> I would like to simply search for the key(s) that begin with that sequence so I can inspect it to determine if we need to install Acrobat.</p>

<p>Is there a way to do a partial registry key search in InstallShield's install script?</p>

14712484

Search for partial registry key in InstallShield

I need to aggregate over upper level with filter on members from lower one.
It is for report that present sales in every year with filter on one specific month.
This is example for FoodMart database and Product Dimension with levels:</p>

```
<ol>
<li>[Product Family]</li>
<li>[Product Department]</li>
</ol>
```

<hr>

<p>MDX:</p>

```
<pre><code>WITH
MEMBER [Measures].[Unit Sales Calculated] AS
    Aggregate(
        Intersect(
            Descendants(
                [Product].CurrentMember,
                [Product].[Product Department],
                SELF
            ),
            [Filtered Product Department]
        ),
        [Measures].[Unit Sales]
    )
SET [Filtered Product Department] AS
Except(
    [Product].[Product Department].Members,
    [Product].[Drink].[Alcoholic Beverages]
)
SELECT
    NON EMPTY [Measures].[Unit Sales Calculated] ON COLUMNS,
    NON EMPTY [Product].[Product Family].Members ON ROWS
FROM [Sales]
</code></pre>
```

This solution works but performance is rather poor.
Is there better way to write this query?</p>

<p>Thanks in advance for your help.</p>

<p>I'm working with an existing query that is called CustSalesbyRoute. I've made a recent change to it to get a distinct count of Route Stops by Customer and this information is stored in a separate table I created for CustRouteStops. However, the query also includes Product Family so this duplicates my distinct Route-Stop count. I've confirmed that several reports use Product Family from this table to pull various data, otherwise, I would eliminate this column and everything would work great. I also know that this essentially goes against relational database integrity; however, I'm left to work on it, and I'm hoping to have a solution that is equivalent to Excel's FREQUENCY/MATCH functions or SUMPRODUCT, etc.</p>

<p>The question is this: Is there a way to display the Customer Route-Stops value for the first instance of rows that have multiple Product Family values and show 0 for any others for the same Customer/Route combination? For example, below is what the query is doing now if I include Product Family:</p>

```
<pre><code>CustID  ProdFamily  Route  #ofStops
10001  Dairy      101    14
10001  Dry Groceries 101    14
10001  Meat        101    14
</code></pre>
```

<p>This is what I would like to see happen because I need to leave Product Family in the table:</p>

```
<pre><code>CustID  ProdFamily  Route  #ofStops
10001  Dairy      101    14  &lt;&lt;&lt; 1st instance will provide the Stops value
10001  Dry Groceries 101    0  &lt;&lt;&lt; remaining rows for same Cust# and Route will show 0
10001  Meat        101    0
</code></pre>
```

<p>Thanks again!</p>

15014711

SQL Server 2008 Provide Value Once for Mult

<p>I'm trying to create DataGrid in a separate UserControl whose DataContext is a List of T.</p>

<p>In the code behind, I create a List, populate the list, then send it to the constructor for the UserControl on which I have the DataGrid I am trying to populate.</p>

<p>The UserControl class is as follows.</p>

```
<pre><code>public partial class QuotePreview : UserControl
{
    private static SelectionList previewList = new SelectionList();

    public SelectionList PreviewList
    {
        get { return previewList; }
    }

    public QuotePreview()
    {
        InitializeComponent();
    }

    public QuotePreview(SelectionList selectedOptions)
    {
        InitializeComponent();

        previewList = selectedOptions;

        QuotePreviewDataGrid.DataContext = previewList;
    }
}
</code></pre>
```

<p>And the Xaml looks like:</p>

```
<pre><code><DataGrid Name="QuotePreviewDataGrid"
    AutoGenerateColumns="False"
    ItemsSource="{Binding}">
    <DataGrid.Columns>
        <DataGridTextColumn Header="Model Number" Binding="{Binding ModelNumber}">
        <DataGridTextColumn Header="Description" Binding="{Binding Description}">
        <DataGridTextColumn Header="List Price per Unit" Binding="{Binding Price}">
    </DataGrid.Columns>
    </DataGrid>
</code></pre>
```

<p>So, I bought into the dream in the form of a surface pro and then I installed Visual Studio 2010 in the hopes of coding on the toilet. However, I cannot get SP1 to install (from this link: here). Has anyone successfully installed SP1 on the surface?</p>

<p>The error I get is:</p>

<blockquote>

<p>KB2736182 does not apply, or is blocked by another condition on your computer. Please see http://go.microsoft.com/fwlink/?LinkId=225649 for more details.</p>

</blockquote>

<p>If you follow the link you'll see this gem:</p>

<p>"Product of the product family Visual Studio 2010 or Team Foundation Server 2010 with Service Pack 1 applied"</p>

15216123

Visual Studio on Surface Pro SP1

<p>Using Mondrian, I would like to get Level in MDX query for each axis.</p>

<p>For example :</p>

<blockquote>

<p>SELECT NON EMPTY {Hierarchize({[Product].[Product Family].Members})} ON COLUMNS</p>

<p>NON EMPTY CrossJoin([Time].[Quarter].Members, [Store].[Store Name].Members) ON
ROWS</p>

<p>FROM [Sales] </p>

<p>WHERE {Hierarchize({[Measures].[Unit Sales]})}</p>
</blockquote>

<p>Expected results are :</p>

<p>COLUMNS : [Product].[Product Family]</p>

<p>ROWS : [Time].[Quarter], [Store].[Store Name]</p>

<p>Recently I used this code :</p>

<blockquote>

<p>axes[i].getSet().getType().getLevel()</p>

</blockquote>

<p>It worked for the COLUMNS axis, but it doesn't work for the ROWS axis.
I suppose this is caused by the arity in ROWS axis which is more than 1.</p>

<p>Is there any way to get the level in an axis which has arity more than 1 ?</p>

<p>Thanks.</p>

I have two low-level questions about how memory interleaving across channels works on Sandy Bridge processors. I've poured through technical documents from Intel, and I still cannot find the answers. Can you help?

Multi-channel memory controllers in modern CPUs stripe data across the memory channels. This allows reads and writes to be carried out in parallel, thus increasing performance.

Question #1: What is the chunk size Sandy Bridge uses for interleaving? I've found some information that suggests that it is the cache-line size. On the other hand, others have suggested that it is [configurable](http://stackoverflow.com/questions/4183461/nehalem-memory-architecture-address-mapping) (at least in older Intel architectures). Which is it? Can you point to an Intel document?

Some CPUs allow interleaving to be disabled. This is confirmed by BIOS settings of some high-end systems such as HP's ProLiant and Fujitsu's Primergy. The closest documentation from Intel that I can find on this is section 4.4.4.3 in this [E5 Product Family Data Sheet](http://www.intel.com/content/dam/www/public/us/en/documents/datasheets/xeon-e5-1600-2600-vol-2-datasheet.pdf). I have gone as far as contacting HP about how their ProLiant works when interleaving is disabled, but even on a conference call, they were unable to answer my question.

Question #2: How is memory mapped across the channels when interleaving is disabled? Presumably, it is different from spare or mirror mode configurations.

15836309

SandyBridge: How does physical memory ma

I would like to extract information, or the query axis element from a given MDX query.
Suppose I have this query :

```
SELECT NON EMPTY {
  Hierarchize({[Product].[Product Family].Members})
} ON COLUMNS,
NON EMPTY Hierarchize (
  Union (
    CrossJoin ( {[Time].[1997].[Q1]},
      CrossJoin ([Store].[Store Name].Members,
        [Store Type].[Store Type].Members
      )
    ),
    CrossJoin({[Time].[1997].[Q2]},
      CrossJoin([Store].[Store Name].Members,
        [Store Type].[Store Type].Members
      )
    )
  )
) ON ROWS FROM [Sales]
WHERE {
  Hierarchize({[Measures].[Unit Sales]})
}
```

The substring I would like to extract has pattern like this :
[...]([...]) or
[...]...].Members

Note that, ... means any alphanumeric, and what inside bracket means can be recurred.
Thus, the results I expect are :

```
[Product].[Product Family].Members; [Time].[1997].[Q1];
[Time].[1997].[Q2]; [Store].[Store Name].Members; [Store Type].[Store
Type].Members; [Measure].[Unit Sales]
```

I tried my best and finally figured this regex :

```
<code>\[.*?[A-Za-z\s]\\(.*?(\\\[.*?[A-Za-z\s]\\)| (\\.Members))
```

<p>I have the below table:</p>

```
<pre><code>&lt;table class="authors-list" border=0 id="ordertable"&gt;
  &lt;tr&gt;
    &lt;td &gt;&lt;input type="text" id="product_1" name="product_1" class="rounded"/&gt;&lt;
  /td&gt;
    &lt;td &gt;&lt;input type="text" size='5' id="qty_1" name="qty_1" class="rounded"/&gt;&lt;
  /td&gt;
    &lt;td class="tdcheckbox"&gt;&lt;input type="checkbox" id="h09_1" name="h09_1" class="
rounded"/&gt;
    &lt;input type="text" id="line_1_09" name="line_1_09" value=""&gt;&lt;/td&gt;
    &lt;td class="tdcheckbox"&gt;&lt;input type="checkbox" id="h12_1" name="h12_1" class="
rounded"/&gt;
    &lt;input type="text" id="line_1_12" name="line_1_12" value=""&gt;&lt;/td&gt;
    &lt;td class="tdcheckbox"&gt;&lt;input type="checkbox" id="h15_1" name="h15_1" class="
rounded"/&gt;
    &lt;input type="text" id="line_1_15" name="line_1_15" value=""&gt;&lt;/td&gt;
    &lt;td&gt;&lt;input type="text" name="cubespercheck_1" id="cubespercheck_1" value="0"
size=5&gt;&lt;/td&gt;
  &lt;/tr&gt;
&lt;/table&gt;
</code></pre>
```

<p>you can see the fiddle here:

http://jsfiddle.net/3Befc/7/</p>

<p>My main goal is to be able to post each checkbox as an individual product. the product field is populated with a product family. example is 38114CR. the checkboxes represent the lengths of the product. the code for a 1.8 meter length of 38114CR is 3811418CR where 18 is the length (1.8)</p>

<p>In the end, I want to be able to post each checked checkbox as its unique product code. so if 0.9 is checked for product 38114CR post the value 3811409CR.</p>

<p>My ultimate goal is to insert the following into a database:
(this is as per the fiddles desired result)</p>

```
<pre><code>**Product      Cubes**
```

```
3011409CR      7
```

```
3011412CR      7
```

```
2011512EX      3
```

```
3011515EX      2
```

<p>I have two relationships.
product family.</p>

<p>a family can have several products. a product belongs to one family.</p>

<p>Taking a product like you can remove the family relationship. ie how could leave a product without family?</p>

<p>I tried this:</p>

```
<pre><code>$product-&gt;getFamily()-&gt;remove();  
$product-&gt;setFamily(null);  
</code></pre>
```

<p>but not working.
must be an instance of my\myBundle\Entity\Family
thanks.</p>

16239733

Removing Associations doctrine symfony2

<p>I'm having a weird issue, I'm using protobuf-net for C# to generate a file which based on Google Protocol Buffer message and then upload it to one of my company's servers.</p>

<p>I created a tool in C# that generates a .proto file to .cs, then I'm using its classes (from .cs file) to fill all the required fields in the message and after that I called to Serializer.Serialize() function and it creates for me the requested file.</p>

<p>BUT, and this is the problem, I have another file (same file) which created in another tool that wrote in C++ (uses the same .proto file that I used), but when I'm trying to upload my file to our servers I'm getting an error that something is wrong.</p>

<p>I compared the 2 files with "Win Merge" software and I noticed a very little differences in 3 different lines (out of 7000+ lines in each file) compared to the file that generated in the C++ tool.</p>

<p>Here is example of 2 line captured from Win Merge tool (on the Left the C++, on the right C#):</p>

<p></p>


<p></p>

<p>I notice that the differences is in the rectangulars (which I don't understand what is there meaning) with the bytes inside them...</p>

<p>Here is the .proto file that I'm using:</p>

```
<pre><code>message Package {  
  
    message ArchDepend {  
  
        message Arch {  
            required string version = 1;  
            required string description = 2;  
        }  
  
        message Firmware {  
            required string version = 1;  
            required string description = 2;  
            required bytes file = 3;  
        }  
    }  
}</pre>
```


i am developing a software using Visual C++ 2008 Express Edition. after build in release mode, i have made a setup file with latest redistributable 2008. the software is running in my PC fine. in my PC this redistributable are installed :




in my friend's PC, the same redistributable are installed. but the software is crashing on my friend's PC.



from the event log it shows:




as you can see, it is demanding 9.0.21022.8 version of redistributable whether there is previously installed latest version of redistributable(9.0.30729.17). so, i go for a google. from the internet, i edit my `C:\Program Files\Microsoft Visual Studio 9.0\VC\include\crtdasm.h`




but it didn't help. then i check my project manifest. and i saw :



but i don't know how to edit manifest (i am new in VC++). and i also check `C:\Program Files\Microsoft Visual Studio 9.0\VC\redist\x86\Microsoft.VC90.CRT\Microsoft.VC90.CRT.manifest`. it shows:



i have tried to find out 9.0.21022.8 version of redistributable in the internet. but i have failed. from my VC Express installer there is a file named `vc_redistmin_x86.exe` :



as you can see the version of the file is 9.0.21022.8. i think this is the redistributable i need. but i cannot install it. it says "run the setup.exe file"

what can i do?

I am an Android developer, I have to create a generic component for parsing xml using sax parser. For any kind of schema I should create a common component through which we can parse the xml and save that into a data file (bean or model object).

Is this possible with SAX, if so can you please assist me?

For ex,

```
<code><?xml version="1.0" encoding="UTF-8"?>
<ns:multiStockDataDownloadResponse xmlns:ns="http://service.tcs.web">
  <ns:return>
    <StockList>
      <Stock changeData="-0.10" companyData="Sprint Nextel Corporation" lastData="5.21"
marketCapData="15586.73" percChangeData="-1.88" tkr="S" >
        <customerProfile value="false" name="isNWCustomer" />
        <customerProfile value="English" name="custLangPref" />
        <customerProfile value="karthi.muthusamy@bankofamerica.com"
          name="fullEmailAddress" />
      </Stock>
      <Stock changeData="+0.43" companyData="Vodafone Group Plc (ADR)" lastData="26.43"
marketCapData="135649.83" percChangeData="2.05" tkr="VOD" >
        <customerProfile value="false" name="isNWCustomer" />
        <customerProfile value="English" name="custLangPref" />
      </Stock>
      <Stock changeData="+0.12" companyData="Verizon Communications Inc." lastData="35.24"
marketCapData="98672.00" percChangeData="0.34" tkr="VZ" >
        <customerProfile value="false" name="isNWCustomer" />
      </Stock>
      <Stock changeData="+0.08" companyData="AT&T Inc." lastData="30.43"
marketCapData="180206.46" percChangeData="0.26" tkr="T" />
      <Stock changeData="-0.22" companyData="Telefonica S.A. (ADR)" lastData="23.47"
marketCapData="107117.00" percChangeData="-0.93" tkr="TEF" />
    </StockList>
  </ns:return>
</ns:multiStockDataDownloadResponse>
</code>
```

Another sample is

```
<code><?xml version="1.0" encoding="UTF-8"?>
<ns:multiStockDataDownloadResponse xmlns:ns="http://service.tcs.web">
  <ns:return>
    <StockList>
      <Stock changeData="+0.08" companyData="AT&T Inc." lastData="30.43"
marketCapData="180206.46" percChangeData="0.26" tkr="T" />
      <Stock changeData="-0.22" companyData="Telefonica S.A. (ADR)" lastData="23.47"
marketCapData="107117.00" percChangeData="-0.93" tkr="TEF" />
    </StockList>
  </ns:return>
</ns:multiStockDataDownloadResponse>
</code>
```


I just started working with SQL. The data is stored as in three tables. An example is given below...

TABLE1

column: product family

TABLE2

column: location

TABLE3 columns of interest:

building plant

product type

forecast2012

forecast2013

forecast2014

forecast2015

If...

any text value stored in "location" matches a given text value in "building plant" & If any text value stored in "product family" matches a given text value in "product type"

then...

grab the contents of the four columns "forecast2012, forecast2013, forecast2014, forecast2015" in the corresponding rows and build a new table consisting of them and their matched "location" and "product family" values.

I just started working with SQL. The data is stored as in three tables. An example is given below...

TABLE1: ProductFamily

```
column: product family
```

TABLE2: facility

```
column: location
```

TABLE3: strap

```
column: build plant
column: prod series
column: 2012 Full Units w/C
column: 2013 Full Units w/C
column: 2014 Full Units w/C
column: 2015 Full Units w/C
column: 2016 Full Units w/C
column: 2017 Full Units w/C
column: 2018 Full Units w/C
```

If... any text value stored in "location" matches a given text value in "building plant" & If any text value stored in "product family" matches a given text value in "product type"

then... grab the contents of the seven columns "201X Full Units w/C:" in the corresponding rows and build a new table consisting of them and their matched "location" and "product family" values.

MY QUERY:

```
select facility.location, ProductFamily.productfamily, strap.[2012 Full Units w/C], [2013 Full Units w/C], strap.[2014 Full Units w/C], strap.[2015 Full Units w/C], [2016 Full Units w/C], strap.[2017 Full Units w/C], strap.[2018 Full Units w/C]
```

<p>I am new to VBA...

I am trying to write a macro that will clear all the selections within a pivot table filter named "Product Family" and select only the item whose name is contained in cell "B33". I am referencing the pivot table in one sheet "sheet8" and trying to change a graph on "Dashboard".</p>

<p>Here is the code...</p>

```
<pre><code> Sub thisisalsotemp()  
,  
,  
' thisisalsotemp Macro  
,  
,  
,  
    Sheets("Dashboard").Select  
    ActiveSheet.ChartObjects("Chart 1").Activate  
    Sheet8.PivotTables("capbylp").PivotFields("Product Family").PivotFields.ClearAllFilters  
    With Sheet8.PivotTables("capbylp").PivotFields("Product Family")  
        .PivotItems(Range("B33")).Visible = True  
    End With  
End Sub  
</code></pre>
```

<p>The error is in the following line:

Sheet8.PivotTables("capbylp").PivotFields("Product Family").PivotFields.ClearAllFilters</p>

<p>The error message is:

Object doesn't support this property or method</p>

<p>@SeanCheshire: Thanks for the help. I feel this is much closer to what I want. However, I couldnt get it to work. I played around with it a little bit and am closer. here is what i have...</p>

```
<pre><code> Sub thisisalsotemp2()  
    Sheets("Dashboard").Select  
    Sheet8.PivotTables("capbylp").PivotFields("Product Family") = Range("B33")  
End Sub  
</code></pre>
```

<p>Error 1004 reads: unable to set the pivotfields property of the pivottable class</p>

<p>in the line: Sheet8.PivotTables("capbylp").PivotFields("Product Family") = Range("B33")</p>

<p>I have one data source which has a column Part_Number.</p>

<p>My second data source has Product_Family_ID, Product_ID and Part_Mask.</p>

<p>Mask is a pattern string used in a like expression where part_number like mask. For instance 'NXA%' or '001-[abcd][456]9-121%'.</p>

<p>Usually we look up legitimate part numbers for a product family based on the available product part masks, but in this instance I need to go in the other direction. Based on a part number, I must find all the related products in that product family and store that in a summary table.</p>

<p>Simulating this in T-SQL:</p>

```
<pre><code>declare @partlist table (partnumber varchar(100))
```

```
insert into @partlist (partnumber) values ('nxampvg1')
```

```
select distinct pl.partnumber, match.Product_ID
from @partlist pl
join ( select m.masks, p.product_id from MCS_ProductFamily_PartMasks m
      join Product p on m.ProductFamilyID = p.ProductFamily_ID) match
  on pl.partnumber like match.Masks
</code></pre>
```

<p>Desired output:</p>

```
<pre><code>Part_Number Product_ID
-----
nxampvg1  15629
nxampvg1  15631
nxampvg1  15632
nxampvg1  15633
nxampvg1  15634
nxampvg1  15635
nxampvg1  15636
nxampvg1  15637
nxampvg1  15638
nxampvg1  15639
</code></pre>
```

<p>How can I accomplish this in an SSIS data flow task?</p>

<p>after install VS 2012 I want to install sql server 2008 R2 but need SP1 </p>

<p>when install sp1 give me this error

A compatible version of Visual Studio 2008 was not detected on the system. This update is designed for only the Microsoft Visual Studio 2008 (ENU) product family, and is not compatible with any Express editions.</p>

18322134

how to install sql 2008 after VS 2012

<p>I'm using ExtJS 4.2 and created a store with a sorter. The store loads data from a JSONP web service call just fine, but it refuses to sort. Below is a representation of my model, store and load call.</p></p>

<p>Model:</p>

```
<pre><code>Ext.define('Desktop.models.products.DtoProductFamilyModel', {
extend: 'Ext.data.Model',
fields: [
    {
        name: 'ProductFamilyId',
        type: 'string',
        useNull: false,
        defaultValue: Util.getBlankGuid()
    },
    {
        name: 'ParentProductFamilyId',
        type: 'string',
        useNull: true,
        defaultValue: Util.getBlankGuid()
    },
    {
        name: 'BaseItemId',
        type: 'string',
        useNull: true,
        defaultValue: Util.getBlankGuid()
    },
    {
        name: 'Name',
        type: 'string',
        useNull: false,
        defaultValue: ""
    },
    {
        name: 'DisplayName',
        type: 'string',
        useNull: false,
        defaultValue: ""
    },
    {
        name: 'ExternalReferenceId',
        type: 'string',
        useNull: true,
        defaultValue: Util.getBlankGuid()
    }
]
});</code></pre>
```

<p>I am binding Multiselect jquery through code behind</p>

<p>and on button click i am rebinding with different values</p>

<p>it shows the changed list,</p>

<p>I have to disabled some items in second list if it is available in first list</p>

<p>suppose
Old list1 is </p>

<p>Date</p>

<p>Revenue</p>

<p>New list1 is</p>

<p>productName</p>

<p>new second list is</p>

<p>Date</p>

<p>Product Family</p>

<p>so as Date was in oldlist1
its disabling in list2</p>

<p>but date is not in newlist1 so it should not disabled in list2</p>

<p>when i look in firebug i saw the date is avaibale in List1 like this</p>

<p></p>

<p>its keep storing old list, but its not visible in list on GUI</p>

<p>The code is like this</p>

<p>I have modified this line in jquery plugin </p>

```
<pre><code>if (isDisabled || IsToDisableIfselectedInOthers(value) == true) {
```

<p>How can we cluster customers from transaction data in R ? For e.g., we have customer name, product code,product family,product modules and units they boughtnow i want to find some pattern via clustering. I have looked over k-means and som in R but not getting the right approach to do it. kindly help</p>

<p>PS: My data is not numeric data,they are categorical</p>

19157556

clustering customers in R with transactional c

<p>I am trying to use Python Pandas to import a CSV file. The example data in this file is as follows where the first row is the column names separated by commas.</p>

```
<pre><code>End Customer Organization ID,End Customer Organization Name,End Customer Top
Parent Organization ID,End Customer Top Parent Organization Name,Reseller Top Parent ID,Reseller
Top Parent Name,Business,Rev Sum Division,Rev Sum Category,Product Family,Version,Pricing Level,
Summary Pricing Level,Detail Pricing Level,MS Sales Amount,MS Sales Licenses,Fiscal Year,Sales Date
11027676,Baroda Western Uttar Pradesh Gramin
Bankgfhgfnjgfnmjmhgmghgmghgmghnmghnmghnmghnmghnngnh,4078446,Bank Of
Barodadfhghgfjytkyukujkyukuhykluiluilui;iooi';po'fserwefvegwegf,1809012,"Hcl Infosystems Ltd -
Partnerdghftrutyhb frhywer5y5tyu6ui7iukluyj,ljgmfgnhfrgweffw",Server &
CALsdgrgrfgrhrytrnhjdghjtyjkukmhjmghmbhmgfngdfbndfhtgh,SQL Server &
CALdfhtrhtrgbhrghrye5y45y45yu56juhydsgfaefwe,SQL
CALdhdfthtrutrjrhjethfdehrerfgwerweqeadfawrqwerwegtrhyjuytjhyj,SQL
CALdtrye45y3t434tkabcjkasdhfhasdjkbaksmjcbfuigkjasbcjkasbkdfhiwh,2005,
Openfkvgjesropiguwe90fujklascnioawfy98eyfuiasdbcvjksbgh,Open
Lklbjdfoiguerogbjvwioergyuiowerhgoshdvgfoisdhyguiserhguisrh,"Open Stddfm,
vdnoghioerivnsdflierohgushdfhovhsiodghuiohdbvgjsjdhgouiwerho",125.85,1,FY07,12/28/2006
12835756,Uttam Strips Pvt Ltd,12835756,Uttam Strips Pvt Ltd,12565538,Redington C/O Fortis
Financial Services Ltd,MBS,Dynamics ERP,Dynamics NAV,Dynamics NAV Business Essentials,Non-
specific,Other,MBS SA,MBS New Customer Enhanc. Def,0,0,FY09,9/15/2008
12233135,Bhagwan Singh Tondon,12233135,Bhagwan Singh Tondon,2652941,H B S Systems Pvt Ltd,
Server & CAL,SQL Server & CAL,SQL CAL,SQL CAL,Non-specific,Open,Open L&SA,
Deferred Open L&SA - New,0,0,FY09,9/15/2008
11602305,Maya Academy Of Advanced Cinematics,9750934,Maya Entertainment Ltd,336146,Embee
Software Pvt Ltd,Server & CAL,Windows Server & CAL,Windows Server HPC,Windows
Compute Cluster Server,Non-specific,Open,Open V/MYO - Rec,OLV Perpet L&SA Recur-Def,0,0,
FY09,9/25/2008
13336009,Remiel Softech Solution Pvt Ltd,13336009,Remiel Softech Solution Pvt Ltd,13335482,
Redington C/O Remiel Softech Solutions Pvt Ltd,MBS,Dynamics ERP,Dynamics NAV,Dynamics NAV
Business Essentials,Non-specific,Other,MBS SA,MBS New Customer Enhanc. Def,0,0,FY09,
12/23/2008
</code></pre>
```

<p>I am using the below code to import:</p>

```
<pre><code>import pandas as pd

df=pd.read_csv('file path.csv',sep=',')
</code></pre>
```

I am trying to import a csv file in Pandas but it throws an error. The format of the data when opened in notepad++ is as follows with first row being column names:

```
"End Customer Organization ID,End Customer Organization Name,End Customer Top Parent Organization ID,End Customer Top Parent Organization Name,Reseller Top Parent ID,Reseller Top Parent Name,Business,Rev Sum Division,Rev Sum Category,Product Family,Version,Pricing Level,Summary Pricing Level,Detail Pricing Level,MS Sales Amount,MS Sales Licenses,Fiscal Year,Sales Date"
```

```
"11027676,Baroda Western Uttar Pradesh Gramin Bankgfhgfnjgfnmjmghgmghgmghnmghnmghnmghnmghnghngh,4078446,Bank Of Barodadfhghgfjytkyukujkyukuhykluiluilui;iooi';po'fserwefvegwegf,1809012,""Hcl Infosystems Ltd - Partnerdghfrutyhb frhywer5y5tyu6ui7iukluyj,ljgmfgnhfrgweffw""",Server & CALsdgrgrfgrhytrnhjdgthjtyjkukmhjmgmhbmghmgfngdfbndfhtgh,SQL Server & CALdfhtrhtrgbhrghrye5y45y45yu56juhydsghfaefwe,SQL CALdhdfthtrutrjurhjetfhdehrerfgwerweqeadfawrqwerwegtrhyjuytjhjy,SQL CALdtrye45y3t434tkabcjkasdhfhasdjkcbaksmjcbfuigkjascbjkasbkdfhiwh,2005, Openfkgjesropiguwe90fujklascnioawfy98eyfuiasdbcvjksbgh,Open Lklbjdfoiguerogbjvwioergyuowerhgoshdvgfoisdhyguiserhguisrh,""Open Std dfm, vdnoghioerivnsdflierohgushdfhovhsiodghuiohdbvgsjdhgouiwerho""",125.85,1,FY07,12/28/2006" "12835756,Uttam Strips Pvt Ltd,12835756,Uttam Strips Pvt Ltd,12565538,Redington C/O Fortis Financial Services Ltd,MBS,Dynamics ERP,Dynamics NAV,Dynamics NAV Business Essentials,Non-specific,Other,MBS SA,MBS New Customer Enhanc. Def,0,0,FY09,9/15/2008" "12233135,Bhagwan Singh Tondon,12233135,Bhagwan Singh Tondon,2652941,H B S Systems Pvt Ltd,Server & CAL,SQL Server & CAL,SQL CAL,SQL CAL,Non-specific,Open,Open L&SA, Deferred Open L&SA - New,0,0,FY09,9/15/2008" "11602305,Maya Academy Of Advanced Cinematics,9750934,Maya Entertainment Ltd,336146, Embee Software Pvt Ltd,Server & CAL,Windows Server & CAL,Windows Server HPC, Windows Compute Cluster Server,Non-specific,Open,Open V/MYO - Rec,OLV Perpet L&SA Recur-Def,0,0,FY09,9/25/2008" "13336009,Remiel Softech Solution Pvt Ltd,13336009,Remiel Softech Solution Pvt Ltd,13335482, Redington C/O Remiel Softech Solutions Pvt Ltd,MBS,Dynamics ERP,Dynamics NAV,Dynamics NAV Business Essentials,Non-specific,Other,MBS SA,MBS New Customer Enhanc. Def,0,0,FY09, 12/23/2008" "7872800,Science Application International Corporation,2839760,GOVERNMENT OF KARNATAKA, 10237455,Cubic Computing P.L,Server & CAL,SQL Server & CAL,SQL Server Standard,SQL Server Standard Edition,Non-specific,Open,Open SA/UA,Deferred Open SA - Renewal,0,0,FY09, 1/15/2009" "13096361,Pratham Software Pvt Ltd,13096361,Pratham Software Pvt Ltd,10133086,Krap Computer,Information Worker,Office,Office Standard / Basic,Office Standard,2007,Open,Open L, Open Std,7132.44,28,FY09,9/24/2008" "12192276,Texmo Precision Castings,12192276,Texmo Precision Castings,4059430,Quadra Systems.
```

<p>Long title and strange problem:

I want to use the with-statement in oracle SQL to reuse a sub-query as well in the select as group by clause. Additionally, I use a case statement in order to create more information and group the results. This statement however throws following error: ORA-00979: not a GROUP BY expression.

</p>

<p>Example query that is not working: I define a query containing the sum of the sales per product family. I sort this query and select the best selling product family out of it. As main result, I want to compare this top selling family to the sum of the sales of other product families (not one by one but all other product families grouped together). I do this following way:</p>

```
<pre><code>WITH
top_family AS (
SELECT *
FROM (SELECT c.family
      FROM products c, sales d
      WHERE c.product_id= d.product_id
      GROUP BY c.family
      ORDER BY SUM(d.quantity) DESC)
WHERE ROWNUM = 1)

SELECT CASE
      WHEN a.family IN (SELECT * FROM top_family)
      THEN 'Most sold category'
      ELSE 'Other categories'
      END Family, SUM(a.price*b.quantity) "Total monetary sales"
FROM products a, sales b
WHERE a.product_id = b.product_id
GROUP BY CASE
      WHEN a.family IN (SELECT * FROM top_family)
      THEN 'Most sold category'
      ELSE 'Other categories'
      END
ORDER BY 1;
</code></pre>
```

<p>An interesting fact is that if I replace the sub-query 'top_family' as defined in the code above directly into the code (so replace every every place containing top_family with the select * from (select ...) statement), it works and gives the desired result. </p>

<p>The problem should probably be caused by using the sub-query defined in a with statement.

<p>I'm having quite a hard time figuring out how to create two dynamic drop down menus.</p>

<p>I need to be able to populate the second drop down menu based on an item that was selected in the first drop down menu. I can populate all data in both menus, but it's not the desired result.</p>

<p>Menu 1 with catalyst notation:</p>

```
<pre><code>&lt;select name="select_productsuiteid" required="yes" onChange="return setmode('selectProdSuite',this.form)"&gt;
  &lt;option value="" selected="Selected"&gt;Please Select a Product Family&lt;/option&gt;
  [% FOREACH prod_fam IN prod_fams %]
    &lt;option value="[% prod_fam.fam_id %]"&gt;[% prod_fam.fam_name %]&lt;/option&gt;
  [% END %]
&lt;/select&gt;
</code></pre>
```

<p>Second menu with catalyst notation. This is the menu that should populate with products based on a product family ID from the chosen product family in the first menu.</p>

```
<pre><code>&lt;select name="select_productid" required="yes" onChange="return setmode('selectProd',this.form)"&gt;
  &lt;option value selected="selected"&gt;(no value)&lt;/option&gt;
  [% FOREACH prod IN prods %]
    &lt;option value="[% prod.prod_id %]"&gt;[% prod.prod_name %]&lt;/option&gt;
  [% END %]
&lt;/select&gt;
</code></pre>
```

21689906

dynamic menus using catalyst

<p>I'm trying to learn C# (and Linq-to-Xml) for handling of XML files, yet having some troubles. </p>

<p>I can get the elements and values, but my output is missing the information I need for logic decisions (id and state attributes in the transaction and target elements). </p>

<p>I think it has to do with the Descendants, but not sure how to grab them.</p>

<p>A little nudge in the right direction?</p>

<p>My XML File</p>

```
<pre><code>&lt;?xml version="1.0"?&gt;
&lt;xliff version="1.2"&gt;
  &lt;file source-language="en-US" datatype="plaintext" category="framework"&gt;
    &lt;body&gt;
      &lt;transaction approved="no" id="1"&gt;
        &lt;source xml:lang="en-US"&gt;Product Family&lt;/source&gt;
        &lt;target state="translated" xml:lang="en-US"&gt;Product Family&lt;/target&gt;
      &lt;/transaction&gt;
    &lt;/body&gt;
  &lt;/file&gt;
&lt;/xliff&gt;
</code></pre>
```

<p>C# Code</p>

```
<pre><code>private void btnOpen_Click(object sender, EventArgs e)
{
    // Show the dialog, using defaults, and get result
    OpenFileDialog ofdResult = new OpenFileDialog();

    if (ofdResult.ShowDialog() == DialogResult.OK)
    {
        try
        {
            if (ofdResult.OpenFile() != null)
            {
                XDocument xmlFile = XDocument.Load(ofdResult.FileName);
                // print elements recursively
                PrintElement(xmlFile.Root);
            }
        }
    }
}
```

I would like to combine two MDX queries from separate dimensions on columns.
Example:

Number of Sales/Product Type vs. Gender and State:

```
| CA | OR | WA | Male | Female  
-----  
food | 125 | 343 | 130 | 570 | 459  
-----  
drink | 123 | 465 | 135 | 678 | 343  
</code></pre>
```

State and Gender are their own respective dimensions, and I would like to do some aggregation (eg. sales count) across different product types (food, drink). Below is some idea of how this might work, although the queries can not be joined as they have different hierarchies. How might I go about tacking on male and female, for example, as columns in this result?

```
<pre><code>SELECT  
  
NON EMPTY  
  
{ [Store].[Store State].Members, [Gender].[Gender].Members } ON COLUMNS,  
  
{ [Product].[Product Family].Members } ON ROWS  
  
FROM [Sales]  
  
WHERE { [Measures].[Sales Count] }  
</code></pre>
```

Example error:
`MondrianEvaluationException: Expressions must have the same hierarchy`

Is there a way to do this effectively in MDX,? If so, may I a specify specific aggregations for each column (eg. aggregate state data by total sales, gender data by profit).

Thank you for your help

<p>So I have this DB: http://i.stack.imgur.com/pQD2Z.jpg</p>

<p>Every table has his ID which I use as PK's and FK's. What I need is to get the Product Family that has more sales by State, something like this: http://i.stack.imgur.com/PrEgl.png.</p>

<p>I'm doing something like this:</p>

```
<pre><code>select
    Sale_Details.state_id,
    Producto_Family.family_id,
    familia_producto.des_familia,
    SUM(Sale_Details.amount) as Amount
</code></pre>
```

<p>And then I do the group by and joints starting from <code>Sale_Details</code> all the way through <code>Product_Family</code>, but I can't get it right because I'm getting some <code>Product_Family</code> twice in different States.</p>

<p>I should get just one Product_Family per State, the one where it has more Sales of that Family, right?</p>

<p>I'm using SQL Server 2008 R2, by the way.</p>

23035924

Query with multiple joins

<p>i have the following two jpa hibernate entities, </p>

```
<pre><code>@Entity
public class Product {

    @Id
    @GeneratedValue(generator = "uuid")
    @GenericGenerator(name="uuid", strategy="uuid2")
    private String id;

    @ManyToOne
    private Type type;

    @ManyToOne
    private Attribute attribute;
}
</code></pre>
```

<p>and</p>

```
<pre><code>@Entity
public class ProductFamily {

    private static final long serialVersionUID = 1L;

    @Id
    @GeneratedValue(generator = "uuid")
    @GenericGenerator(name="uuid", strategy="uuid2")
    private String id;

    @ManyToMany
    @Formula("("
        + " SELECT t.id "
        + " FROM Type t "
        + " WHERE t.id IN ( "
        + "     SELECT p.type_id "
        + "     FROM product p"
        + "     WHERE p.family_id = id"
        + "   )"
        + " order by t.value asc "
        + " )")
    private Set<Type> types;
```


<p>I have two XML files i am trying to merge some elements using xsl.</p>

<p>XML1:</p>

```
<pre><code>&lt;ALL xmlns:a="http://example.com/ns1" xmlns:xsi="http://www.w3.
org/2001/XMLSchema-instance"&gt;
&lt;a:BusinessUnit&gt;
  &lt;a:businessUnitCode&gt;SGS&lt;/a:businessUnitCode&gt;
  &lt;a:longName&gt;Singapore Global Sourcing&lt;/a:longName&gt;
  &lt;a:parentBusinessUnitCode&gt;CGS&lt;/a:parentBusinessUnitCode&gt;
&lt;/a:BusinessUnit&gt;
&lt;a:BusinessUnit&gt;
  &lt;a:businessUnitCode&gt;EGH&lt;/a:businessUnitCode&gt;
  &lt;a:longName&gt;EMS Global HQ&lt;/a:longName&gt;
  &lt;a:parentBusinessUnitCode xsi:nil="true"/&gt;
&lt;/a:BusinessUnit&gt;
</code></pre>
```

<p></p>

<p>XML2:</p>

```
<pre><code>&lt;Get_ProductFamily xmlns:aa="http://example.com/ns2"&gt;
&lt;aa:ProductFamily&gt;
  &lt;aa:integrationId&gt;2323&lt;/aa:integrationId&gt;
  &lt;aa:parentBusinessUnitCode&gt;EGH&lt;/aa:parentBusinessUnitCode&gt;
&lt;/aa:ProductFamily&gt;
&lt;aa:ProductFamily&gt;
  &lt;aa:integrationId&gt;3434&lt;/aa:integrationId&gt;
  &lt;aa:parentBusinessUnitCode&gt;CGS&lt;/aa:parentBusinessUnitCode&gt;
&lt;/aa:ProductFamily&gt;
&lt;aa:ProductFamily&gt;
  &lt;aa:integrationId&gt;4545&lt;/aa:integrationId&gt;
  &lt;aa:parentBusinessUnitCode&gt;CDD&lt;/aa:parentBusinessUnitCode&gt;
&lt;/aa:ProductFamily&gt;
&lt;/Get_ProductFamily&gt;
</code></pre>
```

<p>output:</p>

```
<pre><code>&lt;GroupList&gt;
```

I am working on a highcharts stacked column with column drilldown graph. I based what I am doing in this example: <http://jsfiddle.net/NULTY/753/>

```
var chart;
$(document).ready(function() {

var colors = Highcharts.getOptions().colors,
    categories = ['MSIE', 'Firefox', 'Chrome', 'Safari', 'Opera'],
    name = 'Browser brands',
    level = 0,
    data = [{
        y: 55.11,
        color: colors[0],
        drilldown: {
            type: 'pie',
            name: 'MSIE versions',
            categories: ['MSIE 8.0', 'MSIE 6.0', 'MSIE 7.0', 'MSIE 9.0'],
            level: 1,
            data: [11,10.85, 7.35, 2.41],
            color: colors[0]
        }
    }, {
        y: 21.63,
        color: colors[1],
        drilldown: {
            type: 'pie',
            name: 'Firefox versions',
            categories: ['Firefox 3.6', 'Firefox 4.0', 'Firefox 3.5', 'Firefox 3.0', 'Firefox 2.0'],
            data: [13.52, 5.43, 1.58, 0.83, 0.20],
            color: colors[1]
        }
    }, {
        y: 11.94,
        color: colors[2],
        drilldown: {
            type: 'pie',
            name: 'Chrome versions',
            categories: ['Chrome 10.0', 'Chrome 11.0', 'Chrome 8.0', 'Chrome 9.0', 'Chrome 12.0',
                'Chrome 6.0', 'Chrome 5.0', 'Chrome 7.0'],
            data: [9.91, 0.50, 0.36, 0.32, 0.22, 0.19, 0.12, 0.12],
            color: colors[2]
        }
    }
    ]
    chart = new Highcharts.Chart({
        chart: {
            type: 'column',
            stacked: true,
            zoomEnabled: false
        },
        title: {
            text: 'Browser brands'
        },
        xAxis: {
            categories: categories,
            labels: {
                enabled: false
            }
        },
        yAxis: {
            labels: {
                enabled: true
            }
        },
        series: data
    });

    chart.drilldown('MSIE versions');
    chart.drilldown('Firefox versions');
    chart.drilldown('Chrome versions');
```

<p>I get the following error compiling my new universal app for Windows Phone and Desktop version 8.1:</p>

```
<pre><code> The SDK "MSAdvertisingXaml, Version=8.1" cannot be referenced alongside SDK(s) "MSAdvertisingXaml, Version=6.1", as they all belong to the same SDK product Family "Microsoft. Advertising". Please consider removing references to other SDKs of the same product family. </code></pre>
```

<p>They both use the same tool, AdControl, and it was running phone while I built the Windows Phone side of the app. Once I dropped the same control into the Windows Desktop side of the app, I get this error. I can't get ANYTHING to return when I Google the error message. What is the problem???

25649947

Windows 8.1 AdControl for Universal Apps (P

<p>I'm processing a data.frame of products called "<code>all</code>" whose first variable <code>all\$V1</code> is a product family. There are several rows per product family, i.e. <code>length(levels(all\$V1))</code> < <code>length(all\$V1)</code>.</p>

<p>I want to traverse the data.frame and process by product family "<code>p</code>". I'm new to R, so I haven't fully grasped when I can do something vectorially, or when to loop. At the moment, I can traverse and get subsets by:</p>

```
<pre><code>for (i in levels (all$V1)){
  p = all[which(all[, 'V1'] == i), ];
  calculateStuff(p);
}
</code></pre>
```

<p>Is this the way to do this, or is there a groovy vectorial way of doing this with <code>apply</code> or something? There are only a few thousand rows, so performance gain is probably negligible, but I'd like to develop good habits for larger data ses.</p>

26163209

R - traverse data.frame levels in loop or vecto

<p>I've got a page with 3 GridViews.</p>

```
<pre><code>&lt;div id="Export" runat="server" class="headeropt noprint"&gt;

    &lt;asp:LinkButton runat="server" ID="buttonexport" OnClick="buttonexport_Click"
OnClientClick="Javascript:Noshow();" CssClass="btn btn-default"&gt;
        &lt;asp:Image runat="server" ImageUrl="/images/Excel-16.gif" /&gt;
        &lt;asp:Label runat="server" Text="Export" /&gt;
    &lt;/asp:LinkButton&gt;
&lt;/div&gt;
&lt;div class="col-md-12"&gt;
    &lt;asp:GridView ID="grid1" runat="server" CellPadding="0" CssClass="table" CellSpacing="0"
OnRowDataBound="grid1_RowDataBound" AutoGenerateColumns="false" GridLines="Vertical"
BorderStyle="Solid" ShowFooter="true" OnRowEditing="grid1_RowEditing" datakeynames="grid1"
&gt;
        &lt;Columns&gt;
            &lt;asp:TemplateField HeaderText="Name"&gt;
                &lt;ItemTemplate&gt;
                    &lt;asp:LinkButton ID="lnkname" runat="server" CausesValidation="false"
CommandName="Edit" CommandArgument='&lt;%% Eval("name") %&gt;' Text='&lt;%% Eval("name")
%&gt;'&gt;&lt;/asp:LinkButton&gt;
                &lt;/ItemTemplate&gt;
            &lt;/asp:TemplateField&gt;
            &lt;asp:TemplateField HeaderText="Company"&gt;
                &lt;ItemTemplate&gt;
                    &lt;asp:Label ID="Label2" runat="server" Text='&lt;%% Eval("company") %&gt;'&gt;&lt;/asp:Label&gt;
                &lt;/ItemTemplate&gt;
            &lt;ItemStyle CssClass="alinha-direita" /&gt;
            &lt;FooterStyle CssClass="alinha-direita" /&gt;
        &lt;/asp:TemplateField&gt;
    &lt;/Columns&gt;
&lt;/asp:GridView&gt;

    &lt;asp:GridView ID="grid2" runat="server" CellPadding="0" CssClass="table" CellSpacing="0"
OnRowDataBound="grid2_RowDataBound" AutoGenerateColumns="false" GridLines="Vertical"
BorderStyle="Solid" ShowFooter="true" OnRowEditing="grid2_RowEditing" datakeynames="grid2"
&gt;
        &lt;Columns&gt;
            &lt;asp:TemplateField HeaderText="Product Family"&gt;
                &lt;ItemTemplate&gt;
```

I know that SandDisk Micro SD cards have bad block detection and re-mapping capability. The default mode for an SD card is the 4 bit SD interface. When using the SPI interface does anyone know if the SD card will still do this automatic bad block detection and re-mapping? Based on my reading the SanDisk OEM Product Manual

"The SPI Mode is a secondary communication protocol for cards in the SanDisk microSD Card Product Family. This mode is a subset of the SD Protocol, designed to communicate with an SPI channel, commonly found in Motorola and other vendors' microcontrollers. Detailed information about SPI Mode can be found in Section 7 or the SDA Physical Layer Specification, Version 3.01."

This does not seem to clarify my doubt. Does anyone know the answer?

26984152

Bad block detection in SD card using SPI inter

<p>In a huge products query, I'm trying to get the prices for the last buy for every element. In my first approach, I added a sub-query, on the buys table ordering by date descendant and only getting the first row, so I ensure I got the latest row. But it didn't show any values. Now that I see it again, it's logical, as the sub-query still doesn't have a restriction for the product then lists all the buys and gets the latest one, that doesn't have to be for the product currently being processed by the main query. so returns nothing.</p>

<p>That's the very simplified code:</p>

```
<pre><code>SELECT P.ID, P.Description, P... blah, blah
FROM Products
LEFT JOIN (
  SELECT TOP 1 B.Product,B.Date,B.Price --Can't take out TOP 1 if ORDER BY
  FROM Buys B
  --WHERE... Can't select by P.Product because doesn't exist in that context
  ORDER BY B.Date DESC, B.ID DESC
) BUY ON BUY.Product=P.ID
WHERE (Some product family and kind restrictions, etc, so it processes a big amount of products)
</code></pre>
```

<p>I thought about an embedded query in the main select stmt, but as I need several values it would imply doing a query for each, and that's ugly and bad.</p>

<p>Is there a way to do this and avoid the infamous LOOP? Anyone knows the Good?</p>

27109380

SQLServer get top 1 row from subquery

I'm building a shopping cart. In my shopping cart an item can be composed of other items. I need to display a set of items with their corresponding associated parts in a single template. I know how to show a single item with its corresponding parts in a template, but I can't seem to figure out how to show more than one item, each with its own list of included parts.

I have fiddled with every permutation of tags in the template file:

```
# checkout.html

{% for item in cart_items %}
    <tr>
        <td class="left">
            {{ item.name }}
            <ul>
                {% for part in item.product.buildpart.part_set.all %}
                    <li>{{ part.name }}
                {% endfor %}
            </ul>

        </td>
        <td>${{ item.price }}</td>
        <td>{{ item.quantity }}</td>
        <td class="right">${{ item.lineItemTotal }}</td>
    </tr>
{% endfor %}
</code></pre>
```

Here is the view that generates the template:

```
# views.py

def checkout(request):
    cart_items = get_cart_items(request)

    <snip>

    return render(request, 'checkout.html', locals())
</code></pre>
```

And here's the `get_cart_items()` function that returns all the items in the user's shopping cart:

I am working on the existing view in SQL Server. My user reported now the performance is too slow. Can some one please let me know how can I increase the performance of the query/View

Query:

```
Select FH.ForecastID
,FH.FiscalYear
,FH.FiscalMonth
,FH.ForecastStatusCode
,FH.ForecastStatusDescription
,WF.SubTypeID
,WF.CustomerCode
,WF.ProductID
,WF.EndCustomerName
,CU.RELShortName [Master Customer 1]
,CASE WHEN (WF.EndCustomerName <> '' ) THEN CASE WHEN (CST.[Shortname] IS NULL )
THEN      CU.ShortName ELSE CST.[Shortname] END ELSE CU.ShortName END AS
CustomerShortName
,CASE WHEN (WF.EndCustomerName <> '' ) THEN CASE WHEN (CST.[Shortname] IS NULL )
THEN CASE WHEN  (CU.[CUSTOMER_CATEGORY] = 'ASU') THEN 'AU' ELSE 'GP' END ELSE CASE
WHEN (CST.[CUSTOMER_CATEGORY] = 'ASU') THEN 'AU' ELSE 'GP' END END ELSE CASE WHEN (CU.
[CUSTOMER_CATEGORY] = 'ASU') THEN 'AU' ELSE  'GP' END END AS CustomerCategory
, '' as CustomerShortName
,WF.EndCustomerName as [Disti End Customer]
,CU.CustomerName [Sold To Customer Name]
,WF.CustomerCode [Customer Sold To Number]
,CU.CustomerClass
,CASE WHEN (CU.CustomerClass <> 'Distributor' ) THEN CU.TerritoryCode ELSE WF.[Sales
Office] END  AS [Sales Office]
,FH.REA_Onshore [Off Shore On Shore]
,PR.ProductFamilyName [OSC Product Family(1)]
,PR.ProductClassName [OSC Product Family(2)]
,PR.ProductPartNumber
,FH.ForecastTypeID
,FH.ForecastTypeCode
,FH.ForecastTypeDescription as ForecastTypeDescription
,WF.SubType
, ISNULL(WF.CreatedDate , '') CreatedDate
, ISNULL(WF.ModifiedDate, '') ModifiedDate
,WF.ModifiedBy
,IsNull([MON-3], '0') [MON-3]
```


<p>I modified the Product entity form for a particular CRM environment in 2015. However, I don't see a + sign to add Bundle Products to it.</p>

<p>However, in my trial environment, I'm easily able to do so.</p>

<p>Not sure what went wrong. I checked for both Draft bundle and Active Bundle.</p>

<p>PS: I'm not using Product Family.</p>

28046951

Can't add Bundle Products to a created Bund

```
<p><code>&lt;asp:HyperLinkField DataNavigateUrlFields="runId" DataTextField="Percent"
ControlStyle-CssClass="hlink" HeaderText="% SEEN" ItemStyle-Width="6%"
DataNavigateUrlFormatString="run.aspx?runId={0}" ItemStyle-Font-Underline="true"/></code>> </p>
```

<p>The above is a column from my grid view.Lets call this column 'x'.</p>

<p>I am trying to control the value of x in .cs file as below:</p>

```
<pre><code>protected void GridView2_RowDataBound(object sender, GridViewRowEventArgs e)
{
    if (e.Row.Cells[8].Text.Equals("0"))
    {
        e.Row.Cells[13].Text = "0%";
        return;
    }

    int p,q;
    GridViewRow item = e.Row;
    SqlConnection con = new SqlConnection(connectionstring.ToString());
    string selectSQL = " SELECT COUNT(*) AS 'Count' FROM Analysed WHERE runId =@myvar group by
runId";
    SqlCommand cmd = new SqlCommand(selectSQL, con);
    cmd.Parameters.AddWithValue("@myvar", item.Cells[0].Text);
    SqlDataReader reader;
    try
    {
        con.Open();
        Int32.TryParse(item.Cells[8].Text, out p);
        reader = cmd.ExecuteReader();
        if (reader.HasRows)
        {
            reader.Read();
            Int32.TryParse( reader["Count"].ToString(),out q);
            item.Cells[13].Text =(q/p).ToString() + "%";
        }
        reader.Close();
    }
}
```

<p>I am in desperate need of help. I have been stuck on this problem for days now and have been looking all over the internet, you are my last hope.</p>

<p>I've been trying to create a Windows Installer using WIX and all seems well until I try to customize the standard UI's (minimal to be specific).</p>

<p>I am trying to create a custom dialog that will go into the Minimal UI set that will allow the user to choose to different kinds of install - this seems to be an impossible task.</p>

<p>When I do attempt the customization the compile brings an error. Please help.</p>

<p>Product.wxs</p>

```
<pre><code>&lt;?xml version="1.0" encoding="UTF-8"?&gt;
```

```
&lt;Wix xmlns="http://schemas.microsoft.com/wix/2006/wi"
    xmlns:util="http://schemas.microsoft.com/wix/UtilExtension"&gt;
```

```
&lt;?define vendor="Vendor" ?&gt;
&lt;?define productName="Product Name" ?&gt;
&lt;?define vendorAndProductName="$ (var.vendor) $ (var.productName)" ?&gt;
```

```
&lt;!--
    The language 1033 and codepage 1252 refer to 'English, US'
    See:
    http://msdn.microsoft.com/library/default.asp?url=/library/en-
    us/msi/setup/localizing_the_error_and_actiontext_tables.asp
--&gt;
```

```
&lt;Product Id="*"
    Name="$ (var.vendorAndProductName)"
    Language="1033"
    Codepage="1252"
    Version="$ (var.version)"
    Manufacturer="$ (var.vendor)"
    UpgradeCode="c338cb1c-8a1d-44e4-9aff-b2ad82f095fb"&gt;
    &lt;!--GUID defines product family, installed newer product versions in the same family
will replace older versions--&gt;
```

```
&lt;Package Id="*"
    Keywords="$ (var.vendor) atm vm"
    Description="$ (var.vendor) $ (var.productName) installer"
```

I am currently programming a CPLEX/OPL model using IBM ILOG CPLEX Optimization Studio. I have a problem with using sums or indexes which contain a subset and depend on another parameter/variable, e.g. check the following constraints: NB 2,3,4,8).

Can anyone help me with incorporating these constraints properly?

Please find the source code attached:

```
//Parameter

int maxblock=...;      //number of blocks (I)
int maxprodfam=...;    //number of product families (J)
int maxprod=...;       //number of products (P)
int maxdemand=...;     //number of demand elements (K)

range blocks=1..maxblock;
range prodfam=1..maxprodfam;
range products=1..maxprod;
range demandelements=1..maxdemand;

int startalpha[blocks]=...; //earliest start time of block i
int endalpha[blocks]=...;   //latest completion time of block i
int prodtime[products]=...; //unit production time for product p (a)
int minorsetup[products]=...; //minor setup time per sub-lot of product p (s)
int majorsetup[prodfam]=...; //major setup time for product family j (S)
int demand[products]=...;   //demand elements (d)

//Variablen

dvar int+ x[blocks][demandelements]; //quantity of demand element k satisfied from production in
block i (x)
dvar boolean y[blocks][prodfam];     //product family assessment to blocks (y)
dvar boolean q[blocks][products];    //product assessment to blocks
dvar boolean o[blocks];              //activation of blocks (e.g. if a prodfam is assigns to it)
dvar int+ alpha[blocks];              //start time block
dvar int+ duration[blocks];          //duration of block

//Modell

minimize
alpha[maxblock]+duration[maxblock]; //objective function (minimize the makespan)
```

<p>I have a excel as below:

</p>

<p>For each Sales level3 we have a set of "product family" and a set of "country", now I wish to get a output as:</p>

<p></p>

<p>Each country to have all product families against it. Tried with Vlookup/Index/Match, however I was not able to get the desired output, I would need the output for all countries and sales level3</p>

30451273

Creating a table in excel based on column val

<p>I'm using XCTU to test sending packets. My xbee radio is configured as a Coordinator API-2 (product family XB24-ZB, firmware version 21A7, MAC address 0013A20040BCE8CB). I'm send the following transmit request frame bytes:</p>

<blockquote>
<p>7E 00 12 10 01 00 00 00 00 00 00 00 FF FE 00 00 01 02 03 04 E7</p>
</blockquote>

<p>The receive packet frame has the following bytes in the frame detail panel:</p>

<blockquote>
<p>7E 00 10 90 00 7D 33 A2 00 40 BC E8 CB 00 00 01 01 02 03 04 00</p>
</blockquote>

<p>My problem are the bytes in bold text (the sender's 64 bit address).</p>

<p>The correct bytes, as I understand it, should be:</p>

<blockquote>
<p>00 13 A2 00 40 BC E8 CB</p>
</blockquote>

<p>The checksum for the bytes as I receive them are wrong (0x9C).</p>

<p>However, if I substitute the correct bytes (i.e., I replace 00 7D 33 with 00 13, the checksum value is correct (0xFF).</p>

<p>I see this behavior in my Arduino code as well. I thought it was me, but I get the exact same behavior there (and in a C# project as well) as I get in the XCTU application. (Specifically, the 64 bit address always has 00 7D 33 where I'm expecting 00 13. What am I missing?</p>

<p>Thanx</p>

30469979

Xbee recieve packet 64 bit address is wrong?

<p>I have a C# .Net collection of solutions which started as a proof of concept, and has grown to almost 15 different projects. I am currently in the process of rewriting the whole product family, and trying to maintain best practices to the best of my abilities, with future-proof organisation. </p>

<p>I have done some research, and I am still unclear on the best place to keep delegates in a multi-project product to minimise the likelihood of a need for refactoring in the future. </p>

<p>I would assume the general consensus is that you place them anywhere that makes sense for the use case, but in general I feel there is a best way to structure everything in a solution to minimise problems, promote positive modularity, and ease maintenance. </p>

<p>In many cases it is recommended that they travel with where they are used; presumably declared in the namespace above the class file, which in my case would translate to my common library with the common interfaces which mandate the events. I currently have delegates in their own file, in a 'delegate' namespace. Is there an oversight I am making by doing so, or am I overcomplicating the use case for delegates - or is this inline with current usage expectations?</p>

<p>I have done the typical searches, but haven't found anything credible nor substantial; however this could be a consequence of poor keyword selection.</p>

30587714

Where to put Delgates in .Net Solution

<p>I need to limit the choices in a Django Admin form but cannot come up with a solution. Given these models:</p>

```
<pre><code>class ProductFamily(models.Model):
    name = models.CharField(max_length=250)
    default_product_to_display = models.OneToOneField('Product', limit_choices_to=
{'product_family': ??????})
    # Enclosing Product reference in quotes is necessary since the Product declaration is below
ProductFamily declaration

class Product(models.Model):
    name = models.CharField(max_length=250)
    image = models.ImageField(upload_to='images/', blank=True, null=True)
    product_family = models.ForeignKey(ProductFamily)
</code></pre>
```

<p>What should be placed in the ??????'s in class ProductFamily? I've tried everything I can think of including name, 'name' ProductFamily, 'Product Family', self, self.id. The options with self return an Internal Server Error. The quoted options return: 'invalid literal for int()'. When "name" is used unquoted, it returns:

int() argument must be a string or a number, not 'CharField'.

If I put a hard-coded integer value in to test it, then it works fine, so it is obviously looking for an integer value.

I also tried, without success, placing both

id = models.AutoField(primary_key=True)

in the declaration with id at the ??????'s as well as defining a function that returns self.id, but none of this works. </p>

<p>So - how do I limit the selection of products by showing only those whose product_family id's match those of the current ProductFamily?</p>

30689964

How to fill value in a limit_choices_to option

<p>This program takes input from user product name, product class and product family and then stores it into a file. But after giving inputs and pressing enter program crashes saying product.exe has stopped working.</p>

<p>Here's the code-</p>

```
<pre><code>#include <stdio.h>
#include <conio.h>

void add_new_product(void);
struct product
{
    char P_name;
    char P_class;
    char P_family;
}P[100];
FILE *fp;
void add_new_product()
{
    char ch;
    int i=0;
    fp=fopen("product.txt","w+");
    do
    {
        clrscr();
        printf("\t\t\t Add New Product");
        printf("\n User:");
        printf("\n\n \t\t\t 1.Product Name  :");
        printf("\n\n \t\t\t 2.Product Class  :");
        printf("\n\n \t\t\t 3.Product Family :");
        gotoxy(44,5);
        scanf("%s",&P[i].P_name);
        gotoxy(44,7);
        scanf("%s",&P[i].P_class);
        gotoxy(44,9);
        scanf("%s",&P[i].P_family);
        fprintf(fp,"%s %s %s %s %s %s",P[i].P_family,"|",P[i].P_class,"|",P[i].P_name,"");
        printf("\n \t\t Do you want to add another product?(Y/N) :");
        scanf("%s",&ch);
        i++;
    }while((ch=='Y')||(ch=='y'));
```

<p>I've a table with documents in the format of </p>

```
<pre><code>{
  "_id" : ObjectId("55867f3bfe2b0bea9c634ded"),
  "Best Site CR GU Party ID" : 14783,
  "Best Site CR GU Party Name" : "AUTOMOBILE INSURANCE COMPANY",
  "Product ID" : "C5500",
  "Product Family" : "C5000",
  "Product Description" : "5500 Chassis",
  "Best Site CR Party ID" : 45714558,
  "Best Site CR Party Name" : "INSURANCE COMPANY",
  "LDoS" : "4/27/2008",
  "LDoS FY" : 2008,
  "List Price $" : 3495,
  "Collector View" : "No"
}
</code></pre>
```

<p>and I'm using mongodb java driver 3.0.2. The intention is to aggregate the prices and number of documents for each month of every year in the collection. I've created the following function for map, which works on MongoVUE and fails with the java driver:</p>

```
<pre><code>function Map() {
  var currentYr = new Date().getFullYear();
  var ldoMonth = this['LDoS'].split(/[/-]/)[0].replace(/^0+/, '');
  var key = {partyId: this['Best Site CR GU Party ID'], year: this['LDoS FY'], month: parseInt
(ldoMonth)};

  emit(key, {price: this['List Price $'], count: 1});
}
</code></pre>
```

Exception in thread "main" com.mongodb.MongoCommandException: Command failed with error 16722: 'exception: TypeError: Object 42582 has no method 'split'
at Map (_funcs1:1:99) near '['LDoS'].split(/[/-]/)[0].replace(/^0+/' ' on server localhost:27017.
The full response is { "errmsg" : "exception: TypeError: Object 42582 has no method 'split'\n at Map (_funcs1:1:99) near '['LDoS'].split(/[/-]/)[0].replace(/^0+/' ", "code" : 16722, "ok" : 0.0 }
at com.mongodb.connection.ProtocolHelper.getCommandFailureException(ProtocolHelper.java:77)
</code></pre>

<p>How can I resolve this ? For the sake of completeness, here's the reduce function:</p>

I have two tables, t1,t2 in schema - 'Schema',
t1 has 1 million rows and around 30 columns.

I am running a query like one given below,

```
<pre><code>select b.Contract_ID,
b.Signed,
b.Funding_Source,
b.Theater, b.Country,
b.Partner, b.BEID,
b.Contract_Type, b.TCV,
b.Technology,
b.Partner_Signature_Date,
b.Signature_Date, b.Term,
b.Purchase_Order,
b.Contract_Baseline,
b.Organic_Rate, b.Target_Organic,
b.Target_Incremental,
b.Total_Bookings_Target,
b.Tracking_Start,
b.Tracking_End, b.Qualifier_BEID,
b.Qualifier_BEGeoID,
a.`CSC Global Ultimate ID`,
a.`CSC Company Target ID`,
b.Qualifier_Theater,
b.Qualifier_Country, a.SCMS,
b.Qualifier_POType, b.MCO,
b.Contract_Status, b.Accrual_Start,
b.Accrual_End, b.Booking_Start,
b.Booking_End, b.TMS_Level_1,
b.TMS_Level_2, b.TMS_Level_3,
b.Pf,
b.Allocation,a.`Fiscal Period ID`,
a.Bookings*b.Allocation as Bookings
from
(SELECT * FROM `Schema`.`t1` where `BEID` in
(select distinct (BEID) from Schema.`t2`)) a
INNER JOIN
(SELECT * FROM `Schema`.`t2`) b
where
a.`Business Entity Id` = b.Qualifier_BEID
```


<p>First of all sorry as I may sound quite stupid while asking this.</p>

<p>I want to understand the practical usage of abstract design pattern. Which all APIs have implemented this pattern and under what all use case. </p>

<p>One of the use case which strikes me immediately is the DI of objects which need to be created using run time information.</p>

<p>I have the understanding that this pattern is used to create object of various product families. But for every new product family we have to change the existing factories. Also if there is an addition implementation of any product family we have to provide a new factory for this new implementation.</p>

<p>For example </p>

<p>I have products Frame and TextBox for two types of OS (Windows and MAC). Now we will have two factories one for each Window and Mac so that WindowFactory returns textbox and frame for Windows and MacFactory return the same objects for MAC. Now say I want to add another OS say Solar then in this case I need to write a new factory which returns the corresponding objects for solar.</p>

<p>How API use this patterns in real world?</p>

31569817

Abstract Factory method practice or usage of

<p>I'm trying to build a code that will filter a table by product type, of which there might be multiple items. I need the table to filter through each of the product types to build a hierarchy for each product family.</p>

<p>I'm thinking it should be something like:</p>

```
<pre><code>Sub familyfilter()
```

```
With ActiveSheet.ListObjects(1)
```

```
For Each Item In .Columns(1)
```

```
.AutoFilter.ShowAllData
```

```
.Columns(1).autofilterrange.AutoFilter Field:=3, Criteria1:=Item
```

```
'[insert sub call here for hierarchy]
```

```
Next Item
```

```
End With
```

```
End Sub
```

```
</code></pre>
```

<p>I won't know the values in the family column, so I can't set a list of values to cycle through.</p>

<p>So if anyone knows how to do this for all the items in the column, I'd appreciate it!!</p>

<p>Thanks</p>

31748777

Loop filters for all items in table column of ex

I want to create a new variant group in Akeneo with some fixed attributes to "simulate" the behaviour of a product family. Unfortunately I don't know how to get a `ProductTemplate` with some attributes with empty values.

When I tried my code below, I get an error after opening the created variant group in the Akeneo GUI:

```
Error: Option "attributes" must only contains instances of
"Pim\Bundle\CatalogBundle\Entity\Attribute", got
"Pim\Bundle\EnrichBundle\Form\Type\AvailableAttributesType"
```

My code looks like this:

```
$groupType = $this->groupManager
->getGroupTypeRepository()
->findOneBy(['code' => 'VARIANT']);
$group = $this->groupFactory->createGroup($groupType);
$group->setCode('MY_VARIANT_GROUP');

$attributes = array($this->attributeRepository->findOneByIdentifier('AXIS_ATTRIBUTE'));
$group->setAxisAttributes($attributes);

// ??? How can I create a new product value?
$productValue1 = new ProductValue();
$productValue1->setId('PREDEFINED_ATTRIBUTE1');
$productValue1->setAttribute($this->attributeRepository->findOneByIdentifier
('PREDEFINED_ATTRIBUTE1'));

$productTemplate = new ProductTemplate();
$productTemplate->setValuesData(array($productValue1));

$group->setProductTemplate($productTemplate);
$this->groupSaver->save($group);
```

<p>Following is the code which i am trying to search WT part </p>

```
<pre><code>public static WTSet searchWTPart(String partNumber, String type, boolean exactMatch
,String productfamilyforjsp,String ordertypeformjsp) throws WTEException {
```

```
    System.out.println("Method partNumber "+partNumber);
    long branchId = 0;
    int iPartMaster, iPart;
    String criteria;
    QueryResult qr = null;
```

```
    //wt.pds.PartialResultException qr1 = new PartialResultException(arg0);
    QuerySpec qs= new QuerySpec();
    iPartMaster = qs.addClassList(WTPartMaster.class,true);
```

```
    int defindex = qs.addClassList(StringDefinition.class, false);
    int valueindex = qs.addClassList(StringValue.class, false);
```

```
    // search product Family as per jsp product family Input
```

```
    if(productfamilyforjsp.equalsIgnoreCase("Helical/Emill"))
    {
        productfamilyforjsp="Helical";
    }
```

```
    if(productfamilyforjsp.equalsIgnoreCase("Fluid Coupling"))
    {
        productfamilyforjsp="Fluid Coupling";
    }
```

```
    if(productfamilyforjsp.equalsIgnoreCase("Worm/Altra"))
    {
        productfamilyforjsp="Worm";
    }
```

```
    if(productfamilyforjsp.equalsIgnoreCase("Gear Motor"))
    {
        productfamilyforjsp="Geared motor";
    }
```

```
    if(productfamilyforjsp.equalsIgnoreCase("Blower"))
```


I have a `GridView` control, and inside of this control I have defined a link button using `GridView.ItemTemplate`.

I am using this to open a new window on click. When I click on the link button, however, the page refreshes before opening the new window.

How can I stop the page from refreshing after the link button is clicked?

HTML

```
<pre><code>    <asp:UpdatePanel ID="UpdatePanel4" runat="server">
        <ContentTemplate>

            <asp:GridView ID="DataGrid1" style="visibility:visible" runat="server"
AlternatingRowStyle-BackColor="#E9EDF5" Font-Names="Arial"
                ForeColor="#09538A" Font-Size="12px" BackColor="#ffffff" BorderColor="
DarkGray" Font-Bold="true"
                HeaderStyle-BackColor="#298DC7" EnableViewState="false" CellSpacing="20"
                CellPadding="10" HeaderStyle-Font-Bold="true" AutoGenerateColumns="
False" OnRowCommand="DataGrid1__RowCommand" OnRowDataBound="
DataGrid1__RowDataBound" >
                <HeaderStyle Font-Names="Arial;" CssClass="MyHeaderStyle" Font-Size="
13px" ForeColor="White" Font-Bold="True" Height="20" BackColor="#298DC7" ><
/HeaderStyle>
                <asp:templatefield headertext="NDC" ItemStyle-CssClass="col" ItemStyle-HorizontalAlign="
Justify" HeaderStyle-Width="10%" ItemStyle-Width="10%">
                    <Columns>
                        <itemtemplate>
                            <asp:linkbutton id="productcode" ForeColor="#09538A" runat="server" text='&lt;%=Eval
("product code")%>'\></asp:linkbutton>

                        </itemtemplate>
                    </asp:templatefield>
                </asp:GridView>
            </ContentTemplate>
        </asp:UpdatePanel>

        <asp:AjaxToolkit:ModalPopupExtender ID="ModalPopupExtender1"
BackgroundCssClass="modalBackground" CancelControlID="cancel" TargetControlID="Button3"
runat="server" PopupControlID="pnlpopup"> </asp:AjaxToolkit:ModalPopupExtender>

        <asp:Button ID="Button2" runat="server" Text="Cancel" Width="100px" Height="20px" />
    </code></pre>
```

I have a `GridView` control, and inside of this control I have defined a link button using `GridView.ItemTemplate`.

I am using this to open a new window on click. When I click on the link button, however, the page refreshes before opening the new window.

How can I stop the page from refreshing after the link button is clicked?

Pop up is not displaying when i add Update panel to first grid

if i remove Update panel from first grid, grid is refreshing and popup is displaying

I need to open a popup without refreshing my grid

PLEASE FIND ME THE SOLUTION FOR THIS AS I WAS WORKING ON THIS FROM PAST 2 DAYS

HTML

```
<code>&lt;%@ Page Language="c#" AutoEventWireup="false" CodeFile="ViewData1.aspx.cs" Inherits="ablesas.ViewDataUI1" EnableEventValidation="false"%>
```

```
&lt;asp:UpdatePanel ID="UpdatePanel4" runat="server">
    &lt;ContentTemplate>
```

```
        &lt;asp:GridView ID="DataGrid1" style="visibility:visible" runat="server"
AlternatingRowStyle-BackColor="#E9EDF5" Font-Names="Arial"
        ForeColor="#09538A" Font-Size="12px" BackColor="#ffffff" BorderColor="
DarkGray" Font-Bold="true"
        HeaderStyle-BackColor="#298DC7" EnableViewState="false"
CellSpacing="20"
        CellPadding="10" HeaderStyle-Font-Bold="true"
AutoGenerateColumns="False" OnRowCommand="DataGrid1__RowCommand"
OnRowDataBound="DataGrid1__RowDataBound" >
        &lt;HeaderStyle Font-Names="Arial;" CssClass="MyHeaderStyle" Font-
Size="13px" ForeColor="White" Font-Bold="True" Height="20" BackColor="#298DC7" >&lt;
/HeaderStyle>
```

```
        &lt;asp:templatefield headertext="NDC" ItemStyle-CssClass="col" ItemStyle-HorizontalAlign="
Justify" HeaderStyle-Width="10%" ItemStyle-Width="10%">
        &lt;Columns>
```

```
        &lt;itemtemplate>
```

```
        &lt;asp:linkbutton id="productcode" ForeColor="#09538A" runat="server" text='&lt;%
```

I have a `GridView` control, and inside of this control I have defined a link button using `GridView.ItemTemplate`.

I am using this to open a new window on click. When I click on the link button, however, the page refreshes before opening the new window.

How can I stop the page from refreshing after the link button is clicked?

Pop up is not displaying when i add Update panel to first grid

if i remove Update panel from first grid, grid is refreshing and popup is displaying

I need to open a popup without refreshing my grid

PLEASE FIND ME THE SOLUTION FOR THIS AS I WAS WORKING ON THIS FROM PAST 2 DAYS

HTML

```
<code>&lt;%@ Page Language="c#" AutoEventWireup="false" CodeFile="ViewData1.aspx.cs" Inherits="ablesas.ViewDataUI1" EnableEventValidation="false"%>
```

```
&lt;asp:UpdatePanel ID="UpdatePanel4" runat="server">
    &lt;ContentTemplate>
```

```
        &lt;asp:GridView ID="DataGrid1" style="visibility:visible" runat="server"
AlternatingRowStyle-BackColor="#E9EDF5" Font-Names="Arial"
        ForeColor="#09538A" Font-Size="12px" BackColor="#ffffff" BorderColor="
DarkGray" Font-Bold="true"
        HeaderStyle-BackColor="#298DC7" EnableViewState="false"
CellSpacing="20"
        CellPadding="10" HeaderStyle-Font-Bold="true"
AutoGenerateColumns="False" OnRowCommand="DataGrid1__RowCommand"
OnRowDataBound="DataGrid1__RowDataBound" >
        &lt;HeaderStyle Font-Names="Arial;" CssClass="MyHeaderStyle" Font-
Size="13px" ForeColor="White" Font-Bold="True" Height="20" BackColor="#298DC7" >&lt;
/HeaderStyle>
```

```
        &lt;asp:templatefield headertext="NDC" ItemStyle-CssClass="col" ItemStyle-HorizontalAlign="
Justify" HeaderStyle-Width="10%" ItemStyle-Width="10%">
        &lt;Columns>
```

```
        &lt;itemtemplate>
```

```
        &lt;asp:linkbutton id="productcode" ForeColor="#09538A" runat="server" text='&lt;%
```

<p>I'm working with our IT group to develop an optimizer for logistics operations. The basic design is that it will look at shipments, run a search for additional shipments originating within XX miles of the previous shipment's destination, and link them together in a loop. It will continue to do this until it hits a user-defined set of shipment legs where the loop ends at or close to 1st shipment origin.</p>

<p>The issue we are facing is that the materials we ship are chemicals, which can have interactions if placed in a tank that contained XX chemical before it. The obvious solution is to use a different tank or wash it out, but we also need it to compute solutions prior to that.</p>

<p>My problem is, currently, there is no way on the market to do that prior product optimization.</p>

<p>The question is: Is there some kind of logic table function I can write that will allow the optimizer to see an element in the data set (say, Product Family of 1) that will pull from a product database containing predefined product families (i.e. PF 1 = Chemicals A1-B7, PF 2 = Chemical B8-J8, etc.) and then ping off of a logic table that defines a do not ship with list (i.e. PF 1 cannot ship if PF 2 was on the previous leg.</p>

33001749

Using an element in a data set to drive If/The

<p>I have the following query result:</p>

<p></p>

<p>But I want to group the results by number, and categorize the quantity by month, so the resulting output would be:</p>

<p></p>

<p>How can I create a month bucket to pick up the date and make it a column and place the values accordingly. Here is my attempt so far:</p>

```
<pre><code>select convert(varchar,year(NewShipDate)) + 'M' + MonthBucket,
*
from(

select ItemNumber, des.[Product Family], ItemDescription, des.Country, month(RequestedShipDate)
as 'Month', ItemOrderedQuantity
from FS_COLine co
join FS_Item it on co.ItemKey = it.ItemKey
left outer join FIN_PLANCAP_2..ProductDescriptions des on it.ItemNumber collate database_default
= des.RICNum
where RequestedShipDate &gt;= convert(datetime, '01/01/2016', 120) and
    RequestedShipDate &lt;= convert(datetime, '12/31/2016', 120) and
    isNumeric(it.ItemNumber) = 1 and
    isNumeric(des.RICNum) = 1
    --and it.ItemNumber = 35191305
group by ItemNumber, des.[Product Family], ItemDescription, des.Country, month
(RequestedShipDate), ItemOrderedQuantity
order by ItemNumber
)A
</code></pre>
```

<p>tnis is a long function but the key problem is in the char* variables..
**the function was working fine before i have trasformed it to store the data instead of print to console.</p>

<p>i have tried to use <code>char[]</code> instead of <code>char*</code> that's when i got some buffer overrun error, so now as it is allocated, it shows ??? all over the console.
what is the correct way to concat and use <code>char*</code> on <code>puts();</code></p>

```
<pre><code>MySystemInfo Msi;
puts(Msi.getOsInfo());
```

```
char* MySystemInfo::getOsInfo()
{
    OSVERSIONINFOEX osver;
    BOOL bOsVersionInfoEx;
    HKEY hKey;
    LONG lRet;
    char* RtTmpOsInfo= (char *) malloc(sizeof(char)*70);
    char* s1=(char *) malloc(sizeof(char)*20);
    char* s2=(char *) malloc(sizeof(char)*50);

    // Try calling GetVersionEx() using the OSVERSIONINFOEX structure.
    // If that fails, try using the OSVERSIONINFO structure.
    ZeroMemory(&osver, sizeof(OSVERSIONINFOEX));
    osver.dwOSVersionInfoSize = sizeof(OSVERSIONINFOEX);
    if(!bOsVersionInfoEx = GetVersionEx((OSVERSIONINFO *) &osver))
    {
        osver.dwOSVersionInfoSize = sizeof(OSVERSIONINFO);
        if(!GetVersionEx((OSVERSIONINFO *) &osver))
            return "";
    }

    switch (osver.dwPlatformId)
    {
        //Test for the Windows NT product family.
        case VER_PLATFORM_WIN32_NT:

            if(osver.dwMajorVersion < 4) return "";
            sprintf( s1,"v%d.%d "+ osver.dwMajorVersion, osver.dwMinorVersion);
            //Test for the Windows NT product family.
            if(osver.dwMajorVersion < 4) return "";
            sprintf( s2,"v%d.%d "+ osver.dwMajorVersion, osver.dwMinorVersion);
            return s1+s2;
        }
    }
}
```

<p>I have controller actions which have AuthorizeAttribute on them</p>

<p>Often someone will try an old url which will take them (forms authentication) to the logon page and then redirect to the url, but it may be for whatever reason that they are no longer allowed to access to that page</p>

<p>Is there any way of testing the url before redirecting?</p>

<p>I can decompose the url into the area/controller/action and test it but it feels clumsy to do that</p>

<p>(Extra info)</p>

<p>Our site is part of a product family, in the desktop app we can determine who has access to what parts. e.g. we may have a clocking page, a user accesses it and keeps the url. In the main product we remove their access to this page, the authorizeattribute now says they don't have access to it.</p>

<p>So we get</p>

<p>they try to access the url</p>

<p>forms authentication says they don't have access and reroutes to the logon page</p>

they logon, however they still don't have access to this page and they are redirected again to the logon page.

33367382

AuthorizeAttribute, anyway of checking in ad

<p>I have a created a macro for my spreadsheet which can sent out emails successfully. </p>

<p>However, it can only send e-mails of each individual part numbers which are over the due date. Which means if I have 100 over the due date part numbers, there will be 100 emails being sent out. </p>

<p>I would like my macro to send the email by a range of cells which are of similar product (eg. printer) and are over the due date. There can be other products like laptop, camera, webcam as well. I need to do this as i don't want to spam the receiver's inbox.</p>

<p>How do I do that?</p>

```
<pre><code>Sub LabelArtworkRelease()
```

```
Dim OutApp As Object
Dim Message1 As Object
Dim cell As Range
Dim emailBody As String
Dim Signature As String
```

```
'GET DEFAULT EMAIL SIGNATURE
```

```
Signature = Environ("appdata") & "& "\Microsoft\Signatures\"
```

```
If Dir(Signature, vbDirectory) <& vbNullString Then
```

```
    Signature = Signature & Dir$(Signature & "*.htm")
```

```
Else:
```

```
    Signature = ""
```

```
End If
```

```
Signature = CreateObject("Scripting.FileSystemObject").GetFile(Signature).OpenAsTextStream(1,
```

```
-2).ReadAll
```

```
'End
```

```
Application.ScreenUpdating = False
```

```
'Create a new Outlook session
```

```
Set appOutlook = CreateObject("Outlook.Application")
```

```
On Error GoTo cleanup
```

```
'Declare header variables
```

```
partnumber = Range("A3").Value
```

```
productfamily = Range("B3").Value
```


<p>Product family: XBP24-ZB
Function set: ZigBee Coordinator API
Firmware version: 21A7</p>

<p>Hello, I am currently using Digi's XBee Java Library with API (AP=1) and it works properly. However, another node of my network is associated with an Arduino and I want to use 'Arduino Library for communicating with XBee in API mode' (https://github.com/andrewrapp/xbee-arduino). That Arduino Library requires API Escaped operating mode (API 2). It was not supposed to be a problem, since XBee Java Library supports API 2. Nevertheless, I got an error when trying to open the serial connection with the XBee.</p>

<pre><code>package com.digi.xbee.example;

import com.digi.xbee.api.XBeeDevice;
import com.digi.xbee.api.exceptions.XBeeException;

public class MainApp {
 /* Constants */
 // TODO Replace with the port where your sender module is connected to.
 private static final String PORT = "COM4";
 // TODO Replace with the baud rate of your sender module.
 private static final int BAUD_RATE = 9600;

 private static final String DATA_TO_SEND = "Hello XBee World!";

 public static void main(String[] args) {
 XBeeDevice myDevice = new XBeeDevice(PORT, BAUD_RATE);
 byte[] dataToSend = DATA_TO_SEND.getBytes();

 try {
 myDevice.open();

 System.out.format("Sending broadcast data: '%s'", new String(dataToSend));

 myDevice.sendBroadcastData(dataToSend);

 System.out.println(" >> Success");

 } catch (XBeeException e) {
 System.out.println(" >> Error");
 }
 }
}

I know `PowerPivot` is not programming, but I wanted to see if I could get help or a recommendation on how to get the total rows to correctly calculate the sum of Absolute Values at a higher aggregation level than the detailed data in a `PowerPivot` data model.

Here is my example: This is detailed data format. There are 2 hierarchies:

```
1. Product Group\Product Family\**Material**  '3 columns'
2. Region\**Plant**\SalesMgr\Employee\Customer  '5 columns'
```

Hierarchy represents 8 columns in my data model

All data in the data model is at the lowest level (i.e. Material/Customer). However I want to calculate Forecast Accuracy at Material/Plant Level (a higher aggregation level).

```
DataModel Column9: Sales  'Sales at the detailed Material/Customer'
DataModel Column10: Forecast  'Forecast at the detailed Material/Customer'
Calculated Column11: AbsoluteError = ABS(Forecast - Sales)  'calcd at Mat/Cust'
```

```
PowerPivot DAX formulas/measures, shortened for simplicity
TotalSales:=SUM(Sales)
TotalAbsError:=SUM(AbsoluteError)
MAPE:= TotalAbsError/TotalSales
ForecastAccuracy:= 1 - MAPE (Mean Absolute Percentage Error)
```

This calculates the data correctly at the Material/Plant level when I create my Pivot Table. However the Total values in the Pivot Table are incorrect.

For example, the Total of AbsError is the Sum of 20 rows of Material/Customer Combinations. I need the Total of only the 5 Material/Plant Combinations. The 20 rows of detailed Material/Customer data aggregates up to only 5 rows of Material/Plant Combinations.

I have a sample spreadsheet I can share. Thanks Dimitry for updating the question!

I would like to post the spreadsheet / powerpivot so that the StackOverflow community can see it. I assume I have to post a link. I will start trying to figure out how.

Thanks
David

I have a huge XML file and I have uploaded it in an oracle table. I want to show attributes of the nodes defined in XML as attributes of a table. Below is the DDL of the table where XML is stored.

```
CREATE TABLE TEST_USER.XML_TAB
(
  ID      NUMBER,
  XML_DATA SYS.XMLTYPE
);
```

So far I have managed to built the following query, but the problem with this query is that it returns no data which is against attributes of the node selected.

```
SELECT x.*
FROM XML_TAB t,
XMLTABLE ('/ProductDataeXchangePackage/Items/Item'
PASSING t.XML_DATA
COLUMNS
CATEGORY          VARCHAR2(19 BYTE) PATH
'/ProductDataeXchangePackage/Items/Item/@CATEGORY',
DESCRIPTION        VARCHAR2(91 BYTE) PATH
'/ProductDataeXchangePackage/Items/Item/@DESCRIPTION',
GLOBALLIFECYCLEPHASECODE  VARCHAR2(10 BYTE) PATH
'/ProductDataeXchangePackage/Items/Item/@GLOBALLIFECYCLEPHASECODE',
GLOBALPRODUCTTYPECODE   VARCHAR2(19 BYTE) PATH
'/ProductDataeXchangePackage/Items/Item/@GLOBALPRODUCTTYPECODE',
GLOBALPRODUCTUNITOFMEASURECODE VARCHAR2(2 BYTE) PATH
'/ProductDataeXchangePackage/Items/Item/@GLOBALPRODUCTUNITOFMEASURECODE',
ISTOPELVEL          VARCHAR2(3 BYTE) PATH
'/ProductDataeXchangePackage/Items/Item/@ISTOPELVEL',
ITEMIDENTIFIER       VARCHAR2(7 BYTE) PATH
'/ProductDataeXchangePackage/Items/Item/@ITEMIDENTIFIER',
ITEMUNIQUEIDENTIFIER VARCHAR2(14 BYTE) PATH
'/ProductDataeXchangePackage/Items/Item/@ITEMUNIQUEIDENTIFIER',
OWNERNAME            VARCHAR2(17 BYTE) PATH
'/ProductDataeXchangePackage/Items/Item/@OWNERNAME',
PROPRIETARYPRODUCTFAMILY  VARCHAR2(1 BYTE) PATH
'/ProductDataeXchangePackage/Items/Item/@PROPRIETARYPRODUCTFAMILY',
REVISIONIDENTIFIER      VARCHAR2(11 BYTE) PATH
'/ProductDataeXchangePackage/Items/Item/@REVISIONIDENTIFIER',
REVISIONDATE           VARCHAR2(15 BYTE) PATH
'/ProductDataeXchangePackage/Items/Item/@REVISIONDATE')
```

<p>From this Deutsche Börse web page, under the table header Issuer I want to get the string content <code>'db X-trackers'</code> in the cell next to the one with Name in it.</p>

<p>Using my web browser, I inspect that table area and get the code, which I've pasted into this XML tree just so that I can test my xPath.</p>

```
<pre><code>&lt;root&gt;
  &lt;div class="row"&gt;
    &lt;div class="col-lg-12"&gt;
      &lt;h2&gt;Issuer&lt;/h2&gt;
    &lt;/div&gt;
  &lt;/div&gt;
  &lt;div class="table-responsive"&gt;
    &lt;table class="table"&gt;
      &lt;tbody&gt;
        &lt;tr&gt;
          &lt;td&gt;Name&lt;/td&gt;
          &lt;td class="text-right"&gt;db X-trackers&lt;/td&gt;
        &lt;/tr&gt;
      &lt;/tbody&gt;
    &lt;/table&gt;
  &lt;/div&gt;
&lt;/root&gt;
</code></pre>
```

<p>According to FreeFormatter.com, my xPath below succeeds in retrieving the correct element (<code>Text='db X-trackers'</code>):</p>

```
<pre><code>my_xpath = "//h2['Issuer']/ancestor::div[@class='row']/following-sibling::div//td
['Name']/following-sibling::td[1]/text()"
</code></pre>
```

<p>Note: It goes to <code><h2>Issuer</h2></code> first to identify the right place to start working from.</p>

<hr>

<p>However, when I run this on the actual web page using Selenium WebDriver,</p>

<p>I am using X-CTU v6.3 in Mac OS X El Capitan with XBee S2C</p>

<p>In XCTU, the device is detected as</p>

<p>Function: ZIGBEE TH Reg</p>

<p>Product Family: XB24C</p>

<p>Firmware version: 4059</p>

<p></p>

<p>How do I configure it as a Coordinator at AT mode?</p>

<p>The update firmware button doesn't show anything beyond the function and product family mentioned above. </p>

<p></p>

<p>What am I missing?</p>

36671556

Xbee S2C setting as a Coordinator AT mode

I start on the subject and I have this error I totally understand but I can not solve the need that I wish :</p>

All arguments to function ' {} ' must have same hierarchy .</p>

I have a cube named test in which I use two dimensions usages (Store and Product) and two dimensions (Occupation and Yearly_Income) and a Store sales measurement .</p>

I would like a table with the different products on rows (it no worries) and Occupation and Yearly_Income on columns but I do not know how to work around this error.</p>

```
<code>select
  Crossjoin({[Measures].[Store sales]},{[Occupation].Members,[Yearly_Income].Members})

on columns,
{
  [Product].[Product Family].Members

} on rows

FROM test
</code></pre>
```

Thank you.</p>

36814170

Request error MDX

<p>I have this code (jsfiddle - make sure you stretch the "demo" frame enough that the buttons are on a single line):</p>

```
<pre><code>&lt;!DOCTYPE html&gt;
&lt;html lang="en"&gt;
&lt;head&gt;
  &lt;meta charset="utf-8"&gt;
  &lt;meta http-equiv="X-UA-Compatible" content="IE=edge /"&gt;
  &lt;meta name="viewport" content="width=device-width, initial-scale=1 /"&gt;

  &lt;!-- Latest compiled and minified CSS --&gt;
  &lt;link rel="stylesheet" href="https://maxcdn.bootstrapcdn.com/bootstrap/3.3.6/css/bootstrap.min.css" integrity="sha384-1q8mTJOASx8j1Au+a5WDVnPi2lkFfwwEAa8hDDdjZlpLegxhjVME1fgjWPGmkzs7" crossorigin="anonymous"&gt;

  &lt;!-- Optional theme --&gt;
  &lt;link rel="stylesheet" href="https://maxcdn.bootstrapcdn.com/bootstrap/3.3.6/css/bootstrap-theme.min.css" integrity="sha384-fLW2N01lMqjakBkx3l/M9EahuwPsfENvV63J5ezn3uZzapT0u7EYsXMjQV+0En5r" crossorigin="anonymous"&gt;

  &lt;!-- Latest compiled and minified JavaScript --&gt;
  &lt;script src="https://maxcdn.bootstrapcdn.com/bootstrap/3.3.6/js/bootstrap.min.js" integrity="sha384-0mSbJDEHialfmuBBQP6A4Qrprq5OVfW37PRR3j5ELqxss1yVqOtnepnHVP9aJ7xS" crossorigin="anonymous"&gt;&lt;/script&gt;

&lt;/head&gt;

&lt;body&gt;
  &lt;div class="container"&gt;

    &lt;br/&gt;&lt;br/&gt;&lt;br/&gt;

    &lt;div class="row"&gt;

      &lt;form class="form-horizontal" role="form"&gt;
        &lt;div class="form-group"&gt;
```

<p>I want to combine 3 queries like that in one query but I don't know how can I do this:</p>

<p>Query 1: </p>

```
<pre><code>select {  
Crossjoin({[Measures].[Store sales]}, {[Occupation].[Occupation].Members})  
} on columns,  
{  
[Product].[Product Family].Members  
} on rows  
From test  
</code></pre>
```

36909325

MDX queries test

I want to use columns of the i table in a data.table join for both calculations and for grouping. There appears to be some limitation in the syntax for this. Can you suggest a cleaner way of doing this?

```
require(data.table)
set.seed(1)
```

Table 1

```
DT1 <- data.table(loc = c("L1", "L2"), product = c("P1", "P2", "P3"), qty = runif(12))
```

Table 2

```
DT2 <- data.table(product = c("P1", "P2", "P3"), family = c("A", "A", "B"), price = c(5, 7, 10))
```

A straight join on the tables is fine: [not the issue here, but the requirement to use quoted column names in the `on` clause seems to be inconsistent for data.table]

```
DT1[DT2, on = "product"]
#   loc product    qty family price
# 1: L1    P1 0.1297134    A     5
# 2: L2    P1 0.2423550    A     5
# 3: L1    P1 0.3421633    A     5
# 4: L2    P1 0.6537663    A     5
# 5: L2    P2 0.9822407    A     7
# 6: L1    P2 0.8568853    A     7
# 7: L2    P2 0.7062672    A     7
# 8: L1    P2 0.9224086    A     7
# 9: L1    P3 0.8267184    B    10
#10: L2    P3 0.8408788    B    10
#11: L1    P3 0.6212432    B    10
#12: L2    P3 0.5363538    B    10
```

Calculation using columns of both tables is fine:

```
DT1[DT2, .(family, product, val = qty*price), on = "product"]
```

<p>(my english is not too good)

I need extract in web pages from icecat(I know they have xml files), But I need extract data with php from html.

I try some codes but I not understand how can extract all data, example:
</p>

```
<pre><code>    brand | Product family | product name | short description
```

```
    hp    |    200    |    250 g4    | HP 200 250 G4.....
```

```
        |
```

```
        without: "Short summary description HP 200 250 G4:"
```

```
    .
```

```
    .
```

```
    Category feature | key          | value
```

```
    processor        | processor frequency | 1.9Ghz
```

```
    processor        | processor cores    | 2
```

```
    memory           | Internal memory    | 4Gb
```

```
    memory           | Memory clock speed | 1600Mhz
```

```
    Display          | Display diagonal   | 39.6 cm (15.6")
```

```
    .
```

```
</code></pre>
```

<p>i need put "brand", "Product family" etc in db like columns and value in the tuple

For features need 2 columns key and value:

Processor frequency(key), 1.9 GHz(value).

And the problem is each page have something different, for example some pages have more ean or/and more product code and so on.

but in html have something like this in features:
</p>

```
<pre><code>    &lt;div class="table"&gt;
```

```
        &lt;div class="tableRowHead"&gt;
```

```
            &lt;span class="ds_bold_header " title="Processore Apple iPad Pro 128GB 3G 4G Grigio"
```

```
&gt;Processore&lt;/span&gt;
```

```
        &lt;/div&gt;
```

```
        &lt;div class="tableRow"&gt;
```

```
            &lt;div class="ds_label"&gt;
```

```
                &lt;span class="tip-anchor tip-anchor-text line l_text none_float"&gt; Famiglia
```

```
processore&lt;/span&gt;
```

```
            &lt;/div&gt;
```

```
            &lt;div class="ds_data"&gt;
```

```
Apple
```

```
        &lt;/div&gt;
```

```
    &lt;/div&gt;
```

<p>I written few lines code..</p>

```
<pre><code>book = xlwt.Workbook()
sheet = book.add_sheet('Section details', cell_overwrite_ok=True)
style_detail = xlwt.easyxf('font: name Calibri, height 180,colour_index black;align: wrap on, vert
center, horiz center; border : bottom thin,right thin,top thin,left thin;')
sheet.write_merge(0, 0, 0, 0, 'Product Family')
sheet.write_merge(1, 1, 0, 0, 'Product Category')
sheet.write_merge(0, 0, 1, 1, 'Product')
.
.
sheet.write_merge(n, n, n, n, 'Product') //n is just dynamic number..
</code></pre>
```

<p>Now, After completing all my writing work. Want to apply style for specific cells only(depending on requirement).</p>

```
<pre><code>rw = sheet.row(1)
rw.set_style(style_detail)
</code></pre>
```

<p>If i apply style for specific row then it apply for entire row of sheet(for column A to endless columns). How can i apply style for specific cell of any row only?</p>

<p>Please let us know if any more code or info require to get idea.</p>

<p>Thanks in-advance.</p>

37114641

Apply easyxf style for specific cell or row rang

<p>We have a large product catalog with products grouped under product families.
This is great as we can easily see the products hierarchy.</p>

<p>The problem is that when we create an opportunity it is very difficult to just search for a list of products that fall under one product family.</p>

<p>On the Opportunities form is there a way to modify the Price List Items "Look Up Records" search form to allow the user to filter the price list items by a product family?</p>

<p>Currently the Search form says</p>

```
<pre><code>Look for: Price List Items  
Look in: Price List Items in Entity Price List  
Search:  
</code></pre>
```

<p>Is there a way to add another search field such as Product Family to the filter?</p>

37784151

In Dynamics CRM Online How do I add the Fa

<p>I'm doing simple test application to explore Morphia capabilities. At the moment I'm trying to make a simple aggregation query on SaleStatistics collection. The query is Filter by product description and grouping by product family and subFamily and sum quantity and amount. The issue is that while Morphia was doing a correct replacement of property names on the \$match phase according to the @Property mappings defined in the classes, it wasn't doing the same replacement in the \$group phase. In that case it was using directly the property strings used in the aggregation definition, as you can see in this code snipped from the logging console:</p>

```
<pre><code>2016-06-16 10:09:22 DEBUG AggregationPipelineImpl:36 - stages = [{ "$match" : {
"Producto.Denominacion" : "MAGNA"}}, { "$group" : { "_id" : { "productFamily" : "$product.
productFamily" , "productSubfamily" : "$product.productSubFamily" } , "saleStatisticsQuantity" : {
"$sum" : "$quantity" } , "saleStatisticsAmount" : { "$sum" : "$amount" }}}]
</code></pre>
```

<p>Here is my Entity mapping:</p>

```
<pre><code>@SuppressWarnings("serial")
@Entity(value="EstadisticaDeVentas", noClassnameStored=true)
public class SaleStatistics extends FactTableEntity {

    @Embedded(value="Gasolinera", concreteClass=GasStationEmbedded.class)
    private GasStationEmbedded gasStation;

    @Embedded(value="Producto", concreteClass=ProductEmbedded.class)
    private ProductEmbedded product;

    @Embedded(value="Cliente", concreteClass=ClientEmbedded.class)
    private ClientEmbedded client;

    @Embedded(value="Turno", concreteClass=ShiftEmbedded.class)
    private ShiftEmbedded shift;

    @Embedded(value="Responsable", concreteClass=ResponsibleEmbedded.class)
    private ResponsibleEmbedded responsible;

    @Embedded(value="Isla", concreteClass=IslandEmbedded.class)
    private IslandEmbedded island;

    @Embedded(value="Vehiculo", concreteClass=VehicleEmbedded.class)
    private VehicleEmbedded vehicle;</pre>
```

<p>I am sure this question has already been answered, but I can't find it or the answer was too complicated. I am new to SQL and am not sure how to word this generically.</p>

<p>I have a mySQL database of software installed on devices. My query to pull all the data has more fields and more joins, but for brevity I just included a few. I need to add another dimension to create a report that lists every case where a device has more than one installation of software from the same product family.</p>

<p>sample</p>

<p>Right now I have code kind of like this and it is not doing what I need. I have seen some info on <code>exists</code> but the examples didn't account for multiple joins so the syntax escapes me. Help?</p>

```
<pre><code>select
devices.name,
sw_inventory.product,
products.family_name,
sw_inventory.ignore_usage,

from sw_inventory

inner join products
on sw_inventory.product=products.product_name

inner join devices
on sw_inventory.device_name=devices.name

where sw_inventory.ignore=0

group by devices.name, products.family_name
</code></pre>
```

37867817

SQL Return All Rows Where 2 Values Are Rep

I'm new to Ruby on Rails and I was working on a catalog website which consists of two frames: the first one contains product families and the second one dynamically shows the list of machines within those families as you click them on the first frame. This happens since form target is that frame's name:

I have already inspected [this answer](http://stackoverflow.com/questions/28416002/opening-a-new-tab-in-capybara-poltergeist) but there is an important difference: I want to iteratively click through the product family links in the first frame by working "within_frame ('families_frame')" and get the list of machines in the second frame. However "switch_to_frame" and similar solutions do not work and I get the following error:

`switch_to_window` is not supposed to be invoked from `within`'s, `within_frame`'s or `within_window`'s block. (Capybara::ScopeError)

Because my iterator runs from "within_frame". How can I switch to the resulting frame, reach the content and then switch back to the working frame?

The HTML structure is:

```
<code>&lt;HTML&gt;
&lt;FRAME NAME="families_frame" SRC="../../../productfamily.jsp"&gt;
&lt;FRAME NAME="machines_frame" SRC="../../../blank.jsp"&gt;
&lt;/HTML&gt;
</code></pre>
```

Thank you a lot.

38546028

How to switch to a frame from within anothe

<p>Morning all, </p>

<p>We would like to release our app via Apples Ad Hoc distribution. We "can register up to 100 devices per product family per year that your team uses for development and testing." Our developer account is up for renewal on 20th January, but we want to release on 1st September. Does this mean that the app will stop working for testers on 20th January or will it run for 12 months from 1st September? We need it to run for 12 months from the initial release date, is there anything we need to be aware of to ensure this happens?</p>

<p>Huge thanks in anticipation of your help!</p>

38566173

iOS Ad Hoc Distribution - starting 12 months

<p>I need to show the number of units for a product type in my reports. I'm using a custom formula and this is what I have so far:</p>

<p>IF(ISPICKVAL(Family ,"Specific Product Category"),1,0) * Units_c</p>

<p>the syntax seems to work until I * units_c</p>

38646762

How do I create a custom Salesforce field to s

<p>So I've had a search around, and can't for the life of me understand why this would work perfectly in one browser, and not in the others. On line 13 I'm getting this error in Safari: </p>

<p></p>

On Firefox, I don't get any errors, but the Script breaks in the same fashion. I've tried making the for loop `for (var p in productFamily)` or `for (let p of productFamily)` but it just breaks the script.

Am I looping incorrectly?

<p>Here is my code:</p>

```
<code>$(window).load(function(){
```

```
// All possible families are defined here...
var productFamily = ["Beaches","Leios","Lull"];
```

```
// All possible product types are defined here...
var productType = ["Shelter", "Restroom"];
```

```
// All possible product sizes are defined here...
var sizeRange = ["4x4", "4x8", "6x4", "6x8", "8x4", "8x6"];
```

```
// Here we loop through each Family, Type and Size...
```

```
for ( let p in productFamily ) {
```

```
for ( let t in productType ) {
```

```
for ( let i in sizeRange ) {
```

```
// Get all of the select types...
```

```
$('select[name="properties[' + productFamily[p] + ' ' + productType[t] + ' Size"]', +
```

```
'select[name="properties[' + productFamily[p] + ' ' + productType[t] + ' ' + sizeRange[i] + '
```

```
Frame]"]', '+
```

```
'select[name="properties[' + productFamily[p] + ' ' + productType[t] + ' ' + sizeRange[i] + '
```

Fasteners]"','+

```
'select[name="properties[' + productFamily[p] + ' ' + productType[t] + ' ' + sizeRange[i] + ' '
```

Roof]"','+

```
'select[name="properties[' + productFamily[p] + ' ' + productType[t] + ' ' + sizeRange[i] + ' Column
```

Infill]"','+

```
'select[name="properties[' + productFamily[p] + ' ' + productType[t] + ' ' + sizeRange[i] + ' Soffit
```

<p>I am not quite sure why this piece of code isn't working. </p>

<p>Here's how my data looks like:</p>

```
<pre><code>head(test)
  Fiscal.Year Fiscal.Quarter Seller Product.Revenue Product.Quantity Product.Family Sales.Level.1
Group Fiscal.Week
1    2015      2015Q3 ABCD1234      4000          4 Paper cup Americas Paper Division
32
2    2014      2014Q1 DDH1234       300          5 Paper tissue Asia Pacific Paper Division
33
3    2015      2015Q1 PNS1234       298          6 Spoons EMEA Cutlery 34
4    2016      2016Q4 CCC1234       289          7 Knives Africa Cutlery 33
</code></pre>
```

<p>Now, my objective is to summarize revenue by year.</p>

<p>Here's the dplyr code I wrote:</p>

```
<pre><code>test %>%
  group_by(Fiscal.Year) %>%
  select(Seller,Product.Family,Fiscal.Year) %>%
  summarise(Rev1 = sum(Product.Revenue)) %>%
  arrange(Fiscal.Year)
</code></pre>
```

<p>This doesnt work. I get the error:</p>

```
<pre><code>Error: object 'Product.Revenue' not found
</code></pre>
```

<p>However, when I get rid of select statement, it works but then I don't get to see the output with Sellers, and Product family.</p>

```
<pre><code>test %>%
  group_by(Fiscal.Year) %>%
  # select(Seller,Product.Family,Fiscal.Year) %>%
  summarise(Rev1 = sum(Product.Revenue)) %>%
  arrange(Fiscal.Year)
</code></pre>
```

In Tableau I'm displaying adjusted sales levels per account (rows) by group and product (columns) as a conditional calculated field AGG(adjusted \$) where ADJUSTED \$ is computed as follows:

```
if AVG([SALETYPE]) = 1 then ADJUSTED $ = SUM([$_SALES])
elseif AVG([SALETYPE]) = 2 then ADJUSTED $ = SUM([$_SALES]) * 0.5
else 0
END
```

This works great at a granular sale level (per account by product/group), but Tableau's aggregations/Totals are very confusing to me:

1) When I add table-down Grand Totals, it gives me unadjusted values (i.e. does not adjust SALETYPE 2 downward by 50%) until I add one of my filter dimensions (product family) as a column, at which point the Grand Totals are correct.

2) When I add subtotals across rows, it also gives me unadjusted values. When I add my Row dimension as a Filter and select the whole available universe, nothing changes. However, if I deselect all and select ONE individual account to filter by, the subtotals are accurately computed. I've tried adding ZN() to all my functions to deal with null values but to no avail.

Any thoughts/recommendations how to deal with aggregating conditional values much appreciated.
Thanks.

40095690

tableau totals on calculated fields

<p>I create a report every month at work that parses sales out by product family. Due to the limitations within the report I use for the data, I can't simply use a pivot table to get the data I need for my report. I slice the data into separate worksheets by product family. The number of rows on each sheet vary depending upon the number of customers that bought product in that product family. I currently have a macro that I run each time I create a new sheet that does sums, sumproduct and sumif procedures. I want to also add a pivot table at the bottom of the data on each sheet for further manipulation.</p>

<p>I have no idea what I'm doing wrong, but my code isn't working. Here it is:</p>

```
<pre><code>ActiveWorkbook.PivotCaches.Create(SourceType:=xlDatabase, SourceData:= _
    "ActiveSheet.Name!R1C1:R231C30", Version:=6).CreatePivotTable TableDestination:= _
    "ActiveSheet.Name!R237C3", TableName:="PivotTable21", DefaultVersion:=6
ActiveSheet.Name).Select
Cells(237, 3).Select
</code></pre>
```

40439529

Excel Pivot Table macro to use on multiple w

<p>I'm trying to add a column at a specific index based on the content of a different column:</p>

```
<pre><code>df.insert(10, 'Escalation Status', np.where(df['Reasons for escalation'] == '', 'FALSE', 'TRUE'))
</code></pre>
```

<p>So, when Column "Reasons for escalation" is empty, write "FALSE", if not, write "TRUE" in the newly created "Escalation Status" column.</p>

<p>My problem: The content is always "TRUE", no matter if there is anything in the "Reasons for escalation" field.</p>

<p>example output:</p>

```
<pre><code>Country,Date,Vendor,Product Family,Case number,Reseller Name,OpeningDate,Closing
Date,Case Status,Topic,Escalation Reason,Reasons for escalation
DEU,28.10.2016,VENDOR,,201610281078864,,28.10.2016,28.10.2016,closed,Software issue,TRUE,
Software
DEU,28.10.2016,VENDOR,,201610281078862,,28.10.2016,28.10.2016,closed,Config help,TRUE,
</code></pre>
```

<p>The first row is correct (Reasons for escalation is not empty, it contains "Software"), but the second row should be "FALSE", as the Reasons for escalation is empty</p>

<p>thanks</p>

40706073

python pandas add column content based on

<p>We are creating a database to store test data for our products during manufacture, and I am having difficulty in designing the API that will interact with the data. We have developed the schema per a set of requirements we developed. The schema is not the focus of this post.</p>

<p>My question deals with the correct and most efficient way of querying a specific type of data from the DB.</p>

<p>The schema consists of:</p>

configurations table (stores information about specific products that can be manufactured, i.e. widget A, thingie B)

product family table (stores information about product families that we sell, i.e. widgets, thingies)

required tests (contains all tests for all families of product, i.e. Widget A Size, Thingie B Weight)

a table of test parameter pass/fail criteria (criteria for each product to pass manufacture, i.e. Widget A Max Size, Thingie B Weight Range). Criteria may change over time and the newest entry is the active one.

a table of serial numbers (includes serial number and the associated configuration, i.e. 123 is a Widget A, 456 is a Thingie B)

a table to store the test results (i.e. Serial Number 123's Size is 12", Serial Number 456 Weight is 1.5lbs). Note a test result may not exist yet OR multi tests may have been run. The newest one is the active one.

<p>There are primary keys and relationships that maintain data integrity, etc, etc.</p>

<p>My question is in regards to generating a summary of test results for a specific serial number. I can do this on the client side with large number queries. For example:</p>

Find configuration and family for the serial number (using tables 1 and 5).

In a single query, return all of the tests required for that family (from table 3).

Loop through each row (test) from #2 and find the most current pass fail criteria from table 4.

Loop through each row (test) from #2 and find the most current result (if it exists).

Determine if that test passes and, thus, if the serial number passes all tests.

<p>My question is two fold. One, am I missing a more complex SQL query that lessens the load on

I am very new to the single sign-on options available to me. I currently have a requirement to secure multiple application sets within the same product family and have no idea where to start.

Some of the base requirements would be

User should be able to authenticate once, and based on the credentials user would be redirected to the required application

A central management console should be available for administrators to simplify role assignments as well as grant access to the various applications as required

Users can register for certain applications but certain sensitive applications require administrator approval before the user can successfully log in.

This SSO should also secure an API with some sort of permission logic e.g. only supervisor roles can delete a record

Users should be able to register with OAuth providers such as Facebook, Twitter, Google & Windows live.

The SSO provider should be simple to implement into multitude of platforms such as Windows Apps, Web Apps, Mobile & services

I have no idea where to start, I have done a quick read through of something like ADFS <https://msdn.microsoft.com/en-us/library/bb897402.aspx>, but NO IDEA if this would meet all the listed requirements above.

Any help of pointing me in the right direction would be greatly appreciated!!

<p>I have a table in SQL Server with the following data:</p>

```
<pre><code>+-----+-----+-----+-----+
|Product Family | Product Class | Product      | Sales |
|Food          | Vegetables   | Cauliflower  | 24    |
|Food          | Prepared Meals | Steak & Patatoes | 54    |
|Food          | Fruit        | Apples       | 76    |
|Food          | Fruit        | Oranges      | 14    |
|Food          | Fruit        | Pears        | 32    |
|Electronics   | MP3 Players  | Cool Player Z | 57    |
|Electronics   | MP3 Players  | iStuff 16GB  | 45    |
|Electronics   | TV's         | HD           | 96    |
|Electronics   | TV's         | Ultra HD     | 76    |
+-----+-----+-----+-----+
</code></pre>
```

<p>There is a hierarchy in this data:</p>

```
<ol>
<li>Product Family</li>
<li>Product Class</li>
<li>Product</li>
</ol>
```

<p>I'd like to create a query that will return the sum for each hierarchy level. This union does that:</p>

```
<pre><code>SELECT 1 as Level, [Product Family] as Item, SUM(SALES) as Sales
FROM [dbo].[HK_Temp_01] GROUP BY [Product Family]
```

UNION ALL

```
SELECT 2 as Level, [Product Class] as Item, SUM(SALES) as Sales
FROM [dbo].[HK_Temp_01] GROUP BY [Product Class]
```

UNION ALL

```
SELECT 3 as Level, Product as Item, SUM(SALES) as Sales
FROM [dbo].[HK_Temp_01] GROUP BY Product
</code></pre>
```


I'm using Antlr's string template capabilities and am seeing the following error:

```
<pre><code>Antlr4.StringTemplate.Compiler.TemplateException was unhandled
HResult=-2146233088
Message=Exception of type 'Antlr4.StringTemplate.Compiler.TemplateException' was thrown.
Source=Antlr4.StringTemplate
</code></pre>
```

With the code:

```
<pre><code>class Program
{
    static void Main(string[] args)
    {
        var messageTemplate = "&lt;table style='&lt;border-collapse: collapse; width: 100%'\amp;lt; dir='&lt;ltr'&lt; cellpadding='&lt;0\amp;gt;&lt;tr style='&lt;background-color: #f8f8f9; border: thin #e8eaec solid'\amp;gt;&lt;td style='&lt;font-family: Verdana; font-size: 12pt; background-color: #f8f8f9; border: thin #e8eaec solid; padding: 20px 20px 20px 20px'\amp;gt;&lt;New Order for Vendor:&lt;strong style='&lt;font-family: Verdana; font-size: 12pt;\amp;gt;%VendorName%\amp;lt;/strong&gt;&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;&lt;/td&gt;&lt;/tr&gt;&lt;tr style='&lt;background-color: #f8f8f9; border: thin #e8eaec solid'\amp;gt;&lt;td style='&lt;font-family: Verdana; font-size: 12pt; background-color: #f8f8f9; border: thin #e8eaec solid; padding: 20px 20px 20px 20px'\amp;gt;&lt;table&gt;&lt;tr&gt;&lt;td style='&lt;font-family: Verdana; font-size: 12pt;\amp;gt;Order Number:&lt;/td&gt;&lt;td width='&lt;2px'\amp;gt;&lt;/td&gt;&lt;td style='&lt;font-family: Verdana; font-size: 12pt;\amp;gt;%OrderNumber%\amp;lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td style='&lt;font-family: Verdana; font-size: 12pt;\amp;gt;State:&lt;/td&gt;&lt;td width='&lt;2px'\amp;gt;&lt;/td&gt;&lt;td style='&lt;font-family: Verdana; font-size: 12pt;\amp;gt;%CustomerAddressState%\amp;lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td style='&lt;font-family: Verdana; font-size: 12pt;\amp;gt;County:&lt;/td&gt;&lt;td width='&lt;2px'\amp;gt;&lt;/td&gt;&lt;td style='&lt;font-family: Verdana; font-size: 12pt;\amp;gt;%CustomerAddressCounty%\amp;lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td style='&lt;font-family: Verdana; font-size: 12pt;\amp;gt;Municipality:&lt;/td&gt;&lt;td width='&lt;2px'\amp;gt;&lt;/td&gt;&lt;td style='&lt;font-family: Verdana; font-size: 12pt;\amp;gt;%VendorCity%\amp;lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td style='&lt;font-family: Verdana; font-size: 12pt;\amp;gt;Borrower:&lt;/td&gt;&lt;td width='&lt;2px'\amp;gt;&lt;/td&gt;&lt;td style='&lt;font-family: Verdana; font-size: 12pt;\amp;gt;%Borrowers%\amp;lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td style='&lt;font-family: Verdana; font-size: 12pt;\amp;gt;Product Family:&lt;/td&gt;&lt;td width='&lt;2px'\amp;gt;&lt;/td&gt;&lt;td style='&lt;font-family: Verdana; font-size: 12pt;\amp;gt;%ProductFamily%\amp;lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td style='&lt;font-family: Verdana; font-size: 12pt;\amp;gt;Price:&lt;/td&gt;&lt;td width='&lt;2px'\amp;gt;&lt;/td&gt;&lt;td style='&lt;font-family: Verdana; font-size: 12pt;\amp;gt;%Price%\amp;lt;/td&gt;&lt;/tr&gt;&lt;/table&gt;&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td style='&lt;font-family: Verdana; font-size: 12pt; padding: 20px 20px 20px 20px'\amp;gt;&lt;img src='&lt;https://www.americantitleinc.com/atip/Portals/0/WebLogo_V1.png'\amp;lt;' width='&lt;250'\amp;lt;' height='&lt;95'\amp;lt;' border='&lt;0'\amp;lt;' /&gt;&lt;/td&gt;&lt;/tr&gt;&lt;/table&gt;"
```

<p>I am looking for an data analysis tool that can visualize the data from different sensors in my place. These sensors are all light sensors but from different companies and different product families. I need to compare them and therefore I have to analyze the data that my program stores in text files specified by sensor producer and product family.</p>

<p>Do you have any suggestions?</p>

42032592

Data analysis tool needed

<p>I have <code>Description</code> and <code>Division</code> DropDownList</p>

<p>When I generate data it will be shown in GridView.

When I choose another Item in Description DropDownList the page must be clear but my problem is that the GridView of the previous data still shows even if I choose another Item in the DropDownList already.</p>

<p>Here's my code for <code>Page_load</code></p>

<p>Protected Sub Page_Load(ByVal sender As Object, ByVal e As System.EventArgs) Handles Me.
Load

 userid = If(SessionHandler.UserID = "", User.Identity.Name.ToUpper, SessionHandler.UserID)

</p>

<pre><code> If Not IsPostBack Then
 Description.Items.Clear()

 If com.isAdmin(com.RetUser_Id(userid)) Then

 Description.Items.Add(New ListItem("Number Of Part Numbers/Family Input By User", "1"))

 End If

 Description.Items.Add(New ListItem("Product Family with No CAS Number", "2"))

 Description.Items.Add(New ListItem("Product Family with Inactive Exemption", "3"))

 Description.Items.Add(New ListItem("Part Number Validation", "4"))

 InitializeSearchOptions()

 End If

 ' this conditional statement will not bind the gridview if the sender object is from dropdownlist

 ' this will avoid unnecessary binding and reduce execution time

 Dim ctrlName As String = Page.Request.Params.Get("__EVENTTARGET")

 If ctrlName <> Nothing And ctrlName <> String.Empty Then

 If Not ctrlName.ToLower.Contains("dropdownlist") And ViewState.Item("Query") <>

Nothing Then

 BindGridview(ViewState.Item("Query"))

 End If

Else

 For Each ctrl As String In Page.Request.Form

 Dim c As Control = Page.FindControl(ctrl)

 If Not TypeOf (c) Is System.Web.UI.WebControls.Button Then

<p>I've created a website for my friends company a few months ago while i was a complete newbie and all the stuff i knew about creating websites i learned on Codecademy. The site is pretty big, it's in 2 languages and has about 25 html pages per language. What Codecademy didn't teach me is the SEO importance of a good website folder structure and SEO friendly links, so now i'm trying to correct my mistakes and i've encountered some problems to which i cannot find a solution to. </p>

<p>So, the problem is i'm using .htaccess to remove the .html extensions from my URL's, so when i write the link in to my html i write it without the .html extension. </p>

<p>I have a products folder with a single index file as the starting products page, and that same folder has a few more folders for each of the product families, and each of those product family folders has an index file + a few more html files for each specific product in that product family. </p>

<p>So when the visitor is on a specific product page the link should look like this:</p>

<p>www.mywebsite.com/products/product-family-name/product-name</p>

<p>When i link to a product family from the products page i type in just the product family name without any slashes and it would go to that product family folder and shows the index file from that folder. The problem appears when i try to create a link like shown above, when i try to reach an html file which is in the same folder as the index file from which i'm linking to. It won't work without the .html extension, instead the page is not found. </p>

<p>I type it like this:</p>

<p>/product-family-name/product-name (this doesnt work)</p>

<p>/product-family-name/product-name.html (this works)</p>

<p>I also tried typing in only the product name, but that doesn't work without the .html either.</p>

<p>I could solve this by just creating a new folder for each specific product inside of the product family folder and name them index, but i don't know if that is a good practice, coz it doesn't seem like it is. I just want to know if there is another way to do this.</p>

<p>I hope everyone can understand what i actually want to do, because maybe i complicated it too much. Also, sorry if it's a stupid question, as i said i'm just a newbie and i'm trying to learn. </p>

<p>Thank you in advance.</p>

I have a database where there is a union query that is pulling some data for a report. This has been working fine for some time and I had to switch a field in a table from short text to long text with rich text in order to support additional font options. In doing so, when I run the query the field in question is coming back with funny characters. The table is called tbl_Process and the field is Process. I have tried setting indexes on that field but it's not helping. I can fumble my way around union queries a bit, but they are a weak point and I'm hoping someone could take a look at the query to see if they have any suggestions.

```
SELECT tbl_Areas.Area_Detail AS Area, tbl_Areas.Product, tbl_Areas.Area_ID AS [Area Code], tbl_Areas.Revision AS [Area Book Revision], tbl_Processes.Group, tbl_Processes.Serial_Number AS [Process Serial Number], [Group] & "-" & [Product_Family] & [tbl_Products].[Size] & "-" & [tbl_Processes].[Serial_Number] & "-" & [tbl_Areas].[Area_ID] & "-" & [tbl_Processes]![Revision] AS [Document Name], tbl_Processes.Process, tbl_Processes.Revision AS [Process Revision], tbl_Finished_Product_Families.Common_Name AS [Product Family], tbl_Products.Size AS [Product Size], tbl_Models.Model_Definition AS [Product Model], tbl_ECN.Date_Published AS [ECN Date], Max(tbl_ECN.Revision) AS [ECN Revision], tbl_ECN.Engineer AS [Engineer of Record], tbl_Processes.Sequential_Position
FROM (tbl_Models INNER JOIN (tbl_Finished_Product_Families INNER JOIN tbl_Products ON tbl_Finished_Product_Families.Finished_Product_Family = tbl_Products.Product_Family) ON tbl_Models.Model = tbl_Products.Model) INNER JOIN (tbl_ECN RIGHT JOIN (tbl_Areas INNER JOIN tbl_Processes ON tbl_Areas.Area_ID = tbl_Processes.Area) ON tbl_ECN.Serial_Number = tbl_Processes.Serial_Number) ON tbl_Products.Product_ID = tbl_Processes.Product
GROUP BY tbl_Areas.Area_Detail, tbl_Areas.Product, tbl_Areas.Area_ID, tbl_Areas.Revision, tbl_Processes.Group, tbl_Processes.Serial_Number, [Group] & "-" & [Product_Family] & [tbl_Products].[Size] & "-" & [tbl_Processes].[Serial_Number] & "-" & [tbl_Areas].[Area_ID] & "-" & [tbl_Processes]![Revision], tbl_Processes.Process, tbl_Processes.Revision, tbl_Finished_Product_Families.Common_Name, tbl_Products.Size, tbl_Models.Model_Definition, tbl_ECN.Date_Published, tbl_ECN.Engineer, tbl_Processes.Sequential_Position

UNION SELECT DISTINCT tbl_Areas.Area_Detail, tbl_Areas.Product, tbl_Areas.Area_ID, tbl_Areas.Revision, "OP Book" AS Expr1, Null AS Expr2, "OP-" & [Product_Family] & [tbl_Products].[Size] & "-" & "0000-" & [tbl_Areas].[Area_ID] AS [Document Name], Null AS Expr4, Null AS Expr3, tbl_Finished_Product_Families.Common_Name, tbl_Products.Size, tbl_Models.Model_Definition, Null AS Expr5, Null AS Expr6, Null AS Expr7, 100 AS Expr8
FROM (tbl_Models INNER JOIN (tbl_Finished_Product_Families INNER JOIN tbl_Products ON tbl_Finished_Product_Families.Finished_Product_Family = tbl_Products.Product_Family) ON tbl_Models.Model = tbl_Products.Model) INNER JOIN (tbl_Areas INNER JOIN tbl_Processes ON tbl_Areas.Area_ID = tbl_Processes.Area) ON tbl_Products.Product_ID = tbl_Processes.Product;
```

<p>I need some help doing the following. I have a file in which column M is a measure. For the exercise, Column M - Measure "Forecast, appears every 17 lines under a product.
From columns N -> CG would be that forecast over a long period of time driven by a formula.</p>

<p>In column M there is a also a measure, "locked forecast", I would like a toggle button that allows the user to take the forecast measure -> N134:CG134 to around 4000. This could expand or minimize it products are added or deleted but for now there are around 4000 rows.</p>

<p>When the press the button I would like to see those variable forecasts locked within the "locked forecast" measures
The "locked forecast" measure starts at N140:CG140 and just like the forecast it repeats itself within every product family.</p>

<p>I try to do visible copy paste but I get multiple selection errors, I assume I need some kind of loop.</p>

42255369

Excel VBA cut and paste hard coded value

I am new to using DAX queries and encountered what seems to be a syntax error in a pre-written query when trying to run the same in SSIS, which I have not been able to figure out yet.

[illegible]

<p>I am new in jmeter. I have prepared test script for load testing. Detail is as - </p>

<p>a) In 1st test script - I have added one thread group & made every page http request under this thread group - Test tree detail is as -

Thread group

Visit Home page

Visit Category page

Visit Product family page

Select product

Add to cart

Login

Update billing address

Update shipping

update Payment</p>

<p>This test script is running perfectly. </p>

<p>b) In 2nd test script - I have added thread group for each page's http request - Test tree detail is as -

Thread group1

Visit Home page

Thread group2

Visit Category page

Thread group3

Visit Product family page

Thread group4

Select product

Thread group5

Add to cart

Thread group6

Login

Thread group7

Update billing address

Thread group8

Update shipping

Thread group9

update Payment</p>

<p>But this 2nd test script is showing response error 500 for billing & shipping. also note that for billing and shipping, request parameters including header detail are same for both test scripts . </p>

Tags

<wpf>

<video><encoding><javafx>

<continuous-integration><project-management><software-engineering><configuration-management>

<ruby-on-rails><ruby><layout>

<qt><model><views>

<installer><windows-installer><upgrade>

<jenkins><embedded-linux><build-system>

<coldfusion>

<django-forms>

<salesforce><apex-code><visualforce>

<c#><.net><function><transform><expression>

<jquery><json><list>

<php><content-management-system><expressionengine>

<database><performance><foreign-keys><denormalization><database-indexes>

<indexing><cassandra><database-indexes>

<sharepoint><sharepoint-2007>

<drupal><drupal-7>

<installation><installshield>

<select><sql-server-2008-r2>

<windows-8><visual-studio-2010-sp1>

<mdx><mondrian>

<memory><hardware><intel><datasheet>

<symfony><doctrine>

<sql><database>

<sql-server><sql-server-2008><visual-studio-2012>

<r><cluster-analysis>

<html><perl><drop-down-menu><catalyst>

<union><mdx><olap><aggregation><mondrian>

<sql><join><sql-server-2008-r2>

<windows><windows-phone-8>

<r><loops><traversal><apply>

<sd-card><spi>

<sql><sql-server><sql-server-2008>

<dynamics-crm-2015>

<excel><excel-vba><excel-formula>

<arduino><xbee>

<c#><.net><delegates><namespace-organisation>

<django><python-2.7><django-admin>

<design-patterns><design>

<excel><excel-vba>

<symfony><akeneo>

<if-statement><logic><logistics>

<sql><sorting><group-by>

<asp.net><asp.net-mvc><attributes><authorize-attribute>

<xbee>

<mdx>

<mdx><mondrian>

<python><excel><xlrd><xlwt>

<dynamics-crm-online>

<mysql><sql>

<ruby-on-rails><capybara><poltergeist>

<ios><ad-hoc-distribution>

<salesforce><report>

<tableau>

<excel-vba><pivot-table>

<python><python-3.x><pandas><numpy>

<c#><asp.net><security><single-sign-on><adfs>

<database><validation>

<excel><vba><filtered-index>

