

Id **Body**

Title

<p>I have a friend that has a little bit of a holiday coming up and they want ideas on

<p>I'll add to the list below as people reply, I apologise if I duplicate any entries.</p>

<p>Pros I have so far</p>

Minimal money requirement (they already have a computer)

Will help them to think in new ways

(Rob Cooper) Great challenge, every day really is a fresh challenge in some way,

(Rob Cooper) I like the way it makes me think.. I look at EVERYTHING more logic;

(Rob Cooper) Money is/can be pretty good.

(Rob Cooper) Its a pretty portable trade.. With collaboration tech as it is, you can

(Rob Cooper) It's an exciting industry to work in, there's massive amounts of tech

(Quarrelsome) Jetpacks. Programming is Technology and the more time we spend

(Saj) Profitable way of Exercising Brain Muscles.

(Saj) It makes you look brilliant to some audience.

(Saj) Makes you tech-smart.

(Saj) Makes you eligible to the future world.

(Saj) It's easy, fun, not in a math way..

(kiwiBastard) If the person likes problem solving then programming is no better

(kiwiBastard) Brilliant sense of achievement when you can interact with something

(kiwiBastard) Great way to meet chicks/chaps - erm, maybe not that one ([

(epatel) Learning how to program is like learning spell casting at Hogwarts . The

<p>Cons I have so far</p>

Can be frustrating when it's not working

Not physical exercise

(Rob Cooper) There are a lot of people doing it just for the money. They have no

(Rob Cooper) Not so sure about the initial cost.. Yeah you can get started with Java

(Rob Cooper) Its a lifelong career.. I truly feel you never really become a "master

(Rob Cooper) Some geeks can be hard to work with.. While I think the general ge

(Saj) Can cause virtual damage.

(Saj) Can make one throw their computer away.

(Saj) Can make one only virtually available to the world.

<p>Our team (5-10 developers) plans to adopt Subversion for ou

<p>What is the best way to organize a new repository tree? Is it c

<p>Our projects can be categorized this way (example):</p>

Main Product Line

Main Web App

Library 1

Library 2

...

Windows Client

Another Windows Client

Windows Service

Tools

Tool A

Tool B

Product Line 2

Software 1

Software 2

Product Line 3

App 1

App 2

<p>Some of the work we do at my company is slowly edging towards a product fam

configuration and build management

ease of development cycle

testing

305423

Product Line Engineering

<p>I am working on a software product line for online-tests automatic builds in cool

Thanks </p>

647830

Anyone recommends 'Pure Variants' for Soft'

<p>I have to port a smaller windows forms application (product configurator) to an

<p>I don't have access to a database and using XML is a requirement from their wet

<p>There are roughly 30 different products with roughly 300 different possible conf

<p>How would you solve the 'data access' layer, if you could call it this way? I thoug

<p>Is that even necessary, or smart, performance wise? As I said before, the app is i

657477

xml parsing / querying performance questior

<p>I am hoping that someone (or some people) could help us with a problem that w

<p>We are looking for any assistance (ideas about where to or how to search for th

<p>Some Details:

Some companies have product lines and some don't.

Each company has a list of contacts. If a company has at least one product line, som

A few of the contacts are references (business/personal) for other contacts.

Each company and each contact can have zero or more addresses.</p>

<p>Thank you for any assistance finding a more appropriate solution (My assumptic

<p><a href="http://www.flickr.com/photos/9844492@N08/3480423086/sizes/o/" i

<p>** (from the diagram) Our company has employees/internal application users w

<p>We have a legacy linker that uses libc5, and due to several factors we only have

<p>This linker works on linux kernel 2.6.24, but on 2.6.25 (and 2.6.26) it fails with th

<pre>

```
Virtual memory exceeded in `new'
```

</pre>

<p>We had a similar problem with the corresponding legacy compiler, but with som

<pre>

```
/proc/sys/kernel/randomize_va_space = 0 or 1
```

```
setenv MALLOC_TOP_PAD_ 536870912
```

</pre>

<p>This, however, does not help the linker.</p>

<p>I have found from using "ldd" that the linker has more shared library dependenc

<pre>

```
libg++.so.27 => /usr/lib/libg++.so.27 (0xb7eca000)
```

```
libstdc++.so.27 => /usr/lib/libstdc++.so.27 (0xb7e99000)
```

```
libm.so.5 => /lib/libm.so.5 (0xb7e90000)
```

```
libc.so.5 => /lib/libc.so.5 (0xb7dd3000)
```

</pre>

<p>And I have read that I may have to install the libc5 version of libg++.so.27. I hesit

<p>So, do I find and install the libc5 version of libg++.so.27, or is there some better

<p>Edit</p>

<p>See <a href="http://stackoverflow.com/questions/779964/legacy-gcc-compiler-

795510

legacy linker (uses libc5) fails on linux kernel

<p>Say on my old site I have one level categories of products, with one category bei

<p>Now we are building a new site, and have a 2 level structure... now we have top

<p>Key question -> where do we rewrite the old "BMW Cars" category page ? do we

<p>Say our old BMW Cars had 90% sedans and 10% SUV's, would it be more approp

<p>what if it is 80/20, or 95/5... what percent is the cut off or should we always poi

842071

How do you mod rewrite one level categorie

<p>Has anybody here implemented a software product line approach, as defined by

<p>For years we've basically been trying to follow a product line approach, but I am

<p>This has culminated in my getting an action item at our last PDR to explain the p

983390

Pros and Cons of Product Line Software Deve

<p>I was looking at salesforce.com as a means for our marketing group to manage t

1059047

Outlook Mailing List Distrubution Manageme

<p>I need to exclude a product line from a database so I do pline != prodctline but c
For instance:
here is simlplistic version of my database:</p>

<p>partname, pline, option (3 columns)</p>

<p>i want to exclude all results from a certain product line unless they have X option
soo</p>

<p>part name, product line, option</p>

<p>widget1 10 null</p>

<p>widget2 10 option1</p>

<p>widget3 10 option5</p>

<p>widget4 10 option2</p>

<p>so i might want to exclude all of product line 10 unless it comes with option 1.</p>

<p>or </p>

<p>i might want to exclude all of product line 10 but unless it comes with option 1 a

<p>Hope this helps</p>

<p>I'm not sure how to go about doing this in a query. Is there a sql clause that I'm i

<p>I was trying to do it with where pline != 90 and option = 'option1' but that was n

<p>Thanks</p>

1097950

mysql query excluding a set of data but inclu

<p>I'm working on a storefront application in PHP with MySQL. I'm currently storing

```
<pre><code>ProductLines
    id, name, description, etc.
SpecificProducts
    productLineID
    id, color, size, etc.
ProductImageLinks
    specificProductID
    imageID
Images
    id, imageFileLocation, name, etc.
</code></pre>
```

<p>It's working fine this way, but it seems like it's not very efficient for retrieval pur

<p>For example, I have a page that lists each product line along with a thumbnail of

<p>Another possibility I considered would be to use one query to get all the produc

<p>So my question is, is there a better way to store this data? Or a better way to re

<p>Edit: I'm not actually storing image files in the database. The image files are stor

1148500

How should I store product and product ima

<p>My company has a client that tracks prices for products from different companies

<p>These companies email the prices to our client each day, and of course the emails

<p>Some look sort of like this:</p>

<pre>

This is example text that could be many lines long...

Location 1

| Product 1 | Product 2 | Product 3 |
|-----------|-----------|-----------|
| \$20.99 | \$21.99 | \$33.79 |

Location 2

| Product 1 | Product 2 | Product 3 |
|-----------|-----------|-----------|
| \$24.99 | \$22.88 | \$35.59 |

</pre>

<p>Others look sort of like this:</p>

<pre>

| PRODUCT | PRICE | + / - |
|---------|-------|-------|
| ----- | ----- | ----- |

Location 1

| | | |
|---|---------|---------|
| 1 | 2007.30 | +048.20 |
| 2 | 2022.50 | +048.20 |

Maybe some multiline text here about a holiday or something...

Location 2

| | | |
|---|---------|---------|
| 1 | 2017.30 | +048.20 |
| 2 | 2032.50 | +048.20 |

</pre>

<p>Currently we have individual parsers written for each company's email format. E

<p>It's trivial for us to look at the emails and determine which price goes with which

<p>The code doesn't have to figure out the formats all on its own. The emails fall in

<p>Thanks for any suggestions about where to start.</p>

<p>Our company is migrating its entire product line from a C++ codebase to the .NE

<p>We would like to enjoy some of the benefits of pure managed code, such as Silv

<p>One solution would be for us to load these modules into a lightweight x86 emul:

<p>Does anyone know of such a project?</p>

<p>Sincerely,</p>

<p>Dan</p>

1411311

Lightweight x86 Emulator for .NET / Executin

<p>I'm trying to get a better handle on what it really means for a language to be "dy

<p>The way variables and lists are handled seems very "dynamic langua

<p>With variables, you would just write <code>foo = 3</code> or <code>bar = "Hell

<p>With lists, you can just write something like <code>miscCollection = [3, "Hello W

<p>Are these features enough to qualify for "dynamic language" status?</p>

<p>Interestingly, I've been using C# a lot more and Director/Lingo a lot less, but with

<p>EDIT</p>

<p>Regarding Mark Rushakoff answer, below, here's an attempt to analyze whether

<p><code>Eval</code> - Lingo has <code>do</code> and <code>value</code> I

<p>Higher-Order Functions - If I'm understanding this right, this is basically what

<p>Closures - No support for this as far as I know.</p>

<p>Continuation - No support for this as far as I know.</p>

<p>Reflection - In a sense at least, yes. You actually create new instances of type

<p>Macros - The way the Wikipedia article describes a macro, I don'

<p>So, it seems that Lingo scores a 2 to 3 out of 6 on dynamic features, but I'm not i

1657927

How can you tell if a language is a "dynamic I

<p>My company uses an internally developed package to support internationalizati

<p>I've looked at the Wikipedia entry on <a href="http://en.wikipedia.org/wiki/Inte

<p>For example, years and years ago I read a book called <a href="http://rads.stack

1765119

What Is a Good Introduction and Tutorial on

<p>I have a TabControl where the content of each TabItem is a master-details view.

<p>For the master, I'm using a listbox whose <code>ItemsSource</code> is bound t

<p>When I switch to another tab and then back to the original tab, the listbox selec

<p>What can I do to maintain the listbox selections in each tab when the tab selecti

<p>In normal use the end users will need to 'set up' the detail views the way they lil

<p>The TabControl looks like this:</p>

```
<pre><code>&lt;TabControl
    ItemsSource="{Binding DiagCards}"
    ContentTemplate="{StaticResource DiagCardViewTemplate}"
    SelectedItem="{Binding SelectedDiagCard}" /&gt;
</code></pre>
```

<p>The View for each TabItem has a ListBox that looks like this:</p>

```
<pre><code>&lt;ListBox
    ItemsSource="{Binding DiagCard.DevicesDetected}"
    SelectedItem="{Binding SelectedDevice}" /&gt;
</code></pre>
```

<p>The details are displayed in the TabItem using a ContentControl:</p>

```
<pre><code>&lt;ContentControl
    Content="{Binding SelectedDevice}"
    ContentTemplateSelector="{StaticResource SelectedDeviceTemplateSelector}" /&gt;
</code></pre>
```

<p>I should note that a simple test using hard-coded TabItems and ListBoxes c

```
<pre><code>  &lt;TabControl&gt;
    &lt;TabItem Header="tab 1"&gt;
        &lt;ListBox&gt;
            &lt;ListBoxItem&gt;
                &lt;TextBlock Text="item 1-1"/&gt;
            &lt;/ListBoxItem&gt;
            &lt;ListBoxItem&gt;
                &lt;TextBlock Text="item 1-2"/&gt;
            &lt;/ListBoxItem&gt;
        &lt;/ListBox&gt;
    &lt;/TabItem&gt;
    &lt;/TabControl&gt;
```

<p>I've recently come in contact with a proprietary descendant of UniVerse. Does a

<h1>UPDATED with the official Rocket Software links:</h1>

<p>Special attention needs to be given to <code>SQL Reference</code>:

<p>These links are official from Rocket Software (current owner of Uni* line of prod

<a href="http://www.rocketsoftware.com/u2/downloads/UVPE_RHLINUX_10.3.

<a href="http://serverfault.com/questions/103975/how-do-i-install-u2-universe

<a href="http://www.rocketsoftware.com/u2/pubs/library/103univ/" rel="nofol

<a href="http://www.rocketsoftware.com/u2/pubs/whitepapers.html" rel="nof

<a href="http://www.rocketsoftware.com/u2/pubs/library/" rel="nofollow nore

<p>Here is one that predates Rocket Software's aquisition of the product line:</p>

<a href="ftp://ftp.software.ibm.com/software/data/u2/" rel="nofollow noreferr

<a href="http://www.elink.ibm.com/publications/servlet/pbi.wss?CTY=l

2016486

UniVerse learning materials

<p>I have a php data migration script that <code>serializes</code> an array of text.

<p>Product Line: [56313] LEGO Batman Screenshot\\\\\\\\\\\\\\\\r\\\\\\\\\\\\\\\\n[5

6384] LEGO Batman Screenshot[56446] LEGO Batman Screenshot[56460] LEGO Bati

<p>There are no line breaks in between the different products (as you can see, ther

2058167

PHP Inserting newlines automatically

<p>I am redeveloping the front end and database for a medium size products datab

<p>Categories/Subcategories (multi level)

Products and product lines can be assigned to multiple category trees. Up to 5 level:

<p>Product lines (single level)

Groups of products. Product can only be in single product line.</p>

<p>Manufacturers (single level)

Products and product lines can be assigned to single manufacturer.</p>

<p>Supported software (single level)

Certain products only work with one or more softwares, so a product/line can be as

<p>Attribues (type / options - could be treated so each type is a category and items

Products and product lines can be assigned attributes (eg - color > red / blue / greer

<p>Since all these items are basically types of subcategories, do I put them all toget

<p>Master table idea:</p>

<p>ClassificationTypes (product line, category/sub, manufacturer, software, attribu

-TypeID

-Name</p>

<p>Classifications

-ClassID

-TypeID

-ParentClassID

-Name</p>

<p>ClassificationsProductsAssociations

-ProductID

-ClassID</p>

<p>I would still need at least one more table to link types together (eg - to link attril

<p>If I go with a table for each type it can get messy quick and I will still need a way

<p>Multiple table setup:</p>

<p>Categories

-CategoryID

<p>I'm planning to set up an online store for a friend, unfortunately his product line

<p>The specific issue is that the products are going to number in the hundreds of th

<p>I'd prefer something that's built on ASP.Net MVC since it'll play nicely with some

<p>I'd appreciate any ideas.</p>

<p>Edit: I've done a bit of searching already and I've found several (at least 8) MVC |

<p>Thanks Everybody!</p>

2126226

Need an ASP.Net eCommerce app that I can

<p>Over a year ago, I remember watching one of DevExpress evangelists previewing

<p>On checking today (Imgtfy) I can find only very very limited reference to it, just c

<p>With Javascript arguably the most popular programming language ever and with

<p>Someone once said since there are many style of writing Javascript a rich IDE (be

2432256

How far did DevExpress get with Javascript re

<p>I'm working on a regional ecommerce website (ie. usa, uk, china) that offers a ur

<p>Example URLs:

http://domain.cc

http://domain.com/

http://domair

2866615

i18n - Should the page URIs be translated on

<p>I work for a small E-Commerce shop and we are looking for a process that will h:

<p>Abobe Scene7 does exactly what we are looking to do and the images are server

<p>I'm curious to learn how others handle this process at their organizations. Does

2894247

Looking for a good Dynamic Imaging Solution

<p>I have been reading a lot about how flash development/design had died, and as

<p>I mean, I love coldfusion, and want that to continue to grow, however, if Adobe

<p><a href="http://topnews.us/content/221385-jobs-says-adobes-flash-waning-and"

<p><a href="http://aext.net/2010/03/javascript-jquery-killing-flash-tutorial-jquery-1"

<p>I really don't mind if Flash dies, I do mind greatly if coldfusion does.</p>

<p>Is the success of Flash linked to Coldfusion? If so, why? or why not?</p>

<p>The purpose of this isn't to start some war about flash pro's and con's. I was only

<p>That was my main concern...</p>

<p>And no I am not anti-flash...</p>

<p>But my financial sanity depends on Coldfusion being a success, so that is why I st

<p>Thank You.</p>

2969283

Is jQuery forcing Adobe ColdFusion to abandon

<p>I'm working with shape files in GeoDjango. Right now I'm trying to write a test f

<p>Since shape files aren't in a text format, is there a free application or library I can

<p>I should mention I don't have a license nor access to any of the ESRI pro

3016682

Split or save a subset of a ESRI Shape SHP file

<p>We have tons of products on our site. The vendors often raise the prices of their

<p>So I was wondering if there is a common practice for this?</p>

3335371

Is there a common practice for updating pro

<p>What are web-based databases?</p>

<p>I have heard this term a couple times.
Is it some special database structure or product line name?</p>

<p>Please, give me two words or more for more details. </p>

3467098

What are web-based databases?

<p>Let's say we are developing an E-Commerce Web application for a small to medium sized business.

<p>Up to now I have developed n-tier solutions using ADO.NET and stored procedures.

<p>I would like to move towards an ORM-based approach and am starting to learn about EF.

<p>As regards "overkill", I would like to know if:</p>

- EF is faster than someone with the correct skills coding queries manually
- EF leads to unnecessary code bloat
- EF unnecessarily shields devs from code-level details of their queries
- LINQ-to-Entities is suited for projects of this size

<p>In fact, if anyone thinks that an ORM is overkill for such project I'd like to hear reasons.

3743496

Is Entity Framework Overkill for Web Applications?

<p>Does it make sense to focus on Domain Specific Languages (DSL) development instead of ORM?

<p>Does anyone know any other approach to create and maintain several related Domain Specific Languages (DSL) for Domain Specific Languages (DSL)?

3753417

Software Product Lines (SPL) for Domain Specific Languages (DSL)

<p>I'm using jQuery's \$.ajax method to send and retrieve data to a REST service. So

<p>The problem lies with Chrome, Safari (Webkit) and Internet Explorer browsers. F

<p>As an example:</p>

```
<pre><code>$.ajax ({  
  url: "http://localhost:8080/rest/123/Product Line A/[Product Type B]",  
  type: "POST",  
  dataType: "json",  
  data: { ... },  
  success: function(...) {},  
  error: function(...) {}  
})  
</code></pre>
```

<p>Firefox POSTS the URL in the following format:</p>

```
<pre><code>http://localhost:8080/rest/123/Product%20Line%20A/%5BProduct%20Type%5B  
</code></pre>
```

<p>Chrome, Safari and IE POSTS the URL in the following format:</p>

```
<pre><code>http://localhost:8080/rest/123/Product Line A/[Product Type B]  
</code></pre>
```

<p>The REST services accepts the encoded (Firefox) format - is there a way I can ma

<p>Thanks in advance!</p>

4485808

jQuery's \$.ajax URL Encoding Problems

<p>Microsoft has augmented the existing Simplex (Linear) and Gradient (Non-linear

<p>I haven't heard a lot about people using this new engine and guess that most so

<p>I would therefore like to hear about your opinions and experiences with it, also

5688527

Opinions on and Experiences with Excel 2010

<p>I'm playing with Tibco Rendezvous, Tibco Designer + Tibco Business works for th

What are ActiveEnterprise adapters and ActiveEnterprise Schemas? When and v

What is difference between using Tibco Rendezvous Transport directly and Activ

Is it possible to use XSD schemes to define messages send by Tibco Rendezvous ?

Is there anything like WSDL document to describe what messages the service ex

How to write client for a service using ActiveEnterprise adapters and AESchemas

<p>Perhaps my questions are stupid because I don't grasp basics. </p>

5879902

I'm looking for basic explanations from Tibco

<p>I am working with taxonomies and nodes and I want to show them in a view.</p>

<p>My taxonomies are:</p>

<p>Product Category

- Product Line

-- Product

--- Features (Node)</p>

<p>I want to show this tree in a view but I can not get a good result.</p>

<p>For example I have:</p>

<p>Product category (phones)

- Product line (phone a)

-- Product (phone 104)

- Product line (phone b)

-- Product (phone 202)

- Product line (phone a)

-- Product (phone 124)

- Product line (phone b)

-- Product (phone 242)</p>

<p>And I want this result:</p>

<blockquote>
<p>phones

phone a

phone 104

phone 124

phone b

phone 202

phone 242</p>
</blockquote>

<p>Is this possible?</p>

<p>Amazon recently announced support for Oracle in their RDS product line:
http://aw

<p>I was wondering if anyone has used this, or if there would be a compelling reaso

<p>Obviously, the cost would be a bit higher, and clearly, Oracle is the more "matur

<p>Is the engine more efficient? Could I get away with a smaller instance and save

<p>Are there killer features in the product that make building apps faster / easier to

<p>Does it make sense for a small database, or is Oracle only important for scaling u

<p>I'm in the "evaluation" phase and just trying to get my head around a product th

6181295

Benefits of migrating from MySQL to Oracle 1

<p>To get the core question out of the way first: has anyone used the Ektron conten

<p>Now the background: we have a client with an existing site that is a fusion of Ekt

Drive as much basic content (copy) as possible from the Ektron CMS

Most other content would come from the custom database

Ecommerce functionality should integrate with the main site's cart (the cart is cu

Login status may need to be shared (I know there is already an SO question that

<p>I'd rather not struggle with WebForms and attempting to style Ektron controls, s

<p>Any insight is appreciated. Thanks!</p>

6283150

Ektron Content APIs and ASP.NET MVC

<p>I want to open a popup window of an Image on More Info link but I am not getti

```
<pre><code> &lt;a href="#"?w=700" rel="popup2" class="poplight"&gt;
    &lt;div class="meta"&gt;
    &lt;div class="show-more-info"&gt;+ More Info&lt;/div&gt;
    &lt;/div&gt;
    &lt;/a&gt;
</code></pre>
```

<p>And this is jquery part.</p>

```
<pre><code>&lt;script&gt;

var id_popover_content = '#popover_content';
var id_popover = '#popover';
var id_popover_mask = '#popover-mask';

var template_popover_waiting  = '&lt;div class="waiting"&gt;&lt;/div&gt;';

var current_doc_info = {id:"", url:"", title:"", repo:"", app:'docsearch2', ts:"", user:""};

var template_popover = '&lt;div id="popover" class="popover"&gt;&lt;div class="co
var template_meta = '&lt;p class="item"&gt;&lt;span class="label"&gt;{label}&lt;/sp

var template_popover= '&lt;div id="popup-meta"&gt;&lt;h4&gt;Meta Data&lt;/h4&

    $('body').append($('&lt;div id="popover-mask"&gt;&lt;/div&gt;'));

    $(id_popover_mask).click(on_popover_close);

    $('body').append($(template_popover));

$('.show-more-info').live('click', function(e) {

    alert("helo");
    e.preventDefault();
```

<p>This is a long shot, but anyway ... I am developing a video DSP system based on t
6396979

Anyone working with Stretch Inc's S6 or S7 b:


```
<pre><code>Updated Question
</code></pre>
```

<p>I am getting the error </p>

```
<pre><code>$.nano is not a function
</code></pre>
```

<p>And this is my below code.. Any idea why is it happening so? Or is there anything

<hr>

```
<pre><code>>window.onload=startDPSViewers;
```

```
    function startDPSViewers()
    {
        $('a.action.add-filter').text("");
        dps_ViewerManager.zoomViewerIndex = "http://somehost:8001/viewer/index.html";
        dps_ViewerManager.startViewers();
        DPS.startViewersOnLoad();
    }
}
```

```
var service_base_url = 'https://somehost/d/services/agile/getmeta?id=';
var id_popover_content = '#popover_content';
var search_agile_metadata = service_base_url ;
```

```
    var id_popover = '#popover';
var id_popover_mask = '#popover-mask';
var template_popover_waiting = '&lt;div class="waiting"&gt;&lt;/div&gt;';
var current_doc_info = {id:"", url:"", title:"", repo:"", app:'docsearch2', ts:"", user:""};
var template_popover = '&lt;div id="popover" class="popover"&gt;&lt;div class="content"&gt;
var template_agile_meta = '&lt;p class="item"&gt;&lt;span class="label"&gt;{label}&lt;/span&gt;&lt;/p&gt;';
```

```
var template_popover_agile = '&lt;div id="popup-meta"&gt;&lt;h4&gt;Meta Data&lt;/h4&gt;
var id1="";
var mySplit= "";
var rj="";
```

```
$(function(){
```

<p>I am using Team Foundation Server (TFS) 2008, and am preparing to merge seve

<p>I merging projects because the product line that is contained in all of the project

<p>I have tried researching this, and have found the following resources:</p>

<a href="http://stackoverflow.com/questions/2149919/moving-files-from-one-t

Moving files
control history, breaking merge capabilities

6876199 <p>The second resource, a Microsoft knowledge base article, actually looks pretty u
Team Foundation Server 2008: How to move

<p>I have a table connected to another table through foreign key;</p>

First Table is the brand; it has a brand_id and brand_name fields

Second Table is the Product Line; it has a Line_id and line_name fields

Third Table is the Lines Offered; it has a id, Brand (which is a foreign key from th

<p>If i will look into the third table on mysql the fields contains the id numbers of th

7020520 <p>My question is this, is it possible that the stored value will be the name itself and
Manipulating Foreign Keys output in MYSQL

<p>We are implementing an enterprise financial Web application software. We're u

<h3>Clarification:</h3>

<p>This problem is similar with "variability in time" in software product line (See <a

7498823 <p>But we can't solve it for other object types in spring such as entity, jsp, form?</p>
How to manage multiple version of classes at

<p>I have two tables:</p>

```
<pre><code>class Product(models.Model):
    code = models.ForeignKey(Product)
    regularprice = models.DecimalField (max_digits=8, decimal_places=2)

class Override(models.Model):
    productcode = models.ForeignKey(Product)
    specialprice = models.DecimalField (max_digits=8, decimal_places=2)</pre>
```

Data Example

=====

Product

Code	RegularPrice
------	--------------

C101	1.25
------	------

C102	2.50
------	------

C103	3.00
------	------

Override

ProductCode	SpecialPrice
-------------	--------------

C102	1.50
------	------

</code></pre>

<p>I want to do equivalent of a left outer join. The result set I want to achieve would be

```
<pre><code>Code    RegularPrice    SpecialPrice
C101     1.25         NULL
C102     2.50         1.50
C103     3.00         NULL
</code></pre>
```

<p>How would I do this?</p>

<hr>

<p>EDIT: I am trying to achieve a base price list, with optional override values. The result set I want to achieve would be

<p>Very sorry but I did leave out an important element of this question thinking it was irrelevant. I wish to generate a PriceList of all Products + if any Overrides are present for those products

<p>I wish to generate a PriceList of all Products + if any Overrides are present for those products

<p>The ORM query looks like this:

<p>I've successfully created my post meta boxes, saved the data and I understand h

<p>I have a class per the color scheme that is triggered when the body has a class o

```
<pre><code>&lt;body class="product-drinks"&gt;
</code></pre>
```

<p>OR </p>

```
<pre><code>&lt;body class="product-abcwidgets"&gt;
</code></pre>
```

<p>Depending on what product line is selected in the meta box for that post will de

<p>For example if I chose "product-drinks" then the stylesheet included would be <

<p>Most of the meta box data I need to use within the loop but I also need to acces

<p>I initially thought of placing some of the data in an array while in the loop as suc

<p>(outside of the loop in the header)</p>

```
<pre><code>&lt;body class="&lt;?php echo $page_options['pageBranding'];?&gt;
</code></pre>
```

<p>from within the loop"</p>

```
<pre><code>$page_options = array(
    'pageBranding' =&gt; get_post_meta($post_id, 'pageBranding', true),
    'layout'      =&gt; get_post_meta($post_id, 'pageLayout', true)
);
</code></pre>
```

<p>Am I doing this correctly or is there a better way of doing this? Or should I only r

7679577

Wordpress - referencing get_post_meta insic

<p>I am running an rails 2.3.5 app and getting a nil:Nilclass in a Controller#show.</p>

<p>This is my Show Action</p>

```
<pre><code>def show
  @category = Category.find_by_url_name(params[:id])
  @brands = @category.brands
  @categories = Category.find(:all)
  @meta_title = "#{@category.name}"

  respond_to do |format|
    format.html
      @brand = @brands.first
      @search = Product.search.order(params[:order] || 'descend_by_date')

      @products = @search.paginate(:conditions => { :category_id => @category.id }, :page => 1)
      render :template => 'brands/show'

    format.xml { render :xml => @category }
  end
end
</code></pre>
```

<p>The browser trace info:</p>

```
<pre><code> /Users/tjs/.rvm/gems/ruby-1.8.7-p352/gems/activerecord-2.3.5/lib/active_record/connection_adapters/abstract_adapter.rb:42:in `initialize'
/Users/tjs/.rvm/gems/ruby-1.8.7-p352/gems/searchlogic-2.5.8/lib/searchlogic/abstract_adapter.rb:42:in `initialize'
/Users/tjs/.rvm/gems/ruby-1.8.7-p352/gems/searchlogic-2.5.8/lib/searchlogic/abstract_adapter.rb:42:in `initialize'
/Users/tjs/.rvm/gems/ruby-1.8.7-p352/gems/searchlogic-2.5.8/lib/searchlogic/abstract_adapter.rb:42:in `initialize'
/Users/tjs/.rvm/gems/ruby-1.8.7-p352/gems/searchlogic-2.5.8/lib/searchlogic/abstract_adapter.rb:42:in `initialize'
/Users/tjs/.rvm/gems/ruby-1.8.7-p352/gems/searchlogic-2.5.8/lib/searchlogic/abstract_adapter.rb:42:in `initialize'
/Users/tjs/.rvm/gems/ruby-1.8.7-p352/gems/searchlogic-2.5.8/lib/searchlogic/abstract_adapter.rb:42:in `initialize'
/Users/tjs/.rvm/gems/ruby-1.8.7-p352/gems/searchlogic-2.5.8/lib/searchlogic/abstract_adapter.rb:42:in `initialize'
/Users/tjs/.rvm/gems/ruby-1.8.7-p352/gems/searchlogic-2.5.8/lib/searchlogic/abstract_adapter.rb:42:in `initialize'
/Users/tjs/.rvm/gems/ruby-1.8.7-p352/gems/searchlogic-2.5.8/lib/searchlogic/abstract_adapter.rb:42:in `initialize'
/Users/tjs/Sites/emeraldcg/app/controllers/categories_controller.rb:28:in `show'
/Users/tjs/Sites/emeraldcg/app/controllers/categories_controller.rb:25:in `show'
</code></pre>
```

<p>It points to the show action line 25 and 28, line 25 is the respond_to do |format|

<p>line 28 is the @search = Product line. </p>

<p>Whats weirder is that if I go to edit the category the url: /categories/amps/edit/

<p>So I'm new to grails and I am building a help desk application. The security part \

If logged as administrator user will have access to the administrative panel where h

First question/dilemma is which is the best way to implement the incident wizard? I

7964768

Grails HelpDesk

<p>Warning! This problem is not for the feint of heart. I've spent several d:

<p>I have a <code>Wizard</code> control with about 5 steps, each with several cor

<p>The <code>Wizard</code> along with all <code>PlaceHolder</code>s and their

<p>Depending on the ReferralUrl I call the following function to "Toggle" the view fr

```
<pre class="lang-vb prettyprint-override"><code>Protected Sub ToggleView() Handl
    If Wizard_mv.ActiveViewIndex = 0 Then
        ViewToggle.Text = "Toggle Wizard View"
        fPH1.Controls.Add(wPH1)
        fPH2.Controls.Add(wPH2)
        fPH3.Controls.Add(wPH3)
        fPH4.Controls.Add(wPH4)
        fPH5.Controls.Add(wPH5)
        Wizard_mv.ActiveViewIndex = 1
    ElseIf Wizard_mv.ActiveViewIndex = 1 Then
        ViewToggle.Text = "Toggle Form View"
        wPH1.Controls.Add(fPH1)
        wPH2.Controls.Add(fPH2)
        wPH3.Controls.Add(fPH3)
        wPH4.Controls.Add(fPH4)
        wPH5.Controls.Add(fPH5)
        Wizard_mv.ActiveViewIndex = 0
    End If
End Sub
</code></pre>
```

<p>Immediately after this, I use another function for pre-filling the controls with val

<p>Please do not answer unless you fully understand my problem

<p>Here's a sample of my markup in my <code>Wizard</code> (all styling removed

```
<pre class="lang-html prettyprint-override"><code>&lt;asp:WizardStep ID="Wizard!
&lt;asp:PlaceHolder ID="wPH1" runat="server" ViewStateMode="Enabled"&gt;
&lt;asp:Table ID="ProductInfoTable" runat="server" Width="100%"&gt;
    &lt;asp:TableHeaderRow&gt;
        &lt;asp:TableHeaderCell&gt;&lt;h3&gt;Product Line&lt;/h3&gt;&lt;/asp:Ta
        &lt;asp:TableHeaderCell&gt;&lt;h3&gt;Publication Type&lt;/h3&gt;&lt;/asp:
        &lt;asp:TableHeaderCell&gt;&lt;h3&gt;Request Type&lt;/h3&gt;&lt;/asp:Ta
    &lt;/asp:TableHeaderRow&gt;
```

<p>My problem is that if I click a button and the ajax has not returned yet and I click

<p>Scenario :

I am building a form and presenting a set of options based of drop down selections.

<p>The products are then looped over and I create a table via javascript to display t

8406682

cancel current event click and ajax call when

<p>We have a couple of commercial .Net 2.0 applications that run just fine on Linux

<p>When running our assemblies through <a href="http://mono-framework.com/N

<p>e.g., Our MoMa scan report gives:</p>

```
<pre><code>  Calling Method    Method with [MonoTodo]    Reason
    bool MyMethod ()    bool Type.op_Equality (Type, Type) Implement it properly or
</code></pre>
```

<p>What does this reason actually mean? Presumably, the Equali

8432753

MoMa reason "Implement it properly once 4

<p>I am here to ask for some high-level strategies for maintaining development of a

<p>I don't have experience maintaining mature projects in several platforms, so I w

<p>Thanks for all your feedback!</p>

8929714

Strategies for multi-platform (not just cross-ϕ

<p>I have a example for dynamic jasper report.</p>

<p>I am using NetBeans IDE.</p>

<p>I include library files as follows : </p>

```
<pre><code>Dynamic-jasper-3.2.1.jar
Dynamic-jasper-3.2.1-test.jar
jasperreport-4.5.jar
commons-beanutils-1.8.2.jar
commons-collections-3.2.1.jar
commons-digester-1.7.jar
commons-logging-1.1.jar
junit-3.8.2.jar
</code></pre>
```

```
<pre class="lang-java prettyprint-override"><code>import java.util.Date;
import net.sf.jasperreports.view.JasperDesignViewer;
import net.sf.jasperreports.view.JasperViewer;
import ar.com.fdvs.dj.domain.DynamicReport;
import ar.com.fdvs.dj.domain.builders.FastReportBuilder;
import ar.com.fdvs.dj.test.BaseDjReportTest;
```

```
public class FastReportTest extends BaseDjReportTest {
    public DynamicReport buildReport() throws Exception {
```

```
        FastReportBuilder drb = new FastReportBuilder();
        drb.addColumn("State", "state", String.class.getName(), 30)
            .addColumn("Branch", "branch", String.class.getName(), 30)
            .addColumn("Product Line", "productLine", String.class.getName(), 50)
            .addColumn("Item", "item", String.class.getName(), 50)
            .addColumn("Item Code", "id", Long.class.getName(), 30, true)
            .addColumn("Quantity", "quantity", Long.class.getName(), 60, true)
            .addColumn("Amount", "amount", Float.class.getName(), 70, true)
            .addGroups(2)
            .setTitle("November \"2006\" sales report")
            .setSubtitle("This report was generated at " + new Date())
            .setPrintBackgroundOnOddRows(true)
            .setUseFullPageWidth(true);
```

```
        DynamicReport dr = drb.build();
        return dr;
    }
```

<p>Bootstrap css uses the halflings from <a href="http://glyphicons.com/" rel="no

If I purchased their full product line, how would I incorporate that into the bootstra

9486443

bootstrap Glyphicons

<p>I want to create a library repository of code, if something is in the lib then it will

```
<pre><code>lib\  
JVCL\  
..\\  
JCL\  
..\\  
MyFrameworkABC\  
..\\  
MyLibraryXYZ\  
..\  
</code></pre>
```

<p>Currently I'm using multiples repositories per project or per product line</p>

```
<pre><code>projectA\ -&gt; repositoryA  
..\  
projectB\ -&gt; repositoryB  
..\  
</code></pre>
```

<p>When I make a tag in projectA I want to be able to go back in time exactly to the

<p>Because the two repositories are independent (project and lib), the only linkage

<p>I will be able to get a "bad" solution to my problem if I repeat the lib branch as a

```
<pre><code>projectA\ --&gt; repositoryA\tags\3.4.5  
lib\ --&gt; external to lib repository tag ( \lib\tags\1.5 for example)  
dvcl\  
vcl\  
..  
source\  
documentation\  
build\  
..  
projectB\ --&gt; repositoryB\tags\1.5.2  
lib\ --&gt; external to lib repository tag ( \lib\tags\1.3 for example)  
dvcl\  
vcl\  
..  
source\  
documentation\
```

<p>I'm trying to use knockoutjs to implement a simple click and edit system. The va

```
<pre><code>    function Item(label, value)
{
  this.label = ko.observable(label);
  this.value = ko.observable(value);

  this.editing = ko.observable(false);

  this.editItem = function(e) {
    this.editing(true);
  }

  this.checkEditDone = function(e,f) {

    if (e.which == 13)
    {
      this.editing(false);
    }
    else
      return true;
  };

  return this;
};

var SimpleViewModel = {

  editItem: function(item) {
    item.editing(true);
  },

  templateToUse: function(item) {
    return item.editing() ? 'editTpl' : 'viewTpl';
  },

  title : ko.observable(new Item('Request Title', 'EDIT THIS TITLE')),

  product_line : ko.observable(new Item('Product Line', 'EDIT THIS LINE'))
};

ko.applyBindings(SimpleViewModel);
</code></pre>
```

<p>I have a table: Order Detail. An Order has many details, in my case 100 fields. Is i

<p>Some of the data in the Order Detail table is used by Sales Managers, other data

<p>Should I keep it all together or should I break it apart and which NF would apply

9910058

If I have a table that has 100 fields does that

<p>I have some very ugly data I am trying to massage. It consist of SKUs and I want i

```
<pre><code>PRODUCT_ID
```

```
-----
```

```
313L30WHITE
```

```
313L40WHITE
```

```
313L30BLACK
```

```
3333
```

```
2L10RED
```

```
2L20BLACK
```

```
32341/30/BLK
```

```
</code></pre>
```

<p>Basically, I want to group items by the first numeric characters in the <code>PRC

```
<pre><code>PRODUCT_ID  GROUP
```

```
-----  ----
```

```
313L30WHITE  313
```

```
313L40WHITE  313
```

```
313L30BLACK  313
```

```
3333        3333
```

```
2L10RED      2
```

```
2L20BLACK    2
```

```
32341/30/BLK 32341
```

```
</code></pre>
```

<p>Seems like a SQL solution would not be elegant. Because of that, I would prefer

<p>Anyone have any suggestions? </p>

9969539

How to group rows by the numeric character

<p>I have three tables (lots in reality but these three are the ones I have to worry al

<p>A product line table like...</p>

```
<pre><code>ProductLineId (pk)
Name
Description
Price
Finance Event (FK)
</code></pre>
```

<p>and a finance event table like...</p>

```
<pre><code>EventId (pk)
Event Description
</code></pre>
```

<p>and a Financial Transaction table like...</p>

```
<pre><code>TransactionId (pk)
FinanceEventId (fk)
LotsOfSageReferencesAndOtherForeignKeys
</code></pre>
```

<p>When a sale is processed it creates transaction records based on the Finance Ev

<p>The question is; if someone in the admin then goes in and changes the Finance €

9995227

Non-destructive updates, versioning finance

<p>I am trying to query the <a href="http://developer.pintlabs.com/brewerydb/api

<p>These are two of the JQuery requests i tried (note that "O3tmVI" is a dummy ID)

```
<pre><code> $.ajax({
    url:"http://api.playground.brewerydb.com/beer/" + "O3tmVI" + "?key=A102&";
    dataType: "jsonp",
    jsonpCallback: "callbackfunctie",
    success:function(oData){
        var returnData = oData;
        console.log(returnData);
    }
});
</code></pre>
```

<p>And:</p>

```
<pre><code>$.getJSON("http://api.playground.brewerydb.com/beer/" + "O3tmVI" + "?key=A102&";
    function(data){
        console.log(data);
    });
</code></pre>
```

<p>Both cause this error:</p>

```
<blockquote>
<p>Uncaught SyntaxError: Unexpected token :</p>
</blockquote>
```

<p>Now, the json object returned looks like this:</p>

```
<pre><code>{"message":"Request Successful","data":{"id":"O3tmVI","name":"The F
</code></pre>
```

<p>I have succesfully validated it as valid JSON</p>

<p>Now, the problem is i need a JSONP object in order to request it (cross-domain).

<p>I found this article wich has a short entry on this bug: <a href="http://www.jque

```
<blockquote>
<p>Uncaught SyntaxError: Unexpected token : (in chrome) Invalid Lable (in firefox)
"invalid label" error can be fixed by passing the JSON data to the is callback</p>
```

<p>UPDATE: This problem is probably due to my lack of understa

<p>I'm trying out ASP.Net MVC4 SPA Projects with real-world type scenarios. Since I

<p>Everything was ok until I had to post data with arbitrary parameters:</p>

<p>This is my controller:</p>

```
<pre><code>public class ProductLineController : DbDataController<WebSiteConti
{
    [HttpPost]
    public HttpResponseMessage<Order> AddProductLine(int productId, int ord
    {
        [invoke logic to add the product line]
        [return the updated order]
    }
}
</code></pre>
```

<p>The client code to invoke this controller is on a Knockout viewmodel as follows:</p>

```
<pre><code>this.addProduct = function (product) {
    var prodId = product.ProductId;

    var requestUrl = baseUrl + "productline";
    $.ajax({
        url: requestUrl,
        cache: false,
        type: 'POST',
        data: JSON.stringify({productId: prodId, orderId: orderId}),
        dataType:"json",
        contentType: 'application/json; charset=utf-8',
        success: function (data) {
            self.order(data);
        }
    });
}</code></pre>
```

<p>Very straightforward. I took the precaution to stringify the json parameter data

<p>The Request Headers as reported by Fiddler are:</p>

```
<pre><code>POST http://localhost:50045/api/orderedproduct HTTP/1.1
```


<p>I'm writing a custom text field type for my product SKUs.</p>

<p>If I have a SKU such as <code>ABC-DEF123G/5</code> (just an example), I want

<p>So far, I've got my <code>schema.xml</code> looking like:</p>

```
<pre><code>&lt;fieldType name="sku" class="solr.TextField" omitNorms="false"&g
&lt;analyzer&gt;
  &lt;tokenizer class="solr.KeywordTokenizerFactory"/&gt;
  &lt;filter class="solr.LowerCaseFilterFactory"/&gt;
  &lt;filter class="solr.WordDelimiterFilterFactory"
    splitOnCaseChange="0"
    splitOnNumerics="0"
    stemEnglishPossessive="0"
    catenateAll="1"
  /&gt;
  &lt;filter class="solr.EdgeNGramFilterFactory" minGramSize="3" maxGramSize=
&lt;/analyzer&gt;
&lt;/fieldType&gt;

&lt;!-- For use in Sunspot: --&gt;
&lt;dynamicField name="*_sku" stored="false" type="sku" multiValued="true" inde
</code></pre>
```

<p>This works well in that I can search for parts of a SKU, e.g. <code>DEF123</code>

<p>When I do analysis on my schema I see that searching for <code>ABCDEF123G5</code>

<p>I have restarted Solr and reindexed my documents. Many times.</p>

<p>Any pearls of wisdom on indexing SKUs or similar?</p>

<hr>

<p>This editor (aitchn

<blockquote>

<p>A stock-keeping unit or SKU is a number or code used to identify each unique product or item for sale in a store or other business.</p>

<p>It is a unique identifier for each distinct product and service that can be purchased. The usage of SKU is rooted in data management, enabling the company to systematically track its inventory or product

<p>I'm facing a problem when I try to grab the Extended Amount Attribute inside th
As follows my requirements are that upon creation of a an Opportunity Product Line

```
<pre><code>// Part where I grab the value  
Entity entity = (Entity)context.InputParameters["Target"];  
Money extenedAmount = (Money)entity["baseamount"];  
  
//Create new line  
Entity oppportunity_product = new Entity("opportunityproduct");  
oppportunity_product["manualdiscountamount"] = extenedAmount;  
  
service.Create(oppportunity_product);  
</code></pre>
```

<p>Is it even possible to grab the amount? Would really much appreciate if someone

11160383

Grab System Created Values CRM 2011

<p>I have a ViewModel called AssetSearchModel with a property of type: List. </p>

<p>When I post from the ViewModel, all the properties of my List get binded back t

<p>That domaincontrol has a couple of properties and then its own nested list... noi

```
<pre><code>public class AssetSearchModel
{
    public List<SearchControlModel> SearchControls { get; set; }

    public AssetSearchModel()
    {
    }
}
```

```
public class SearchControlModel
{

    /// <summary>
    /// Asset identifier.
    /// </summary>
    [DisplayName("AssetId ID")]
    public int SearchOptionID { get; set; } // this gets bound ok

    [DisplayName("Asset Customer ID")]
    public int AssetCustomerID { get; set; } // this gets bound ok

    [DisplayName("Portal ID")]
    public int PortalID { get; set; } // this gets bound ok

    [DisplayName("Calling Page")]
    public string CallingPage { get; set; } // this gets bound ok

    [DisplayName("Display Control")]
    public string DisplayControl { get; set; } // this gets bound ok

    [DisplayName("Display Text")]
    public string DisplayText { get; set; } // this gets bound ok

    public string ControlValue { get; set; } // this gets bound ok

    [DisplayName("Search Table")]
```

<p>I'm developing a search engine type of application using JSF. Upon searching usi

<p>I tried jquery UI multiselect plugin, but the headers remain the same for all cate

<p>Is there any other way to change the header dynamically or any other compone

11779938

autocomplete for multiple search categories

<p>I'm trying to add a product to an ubercart order in Drupal 6, for a "free gift for re
What I am struggleing with, is adding the product to the order. I'm able to add the p

<blockquote>

<p>uc_cart_add_item(\$settings['gift_product'], \$settings['gift_product_quantity']

</blockquote>

<p>To avoid fraud, and the customer not just clicking back and change the quantity
The following code, does not add a product line, but a "charge", but it's the closest I

<blockquote>

<p>uc_order_line_item_add(\$order->order_id, \$settings['gift_product'], \$produc

</blockquote>

<p>As a side thing, I would like to know, if it's possible, and then how, to set the pri

<p>I've been searching for a solution for this, for the most of a week, but I can't see

<p>Thank you in advance.</p>

11811680

Ubercart 2.x - Add produkt line to order via p

<p>Check is a model that has the attributes product_line_id and ·

<p>I have four instances of the Check model. They all have different dates. Two be

<p>How do I call a query on the Check model to return one check for each product I

11818944

SQL query in rails to group ordered records

<p>I am pulling out order details in Magento (4.1.1) with the below code, which wo

```
<pre><code>$_customerId = Mage::getSingleton('customer/session')-&getCustor
    $lastOrderId = Mage::getSingleton('checkout/session')-&getLastOrderId();
    $order = Mage::getSingleton('sales/order');
    $order-&load($lastOrderId);
    $_totalData = $order-&getData();
    $_order = $this-&getOrder();
    $allitems = $order-&getAllItems();
    $index = 1;

    $data = ""

    foreach($allitems as $item)
    {
        $cjData.="| ".$item-&getPrice().": ".$item-&getName().": ".$item-&getQ
        $index++;
    }

    echo $cjData
</code></pre>
```

<p>If the same item is purchased multiple times in the same order, I need to treat tl

11969754

If the same item is purchased multiple times

<p>I am about to start work on a Mozilla plugin for my company's main product line

<p>However, I was just reading the documentation and I found this:</p>

<blockquote>

<p>For Gecko versions before 2.0, you should choose the Gecko SDK version for th
</blockquote>

<p>Someone please tell me this doesn't mean what I think it means. Does this mear

12007977

Mozilla Plugins, will I have to recompile each

<p>I'm working on a Volusion webstore. I'm doing some custom templating, design

<p>The Volusion Support Center has the following article:</p>

<blockquote>

<p>There may be times when you need to close your storefront for a brief period.

To temporarily close your store:

Go to Settings > Maintenance in your Admin Area.

Click Close My Store.

To re-open the store when your changes have been made, click Open My Store. </|

<p>Closing the store does not hinder your access to the Admin Area. While the sto

Visitors to your storefront will be greeted with a default message stating that the s

You can tailor this message by clicking [Customize Your Maintenance Message Here](#)

</blockquote>

<p>Sadly, this is not what I want. I want my production webstore to keep running w

<p>What would be a good way to achieve this? I've been thinking about copying all

12697309

Duplicate a Volusion webstore for testing pu

<p>I have 3 models:</p>

```
<pre><code>class ProductLine < ActiveRecord::Base
  has_many :specifications
  has_many :specification_categories, :through => :specifications,
end
```

```
class Specification < ActiveRecord::Base
  belongs_to :product_line
  belongs_to :specification_category
end
```

```
class SpecificationCategory < ActiveRecord::Base
  has_many :specifications
  has_many :product_lines, :through => :specifications
end
</code></pre>
```

<p>Basically, we are showing the specifications as a subset of data on the product li

<p>Controller:</p>

```
<pre><code>@product_line = ProductLine.find(params[:id])
@specification_categories = @product_line.specification_categories)
</code></pre>
```

<p>View:</p>

```
<pre><code>@specification_categories.each do |specification_category|
  ...
  specification_category.specifications.each do |specification|
    ...
  end
end
</code></pre>
```

<p>The issue here is getting rails to filter the specifications by ProductLine. I've trie

<p>I came across a timeout function in a product line code which get me really conf

```
<pre><code>int TestTimeOut(unsigned long Timed_Val1, unsigned long Timed_Val2
{
    Timed_Val2 = Timed_Val1 + (Timed_Val2 * 200);
    if (((Timed_Val1 > Timed_Val2) && (sys_msec < Timed_Val1) &am
        return TRUE;
    return FALSE;
}
</code></pre>
```

<p>And here is how it's used:</p>

```
<pre><code>unsigned long Timeout = sys_msec;
#define MAX_TIMEOUT 15L

    while (!com_eot(1)) //to check if some transmission in progress in COM1
        if (TestTimeOut(Timeout, MAX_TIMEOUT))
            return FALSE;
    return TRUE;
</code></pre>
```

<p>How does it work? I am totally confused by the 3 lines in TestTimeOut(). Thanks,

13239129

A simple timeout function

<p>Hi I am using InfoWindow to get custom popup on google maps,
but I can't set it width, I tried setting it inline to wrapper tag, but it doesn't work.
In this case I need it to be 750px.</p>

<p>Here is jsfiddle: http://jsfidd
and here is html file: <a href="http://www.mediafire.com/view/?66dbe6xzn1mul10

<p>Here is method that is setting InfoWindow content:</p>

```
<pre><code> function getContent(parts, kmlEvent) {  
  
    var content = "" +  
    "&lt;div id='width800' class='google-infobox-content' &gt;" +  
    "&lt;div class='image'&gt;" +  
    "&lt;img src='http://maps.google.com/maps/api/staticmap?center=" + kml  
    "&lt;br /&gt;" +  
    "&lt;a href='https://maps.google.com/maps?sensore=true&amp;daddr=" +  
    "&lt;a href='http://maps.google.com/help/maps/directions/Somewhere' t:  
    "&lt;/div&gt;" +  
    "&lt;div class='location'&gt;" +  
    "&lt;p&gt;" + parts[0] + "&lt;/p&gt;" +  
    "&lt;p&gt;" + parts[1] + "&lt;/p&gt;" +  
    "&lt;p&gt;" + parts[2] + "&lt;/p&gt;" +  
    "&lt;br/&gt;" +  
    "&lt;p&gt;" + parts[3] + "&lt;/p&gt;" +  
    "&lt;/div&gt;" +  
    "&lt;div class='contact'&gt;" +  
    "&lt;p&gt;" + parts[4] + "&lt;/p&gt;" +  
    "&lt;p&gt;" + parts[5] + "&lt;/p&gt;" +  
    "&lt;a href='mailto:" + parts[6] + "' &gt;" + parts[6] + "&lt;/a&gt;" +  
    "&lt;a href='" + parts[7] + "' target='_blank' &gt;" + parts[7] + "&lt;/a&gt;" +  
    "&lt;/div&gt;" +  
    "&lt;div class='others'&gt;" +  
    "&lt;p&gt;&lt;b&gt;Product line&lt;/b&gt;&lt;/p&gt;" +  
    "&lt;p&gt;" + parts[8] +  
    "&lt;/p&gt;" +  
    "&lt;/div&gt;" +  
    "&lt;/div&gt;";  
  
    return content;  
}  
</code></pre>
```

<p>I have a drupal commerce + line items + taxonomies + fancy attributes.</p>

<pre><code>Product:

-sku

-...

-shape (product line item) - taxonomies (text + image)

</code></pre>

<p>And taxonomies images doesn't display at all (text is ok).</p>

<p>When I do it with product variations (shape (product field) - taxonomies (image)

<p>How I'll display the taxonomy image from a line item?

(maybe some other solution?)</p>

13961422

Drupal commerce line items + images

<p>I have a faulty xml feed. It cuts off some of the nodes, they are broken and I get

```
<pre><code>Warning: DOMDocument::load() [function.DOMDocument-load]: Prem
hotelDescription line 30760 in /srv/disk9/561574/www/source.xml, line: 30760 in /:
Warning: DOMDocument::load() [function.DOMDocument-load]: Premature end of
Warning: DOMDocument::load() [function.DOMDocument-load]: Premature end of
0
</code></pre>
```

<p>I have setup an error handler but I'm not sure how to, or if it is even possible, to

```
<pre><code>/* load the file on the DOM*/
$dom = new DomDocument();
$dom->load($filename);

if (!$dom->load($filename)) {
    foreach (libxml_get_errors() as $error) {
        // handle errors here
    }

    libxml_clear_errors();
}
</code></pre>
```

<p>Any help greatly appreciated, thanks.</p>

14213470

Skip xml "premature end of data" error

<p>Alright, so I have these checkboxes of Products and I want to make sure at least

<p>To do this, my ViewModel contains:</p>

```
<pre><code>[DisplayName(@"Product Line")]
[MinChecked(1)]
public List<CheckboxInfo> ActiveProducts { get; set; }
</code></pre>
```

<p>The View simply contains:</p>

```
<pre><code>@Html.EditorFor(x => x.ActiveProducts)
</code></pre>
```

<p>That EditorTemplate contains:</p>

```
<pre><code>@model Rad.Models.CheckboxInfo

@Html.HiddenFor(x => x.Value)
@Html.HiddenFor(x => x.Name)
@Html.CheckBoxFor(x => x.Selected)
@Html.LabelFor(x => x.Selected, Model.Name)
</code></pre>
```

<p>The custom dataannotation is:</p>

```
<pre><code>[AttributeUsage(AttributeTargets.Property, AllowMultiple = true)]
public class MinCheckedAttribute : ValidationAttribute, IClientValidatable
{
    public int MinValue { get; set; }

    public MinCheckedAttribute(int minValue)
    {
        MinValue = minValue;
        ErrorMessage = "At least " + MinValue + " {0} needs to be checked.";
    }

    public override string FormatErrorMessage(string propName)
    {
        return string.Format(ErrorMessage, propName);
    }
}
```

```
protected override ValidationResult IsValid(object value, ValidationContext valida
```

<p>I'm working with a crosstab in cognos now.</p>

<p>Page 1 contains crosstab</p>

<p>Page 2 contains list</p>

<p>Fact - Revenue

Dimension - Product line, Year</p>

<p>If I click on the revenue (cell value) it should goto the particular record in anothe
However, the fact could not be bookmarked. I don't know why. Do you have sugges

<p>Thanks in advance. </p>

14277751

Why bookmark is not working for facts in cog

<p>I would like to know if I can use the promotion group functionality to take one p

<p>I want this to used it as compatibility rule, I.E., a product from product line A exc

14477522

Siebel promotion groups

<p>I have a MDX Dimension , whose main hierarchy has the following levels :</p>

```
<ol>
<li> <strong>Product Line</strong> key : PLid</li>
<li> <strong>Profit Center</strong> key : PCid</li>
<li> <strong>Team</strong> key : TEid</li>
<li> <strong>Employee</strong> ( binding level to my fact tables ) </li> key: EMPid
</ol>
```

<p>This one works fine, but the users want a flexible upper part of the hierarchy, th

```
<ol>
<li><strong>Year</strong> </li>
<li><strong>Product Line</strong> </li>
<li><strong>Profit Center</strong> </li>
<li><strong>Team</strong> </li>
<li><strong>Employee</strong> </li>
</ol>
```

<p>with the attribute relationship "Product Line" -> "Profit Center" varying a lot fro

<p>The problem I have is that facts are more than often linked to more than one el

<p>I have a table giving the association (Year, PLid, PCid)</p>

<p>What I can't do is forcefully binding elements of the fact table on this new hiera

<p>I'm working with a crosstab in cognos now.</p>

<p>Page 1 contains crosstab</p>

<p>Page 2 contains list</p>

<p>Fact - Revenue Dimension - Product line, Year</p>

<p>If I click on the revenue (cell value) it should goto the particular record in anothe

<p>Thanks in advance.</p>

14563838

How to pass two values when a bookmark is

<p>I'm trying to figure out how to integrate an accordion type of menu and a flyout

<p>Has anyone seen any existing code like this or better yet, can anyone show me h

```
<pre><code>&lt;ul&gt;
&lt;li&gt;Manufacturer 1 (drops product lines in accordion)
&lt;ul&gt;
&lt;li&gt;Product Line 1
&lt;ul&gt;
&lt;li&gt;Product 1&lt;/li&gt; (flyout menu for products)
&lt;li&gt;Product 2&lt;/li&gt;
&lt;/ul&gt;
&lt;/li&gt;
&lt;li&gt;Product Line 2
&lt;ul&gt;
&lt;li&gt;Product 1&lt;/li&gt;
&lt;li&gt;Product 2&lt;/li&gt;
&lt;/ul&gt;
&lt;/li&gt;
&lt;/ul&gt;
&lt;/li&gt;
&lt;li&gt;Manufacturer 2
etc...
</code></pre>
```

14649428

accordion menu with nested flyouts

<p>I am not sure if this is possible , this might look strange, but I am having nightma

<p>I have a strange requirement where I need to pass a string that is 20000 charact

<p>Let me give a little background</p>

<p>I have a Dimension in the cube with an attribute called Product Line Code which

<p>Following is what I have done which is not a big deal I know
wrote a small function in SQL that reads the values from Report Filter table to creat
{[Product].[Product Line].[Code].&[1],[Product].[Product Line].[Code].&[2]

<p>when I call this function in SSRS Dataset, it returns a blank value though it works

<p>My question is how do I pass this big value string through SSRS parameter to use

<p>Is there any other option, has any one come across this kind of Scenario.</p>

<p>Appreciating your help</p>

<p>Thanks
Alex Sebas</p>

14700391

SSRS-MDX Slicer(Passing big String as a Slicer

<p>Currently I'm working Cognos 10.1 report studio. </p>

<p>The requirement is that the output should be in such a way that the crosstab sh

<p>Eg:
Crosstab has the product line in row; product in column; revenue in d

<hr>

<p>The number of products for each product line differs. The crosstab should be in

<hr>

<p>Please help me.</p>

15000903

How to control the report output in Cognos 1

<p>I have a question regarding a problem I'm facing. Is there any way I can have a w

<p>My scenario: I have a workflow waiting until 6 months before contractline expir

<p>Problem: The contract can have more than one contractline expiring at the same

<p>Any help would be much appreciated. Thanks.</p>

15413278

CRM Dynamics Workflow Waiting Conditions

<p>Background</p>

<p>I am trying to predict the sales for a product line (y_{test} in the sample at the end of the time period).

<p>For instance, if you make accessories for a particular smartphone model, the accessories sales are a function of the time period.

<p>Details</p>

<p>I have some time series data and would like to fit a regression model using `glm`. The dependent variable is y_{test} and the independent variable is x_{test} .
</p>

<p>Where p is the time period, y_{p} is the dependent variable, x_{p} is the independent variable.

<p>Through the first three time periods, the function would expand to something like this:

```
<code>#y[1] = c0 + c1*(x[1]*(1-integrate(function(q) {pgamma(q, c2, c2/c3)}, 0, x[1])$value) +  
#y[2] = c0 + c1*(x[1]*(1-integrate(function(q) {pgamma(q, c2, c2/c3)}, 1, 2)$value) +  
#y[3] = c0 + c1*(x[1]*(1-integrate(function(q) {pgamma(q, c2, c2/c3)}, 2, 3)$value) +  
</code></pre>
```

<p>So, I have historical data for x_{p} and y_{p} , and I want to predict y_{test} given x_{test} .

<p>I think the solution is to use `glm` and create a custom family function.

<p>Here is some example data:</p>

```
<code># Survival function (the integral part):  
fsurv<-function(q, par) {  
  l<-length(q)  
  out<-vapply(1:l, function(i) {1-integrate(function(x) {pgamma(x, par[1], par[1]/par[2])$value, 0, x[i]}), FUN.VALUE=0)  
  return(out)}</code>
```

```
# Sum up the products:  
frevsumprod<-function(x,y) {  
  l<-length(y)  
  out<-vapply(1:l, function(i) sum(x[1:i]*rev(y[1:i])), FUN.VALUE=0)  
  return(out)}</code>
```

```
# Sample data:  
p<-1:24 # Number of periods  
x_test<-c(1188, 2742, 4132) # Sample data  
y_test<-c(82520, 308910, 749395, 801905, 852310, 713935, 624170, 603960, 640000, 680000, 720000, 760000, 800000, 840000, 880000, 920000, 960000, 1000000, 1040000, 1080000, 1120000, 1160000, 1200000)  
c<-c(-50, 161147, 128, 787437, 0, 817085, 13, 845487) # Coefficients and parameters
```

<p>We are working on two product lines that will share the same code. </p>

<p>For functionality that differs, I have both product lines implement the same inte

<p>For code that is deep inside the business logic, it is very hard to have product lin

<p>So I am planning to implement a Factory class which will have static methods to

<p>So with the above approach, the factory(which internally contains ProductLine1

<p>Do you know a better approach to this problem. Please note that ProductLine1 \

<p>The factory approach typically exposes an interface, but the problem with interf

<p>I would really appreciate if some experts would shed some light.</p>

15534118

2 Product lines sharing same code

<p>I am building a page to bring attention to available parts and accessories for a pr

<p><a href="http://www.snoscoot.com/fcaccessories/hondapowerequipment/test.

<p>Here's a link to a screenshot pointing out what I need to be able to make disapp

<p>The pages that are going to be displayed in that iFrame always have the "div" cl

15574561

<div> blocker for iframe content

<p>Just started trying out Breeze today, long time EF user - think I found a bug in Br

<p>I have a simple hierarchy in EF Code First:</p>

```
<pre><code>// For testimonials about the product line in general
public class Testimonial
{
    public int Id { get; set; }

    public string Text { get; set; }
}

// For testimonials specific to a single product
[Table("ProductTestimonial")]
public class ProductTestimonial : Testimonial
{
    public Product Product { get; set; }
}
</code></pre>
```

<p>So just to be clear there's 2 tables here, Testimonial and ProductTestimonial, bo

<p>So I setup the BreezeController via WebApi:</p>

```
<pre><code>[BreezeController]
public class EFController : ApiController
{
    private readonly EFContextProvider<EfDb> _db = new EFContextProvider<EfDb>()

    [HttpGet]
    public string Metadata()
    {
        return _db.Metadata();
    }
}
</code></pre>
```

<p>And I go to load it in breeze.js:</p>

```
<pre><code>var manager = new breeze.EntityManager('/api/ef');
manager.executeQuery(breeze.EntityQuery.from('Product'));
</code></pre>
```

<p>Kahlamo Exception. It says:</p>

<p>My hope was, that engines would enable me to easily add or remove features in

<p>The case would be a product line of apps that are pretty similar. I would start de

<p>I would like this to work a bit like aspects in AOP, where I can declare dependen

15888226

How to easily remove Rails engines?

<p>How can I make the A line chart with a data table docked under the x-axis in das

<p>http://

<p>The Chart Name is Product Line Global Revenue </p>

16076514

A line chart with a data table docked under t

<p>I have two lead forms created. One for Office Furniture Product Line and the oth

16090153

CRM 2011 Set static values to same option se

<p>I've created a sub-grid in Contacts Entity to show related lead records for the co

<p>When the user clicks Add new lead from the sub-grid in contacts form, it should

16107663

How to set a default form from sub-grid

<p>http://adamginther.com

<p>I currently have toggle activated for each piece work on my portfolio. I want to r

```
<pre><code>&lt;section id="displays"&gt;
  &lt;div id="dragonupdisplay"&gt;
    &lt;p&gt;&lt;class id="blueText"&gt;You are viewing: DragonUp Wireframes &l
      &lt;br&gt;
      &lt;br&gt;
      I was tasked with proposing a re-design of its UI. Currently, the game has 10 c
      &lt;img src="images/work/dragonup-wireframe1.png"&gt;
    &lt;/div&gt;
    &lt;div id="provincedisplay"&gt;
      &lt;p&gt;&lt;class id="blueText"&gt;You are viewing: Province Sports Wirefram
        &lt;br&gt;
        &lt;br&gt;
        There was plenty of focus made on creating an experience that is custom tail
        &lt;img src="images/work/provincesports.png"&gt;
      &lt;/div&gt;
      &lt;div id="canucksdisplay"&gt;
        &lt;p&gt;&lt;class id="blueText"&gt;You are viewing: Canucks Usability Tests;
        &lt;br&gt;
        &lt;br&gt;
        I was tasked with testing the usability of Canucks.NHL.com's community featu
        &lt;img src="images/work/canucks1.png"&gt;
      &lt;/div&gt;
      &lt;div id="pencilmeindisplay"&gt;
        &lt;p&gt;&lt;class id="blueText"&gt;You are viewing: Pencil Me In Concept
        &lt;br&gt;
        &lt;br&gt;
        The app's main intent was to create a booking system that was easier and fas
        &lt;img src="images/work/pencilmein1.png"&gt;
      &lt;/div&gt;
      &lt;div id="attackdisplay"&gt;
        &lt;p&gt;&lt;class id="blueText"&gt;You are viewing: Attack of the Space Lep
        &lt;br&gt;
        &lt;br&gt;
        The goal of this website was to tell an interactive story by creating advanced
        &lt;img src="images/work/responsive1.png"&gt;
      &lt;/div&gt;
      &lt;div id="rebelliousdisplay"&gt;
        &lt;p&gt;&lt;class id="blueText"&gt;You are viewing: Rebellious by Nav Mc
        &lt;br&gt;
```

<p>I've got a list of about 200,000 plus records divided up by sub-product line which

<p>For example: </p>

<p>(BTW, how do I actually show a table in my question?)</p>

<p>What I want is a where statement which will only include results that have ONLY

<p>Any ideas? </p>

16845696

SQL Where Only In

<p>I am using Fixed Product Taxes (FPT) which we are calling a "Service Fee" to char

<p>This works great, but when I apply a "Promo Code" (Shopping Cart Price Rule) th

<p>I cannot post an image, but here is what the cart shows:

Product Line Item: \$22 (\$18 + \$4 FPT (we call it a "service fee"))

Subtotal: \$22

Discount (PROMO): -\$22

Grand Total: \$4</p>

<p>The total should have been calculated to be \$0, since \$22 - \$22 = 0.</p>

<p>I have already tried setting "Apply Discounts To FPT" to YES in System > Configur

<p>The Shopping Cart Price Rule uses a "Fixed Price Discount" of \$22, when the pro

<p>I am using Magento Community 1.6.1.0.</p>

17220501

Incorrect Grand Total in Magento

<p>I have a series of files outlining different product builds, and each file is named v

<p>Edit:

The pertinent info here is "2940UB200L". "2940" is the product line, given by the us

<p>Sample text... Doesn't seem to be formatting the same in the preview as what I'

<p>PRODUCTION PLANT INDENTED BILL

PARENT ITEM NO. DESCRIPTION ROUND RING

2940UB200L ENGR DRAW 00000LM000/ZN31
 STANDARD BATCH QUANTITY 1.000 RELATIVE SEQ RELATIVE
LEVEL NO. ITEM NO. DESCRIPTION DRAWING NUMBER PER</p>

<p>Working code:</p>

<pre><code>Sub ChangeFileName()

```
Dim objFSO As Object
Dim objFolder As Object
Dim objFile As Object
Dim ProdLine As String 'Product Line to search
Dim CatNum As String 'Full Part number
'Get the folder object associated with the directory
With Application.FileDialog(msoFileDialogFolderPicker)
    .AllowMultiSelect = False

'Close macro when no folder is selected
If .Show &lt;&gt; -1 Then MsgBox "No folder selected! Exiting sub...": Exit Sub
myDir = .SelectedItems(1)
```

```
On Error Resume Next
```

```
FolderName = .SelectedItems(1)
Err.Clear
```

```
On Error GoTo 0
```

```
End With
```

```
'Gives File list a header
Set objFolder = objFSO.GetFolder(FolderName)
'Prompts user for Product Line
ProdLine = InputBox("Enter product line prefix (example: 2940)")
```


<p>Within a AmCharts Line Chart (Javascript) there is a setting to change the colour

<p>There is also a setting to change the base negative value from 0 to something el:

<p>What I have is 2 line graphs, one a target line (straight gradient of 1:4) and the o

<p>Does anyone know if there is a way to have the negativeBase value be somethin

<p>Sorry no current JS Fiddle as the production data is for a private firm.</p>

17691611

AmCharts Negative Base Line Trend

<p>Our software product line requires developing and maintaining multiple softwar

<p>Much searching has turned up little specific advice on how to adapt Git and Git I

<p>The key question is what have others found to be a good approach for implemei

<p>UPDATES:</p>

<p>Distilling the answers below (particularly @Rasmus') with more targeted searchi

<p>We won't continue to use Git Flow. Instead, we will apply Driessen's model to e

```
<pre><code>r1.5/develop
</code></pre>
```

<p>All versions of a project are contained in the Git repository. Starting a new proje

<p>We establish one central public repository per project on a server that will be th

<p>In some Git GUIs (such as SourceTree for example) this branch structure is recog

<p>Apologies for not up-voting any answers; my reputation on SO is not yet the mir

18220663

Advice on multiple release lines and git-flow,

<p>I am currently developing a report using DynamicJasper. This is the first time I'm

```
<pre><code>state1
branch  productline  columnItem  columnCode
branch  productline  columnItem  columnCode
branch  productline  columnItem  columnCode
branch  productline  columnItem  columnCode
branch  productline  columnItem  columnCode

state2
branch  productline  columnItem  columnCode
branch  productline  columnItem  columnCode
branch  productline  columnItem  columnCode
branch  productline  columnItem  columnCode
branch  productline  columnItem  columnCode
</code></pre>
```

<p>But currently, what I'm having is</p>

```
<pre><code>state1
branch  productline  columnItem  columnCode

state2
branch  productline  columnItem  columnCode

state1
branch  productline  columnItem  columnCode

state2
branch  productline  columnItem  columnCode

...
</code></pre>
```

<p>Its like they are never grouped at all.</p>

<p>Here is my runnable code : </p>

<p>GroupTest.java</p>

```
<pre><code>import net.sf.jasperreports.engine.JRDataSource;
import net.sf.jasperreports.engine.JasperPrint;
import net.sf.jasperreports.engine.data.JRBeanCollectionDataSource;
```

<p>I have a database of order line items. Two of the columns are for controlling bat

<p>The table (<code>ord_lin</code>) has 171,602 records that pertain to a particul

<p>I'm not well versed in Oracle, or even SQL, so I don't know if it's possible but wo

<p>If that's not an option, how would I go about creating the unique values for each

<p>Notes: The batch system was originally made for a whole new

<p>I'm also aware that I could do things like make another field to act as a "batched

18456036

Bypass or fulfill unique constraint for large u

<p>I have a dimension table called <code>Product_Dim</code></p>

```
<pre><code>Create Table Product_Dim
(
Product_ID INT primary key,
Product_Line CHAR(20),
Product_Category CHAR(25),
Product_Group CHAR(25),
Product_Name CHAR(45),
Supplier_Country CHAR(2),
Supplier_Name CHAR(30),
Supplier_ID INT
)
</code></pre>
```

<p>and two source tables <code>Supplier</code> and <code>Product_List</code></p>

<p>Product_list is as follow :</p>

```
<pre><code>Product_ID
Product_Name
Supplier_ID
Product_Level
Product_Ref_ID
</code></pre>
```

<p>where Product_Level has the values (1,2,3,4)</p>

<p>1 means it is a product
2 means it is a product group
3 means it is a product category
4 means it is a product line</p>

<p>so in order to fill my <code>Product_Dim</code> table
I did drag 4 times <code>Product_list</code> (Changing the query accordingly to <c
and one supplier</p>

<p>so for the join i do the following :</p>

```
<pre><code> product_list.Product_Name =&gt; PProduct_Name
product_group.Product_Name =&gt; PProduct_Group
product_line.Product_Name =&gt; PProduct_line
product_group.Product_category =&gt; PProduct_category
</code></pre>
```

<p>I'm using woocommerce product categories shortcode [prod

<p>because I'm displaying categories on product line page - and currently only 4 cat

<p>I have added this short code also <code>[product_categories per_page="4" colu

```
<pre><code>remove_action('woocommerce_pagination', 'woocommerce_paginatic
function woocommerce_pagination() {
    wp_pagenavi();
}
add_action( 'woocommerce_pagination', 'woocommerce_pagination', 10);
</code></pre>
```

<p>It is not worked.Is there a way to add pagination in woocommerce?</st

18585747

woocommerce product categories shortcode

<p>I've created a magento (1.7 CE) local module to add, in the Admin section, some Internally all seems to work good except that i'm not succeeding in replacing the ter

<p>In app/design/adminhtml/default/default/layout/sales.xml i have this code</p>

```
<pre><code>&lt;adminhtml_sales_order_view&gt;
    &lt;reference name="head"&gt;
        &lt;action method="addJs"&gt;&lt;file&gt;mage/adminhtml/giftmessage.js&lt;/file&gt;
        &lt;action method="addJs"&gt;&lt;file&gt;mage/adminhtml/giftoptions/tooltip.js&lt;/file&gt;
    &lt;/reference&gt;
    &lt;reference name="content"&gt;
        &lt;block type="adminhtml/sales_order_view" name="sales_order_edit"&gt;&lt;/block&gt;
    &lt;/reference&gt;
    &lt;reference name="left"&gt;
        &lt;block type="adminhtml/sales_order_view_tabs" name="sales_order_tabs"&gt;&lt;/block&gt;
        &lt;block type="adminhtml/sales_order_view_tab_info" name="order_tab_info"&gt;&lt;/block&gt;
        &lt;block type="adminhtml/sales_order_view_messages" name="order_messages"&gt;&lt;/block&gt;
        &lt;block type="adminhtml/sales_order_view_info" name="order_info"&gt;&lt;/block&gt;
        &lt;block type="adminhtml/sales_order_view_items" name="order_items"&gt;&lt;/block&gt;
        &lt;action method="addItemRender"&gt;&lt;type&gt;default&lt;/type&gt;&lt;/action&gt;
        &lt;...
    &lt;/reference&gt;
&lt;/adminhtml_sales_order_view&gt;
&lt;/code></pre>
```

<p>I would like to replace the template set by the LAST line you see (the addItemRender)

<p>In my module config.xml i have</p>

```
<pre><code>&lt;adminhtml&gt;
    &lt;layout&gt;
        &lt;updates&gt;
            &lt;my_ext&gt;
                &lt;file&gt;myext_update.xml&lt;/file&gt;
            &lt;/my_ext&gt;
        &lt;/updates&gt;
    &lt;/layout&gt;
&lt;/adminhtml&gt;
&lt;/code></pre>
```

<p>and in app/design/adminhtml/default/default/layout/myext_update.xml i have

```
<pre><code>&lt;?xml version="1.0"?&gt;
&lt;/code></pre>
```

<p>I am having a strange problem. I have an .htaccess file that will work only if I ma

```
<pre><code>Options +FollowSymLinks -MultiViews
# Turn mod_rewrite on
RewriteEngine On
RewriteBase /

#products.php pages
RewriteCond %{THE_REQUEST} html/products.php
RewriteCond %{QUERY_STRING} ^slug=(.*)$
RewriteRule ^html/products\.php$ http://www.example.com/products/%1? [R=301]
RewriteRule ^products/(.*)$ /html/products.php?slug=$1 [L]

#specs.php pages
#RewriteCond %{THE_REQUEST} html/specs.php
#RewriteCond %{QUERY_STRING} ^prodslug=(.*)$
#RewriteRule ^html/specspage\.php$ http://www.example.com/specs/%1? [R=301]
#RewriteRule ^specs/(.*)$ /html/specs.php?prodslug=$1 [L]
</code></pre>
```

18730460

Unable to rewrite two urls to same folder wii

<p>I wanna build a Shopping Cart to submit enquiry about the products and to buy
Each of the products will have varying levels of categories. </p>

<p>Examples
1. Brand > Product Line > Category 1 > Category 2 > Product
2. Brand > Product Line > Category 1 > Product
3. Brand > Product Line > Product</p>

<p>Now the user has to be able to add the products from various brands to a shopp

<p>Is there any Ready made CMS avaiable that i can use to get a shorter turn aroun

<p>I would love to use wordpress or cakephp to build the same.</p>

18757450

Shopping Cart with just Enquiry

<p>I have a web app that we're still stuck in asp.net 2.5 with. We've started using s

<p>In the future we're going to change our ASP.NET web form architecture into ah I

<p>The criteria object we pass in has 20 or so values and a couple of collections (prc

18860906

Accessing JSON on server side (asp.net)

<p>I am trying to make webpage with image that have products in the center. but tl

<p>How can you make it load so the image is center? </p>

<p>in the body</p>

```
<pre><code>&lt;img alt="The Argan Tree Product Line" src="images/products2.jpg"
</code></pre>
```

<p>css for element</p>

```
<pre><code>#bgimage{
  z-index: -999;
  width: auto;
  height: 100%;
  top: 0;
  left: 0;
  position: relative;
  min-width:960px;
  min-height:720px;
}
</code></pre>
```

<p>I am using this jquery to make the image change size when browser is different :

```
<pre><code>$(document).ready(function()
{
  if ($(document).height() &lt; (.75 * $(document).width())){
    var wide = $(document).width();
    if (wide>960){
      $("#bgimage").css("min-width", wide + "px");
      var high = .75 * $(document).width();
      $("#bgimage").css("min-height", high + "px");
      $("#content-wrapper").css("width", wide + "px");
      $("#content-wrapper").css("height", high + "px");
    }
  }
}
```

```

  if ($(document).height() &gt;= (.75 * $(document).width())){
    var high = $(document).height();
    if (high>720){
      var wide = 1.33 * high;
      $("#content-wrapper").css("width", wide + "px");
    }
  }
}
```

<p>We recently adopted the concept of feature branches in one of our bigger proje

<p>For each so-called feature, we are creating the following:</p>

a branch from 'main', aptly named after what the feature is supposed to be

a new team in the project portal, containing the people that will work on the fea

a build definition to validate check-ins against the source on the branch

<p>The main point I would like to see discussed here is about the build definition. C

<p>The question then, is: what is the best practice on associating work items to a bu

<p>In our case, these feature branches are supposed to be disposable: we would lik

<p>If I associate work items with these temporary builds, I'll lose tracking capability

<p>Would it be feasible to disable work item integration with the feature branches

<p>Update:</p>

<p>I just found something similar (but not exactly like what I wanted) in <a href="ht

<p>Would still like to hear what your thoughts are in regards to the builds in this sce

19252933

TFS Work Item<->Build association best prac

<p>I have been using Magmi to import products by adding items to the file " export

But when I have products that need to be remove,what I did was by removing the w

<p>Thanks so much</p>

19333400

Magmi import doesn't remove the products

<p>I'm evaluating tools that helps to manage branch for my team. We are working c

<p>Basically, what I want is to reach what <a href="http://nvie.com/posts/

<p>But because we are already using TFS (2012 today, but 2013 upgrade in the pipe

<p>Then I was looking for guidance, and I found this software. I've seen the short w

<p>Let's say I've finished working on a feature or a hotfix. How can I guide the devel

<p>The tools said "automate branching task in the ALM Rangers branching guidance

<p>Did I miss something? Is there any other resource that can help me?</p>

<p>I like GIT... I believe in its strong branching features. But I feel the git experience

<p>As my team (including me) is not mature in managing branching, I must keep thi

19445074

I don't understand the usage of the TFS bran

<p>Is there a more efficient query than the following </p>

```
<pre><code>DT[, list(length(unique(OrderNo)) ),customerID]
</code></pre>
```

<p>to refine a LONG format table with customer id's, order number and product lin

<p>Trying to work out unique purchases. <code>length()</code> gives a count of al

<h1>Edit from here:</h1>

<p>Here is some dummy code. Ideally what i am looking for is the output from the f

```
<pre><code>df &lt;- data.frame(
  customerID=as.factor(c(rep("A",3),rep("B",4))),
  product=as.factor(c(rep("widget",2),rep("otherstuff",5))),
  orderID=as.factor(c("xyz","xyz","abd","qwe","rty","yui","poi")),
  OrderDate=as.Date(c("2013-07-01","2013-07-01","2013-07-03","2013-06-01"
  )
  )
```

DT.eg <- as.data.table(df)

#Gives unique order counts

DT.eg[, list(orderlength = length(unique(orderID))),customerID]

#Gives counts of all orders by customer

DT.eg[,.SD, keyby=list(orderID, customerID)][, .N, by=customerID]

^

|

This should be .N, not .SD ~ R.S.

```
</code></pre>
```

19555310

efficient use of R data.table and unique()

<p>I'm attempting to make a script on my own that would be beneficial for technici

<p>I want my script to issue a prompt asking the user for how many of each type of

<p>Please review the code below and any help and/or suggestions is greatly apprec

```
<pre><code>function (t)
  local t = {}
  a,b = i,brackets
  io.write ("Enter Total Number of Small Products")
  answer = io.read()
  if answer then
    brackets = table.insert (t,#t+1,(answer * 1))
  end
  io.write ("Enter Total Number of Medium Products")
  answer = io.read()
  if answer then
    brackets = table.insert (t,#t+1,(answer * 2))
  end
  io.write ("Enter Total Number of Large Products")
  answer = io.read()
  if answer then
    brackets = table.insert (t,#t+1,(answer * 4))
  end
  local sum = 0
  for i,brackets in ipairs (t) do
    sum = sum + brackets
  end
  print (sum)
end
</code></pre>
```

19847184

Placing User Input into Table and Sum the To

<p>I am having a problem in passing entered data from the edit view to a createPDF
I have a Model Delivery that belongsTo Project. On the edit view of Delivery, I am pu
After a bit of looking, I found <a href="http://topdsoft.com/stories/view/186" rel="i

```
<pre><code>array(  
key_1 =&gt; array(  
qty =&gt; '1',  
description =&gt; 'Blah',  
assetNo =&gt; '11te';  
),  
key_2 =&gt; array(  
qty =&gt; '5',  
description =&gt; 'Blah',  
assetNo =&gt; 'sdvvs';  
)) etc...  
</code></pre>
```

<p>Anyone got a clue as to how I might go about this?</p>

20116417

Dynamic vitual fields? Or pass array from one

<p>Okay. So I have a list that goes like this (basically)

A) Mnfctr a

a) Product Line

B) Mnfctr b

b) Product line

I want the list to expand and collapse because the page is unnecessarily big to accor

```
<pre><code>  &lt;script type="text/javascript"&gt;
    function toggle(id) {
```

```
        ul = "ul_" + id;
        img = "img_" + id;
        ulElement = document.getElementById(ul);
        imgElement = document.getElementById(img);
        if (ulElement){
            if (ulElement.className == 'closed'){
                ulElement.className = "open";
                imgElement.src = "images/opened.gif";
            }
            else{
                ulElement.className = "closed";
                imgElement.src = "images/closed.gif";
            }
        }
    }
}
```

```
    &lt;/script&gt;
</code></pre>
```

<p>the css</p>

```
<pre><code> #portslist{
    color:black;
    border: 1px solid #babec9;

}
#portslist ul {
    color:black;
    font-size: 12px;
    padding-left:3px;
}
#portslist ul li {
```

<p>Hello i am currently using WordPress to build a brand site however i have run in

20608042

Make a Parent page not linked in breadcrum

<p>I'm getting now infrequently an error when creating a Google Chart within Goog

<p>The code bellow creates a blob, but, in 25% of the time, the image contains a ba

```
<pre><code>'undefined' is not a function (evaluating 'b.G()')
</code></pre>
```

<p>I'm familiar with this error in the JS/HTML world, and it usually indicates that the

<p>The App Script code is as follow and run correctly in roughly 75% of the time:</p>

```
<pre><code> // Get data for chart
var dataTable = SpreadsheetApp.getActiveSpreadsheet()
    .getSheetByName("Chart_Data")
    .getRange("A1:F91")
    .getDataTable(true);

// Wait 3 seconds and flush any activity
Utilities.sleep(3000);
SpreadsheetApp.flush();

// Test if data object is empty
if (dataTable==null) {
    Logger.log("Error, dataTable is null");
}

// Create Line Chart Builder
var lineChart = Charts.newLineChart()
    .setTitle('Weekly Activations by product line (7 days rolling)')
    .setLegendPosition(Charts.Position.RIGHT)
    .setDimensions(600, 400)
    .setDataTable(dataTable)
    .setColors(["blue", "DarkGreen", "DarkRed", "#eec", "#cee"]);

// Wait 3 seconds and flush any activity
Utilities.sleep(3000);
SpreadsheetApp.flush();

// Test if chart builder object is empty
if (lineChart==null) {
    Logger.log("Error, lineChart is null");
}
```

<p>I am building a web app using shiny, and I'm unsure how to best structure the app

<p>I tried to come up with a simple application to reproduce the problem. My setup

<p>I will list some code for such an example below, where some sample data is also

<p>My questions are:</p>

<p>1) I am wondering in which order things are executed, in particular when the app

<p>2) What is the current best practice when the inputs depend on data/server.R? I

<p>Here is the code for the two files:</p>

```
<pre><code># ui.R
#####
```

```
library(shiny)

shinyUI(pageWithSidebar(

  headerPanel("New Application"),

  sidebarPanel(
    htmlOutput("dateInput"),
    htmlOutput("prodInput")
  ),

  mainPanel(
    plotOutput("salesplot")
  )

))
```

```
</code></pre>
```

<p>And:</p>

```
<pre><code>#server.R
#####
```

```
library(shiny)
library(filehash)
```

<p>I am currently trying to apply some conditional formatting to a report that will a

<p>The problem I have is that several charts are built off a single data set and filters

<p>I have tried the method I mentioned above, however I think that because my da

<p>Any assistance would be greatly appreciated.</p>

<p>Dan</p>

20963840

SSRS Chart visibility based on data

<p>I have the following javascript code I use with casperjs to iterate some links and

<p>Here is my snippet</p>

```
<pre><code>casper.each(links, function (self, link) {

this.thenOpen(link, function () {
    //get work order info
    var town_selector = 'div tr';
    var town_names_info = this.getElementsInfo(town_selector);
    var town_names = [];
    for (var i = 0; i < town_names_info.length; i++) {
        town_names.push(town_names_info[i].text.trim().replace(/\n\s+\n/, ''));
    }
    var jsonTest = arrayToObject(town_names);
    json.push(JSON.stringify(jsonTest));
    casper.capture('./images/workOrder' + workOrder + '.png');
    workOrder++
    utils.dump(jsonTest);
    array.push(jsonTest);
    casper.thenClick(x('/html/body/table[2]/tbody/tr/td[2]/a[2]'), function () {
        //more some stuff here
        someLinks = this.evaluate(getLinks);

        for (var i = 0; i < someLinks.length; i++) {
            someLinks[i] = "https://somelink" + someLinks[i];
        }
        casper.each(someLinks, function (self, link) {
            self.thenOpen(link, function () {
                var selector = 'div tr';
                var names_info = this.getElementsInfo(town_selector);
                var names = [];
                for (var i = 0; i < names_info.length; i++) {
                    names.push(names_info[i].text.trim().replace(/\n\s+\n/, ''));
                }
                var jsonTest = arrayToObject(names);
                json.push(JSON.stringify(jsonTest));
                utils.dump(jsonTest);
                array.push(jsonTest);
                fs.write('results.json', JSON.stringify(array), 'w');
                casper.capture('./images/lineltem' + lineltem + '.png');
                lineltem++
            });
        });
    });
});
</code></pre>
```

<p>In my View I have to put several render partial pages to dynamically add rows in

<p>To add the first table I have followed:

<a href="http://blog.stevensanderson.com/2010/01/28/editing-a-variable-length-li:

<p>I have followed the instructions in the link but my main view looks like this: </p>

```
<pre><code>&lt;table id="editorRows" style="width: 100%;"&gt;
&lt;tr&gt;
  &lt;th&gt;Column1&lt;/th&gt;
  &lt;th&gt;Column2&lt;/th&gt;
  &lt;th&gt;Column3&lt;/th&gt;
&lt;/tr&gt;

@foreach (var item in Model.Entity.ListPlans)
{
  Html.RenderPartial("PlanEditorRow", item);
}

&lt;/table&gt;
&lt;b&gt;&lt;i&gt;@Html.ActionLink("Add another plan...", "BlankPlanEditorRow", n
</code></pre>
```

<p>The partial view (PlanEditorRow) is:</p>

```
<pre><code>@model Project.Models.Plan
@using Project.Helpers

&lt;tr class="editorRow"&gt;
@using (Html.BeginCollectionItem("assignedPlans"))
{

  &lt;td&gt;
    @Html.EditorFor(x =&gt; x.Data1)
  &lt;/td&gt;
  &lt;td&gt;
    @Html.EditorFor(x =&gt; x.Data2)
  &lt;/td&gt;

  &lt;td&gt;
    @Html.EditorFor(x =&gt; x.Data3)
  &lt;/td&gt;
  &lt;td&gt;
```

<p>I want to share the JRE of my main application with add-ons which will be install

<p>Is it possible to define the path of the shared JRE instead of using "...\\common fi

<p>I'd like to use something like </p>

<p>"...\\common files\\my company\\product line1\\jre"

and

"...\\common files\\my company\\product line2\\jre"</p>

21752456

How to change the location of a shared JRE in

<p>I'm trying to setup a delete link for a join table entry.</p>

<p>I have a <code>@miniatures</code> model which has_many <code>@lines</code>

<p>On my <code>@miniatures</code> show page I call the associated <code>@lines</code>

```
<pre><code>&lt;% @miniature.lines.each do |line| %&gt;
  &lt;%= link_to line.name, line %&gt;
&lt;% end %&gt;
</code></pre>
```

<p>That all works fine. All associations correct etc. What I'm trying to do is add a litt

```
<pre><code>&lt;% @miniature.lines.each do |line| %&gt;
  &lt;%= link_to line.name, line %&gt;
  &lt;%= link_to '&lt;i class="fa fa-times"&gt;&lt;/i&gt;'.html_safe, miniline_path(:miniature_id => @miniature.id, :line_id => line.id), :confirm => 'Are you sure?', :method => :delete %&gt;&lt;br /&gt;
&lt;% end %&gt;
</code></pre>
```

<p>In my mini lines_controller I have the following destroy action</p>

```
<pre><code>def destroy
  Miniline.find_by_miniature_id_and_line_id(params[:miniature_id, :line_id]).destroy
  flash[:success] = "Miniature removed from product line."
  redirect_to :back
end
</code></pre>
```

<p>It's currently returning <code>wrong number of arguments (2 for 1)</code>.</p>

21861814

Delete a join table entry from associated model

<p>We have a custom content slider, made up of an unordered list. There is a functi

<p>I'm trying to randomize the order of the content slides, so that the same combin

<p>The functions are here: </p>

```
<pre><code>/**
 * Prepare a rotator
 * @return null
 */
(function($)
{
    $.fn.prepRotator = function()
    {
        return this.each(function()
        {
            // Set the navigation
            var count = $(this).children().length;
            for (i = 1; i &lt;= count; i++)
            {
                $(this).siblings('#rotatorNavigation').append("&lt;a href='#'    name='' + i .
                $(this).children(':eq(' + (i-1) + ')').attr('name', i);
            }
            $(this).children().preload();
            $(this).siblings('#rotatorNavigation').find('a:first').addClass('active');

            // Set the rotation
            function rotate()
            {
                if ($('.rotator li.active').next('li').length &gt; 0)
                    $('.rotator li.active').next('li').showRotatorItem();
                else
                    $('.rotator li:first').showRotatorItem();
                globals.RotatorTimeout = setTimeout(function(){ rotate(); }, 5000);
            }
            globals.RotatorTimeout = setTimeout(function(){ rotate(); }, 5000);

            // Set the buttons
            $('#rotatorNavigation a').unbind('click').click(function()
            {
```


<p>Considering the following two arrays. How can I append array "lines" to array "a

```
<pre><code>array1 = [
{
  "Activity #": "1111111",
  "Customer": "Last, First",
  "Tenure": "0 Year 2 Months",
  "Account #": "0000000"
}];
```

```
lines = [
{
  "Line #": "1",
  "Action Required": "New",
  "Status": "Closed",
  "Product Line": "test line1",
  "Product": "product1"
},
{
  "Line #": "2",
  "Action Required": "New",
  "Status": "Closed",
  "Product Line": "test line2",
  "Product": "product2"
}];
</code></pre>
```

<p>I would like something like this.</p>

```
<pre><code>my_array = [
{
  "Activity #": "1111111",
  "Customer": "Last, First",
  "Tenure": "0 Year 2 Months",
  "Account #": "0000000",
  "lines": [{
    "Line #": "1",
    "fields": "keys"
  },
  {
    "Line #": "2",
    "fields": "keys"
  }
]
}
```

<p>I've been research the relative performance of ARM parts, and have found it diff

<p>What I've come up with so far, based on Linpack scores of different phone/table

A9 = 32 MFLOPS/Core/GHz

A15 = 100 MFLOPS/Core/GHz

Apple A7 = 350 MFLOPS /Core/GHz (!)

<p>So a couple questions arise:</p>

Where does the A12, A17, A53, A57 fit into this spectrum

Why is Apple's A7 floating point so good? It is purely due to the 64bit internals, c

22217790

What ARM Floating Point Performance Compar

<p>How can I create a underline that fills up the white space between the end of a t

<p>I'm trying the following:</p>

<p>I want the product line to break when the screen gets smaller. I want the price t

<p>Big screen:

Old Cheese – Salad, Avocado, Egg, Herbal Mayo.....500</p>

<p>Smaller screen:

Old Cheese – Salad, Avocado, Egg,

Herbal Mayo.....500</p>

<p>Extra small screen:

Old Cheese – Salad,
Avocado,

Egg, Herbal
Mayo.....500</p>

<p>I have the following markup:</p>

<h2>HTML</h2>

```
<pre><code>&lt;div class="productline"&gt;
    &lt;div class="product"&gt;
        Old Cheese – Salad, Avocado, Egg, Herbal Mayo
    &lt;/div&gt;
    &lt;div class="line"&gt;&amp;nbsp&lt;/div&gt;
    &lt;div class="price"&gt;500&lt;/div&gt;
&lt;/div&gt;
</code></pre>
```

<h2>CSS</h2>

```
<pre><code>.productline {
    width:300px;
}
.product {
    display:table-cell;
    white-space: nowrap;
}
.line {
    border-bottom: 1px solid black;
    display: table-cell;
    width:100%;
```

<p>first,thanks for everyone taking time reading this...
for example,like a product line,each page will create some params,
and the current page may need to user the params created in the previous page..
I am not sure how to pass params through these pages,
maybe i need to say ,don't know choose which way.
we can use cookie、 session、 javabean and maybe others
using the cookie may results in some mistakes because of it's expires,
and using the session,i dont't know whether it would bring pressure to the server..
anyone can give me some suggestions?</p>

<hr>

<p>in the end,sorry for my english...</p>

22658918

pass parameters through serials pages

<p>What would you like to be able to do for example is:</p>

<p>I have an active state 'order.detail' in shell, in these details would provide a link

<p>But this link should display the state ' product.detail' as a frame in a dialog withc

<p>Also the 'product.detail' state, to be used as a main view of the shell, and to allo

<p>What I mean is, allow consult the details of something without leaving the curre

22800129

Many active states simultaneously with ui-ro

<p>I am trying to integrate DynamicJasper report with Struts2 in my project. Strut2

<p>I have the following error thrown during execution </p>

```
<pre><code>org.apache.catalina.core.StandardWrapperValve invoke
SEVERE: Servlet.service() for servlet [default] in context with path [/proj] threw exce
java.lang.NoSuchMethodError: com.opensymphony.xwork2.ActionContext.get(Ljav:
  at ar.com.fdvs.dj.struts2.DJStruts2Result.doExecute(DJStruts2Result.java:138)
  at org.apache.struts2.dispatcher.StrutsResultSupport.execute(StrutsResultSupport
  at com.opensymphony.xwork2.DefaultActionInvocation.executeResult(DefaultActi
  at com.opensymphony.xwork2.DefaultActionInvocation.invoke(DefaultActionInvc
  at com.opensymphony.xwork2.interceptor.DefaultWorkflowInterceptor.doIntercept
  at com.opensymphony.xwork2.interceptor.MethodFilterInterceptor.intercept(Me
  at com.opensymphony.xwork2.DefaultActionInvocation.invoke(DefaultActionInvc
  at com.opensymphony.xwork2.validator.ValidationInterceptor.doIntercept(Validat
  at org.apache.struts2.interceptor.validation.AnnotationValidationInterceptor.doli
  at com.opensymphony.xwork2.interceptor.MethodFilterInterceptor.intercept(Me
  at com.opensymphony.xwork2.DefaultActionInvocation.invoke(DefaultActionInvc
  at com.opensymphony.xwork2.interceptor.ConversionErrorInterceptor.intercept(
  at com.opensymphony.xwork2.DefaultActionInvocation.invoke(DefaultActionInvc
  at com.opensymphony.xwork2.interceptor.ParametersInterceptor.doIntercept(Pa
  at com.opensymphony.xwork2.interceptor.MethodFilterInterceptor.intercept(Me
  at com.opensymphony.xwork2.DefaultActionInvocation.invoke(DefaultActionInvc
  at com.opensymphony.xwork2.interceptor.ParametersInterceptor.doIntercept(Pa
  at com.opensymphony.xwork2.interceptor.MethodFilterInterceptor.intercept(Me
  at com.opensymphony.xwork2.DefaultActionInvocation.invoke(DefaultActionInvc
  at com.opensymphony.xwork2.interceptor.StaticParametersInterceptor.intercept
  at com.opensymphony.xwork2.DefaultActionInvocation.invoke(DefaultActionInvc
  at org.apache.struts2.interceptor.MultiselectInterceptor.intercept(MultiselectInte
  at com.opensymphony.xwork2.DefaultActionInvocation.invoke(DefaultActionInvc
  at org.apache.struts2.interceptor.CheckboxInterceptor.intercept(CheckboxInterce
  at com.opensymphony.xwork2.DefaultActionInvocation.invoke(DefaultActionInvc
  at org.apache.struts2.interceptor.FileUploadInterceptor.intercept(FileUploadInte
  at com.opensymphony.xwork2.DefaultActionInvocation.invoke(DefaultActionInvc
  at com.opensymphony.xwork2.interceptor.ModelDrivenInterceptor.intercept(Mc
  at com.opensymphony.xwork2.DefaultActionInvocation.invoke(DefaultActionInvc
  at com.opensymphony.xwork2.interceptor.ScopedModelDrivenInterceptor.interc
  at com.opensymphony.xwork2.DefaultActionInvocation.invoke(DefaultActionInvc
  at org.apache.struts2.interceptor.debugging.DebuggingInterceptor.intercept(Deb
  at com.opensymphony.xwork2.DefaultActionInvocation.invoke(DefaultActionInvc
  at com.opensymphony.xwork2.interceptor.ChainingInterceptor.intercept(Chainin
  at com.opensymphony.xwork2.DefaultActionInvocation.invoke(DefaultActionInvc
  at com.opensymphony.xwork2.interceptor.PrepareInterceptor.doIntercept(Prena
```

<p>I have a form and I can dynamically add more lines but if I try to remove a specif

<p>Here is the html:</p>

```
<pre><code>&lt;form class="order-form"&gt;
  &lt;div class="product-lines"&gt;
&lt;!-- Product Line Section --&gt;
  &lt;div class="product-line"&gt;
&lt;a href="#" alt="close" class="btn-close" title="Remove"&gt;&lt;img alt="remove
&lt;input class="input-text" name="product-code" type="text" placeholder="Produc
&lt;input class="input-text" name="product-quantity" type="text" placeholder="Qu
&lt;input class="input-text" name="product-discript" type="text" placeholder="Disc
&lt;label class="label-sign"&gt;&amp;pound;&lt;/label&gt;
&lt;input class="input-text" name="product-price" type="text" placeholder="RRP Pr
&lt;br&gt;
  &lt;/div&gt;
&lt;/div&gt;

&lt;div id="product-btn"&gt;
&lt;input name="btn-add-line" type="button" value="Add new line"&gt;&lt;/input&
&lt;input name="btn-update" type="button" value="Update"&gt;&lt;/input&gt;
&lt;input name="btn-submit" type="submit" value="Submit Order"&gt;&lt;/input&
&lt;label class="label-sign"&gt;&amp;pound;&lt;/label&gt;
&lt;input class="input-text" name="order-info" type="text" placeholder="Order tot
&lt;/div&gt;
&lt;/form&gt;
</code></pre>
```

<p>The jQuery code I have tried:</p>

```
<pre><code>$(".btn-close").on("click", function(e){
  $(e.currentTarget).parent().remove();
});
</code></pre>
```

<p>I've also Tried </p>

```
<pre><code>$(e.currentTarget).parents("div.product-lines").next("div.product-line").r
</code></pre>
```

<p>Any help would be most appreciated, also a explanation would be very helpful fi

<p>I have a form and when I enter a number and "keyup" it should display the total

<p>I've added a js fiddle link, Any help mu appreciated</p>

<p>JSFiddle<

```
<pre><code>&lt;form class="order-form"&gt;
&lt;div class="product-lines"&gt;
  &lt;!-- Product Line Section --&gt;
  &lt;div class="product-line"&gt; &lt;a href="#" alt="close" class="btn-close" title=

    &lt;input class="input-text" name="product-code" type="text" placeholder="Pr
    &lt;input class="input-text" name="product-quantity" type="text" placeholder=
    &lt;input class="input-text" name="product-discript" type="text" placeholder='
    &lt;label class="label-sign"&gt;&amp;pound;&lt;/label&gt;
    &lt;input class="input-text" name="product-price" type="text" placeholder="Rf
    &lt;br&gt;
  &lt;/div&gt;
&lt;/div&gt;
&lt;p&gt;Line below dynamically generated&lt;/p&gt;
&lt;div class="product-lines"&gt;
  &lt;!-- Product Line Section --&gt;
  &lt;div class="product-line"&gt; &lt;a href="#" alt="close" class="btn-close" title=

    &lt;input class="input-text" name="product-code" type="text" placeholder="Pr
    &lt;input class="input-text" name="product-quantity" type="text" placeholder=
    &lt;input class="input-text" name="product-discript" type="text" placeholder='
    &lt;label class="label-sign"&gt;&amp;pound;&lt;/label&gt;
    &lt;input class="input-text" name="product-price" type="text" placeholder="Rf
    &lt;br&gt;
  &lt;/div&gt;
&lt;/div&gt;
&lt;br&gt;
&lt;div id="product-btn"&gt;
  &lt;input name="btn-add-line" type="button" value="Add new line"&gt;&lt;/input&gt;
  &lt;input id="btn-update" name="btn-update" type="button" value="Update"&gt;
  &lt;!-- Clear All Button --&gt;
  &lt;input id="btn-removeAll" name="btn-removeAll" type="reset" value="Remov
  &lt;input name="btn-submit" type="submit" value="Submit Order"&gt;&lt;/input&gt;
  &lt;label class="label-sign"&gt;&amp;pound;&lt;/label&gt;
  &lt;input class="input-text" name="order-total" type="text" placeholder="Order t
&lt;/div&gt;
</code></pre>
```

<p>I am aware that nesting is a problem with form tags. However, my page does no

<p>I have one p:commandButton that I want to use to submit the form. It works ocl

<p>Also--If I comment out the menu form completely it works as intended.</e

<p>Thanks.</p>

<p>Action Method:</p>

```
<pre><code> public String insertLocationAction(){
    System.out.println("***** Method Fired.");
    DatabaseManager.insertLocation(newLocation);
    return "locations";
}
</code></pre>
```

<p>XHTML Page:</p>

```
<pre><code>&lt;?xml version="1.0" encoding="UTF-8"?&gt;
&lt;!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
    "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd"&gt;
&lt;html xmlns="http://www.w3.org/1999/xhtml"
    xmlns:h="http://xmlns.jcp.org/jsf/html"
    xmlns:p="http://primefaces.org/ui"
    xmlns:f="http://xmlns.jcp.org/jsf/core"
    xmlns:ui="http://xmlns.jcp.org/jsf/facelets"&gt;
&lt;f:view&gt;
    &lt;ui:debug rendered="#{facesContext.application.projectStage eq 'Developmen
    &lt;h:head /&gt;
    &lt;p:messages /&gt;
    &lt;p:layout fullPage="true"&gt;
        &lt;p:layoutUnit position="west" size="260" header="Menu" resizable="false" c
        &lt;h:form id="menuForm"&gt;
            &lt;p:menu style="width: 240px;" &gt;
                &lt;p:submenu label="Locations" style="width: 240px;"&gt;
                    &lt;p:menuItem value="All Locations" outcome="/pages/locations.xhtml
                    &lt;p:menuItem value="Create New" action="#{locationBackingBean.adc
                &lt;/p:submenu&gt;
                &lt;p:submenu label="Queries" style="width: 240px;"&gt;
                    &lt;p:menuItem value="Product Group Sales" outcome="/pages/product
                    &lt;p:menuItem value="Product Line Sales" outcome="/pages/productLi
                &lt;/p:submenu&gt;
            &lt;/h:form&gt;
        &lt;/p:layoutUnit&gt;
    &lt;/p:layout&gt;
&lt;/f:view&gt;
```


<p>I am looking at options to create dynamic web forms within my asp.net applicati

<p>However the forms I need to create are more of structured documents to captu

<p>Though infopath appears to fit in to creation of structured documents, i am not

<p>The different options I am exploring are :</p>

Combine dynamic web form creation using jquery/knockout with a fluid grid libr

Gridster

Check if i can publish word forms and capture the user entered data on submit a

Use Nintex or similar paid product

<p>Any suggestions or directions will be helpful.</p>

23754991

How to create dynamic structured document

<p>To give some background on this, I've got a handful of 2000, 2005, 2008, 2008R2

<p>Just to warn you, this isn't as simple as looking at the major product version. Fo

<p>I tried sidestepping this and querying the sys.all_views view, but ironically the sy

<p>I could use a "poor practice" workaround in place that runs some DSQL within a

<p>So, to my question: Does anyone have a procedure that they can share that will

<p>I've got no problems coming up with said routine myself, but was hoping someo

<p>Thanks,</p>

<p>John</p>

23809712

Programmatic Comparison of SQL Server Ver

<p>I have started using magmi to import products, using the option <code>create n
I have defined an attribute set in Magento called <code>Books</code>, which inclu

<p>Here is a sample from the CSV file (only the first few columns):</p>

<p>Header:</p>

<blockquote>
<p>sku,_store,_attribute_set,_type,categories,_product_websites,name</p>
</blockquote>

<p>Product Line:</p>

<blockquote>
<p>ZZ001,,Books,simple,MyCategory/MySubCategory,base,Book Title</p>
</blockquote>

<p>On the above example, ZZ001 is created, but with an attribute set of <code>Def:

<p>Store is blank - is this a problem?</p>

<p>Someone else asked a question about this - but I didn't see a satisfactory answer

23846337

magmi attribute_set ignored - always set to (

<p>We have a client with following existing product line</p>

Website1 (Uses form authentication using user information stored in SqlDB for v

WebSite2 (Uses form authentication using user information stored in SqlDB for v

WinApplication1 (uses Active Directory to authenticate user)

<p>More products in line for future release.</p>

<p>They want to implement Single Sign on (SSO) for all their products with followin

Product list that will be accessing by a user will be depended on his/her role.

It should be configurable. Roles are being defined in DB having Fk relation
with user table.

SSO service should be flexible to accommodate new product.

should use SAML to sucure token.

WinApplication1 has link for website1 and website2. If an user is login in WinApp
and click on any links of website1/website2, user should able to access the sites
entering his credential.

If user is logged in in any product that user should be all to access any other pro
he has access right without enternting userid/password.

<p>We have following query</p>

We are planning to implement SSO using WCF and WIF. Can all above requireme
by using WIF.

We want to keep user authentication part in respective product as each product
own user store. OR WE SHOULD HAVE CENTRALIZED USER STORE?

What shouldl be the responsibility of STS (implemented in WCF) in respect to SS
security?

<p>We have read lot about WIF from MSDN(<a href="http://msdn.microsoft.com/e

<p>I'm getting this error whenever I run this code - I've been staring at it for hours t

```
<pre><code> public void GeneratePDF(Guid id)
{
    ceTe.DynamicPDF.Document doc = new ceTe.DynamicPDF.Document();
    doc.Author = new IssueTracker.ActiveDirectory.Searcher().FindBySAMAccountN
    doc.Creator = "GPO Pricing Application";
    doc.Title = "GPO Pricing Recommendation";

    Page page = new Page(ceTe.DynamicPDF.PageSize.Letter, ceTe.DynamicPDF.Pa

    doc.Pages.Add(page);

    Worksheet worksheet = repo.GetByID(id);

    AddElement(page, "Report Name: ", worksheet.Name, 0, 0 );
    AddElement(page, "Customer Name: ", worksheet.CustomerName, 0, 20);
    AddElement(page, "Allied Group: ", worksheet.AlliedGroup, 0, 40);
    AddElement(page, "City, State: ", worksheet.City + ", " + worksheet.State, 0, 60);
    AddElement(page, "Gross Annual Sales: ", string.Format("{0:C}", worksheet.Anr

    var Y = 100;
    Table2 table = new Table2(0, Y, 850, 600);
    table.Border.Width = 0.5f;
    table.CellDefault.Border.Width = 0.5f;
    table.Columns.Add(45); // Contract Id
    table.Columns.Add(125); // Product Line
    table.Columns.Add(75); // SKU
    table.Columns.Add(150); // Description
    table.Columns.Add(30); // Qty
    table.Columns.Add(50); // Current Price (ea)
    table.Columns.Add(50); // Current Spend
    table.Columns.Add(50); // New Price (ea)
    table.Columns.Add(50); // New Spend
    table.Columns.Add(50); // Variance

    Row2 row = table.Rows.Add(10, Font.TimesBold, 8);
    row.CellDefault.VAlign = VAlign.Top;
    row.CellDefault.Align = TextAlign.Center;
    row.Cells.Add("Contract Id");
    row.Cells.Add("Product Line");
    row.Cells.Add("SKU");
    row.Cells.Add("Description");
```

<p>Alright, howdy

I have a client who I built a site for, call it www.site1.com</p>

<p>That client is now expanding and creating a new product line so they bought an

24661408

WP 2 Domains One Hosting Account

<p>I have got the following array:</p>

```
<pre><code>Array
```

```
(
```

```
[Exo Wetline FOR April:2014] =&gt; Array
```

```
(
```

```
[0] =&gt; Array
```

```
(
```

```
[ProductRowId] =&gt; 2000453
```

```
[SKU] =&gt; P2000453
```

```
[ProductLineName] =&gt; Exo Wetline
```

```
[ProductName] =&gt; High Degree 16 oz.
```

```
[ProductSize] =&gt; 16
```

```
[LastSoldDate] =&gt; 04/16/14
```

```
[AvgUnitPrice] =&gt; 17.99
```

```
[AvgSellingPrice] =&gt; 17.99
```

```
[AvgUnitCost] =&gt; 17.99
```

```
[ExpectedMargin] =&gt; 0
```

```
[ActualMargin] =&gt; 0
```

```
[QuantitySold] =&gt; 2
```

```
[PreDiscountTotal] =&gt; 35.98
```

```
[TotalDiscount] =&gt; 6.31
```

```
[TotalSales] =&gt; 29.67
```

```
[SoldDate] =&gt; 04/01/14
```

```
)
```

```
[1] =&gt; Array
```

```
(
```

```
[ProductRowId] =&gt; 2000451
```

```
[SKU] =&gt; P2000451
```

```
[ProductLineName] =&gt; Exo Wetline
```

```
[ProductName] =&gt; Top Notch 32 oz.
```

```
[ProductSize] =&gt; 32
```

```
[LastSoldDate] =&gt; 04/30/14
```

```
[AvgUnitPrice] =&gt; 28.99
```

```
[AvgSellingPrice] =&gt; 28.99
```

```
[AvgUnitCost] =&gt; 28.99
```

```
[ExpectedMargin] =&gt; 0
```

```
[ActualMargin] =&gt; 0
```

```
[QuantitySold] =&gt; 1
```

```
[PreDiscountTotal] =&gt; 28.99
```

```
[TotalDiscount] =&gt; 8.8
```

<p>I have a general question about the structure of my object model. Perhaps I am

```
<pre><code>public class Item
{
    public string ItemNumber { get; set; }
    public string Description { get; set; }
    public double Cost { get; set; }
}
```

```
public class SerializedItem : Item
{
    public string SerialNumber { get; set; }
    public MyObject Location { get; set; }
}
```

```
</code></pre>
```

<p>An Item is a generic definition of an item, and contains information common to

<p>Maybe this is a more appropriate approach? I don't have a lot of experience usir

```
<pre><code>public class Item
{
    public string ItemNumber { get; set; }
    public string Description { get; set; }
    public double Cost { get; set; }
}
```

```
public class SerializedItem : Item
{
    private Items _item;
    public SerializedItemz(Item item)
    {
        _item = item;
    }
}
```

```
public new string ItemNumber
{
    get { return _item.ItemNumber; }
    set { _item.ItemNumber = value; }
}
```

```
public new string Description
{
```

<p>I read some example code to extract the data from Website using VBA in Excel, I

<p>Problem:

I need to extract the information from TE website , in this case, its link is <code>http

<p>There are some comments I found that I will need to know some HTLM in order

<p>I tried to look into the code of the page then I found the information hidden but

```
<pre><code>`&lt;span class="te-search-gallery-family"&gt;2.5mm Signal Double Loc
`&lt;span class="te-search-gallery-desc"&gt;2.5 SIGNAL D/LOCK PLUG HSG 11P&lt;/s
</code></pre>
```

<p>and</p>

```
<pre><code>&lt;th class="first-cell"&gt; Product Type&lt;/th&gt;
      &lt;th&gt; Connector Type&lt;/th&gt;
      &lt;th&gt; Connector Style&lt;/th&gt;
      &lt;th&gt; Product Line&lt;/th&gt;
      &lt;th&gt; Centerline&lt;/th&gt;
      &lt;th&gt; Application Use&lt;/th&gt;
      &lt;th&gt; Applies To&lt;/th&gt;
      &lt;th&gt; Wire/Cable Type&lt;/th&gt;
      &lt;th&gt; Contact Type&lt;/th&gt;
      &lt;th class="last-cell"&gt; Number of Positions&lt;/th&
      &lt;/tr&gt;
&lt;/thead&gt;
&lt;tbody&gt;
  &lt;tr&gt;
    &lt;td class="first-cell"&gt; Connector&lt;/td&gt;
    &lt;td&gt; Housing&lt;/td&gt;
    &lt;td&gt; Plug&lt;/td&gt;
    &lt;td&gt; 2.5mm Signal Double Lock&lt;/td&gt;
    &lt;td&gt; 2.50 mm [0.098 in]&lt;/td&gt;
    &lt;td&gt; Wire-to-Wire&lt;/td&gt;
    &lt;td&gt; Wire/Cable&lt;/td&gt;
    &lt;td&gt; Discrete Wire&lt;/td&gt;
    &lt;td&gt; Socket&lt;/td&gt;
    &lt;td class="last-cell"&gt; 11&lt;/td&gt;
  &lt;/tr&gt;
</code></pre>
```

<p><a href="http://www.te.com/catalog/products/en?q=917695-1" rel="nofollow t

<p>I have two DataGridComboBoxColumns (technically DataGridTemplateColumns)

<p>The first column's ItemsSource is bound to a static resource -- no problem there

<p>The second column's ItemsSource is dependent on the value chosen by the first

<p>The problem with using the first column's SelectedValue as ObjectDataProvider'

<p>I'd really like to pass in the first column's Text value to the ObjectDataProvider a

<p>Here's excerpts of my problem XAML:</p>

```
<pre><code>&lt;!--
```

My ObjectDataProvider. It returns a collection of strings for the user to choose from
The first DataGridTemplateColumn feeds ObjectDataProvider a MethodParameter.

The method is simple. It looks like:

```
public List<String> ProductLineCategoryList_CategoryCodes(string productLi
{
    // return a list of strings based from an object collection, filtered by the passed
}
--&gt;
```

```
&lt;ObjectDataProvider x:Key="categoryCodes" ObjectType="{x:Type e:ItemsProvidi
&lt;ObjectDataProvider.MethodParameters&gt;
    &lt;x:StaticExtension Member="sys:String.Empty"/&gt;
    &lt;/ObjectDataProvider.MethodParameters&gt;
&lt;/ObjectDataProvider&gt;
```

```
&lt;!--
```

This DataGridComboBoxColumn lets the user choose a ProductLineCode.

Its SelectedValue provides a string value for the ObjectDataProvider's MethodParam
The ObjectDataProvider is used as the ItemsSource for the DataGridComboBoxColui
below this one.

The problem with using SelectedValue to feed ObjectDataProvider a MethodParam
a second row is added to my DataGrid and the second row uses a different ProductL
the first row, it clears the first row's ProductLineCategoryCode value.

```
--&gt;
```

```
&lt;DataGridTemplateColumn
```

```
    Header="Product Line"
```

```
    ClipboardContentBinding="{Binding ProductLineCode}"&gt;
```

```
&lt;DataGridTemplateColumn.CellEditingTemplate&gt;
```

```
&lt;DataTemplate&gt;
```

<p>The purpose is to color a single field and not the entire fields in the tree. For eg:

25801674

How to color a single field in tree view in ope

<p>I'm trying to simplify my stylesheet so if I want to change the color of my default

```
<pre><code>.dark-grey { color: #232323; }
.med-grey { color: #616161; }
.light-grey { color: #e2e3e4; }
.orange { color: #f66511; }
.light-orange { color: #f66511; }
.blue { color: #2251a4; }
.white { color: #ffffff; }
</code></pre>
```

<p>In my example, why is my Subaru Forester</p> not turning bl

<p>Do I have to put all those colors under my div for the colors to work?</p>

<p>Here's my jsfiddle: <a href="http://jsfiddle.net/huskydawgs/1ysq0c3y/7/" rel="r

<p>Here's my code:</p>

```
<pre><code>&lt;p class="orange"&gt;&lt;strong&gt;Honda CRV&lt;/p&gt;
&lt;p&gt;See full features and specs of the 2014 Honda CR-V SUV at the Official Hon
```

```
&lt;div id="wrapper-landing"&gt;
&lt;p class="blue"&gt;&lt;strong&gt;Subaru Forester&lt;/strong&gt;&lt;/p&gt;
&lt;p&gt;Fuji Heavy Industries, the company that builds Subaru vehicles, is a master
```

```
&lt;/div&gt;
</code></pre>
```

<p>Here's my CSS:</p>

```
<pre><code>body {
  color: #666666;
  font-family: 'SegoeRegular', Helvetica, Arial, sans-serif;
  font-size: .8em;
  text-align: left;
  line-height: 1.6em;
  margin: 0;
  padding: 0 0 0 0;
}
```

```
blue { color: #2251a4; }
```

<p>I need to exclude VAT from details product line, my customers demands me this

<p>I have been researching and I found <code>order_conf.html</code> file and it c
Is there any value to show item price without VAT in product description ?</p>

26177143

How to exclude VAT from order.conf in Prest

<p>I have an html table within a list view, and have a hidden label in it called "vehicle_

```
<pre><code>var vehicle_number = $(this).closest('tr').children('#vehicle_num').text</code></pre>
```

<p>Below is the code for the listview. How can I get the value of the label?</p>

```
<pre><code><asp:ListView ID="lvEquipmentList" runat="server" DataKeyNames=
    <asp:LayoutTemplate>
        <table id="table-equipment-list" class="table table-list">
            <thead>
                <tr>
                    <th scope="col" class="product-line">Product line</th>
                    <th scope="col" class="model-number">Model #</th>
                    <th scope="col" class="serial-number">Serial #</th>
                    <th scope="col" class="dar-status">DAR Status</th>
                    <th scope="col" class="ship-date">Ship Date</th>
                </tr>
            </thead>
            <tbody>
                <asp:PlaceHolder ID="ItemPlaceholder" runat="server" />
            </tbody>
        </table>
    </asp:LayoutTemplate>
    <asp:ItemTemplate>
        <tr>
            <th scope="row" class="product-line"><div class="icon"><img s
            <td class="model-number"><%=Eval("model")%><label class="
            <td class="serial-number"><%=Eval("serial_number")%></td>
            <td class="dar-status"><img src='<%=Eval("display_status") %>'
            <td class="ship-date"><%=Eval("date")%></td>
        </tr>
    </asp:ItemTemplate>
    <asp:EmptyDataTemplate>
        <table id="table-equipment-list" class="table table-list">
            <thead>
                <tr>
                    <th scope="col" class="product-line">Product line</th>
                    <th scope="col" class="model-number">Model #</th>
                    <th scope="col" class="serial-number">Serial #</th>
                    <th scope="col" class="dar-status">DAR Status</th>
                    <th scope="col" class="ship-date">Ship Date</th>
                </tr>
            </thead>
            <tbody>
                <tr>
                    <td colspan="5">No equipment found</td>
                </tr>
            </tbody>
        </table>
    </asp:EmptyDataTemplate>
    </code></pre>
```

<p>I am kinda new to gradle... I created a Java API (now a Gradle project which build

<p>Ideally what I would like to do is create two variants, (lets say "Pro" and "Lite" for

<p>Is it possible to use gradle to build two different jars?

1. One which is the Pro full API

2. One which is the Lite API stripped of the relevant classes.</p>

<p>I see some mention of "flavours" on the net but seems all the hits are to do with

<p>The worse case scenario is that I create a new project containing just the needed

<p>Another way could be to structure the existing project into different projects and

<p>Many thanks to anyone who can shed some light here... </p>

26413017

Creating variants for programming APIs in Gr

<p>I have a report with a static choice on the prompt page. The user can choose 'Fu

<p>For a simplified example, say my report has these columns: Customer, Product, I

<p>I would like to be able to show/hide the Date column based on the detail level c

<p>I have thought about doing a separate report page for Full Detail and Summary,

<p>
</p>

<p>Full detail:</p>

```
<pre>
Customer  Product  Date      Qty    Value
ABCD      Things   22/10/2014  10     1.00
           21/10/2014  40     4.00
           23/10/2014  50     5.00
</pre>
```

<p>Summarised (How it looks at the moment, after hiding the Date column):</p>

```
<pre>
Customer  Product  Qty    Value
ABCD      Things   10     1.00
           40     4.00
           50     5.00
</pre>
```

<p>Summarised (How I would like it to look):</p>

```
<pre>
Customer  Product  Qty    Value
ABCD      Things   100    10.00
</pre>
```

<p>
</p>

<p>I am using Cognos Report Studio 10.1.1</p>

<p>This is just a general question about the helper "form_for". I'm working on a pro

```
<pre><code>No route matches [POST] "/products/new"
</code></pre>
```

<p>and</p>

```
<pre><code>No route matches [POST] "/products/5/edit"
</code></pre>
```

<p>Here's the code:</p>

```
<pre><code>  &lt;%= form_for(:product) do |f| %&gt;
    &lt;% if @product.errors.any? %&gt;
      &lt;div id="error_explanation"&gt;
        &lt;h2&gt;&lt;%= pluralize(@product.errors.count, "error") %&gt; prohibited thi

        &lt;ul&gt;
          &lt;% @product.errors.full_messages.each do |message| %&gt;
            &lt;li&gt;&lt;%= message %&gt;&lt;/li&gt;
          &lt;% end %&gt;
        &lt;/ul&gt;
      &lt;/div&gt;
    &lt;% end %&gt;

    &lt;div class="field"&gt;
      &lt;%= f.label :title %&gt;&lt;br&gt;
      &lt;%= f.text_field :title %&gt;
    &lt;/div&gt;
    &lt;div class="field"&gt;
      &lt;%= f.label :price %&gt;&lt;br&gt;
      &lt;%= f.text_field :price %&gt;
    &lt;/div&gt;
    &lt;div class="actions"&gt;
      &lt;%= f.submit %&gt;
    &lt;/div&gt;
  &lt;% end %&gt;
</code></pre>
```

<p>and in the product_controller</p>

```
<pre><code> def create
  @product = Product.new(product_params)
```


<p>hello i am exporting data from mysql to excell in codeignater its working fine on
but it's not working on server .on server its print only array like this.</p>

```
<pre><code>Array
(
  [0] => Array
    (
      [id] => 135
      [type] => 3
      [product_service] =>
      [email] => bewcontrols@gmail.com
      [first_name] => gurwinder sigh
      [last_name] =>
      [company_name] =>
      [country] =>
      [state] =>
      [city] =>
      [phone_number] => 91-011-09971587701
      [mobile] => 09971587701
      [fax_number] =>
      [address] => f-127 mayapuri indl area phase2 new delhi
      [zipcode] =>
      [message] => Subject: Fwd to purchase/ maint. for repairing of SOLENOID
    )
  )
</code></pre>
```

<p>Dear Sir,</p>

<p>I'd like to take this opportunity to introduce BEW Pneumatic
Controls,Delhi, to you.</p>

<p>We manufacture Heavy Duty Solenoid Valves in Spool construction
using all-Aluminium fittings.While most manufacturers use plastic
fittings,plastic cages, we at BEW pioneered Aluminium fittings and
have incorporated them across our product line.</p>

<p>Please find attached our latest product catalogue for your perusal and
we look forward to hearing from you soon.</p>

<p>Best Regards,</p>

<p>Gurwinder Singh
Mobile-09811019362,
and 09971587701</p>

<p>Using CodeIgniter, I am creating an admin area where I am able to create footnc

<p>HTML</p>

```
<pre><code>&lt;p&gt;Choose Product Line&lt;/p&gt;
&lt;label&gt;&lt;input type="checkbox" name="productline[]" value="1" /&gt;Produ
&lt;label&gt;&lt;input type="checkbox" name="productline[]" value="2" /&gt;Produ
&lt;label&gt;&lt;input type="checkbox" name="productline[]" value="3" /&gt;Produ
&lt;label&gt;&lt;input type="checkbox" name="productline[]" value="4" /&gt;Produ
</code></pre>
```

<p>PHP</p>

```
<pre><code>for ( $i = 0; $i &lt; count( $this-&gt;input-&gt;post( 'product[]' ) ); $i++ )
{
    $line__id = $this-&gt;input-&gt;post( 'product' )[$i];

    $footnote_data = array(
        'line__id' =&gt; $line__id,
        'code' =&gt; $this-&gt;input-&gt;post( 'footnotecode' ),
        'text' =&gt; $this-&gt;input-&gt;post( 'footnotetext' ),
        'status' =&gt; $this-&gt;input-&gt;post( 'status' ),
        'createdon' =&gt; date( 'Y-m-d H:i:s' )
    );

    error_log( print_r( $footnote_data, true ) );
}
</code></pre>
```

<p>Which will output something like this:</p>

<p>LOG:</p>

```
<pre><code>Array
(
    [line__id] =&gt; 1
    [code] =&gt; ABC123
    [text] =&gt; Hello World
    [status] =&gt; 1
    [createdon] =&gt; 2014-12-31 22:28:59
)
```

Array

```

<pre><code>&lt;!DOCTYPE html&gt;
&lt;html lang="en"&gt;
&lt;head&gt;
    &lt;meta charset="utf-8"&gt;
    &lt;title&gt;Little Things&lt;/title&gt;
&lt;?php echo link_tag('resources/css/style.css'); ?&gt;
    &lt;script src="http://code.jquery.com/jquery-latest.min.js" type="text/javascript
    &lt;script type="text/javascript" src="&lt;?php echo base_url('resources/js/scip
    &lt;script type="text/javascript"&gt;var $rows = $('#table tr');
$( '#search').keyup(function() {
    var val = $.trim($(this).val()).replace(/ +/g, ' ').toLowerCase();

    $rows.show().filter(function() {
        var text = $(this).text().replace(/\s+/g, ' ').toLowerCase();
        return !~text.indexOf(val);
    }).hide();
});
&lt;/script&gt;
&lt;/head&gt;
&lt;body&gt;
&lt;div id="container"&gt;
    &lt;div id="top"&gt;
        &lt;img id="logo" src="&lt;?php echo base_url('resources/images/logo.jpg'); ?&
        &lt;/div&gt;
        &lt;div id="main"&gt;
            &lt;div id='cssmenu'&gt;
&lt;ul&gt;
    &lt;li class='active'&gt;&lt;a href="&lt;?php echo base_url('index.php/LittleContro
    &lt;li class="element"&gt;&lt;a href="#"&gt;&lt;span&gt;Shopping Cart&lt;/span&g

    &lt;li class="element"&gt;&lt;a href="#"&gt;&lt;span&gt;Wish List&lt;/span&gt;&lt;

    &lt;li class="element"&gt;&lt;a href="#"&gt;&lt;span&gt;Contact&lt;/span&gt;&lt;/
    &lt;li id="name"&gt;
    &lt;?php
        if($this-&gt;session-&gt;userdata('email'))
        {
            echo "&lt;a href='#'&gt;&lt;span&gt;Welcome ". $user."&lt;/span&gt;&lt;/a&
        }
        else
        {
            echo "&lt;a href='#'&gt;&lt;span&gt;Welcome Guest&lt;/span&gt;&lt;/a&gt;

```

<p>I have a workbook that has 2 worksheets and sub-sheets Named as per Product

NEW DATA sheet

Master Table sheet ("DBQ Query Result")

Subsheets (Driling and Workover, Fishing, Liner Systems, Professional Services, V

<p>They both have same headers, within the column headers there is a uniqueID cc

<h3>PART A</h3>

<p>I would like to match uniqueID between those 2 sheets and:</p>

When there is a match, compare row cell values for each column and update if t

When there is a uniqueID in NEW DATA sheet that does not exist in Master Tabl

<h3>PART B</h3>

<p>I would like to have a new button that when pressed, UniqueID from Master Pag

When there is a match, update subsheet row according to UNIQUEID

When there is no match, that means a new UNIQUEID is created and this should

<p>I would like to accomplish the above using VBA macro please. I have attached a

<p>Please let me know if you need any additional information.</p>

27919420

Compare all columns between two sheets ba

<p>my requirement is quite simple, just want to connect to emc storage server and i googled the web and found someone mentioned emc have the apis, but i did not my second option is using ESIPSToolKit, but it need power shell and a windows serve

<p>Thank you in advance. </p>

<p>here are some details, hope can help some one:

1) vnx and vmax are two very different product line.

2) ViPR have the rest api to manage vnx and vmax.

3) unisphere only support vmax for rest api

4) Celerra xml api only support file in vnx, no block support</p>

27935790

is there a .NET or REST (http) API for EMC (VI

<p>I'm using Dynamic jasper library to create dynamic columns for my report.

This is my code:
</p>

```
<pre><code>FastReportBuilder drb = new FastReportBuilder();
    DynamicReport dr = drb.addColumn("State", "state", String.class.getName(),30)
        .addColumn("Branch", "branch", String.class.getName(),30) // title, proper
        .addColumn("Product Line", "productLine", String.class.getName(),50)
        .addColumn("Item", "item", String.class.getName(),50)
        .addColumn("Item Code", "id", Long.class.getName(),20)
        .addColumn("Quantity", "quantity", Long.class.getName(),30)
        .addColumn("Amount", "amount", Float.class.getName(),30)
        .addGroups(2) // Group by the first two columns
        .setTitle("November 2006 sales report")
        .setSubtitle("This report was generated at" + new Date())
        .setUseFullPageWidth(true) //make columns to fill the page width
        .build();

    JRDataSource ds = new JRBeanCollectionDataSource(TestRepositoryProducts.getItems());
    JasperPrint jp = DynamicJasperHelper.generateJasperPrint(dr, new ClassicLayout(), ds);
    JasperViewer.viewReport(jp);
</code></pre>
```

<p>And this is my class <code>TestRepositoryProducts</code>:
</p>

```
<pre><code>import java.util.ArrayList;
import java.util.Collection;
import java.util.Vector;

public class TestRepositoryProducts {

    public static Collection<Object> getDummyCollection() {
        Collection<Object> v = new ArrayList<Object>();
        v.add("qsdqsd");
        v.add("qsdqds");
        v.add("qsdqds");
        v.add("qsdqds");
        v.add(32165);
        v.add(65456);
        v.add(1.5);
        return v;
    }
}</pre>
```

<p>In the template for WooCommerce PDF invoices I see this piece of code <code>|

<p>In particular, I don't need the Qty, Total ex., Tax (in the product line), the Price Ir

<p>I really not know how and where I do that. Please advise.</p>

28326401

Changing [[ORDERINFO]] in WooCommerce F

<p>I am running an api for magento shop to connect to economics : please check th

<p>I just paste the folder in root directory and getting my order through </p>

```
<pre><code>$orderId= Mage::getSingleton('checkout/session')-&gt;getLastRealOrd
$order= Mage::getSingleton('sales/order')-&gt;loadByIncrementId($orderId);
</code></pre>
```

<p>My question is I need to include api folder in root director / vendor / autoload.p
So that when an new order is been placed in my shop the total order details will be

<p>Any idea on this... thanks in advance.</p>

<p>Create a new Order This method lets you create a newOrder to a specific Debtor

```
<pre><code>&lt;?php
require(Mage::getBaseDir()).DS.'Economic-PHP-SDK-master'.DS.'vendor'.DS.'autoloa
use tkj\Economics\Client;
use tkj\Economics\Order\Order;
$client = new Client($agreementNumber,$userID, $password);
$order = new Order($client);
$debtorNumber = 101;
$newOrder =$order-&gt;create($debtorNumber, function($line)
{
    $data = array(
        "product"    =&gt; 301,
        "description" =&gt; "Description of line.",
        "price"      =&gt; 825.00,
        "qty"        =&gt; 5,
        "unit"       =&gt; 2);
    $line-&gt;add($data);
});
</code></pre>
```

<p>class EconomicAPI_Model_Observer {</p>

```
<pre><code>public function ordermigrate($observer) {
```

```
    $orderId = Mage::getSingleton('checkout/session')-&gt;getLastRealOrderId();
    $order = Mage::getSingleton('sales/order')-&gt;loadByIncrementId($orderId);
```

```
    //echo "order subtotal: " $order-&gt;getSubtotal() "&lt;br&gt;";
```


<p>I'm afraid I may be asking a really dumb question, but I can't seem to find anythi

<p>I understand that in csharp the *.csproj file can be unloaded and modified with |

What is the difference in a *.proj and *.csproj file?

Can a *.proj be setup in VS to load on Build with F6 or does using this require usi

Does dirs.proj load automatically? If so, my study-by is not working correctly, ye

Or am I overlooking something all the way around with "dirs.proj" Maybe it's ju:

<p>Anyways, I've seen dirs.proj mentioned in several forums regarding issues, but n

<p>Thanks in advance.</p>

28832703

How is dirs.proj used?

<p>Got the following - reduced to a minimum - code:</p>

<p>CSS:</p>

```
<p><div class="snippet" data-lang="js" data-hide="false">
<div class="snippet-code">
<pre class="snippet-code-css lang-css prettyprint-override"><code>  html {
  height: 100%;
}
```

```
  body {
    height: 100%;
    font-size: 1.5em;
    line-height: 1.5;
    font-family: Arial, Verdana, Helvetica, sans-serif;
  }
```

```
  a, a:link, a:active, a:visited {
    color: #e23427;
    text-decoration: none;
  }
```

```
  li {
    list-style: none;
  }
```

```
  /**1. Ebene Hauptnavigation**/
```

```
  ul.topNav {
    float: left;
    width: 700px;
    margin: 100px 0 0 40px;
```

```
  }
  ul.topNav li {
    float: left;
    position: relative;
  }
```

```
  ul.topNav li a.tmp {
    color: inherit;
    float: left;
    height: 20px;
    padding: 0 10px;
```

<p>I have a form in which I wanted to have the Submit button have a pop-up to ask

<p>Wondering if this might be because of a clash with the JS or another part of the

<p>Code:</p>

```
<pre><code>{% extends "prod/page_base.html" %}
```

```
{% load dajaxice_templatetags %}
```

```
{% load static %}
```

```
{% block title %}{{ edit_add }} product configuration{% endblock %}
```

```
{% block dajax %}
```

```
    {% dajaxice_js_import %}
```

```
    &lt;script src="{% static 'dajax/jquery.dajax.core.js' %}"&gt;&lt;/script&gt;
```

```
{% endblock %}
```

```
{% block script %}
```

```
&lt;script src="http://ajax.googleapis.com/ajax/libs/jquery/1.10.2/jquery.min.js"&g
```

```
&lt;script&gt;
```

```
$(document).ready(function(){
```

```
    if ($("#id_line").val() != "group1" &amp;&amp; ($("#id_line").val() != "group2") {
```

```
        $("#group_fields").hide();
```

```
    }
```

```
    $("#id_line").click(function() {
```

```
        if ($("#id_line").val() != "group1" &amp;&amp; ($("#id_line").val() != "group2") {
```

```
            $("#group_fields").hide();
```

```
        }
```

```
    else {
```

```
        $("#group_fields").show();
```

```
    }
```

```
});
```

```
});
```

```
&lt;/script&gt;
```

```
{{ form.media }}
```

```
{% endblock %}
```

```
{% block pagetitle %}{{ edit_add }} Product Configuration{% endblock %}
```

```
{% block page_content %}
```

```
{% if form.errors or formset.errors %}
```

I'm adding a new column in a table, and while doing the alteration I received an

Please see below:

`ALTER TABLE dbname.table_name ADD COLUMN column_name TINYINT`
 ERROR 1062 (23000): Duplicate entry '300866' for key 'PRIMARY'

```
<pre><code>mysql>show create table dbname.table_name\G
***** 1. row *****
Table: table_name
Create Table: CREATE TABLE `table_name` (
  `id` int(10) unsigned NOT NULL AUTO_INCREMENT,
  `sku` varchar(255) NOT NULL,
  `status` enum('active','inactive','deleted') NOT NULL DEFAULT 'active',
  `status_supplier_config` enum('active','inactive','deleted') NOT NULL DEFAULT 'act
  `name` varchar(255) NOT NULL,
  `description` text COMMENT 'Description of the product',
  `fk_catalog_brand` int(10) unsigned DEFAULT NULL,
  `primary_category` int(10) unsigned DEFAULT NULL,
  `fk_catalog_import` int(10) unsigned DEFAULT NULL,
  `display_if_out_of_stock` tinyint(1) DEFAULT '0',
  `fk_catalog_config_group` int(10) unsigned DEFAULT NULL,
  `fk_catalog_attribute_set` int(10) unsigned NOT NULL,
  `pet_status` set('creation','edited','images') DEFAULT NULL,
  `pet_approved` tinyint(1) NOT NULL DEFAULT '0',
  `created_at` datetime DEFAULT NULL,
  `created_by_config` varchar(50) DEFAULT NULL,
  `updated_at` timestamp NOT NULL DEFAULT CURRENT_TIMESTAMP ON UPDATE C
  `updated_by_config` varchar(50) DEFAULT NULL,
  `activated_at` datetime DEFAULT NULL,
  `supplier_name` varchar(255) DEFAULT NULL,
  `sku_supplier_config` varchar(255) DEFAULT NULL COMMENT 'SKU of product at si
  `creation_source_config` varchar(255) NOT NULL DEFAULT '',
  `product_line` varchar(255) DEFAULT NULL COMMENT 'Product Line/Range/Sub-Bi
  `model` varchar(255) DEFAULT NULL COMMENT 'Model ID of Manufacturer part ni
  `fk_catalog_attribute_option_global_supplier_type` int(10) unsigned DEFAULT NUI
  `fk_catalog_attribute_option_global_season` int(10) unsigned DEFAULT NULL CON
  `fk_catalog_attribute_option_global_gender` int(10) unsigned DEFAULT NULL CON
  `fk_catalog_attribute_option_global_production_country` int(10) unsigned DEFAU
  `imported` tinyint(1) unsigned DEFAULT NULL COMMENT 'Is the product imported
  `note` varchar(255) DEFAULT NULL COMMENT 'Note / comment',
  `source_url_1` text COMMENT 'Product URL (scraped products)',
  `source_cost_1` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 1 (Gross)'
  `source_cost_2` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 2 (Gross)'
  `source_cost_3` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 3 (Gross)'
  `source_cost_4` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 4 (Gross)'
  `source_cost_5` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 5 (Gross)'
  `source_cost_6` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 6 (Gross)'
  `source_cost_7` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 7 (Gross)'
  `source_cost_8` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 8 (Gross)'
  `source_cost_9` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 9 (Gross)'
  `source_cost_10` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 10 (Gross)'
  `source_cost_11` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 11 (Gross)'
  `source_cost_12` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 12 (Gross)'
  `source_cost_13` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 13 (Gross)'
  `source_cost_14` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 14 (Gross)'
  `source_cost_15` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 15 (Gross)'
  `source_cost_16` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 16 (Gross)'
  `source_cost_17` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 17 (Gross)'
  `source_cost_18` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 18 (Gross)'
  `source_cost_19` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 19 (Gross)'
  `source_cost_20` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 20 (Gross)'
  `source_cost_21` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 21 (Gross)'
  `source_cost_22` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 22 (Gross)'
  `source_cost_23` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 23 (Gross)'
  `source_cost_24` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 24 (Gross)'
  `source_cost_25` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 25 (Gross)'
  `source_cost_26` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 26 (Gross)'
  `source_cost_27` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 27 (Gross)'
  `source_cost_28` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 28 (Gross)'
  `source_cost_29` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 29 (Gross)'
  `source_cost_30` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 30 (Gross)'
  `source_cost_31` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 31 (Gross)'
  `source_cost_32` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 32 (Gross)'
  `source_cost_33` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 33 (Gross)'
  `source_cost_34` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 34 (Gross)'
  `source_cost_35` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 35 (Gross)'
  `source_cost_36` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 36 (Gross)'
  `source_cost_37` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 37 (Gross)'
  `source_cost_38` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 38 (Gross)'
  `source_cost_39` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 39 (Gross)'
  `source_cost_40` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 40 (Gross)'
  `source_cost_41` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 41 (Gross)'
  `source_cost_42` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 42 (Gross)'
  `source_cost_43` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 43 (Gross)'
  `source_cost_44` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 44 (Gross)'
  `source_cost_45` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 45 (Gross)'
  `source_cost_46` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 46 (Gross)'
  `source_cost_47` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 47 (Gross)'
  `source_cost_48` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 48 (Gross)'
  `source_cost_49` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 49 (Gross)'
  `source_cost_50` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 50 (Gross)'
  `source_cost_51` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 51 (Gross)'
  `source_cost_52` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 52 (Gross)'
  `source_cost_53` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 53 (Gross)'
  `source_cost_54` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 54 (Gross)'
  `source_cost_55` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 55 (Gross)'
  `source_cost_56` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 56 (Gross)'
  `source_cost_57` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 57 (Gross)'
  `source_cost_58` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 58 (Gross)'
  `source_cost_59` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 59 (Gross)'
  `source_cost_60` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 60 (Gross)'
  `source_cost_61` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 61 (Gross)'
  `source_cost_62` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 62 (Gross)'
  `source_cost_63` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 63 (Gross)'
  `source_cost_64` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 64 (Gross)'
  `source_cost_65` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 65 (Gross)'
  `source_cost_66` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 66 (Gross)'
  `source_cost_67` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 67 (Gross)'
  `source_cost_68` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 68 (Gross)'
  `source_cost_69` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 69 (Gross)'
  `source_cost_70` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 70 (Gross)'
  `source_cost_71` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 71 (Gross)'
  `source_cost_72` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 72 (Gross)'
  `source_cost_73` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 73 (Gross)'
  `source_cost_74` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 74 (Gross)'
  `source_cost_75` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 75 (Gross)'
  `source_cost_76` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 76 (Gross)'
  `source_cost_77` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 77 (Gross)'
  `source_cost_78` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 78 (Gross)'
  `source_cost_79` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 79 (Gross)'
  `source_cost_80` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 80 (Gross)'
  `source_cost_81` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 81 (Gross)'
  `source_cost_82` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 82 (Gross)'
  `source_cost_83` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 83 (Gross)'
  `source_cost_84` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 84 (Gross)'
  `source_cost_85` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 85 (Gross)'
  `source_cost_86` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 86 (Gross)'
  `source_cost_87` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 87 (Gross)'
  `source_cost_88` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 88 (Gross)'
  `source_cost_89` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 89 (Gross)'
  `source_cost_90` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 90 (Gross)'
  `source_cost_91` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 91 (Gross)'
  `source_cost_92` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 92 (Gross)'
  `source_cost_93` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 93 (Gross)'
  `source_cost_94` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 94 (Gross)'
  `source_cost_95` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 95 (Gross)'
  `source_cost_96` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 96 (Gross)'
  `source_cost_97` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 97 (Gross)'
  `source_cost_98` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 98 (Gross)'
  `source_cost_99` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 99 (Gross)'
  `source_cost_100` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 100 (Gross)'
  `source_cost_101` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 101 (Gross)'
  `source_cost_102` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 102 (Gross)'
  `source_cost_103` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 103 (Gross)'
  `source_cost_104` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 104 (Gross)'
  `source_cost_105` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 105 (Gross)'
  `source_cost_106` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 106 (Gross)'
  `source_cost_107` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 107 (Gross)'
  `source_cost_108` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 108 (Gross)'
  `source_cost_109` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 109 (Gross)'
  `source_cost_110` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 110 (Gross)'
  `source_cost_111` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 111 (Gross)'
  `source_cost_112` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 112 (Gross)'
  `source_cost_113` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 113 (Gross)'
  `source_cost_114` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 114 (Gross)'
  `source_cost_115` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 115 (Gross)'
  `source_cost_116` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 116 (Gross)'
  `source_cost_117` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 117 (Gross)'
  `source_cost_118` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 118 (Gross)'
  `source_cost_119` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 119 (Gross)'
  `source_cost_120` decimal(11,2) DEFAULT NULL COMMENT 'Cost Supplier 120 (Gross)'
  `source_cost_121` decimal(11,2) DEFAULT
```

<p>I have the following models</p>

```
<pre><code>Shipment (id, product_id, ...)
Product (id, product_id, some_attribute:boolean, ...)
</code></pre>
```

<p>Where a shipment belongs to a product and a product has many shipments. Fur

<p>I want to find all the shipments for which the <code>some_attribute</code> on

<p>For example, in this example</p>

```
<pre><code>shipment1 (id = 1, product_id = 1)
shipment2 (id = 2, product_id = 2)

product1 (id = 1, product_id = 3, some_attribute = false)
product2 (id = 2, product_id = 4, some_attribute = false)
product3 (id = 3, product_id = null, some_attribute = false)
product4 (id = 4, product_id = null, some_attribute = true)
</code></pre>
```

<p>only <code>shipment2</code> should be returned, because it's product line goe

<p>Much appreciated</p>

<p>EDIT:</p>

<p>For clarity, the product chain can arbitrarily long, but in practice, it's usually aro

29923593

Find all records matching attribute on self as:

<p>So I'm just trying to make a couple nav links drop down using bootstrap, but for

```
<pre><code>&lt;head&gt;
```

```
&lt;title&gt;Flemington Supply | &lt;?php echo $pageTitle; ?&gt;&lt;/title&gt;
```

```
&lt;script type='text/javascript' src='support/jquery.min.js'&gt;&lt;/script&gt;
```

```
&lt;link href = "bootstrap-3.3.4-dist/css/bootstrap.min.css" rel = "stylesheet" media
```

```
&lt;link rel="stylesheet" type="text/css" href="redox.css"&gt;
```

```
&lt;link href="support/carousel.css" rel="stylesheet"&gt;
```

```
&lt;script type='text/javascript' src="http://imsky.github.io/holder/holder.js"&gt;&lt;/script type='text/javascript' src="bootstrap-3.3.4-dist/js/bootstrap.min.js"&gt;&
```

```
&lt;script src="support/carousel.js"&gt;&lt;/script&gt;
```

```
&lt;meta name="viewport" content="width=device-width, initial-scale=1"&gt;
```

```
&lt;script type="text/javascript"&gt;
```

```
document.getElementsByClassName('changetext').onmouseover.style.color = "#0000ff";
```

```
&lt;/script&gt;
```

```
&lt;/head&gt;
```

```
&lt;body&gt;
```

```
&lt;div class = "nav navbar"&gt;
```

```
&lt;div class = "container"&gt;
```

```
&lt;div&gt;
```

```
&lt;ul class = "pull-left"&gt;
```

```
&lt;li&gt;
```

```
&lt;a href = "#"&gt;&lt;img src = "site1/images/flemsupp.jpeg" height = "60
```

```
&lt;/li&gt;
```

```
&lt;li&gt;&lt;a href = "#"&gt;Linecard&lt;/a&gt;&lt;/li&gt;
```

```
&lt;li class="dropdown"&gt;
```

```
&lt;a href="#" class="dropdown-toggle" data-toggle="dropdown" role="button" aria-expanded="false"&gt;
```

```
Company &lt;span class="caret"&gt;&lt;/span&gt;
```

```
&lt;/a&gt;
```

```
&lt;ul class="dropdown-menu" role="menu" aria-labelledby="dropdownMenu1"&gt;
```

```
&lt;li role="presentation"&gt;&lt;a role="menuitem" tabindex="-1" href="#"&gt;
```

```
&lt;li role="presentation"&gt;&lt;a role="menuitem" tabindex="-1" href="#"&gt;
```

<p>On an existing Zend Framework website with few controllers and no modules I r

<p>For example, I currently have :</p>

```
<pre><code>/products
/products/id/1
/training
/commonpage
</code></pre>
```

<p>I want to add a product line level, without duplicating my controllers in x modul

<p>So my new paths will be :</p>

```
<pre><code>/line1/products
/line1/products/id/1
/line2/training
/commonpage
</code></pre>
```

<p>What I tried so far is this route (located in my Bootstrap file) :

```
<pre><code>protected function _initRoutes()
{
    $router = Zend_Controller_Front::getInstance()-&getRouter();
    $router-&addRoute('productLineRoute', new Zend_Controller_Router_Route(
        ':line/:controller/:action',
        array('module' =& 'default'),
        array('line' =& '(' . implode('|', Zend_Registry::getInstance()-&constants-&
    ));
}
</code></pre>
```

<p>But without any success (it gives me a 404).

How can I build a single route that match all uri under those conditions :</p>

The prefix of the uri match a value in my product lines array

The route is valid only if the controller requested is allowed to be accessed in a "

<h1>UPDATE</h1>

<p>in membership.py file the class account_invoice_line wich inherits 'account.invo and override the write method wich will create a new member line when a new line is created in an existed invoice. For me its not correct when a a new line of invoice is in an existing invoice it must be related to the existed member line and not create a so i must override the write methode, but the problem that the write method in me . So can someone tell me how to override the write method without passing by the

```
<pre><code>class account_invoice_line(osv.osv):
    _inherit='account.invoice.line'

def write(self, cr, uid, ids, vals, context=None):
    """Overrides orm write method
    """
    member_line_obj = self.pool.get('membership.membership_line')
    res = super(account_invoice_line, self).write(cr, uid, ids, vals, context=context)
    for line in self.browse(cr, uid, ids, context=context):
        if line.invoice_id.type == 'out_invoice':
            ml_ids = member_line_obj.search(cr, uid, [('account_invoice_line', '=', line.id]
            if line.product_id and line.product_id.membership and not ml_ids:
                # Product line has changed to a membership product
                date_from = line.product_id.membership_date_from
                date_to = line.product_id.membership_date_to
                if line.invoice_id.date_invoice > date_from and line.invoice_id.date_inv
                    date_from = line.invoice_id.date_invoice
                member_line_obj.create(cr, uid, {
                    'partner': line.invoice_id.partner_id.id,
                    'membership_id': line.product_id.id,
                    'member_price': line.price_unit,
                    'date': time.strftime('%Y-%m-%d'),
                    'date_from': date_from,
                    'date_to': date_to,
                    'account_invoice_line': line.id,
                }, context=context)
            if line.product_id and not line.product_id.membership and ml_ids:
                # Product line has changed to a non membership product
                member_line_obj.unlink(cr, uid, ml_ids, context=context)
    return res

def unlink(self, cr, uid, ids, context=None):
    """Remove Membership Line Record for Account Invoice Line
    """
    member_line_obj = self.pool.get('membership.membership_line')
    for id in ids:
```


<p>I have an Excel file that in Excel 2007 is correctly authenticating with a server an

<p>I understand that Excel 2010 can have authentication issues using non-SSL conn

<p><a href="http://answers.microsoft.com/en-us/office/forum/office_2010-excel/ε

<p>I know that this file is currently using HTTP to connect to this DB. Is this what is c

<p>Relevant code snippets:</p>

```
<pre><code>g_sServer = "http://" + g_sServer
```

```
g_sProductLine = g_oDom.documentElement.selectSingleNode("PRODLINE").Text
```

```
'If no product line is in the variable after the login...
```

```
If g_sProductLine = "" Then
```

```
    'Build the message
```

```
    s = "Your Login has Failed. "
```

```
    s = s & "Please click the Re-Login button if you would like to try again."
```

```
</code></pre>
```

<p>Thanks for your help</p>

30672306

Excel 2010 server authentication failing

```
<pre><code>&lt;report xmlns="http://developer.cognos.com/schemas/report/7.0/"
expressionLocale="en-us"&gt;
&lt;modelPath&gt;/content/package[@name='GO Sales and Retailers']
/model[@name='model']&lt;/modelPath&gt;
&lt;queries&gt;
&lt;query name="Query1"&gt;
&lt;source&gt;
&lt;model/&gt;
&lt;/source&gt;
&lt;selection&gt;
&lt;dataItem name="Revenue" aggregate="total"&gt;
&lt;expression&gt;[gosales_goretailers].[Orders].[Revenue]&lt;/expression&gt;
&lt;/dataItem&gt;
&lt;dataItem name="Sales territory" aggregate="none"&gt;
&lt;expression&gt;[gosales_goretailers].[Countries].[Sales territory]
&lt;/expression&gt;
&lt;/dataItem&gt;
&lt;dataItem name="Order method" aggregate="none"&gt;
&lt;expression&gt;[gosales_goretailers].[Orders].[Order method]&lt;/expression&gt;
&lt;/dataItem&gt;
&lt;dataItem name="Order year" aggregate="none"&gt;
&lt;expression&gt;[gosales_goretailers].[Orders].[Order year]&lt;/expression&gt;
&lt;/dataItem&gt;
&lt;dataItem name="Product line" aggregate="none"&gt;
&lt;expression&gt;[gosales_goretailers].[Products].[Product line]&lt;/expression&gt;
&lt;/dataItem&gt;
&lt;/code></pre>
```

<p>i want to store the text value within the expression tag with its corresponding d:

<p>means i want the output like this:

- (1) Revenue=[gosales_goretailers].[Orders].[Revenue]
- (2) Sales territory=[gosales_goretailers].[Countries].[Sales territory]...</p>

<p>I used the following code to store all text values in a list within the Expression ta

```
<pre><code>    final ArrayList&lt;String&gt; dataItemList=new ArrayList&lt;String&
    final ArrayList&lt;String&gt; expressionList=new ArrayList&lt;String&gt;();
    final ArrayList&lt;String&gt; retList=new ArrayList&lt;String&gt;();

    try
    {
        SAXParserFactory factory = SAXParserFactory.newInstance();
```

<p>So the user uploads a stock file csv with all of the products in. The file is formatt

```
<pre>
productcode,size1,size2,size3,size4,size5
</pre>
```

<p>and has that info for each product line.</p>

<p>I have the following code which deals with the uploaded file and pulls that info f

```
<pre><code>&lt;?php
if (isset($_GET['uploadfile'])) {
    $file = fopen($_FILES['csvfile']['tmp_name'], 'r+');
    while(!feof($file)) {
        $line = fgetcsv($file, 0, ',');

        list($productcode, $v9cm, $v1litre, $v2litre, $v3litre, $v5litre, $v7litre) = $line;

        $stmt = $db-&gt;prepare("UPDATE stock SET 9cm = '$v9cm', 1litre = '$v1litre', 2
        if ($stmt === FALSE) {
            echo "an error has occured";
        }

        $stmt-&gt;execute();
        $stmt-&gt;close();
    }
    fclose($file);
}
?&gt;
</code></pre>
```

<p>It seems to work fine and is updating each record in the database as expected, t

```
<pre>
bob,11,44,54,23,12
</pre>
```

<p>This code 'bob' isn't in the database, so cannot be updated, so there should in th

<p>We create a website for a bikeshop. In the first step we will just show the produ
We want to describe the product line with a headline, text and a picture.</p>

<p>Is it possible to describe a product line with Schema.org?
I just found a Schema.org type for a product.</p>

31334370

Describe a product line with Schema.org

<p>My ListView contains a successfully implemented TreeView as an item source in

<p>Here is the CellTemplate for the TreeView:</p>

```
<pre><code>&lt;GridViewColumn.CellTemplate&gt;
    &lt;DataTemplate DataType="workFlow:AssemblyModels"&gt;
        &lt;Grid Background="Transparent"&gt;
            &lt;Grid.ColumnDefinitions&gt;
                &lt;ColumnDefinition Width="*" /&gt;
            &lt;/Grid.ColumnDefinitions&gt;

            &lt;Grid.RowDefinitions&gt;
                &lt;RowDefinition Height="*" /&gt;
            &lt;/Grid.RowDefinitions&gt;

            &lt;TreeView Grid.Row="0"
                Grid.Column="0"
                Background="Transparent"
                Focusable="False"&gt;
                &lt;TreeViewItem Header="Product Line List"
                    ItemsSource="{Binding Path=ProductLine}"
                    Background="Transparent"&gt;
                    &lt;TreeViewItem.ItemContainerStyle&gt;
                        &lt;Style TargetType="TreeViewItem"&gt;
                            &lt;Setter Property="Background" Value="Transparent" /&gt;
                        &lt;/Style&gt;
                    &lt;/TreeViewItem.ItemContainerStyle&gt;
                &lt;/TreeViewItem&gt;
            &lt;/TreeView&gt;
        &lt;/Grid&gt;
    &lt;/DataTemplate&gt;
&lt;/GridViewColumn.CellTemplate&gt;
</code></pre>
```

<p>Thanks in advance for any assistance that can be provided to fix this issue.</p>

<p>James</p>

<p>Okay, I know the title is a bit confusing so let me explain it a little bit more.</p>

<p>We have different groups of clients and they want to have their own app, meani

<p>Of course, we can submit different app for different client. But the maintenance

<p>As a developer, I want to have a generic app for app submission and update. But

<p>I have also done preliminary search on this question but the answer I got is a no

<p>Many Thanks!</p>

<p>P.S. I found a group of apps on App Store which cover the question I asked. It is

31577636

Changing iOS and Android app's name and ic

<p>Let me start off by saying I'm not the most advanced programmer - at all. I have

<p>I have created the following div in the CSS portion: </p>

```
<pre><code>.Social {  
  width: 6%;  
  position: absolute;  
  top: -7.5em;  
  left: 87%;  
  font-family: Arial, Helvetica, sans-serif;  
  font-size: 12px;  
  font-weight: normal;  
  color: #000;  
  
}  
</code></pre>
```

<p>Additionally, I have implemented the following HTML </p>

```
<pre><code>&lt;div class="fullscreen"&gt;  
&lt;div class="Social"&gt;  
  
&lt;a href="https://www.facebook.com/alliedsystemscompany" target="_blank"&g  
&lt;a href="https://www.linkedin.com/company/allied-systems" target="_blank"&g  
  
&lt;/div&gt;  
</code></pre>
```

<p>The website URL is <a href="http://www.alliedsystems.com/home.htm" rel="no

<p>Our company has a rather small product line but the usage can be quite comple:

<p>The current situation is that the (internal and external) documentation is spread

<p>In general, we want to provide the following kinds of documentation (sorted by

Quick start guide

User guide

Help texts in webinterface

Administration manual

Training manual

Internal documentation (for developers)

<p>Much of the content is the same for all of the manuals (general information), so

<p>I've had a look at some tools which are often recommended on stackoverflow (r

<p>Of course it would be possible to use just LaTeX and include just the parts suited

<p>So I am wondering:</p>

Is there a best pratice on how to write reusable documentation?

How do big(ger) companies manage their documentation?

Is there a way to have all documentation in a single place and compile different

<p>For internal documentation it would be nice to include parts from the code but i

31749306

Best pratice for writing reusable documentat

<p>While creating purchase order, If I add the same products twice , it creates two

<p>Please anyone help me with this.</p>

31780726

How to eliminate duplicate products in odoo


```
<ol>
<li>Duplicated attriubte set for new product line. </li>
<li>Attributes set show in backend and front end. </li>
<li>Created new attribute and added to attribute set.</li>
<li>New attribute show's in back end but not front end.</li>
<li>If I add the new attribute to the orignal set that was duplicated the new attribu
</ol>
```

<p>So basicly A new attribute added to a duplicate set won't show on the front end

<p>I've checked to make sure the attribute is visable on front end etc and tried it se

<p>The goal is to be able to duplicate a attribute set and add new attributes for diff

<p>I've called the attribute group by ID (spec's). This code is working. </p>

```
<pre><code>&lt;?php
require_once 'app/Mage.php';
Mage::app();

$attributeGroupCollection = Mage::getResourceModel('eav/entity_attribute_group'
$product = $this-&gt;getProduct();

foreach ($attributeGroupCollection as $attributeGroup) {
    $attributeGroup-&gt;getAttributeGroupId();
    $attributeSpecs = Mage::getResourceModel('eav/entity_attribute_collection')
        -&gt;setAttributeGroupFilter(41);

}
?&gt;
</code></pre>
```

<p>Help is appreciated, thanks</p>

<p>Currently, I am participating in the design of a new data warehouse. I am quite r

<p>I would like to illustrate my problem with a short example, e.g. a sales data mart

<p>I can imagine the following three different approaches:</p>

Joining via a Bridge Table - I prefer that one, but I am not sure about this becaus

Introducing two seller foreign keys into the fact table - I would use this approach

One record in the fact table per seller - I create a duplicate for the records whicl

<p>Do you have any considerations regarding this? It would be great if you could sh

31964317

Star schema and bridge tables for many to 1/

<p>Can somebody give me some insights what is the difference between Netflix Zu

<p>Seems that both product line are maintained.

And version 2 is using Guice for DI and there are some difference in Filter implemen

32168720

What is difference between Netflix Zuul versi

<p>In Excel, I want to change the color of the row at every change in a particular row

<p>For example:</p>

<pre><code>Customer Product Line Product

1 Outdoor Lawn Jarts

1 Indoor Nerf Hoops

2 Outdoor Ball Game

3 Indoor Fort Builder

4 Indoor Twist'Em

4 Indoor Silly Silly

</code></pre>

<p>In this example, I would want customer 1 to be light blue; customer 2, white; cu

<p><img

<p>I'd prefer to use a formula if possible.

Thanks.</p>

<p>EDIT: Customer numbers are non-consecutive numbers (1,15,49406, etc.)</p>

32254209

Excel Change Row color at every change in v

<p>I want a regular expression for VB.NET to remove all hyperlinks in a string, includ

```
<ul>
<li><a href="http://www.example.com" rel="nofollow">http://www.example.com<
<li><a href="http://www.example.com/" rel="nofollow">http://www.example.com
<li><a href="https://www.example.com" rel="nofollow">https://www.example.com
<li><a href="http://www.example.com/page.html?t=7" rel="nofollow">http://www
<li><a href="http://example.com?q=test&amp;sort=1" rel="nofollow">http://exam
<li>www.example.com</li>
<li>etc</li>
</ul>
```

<p>Here's the string I'm working with in which all links need to be removed:</p>

```
<pre><code>Dim description As String
```

```
description = "Deep purples blanket / wrap. It is gorgeous" &amp; _
"in newborn photography. " &amp; _
"layer" &amp; _
"beneath the baby.....the possibilities are endless!" &amp; _
"You will get this prop! " &amp; _
"Gorgeous images using Lavender as a basket filler " &amp; _
"Photo by Benbrook, TX" &amp; _
"Imaging, Ontario" &amp; _
"http://www.photo.com?t=3" &amp; _
" www.photo.com" &amp; _
" http://photo.com" &amp; _
" https://photo.com" &amp; _
" http://www.photo.nl?t=1&amp;url=5" &amp; _
"Photography Cameron, NC" &amp; _
"Thank you so much ladies!!" &amp; _
"The flower halos has beautiful items!" &amp; _
"http://www.enchanting.etsy.com" &amp; _
"LIKE me on FACEBOOK for coupon codes, and to see my full product line!" &amp; _
"http://www.facebook.com/byme"
</code></pre>
```

<p>What I have now:</p>

```
<pre><code>description = Regex.Replace(description, _
    "((http|https|ftp)\:\/\/[a-zA-Z0-9\-\.]+(\.[a-zA-Z]{2,3})?(:[a-zA-Z0-9]*)?\/?([
</code></pre>
```

according to the documentation, the <https://developer.bigcommerce.com>

```
<pre><code>{
  "tracking_number": "EJ958083578US",
  "comments": "Ready to go...",
  "order_address_id": 1,
  "items": [
    {
      "order_product_id": 15,
      "quantity": 2
    }
  ]
}
```

In our business, a shipment almost invariably contains ALL items from the relevant order.

That being the case, is there a way to create a shipment without listing all items?

We are simply wishing to automate the process of <https://support.bigcommerce.com>

32448359

Bigcommerce API - Create Shipment - Include Items

<p>I'm finding that when I update an order with the BigCommerce API that the Proc

<p>I am placing the update call as documented here: <a href="https://developer.bi

<p>The update is successful but my original product is now two product lines.
It appears as though BC is interpreting what I am sending as new Product lines and r

<p>I am passing the 'id' for the orderProducts.</p>

<p>Is there something I need to pass to indicate the line items are to be updated an

<p>Here is the JSON I am sending:</p>

```
<p><div class="snippet" data-lang="js" data-hide="false">
<div class="snippet-code">
<pre class="snippet-code-js lang-js prettyprint-override"><code>{
  "customer_id": 1,
  "date_created": "Mon, 14 Sep 2015 19:28:01 +0000",
  "status_id": 11,
  "base_shipping_cost": "0.0000",
  "shipping_cost_ex_tax": "0.0000",
  "shipping_cost_inc_tax": "0.0000",
  "base_handling_cost": "0.0000",
  "handling_cost_ex_tax": "0.0000",
  "handling_cost_inc_tax": "0.0000",
  "base_wrapping_cost": "0.0000",
  "wrapping_cost_ex_tax": "0.0000",
  "wrapping_cost_inc_tax": "0.0000",
  "total_ex_tax": "34.0000",
  "total_inc_tax": "34.0000",
  "items_total": 16,
  "items_shipped": 0,
  "payment_method": "Manual",
  "refunded_amount": "0.0000",
  "order_is_digital": "false",
  "ip_address": "64.231.103.57",
  "geoip_country": "Canada",
  "geoip_country_iso2": "CA",
  "discount_amount": "0.0000",
  "ebay_order_id": 0,
  "billing_address": {
    "first_name": "Charles",
    "last_name": "Delfe"
```

<p>I'm running a report that gives me the total of sales for a product line represent

<p>So a report looking at the combined totals of product line A and product line B v

<p>I can't just simply title the report "Product Line A" and "Product Line B")
I tried placing product_line_value in the page header or as a group header but this c

<p>Also, I need to print and file each report. So if I have a month where no sales occ

<p>Is there a way to set up the report so that both product lines appear at the top c

<p>So what I'm getting is:</p>

<p>Page 1 Header: Product A
Page 1: Product A</p>

<p>Page 2 Header: Product B
Page 2: Product B</p>

<p>Page 3 Header: Product B
Page 3: Product A and B totals</p>

<p>What I want is the page header to be:</p>

<p>Page 1 Header: Product A + Product B
Page 1: Product A</p>

<p>Page 2 Header: Product A + Product B
Page 2: Product B</p>

<p>Page 3 Header: Product A + Product B
Page 3: Product A and B totals</p>

<p>Thanks</p>

33022829

How to present info on two versions of the s:

<p>I've been handed a problematic Access 2007 data base solution. The problem to

<p>There are approximately 100 users globally with three or four writers, the rest b

<p>To solve the issues, I'm proposing to do the following based on research to date.

<p>1) Create a split data base thereby isolating the front end user interfaces from th

<p>2) Create two front end interphase databases connecting to the backend. One i

<p>3) For the readers, I'll be adding the following code to each form's <code>Form_

```
<pre><code> Me.AllowEdits = False
    Me.DataEntry = False
    Me.RecordLocks = 0 ' No Locks
</code></pre>
```

<p>This seems to work (in the limited testing that I can perform) in that it allows the

<p>4) For the writers the following to the same <code>On-Load</code> event:</p>

```
<pre><code> Me.AllowEdits = False
    Me.DataEntry = True
    Me.RecordLocks = 2 ' Edited Record
</code></pre>
```

<p>This works in preventing writers from saving changes to the form but allows edit

<p>5) I'm going to move all the records from the three data bases into one as the o

<p>So far so good I'm thinking.</p>

<p>The next plan is to place the data base (Front and Back) on SharePoint. However

<p>A) Will SharePoint's own permission levels interfere with those set internally in t

<p>B) Why can't I place the two instances of the Front Ends that multiple users can

<p>Lastly, if the SharePoint thing is a non-starter for any reason, I can use a shared

<p>Any thoughts would be appreciated. Thanks</p>

<p>first thanks to all for all i learned here.</p>

<p>this is my input csv :</p>

```
<pre><code>TYPEμREFμCOLORμ
PRODUCTμ354μblueμ
MODELμ354μμ
MODELμ354μμ
PRODUCTμ253μgreenμ
MODELμ253μμ
MODELμ253μμ
</code></pre>
```

<p>the separator is {FS="μ";OFS="μ"}</p>

<p>what i have :</p>

- each PRODUCT line contain a value in COLOR column.
- each MODEL line contain a empty COLOR column.

<p>What i want :</p>

- i want to copy Color string from each PRODUCT line in color string of each MODEL line.
- (REF is the Sync KEY linking PRODUCT and MODEL.)

<p>Result i want :</p>

```
<pre><code>TYPEμREFμCOLORμ
PRODUCTμ354μblueμ
MODELμ354μblueμ
MODELμ354μblueμ
PRODUCTμ253μgreenμ
MODELμ253μgreenμ
MODELμ253μgreenμ
</code></pre>
```

<p>I hope i was clear....</p>

<p>i tried to work with if and -v a long time. </p>

<p>I am not a QWEB specialist and I try to change the standard purchase order by a

<p>Can somebody help me?</p>

<p>Thanks in advance</p>

<p>L. Adam</p>

33362656

ODOO8 - Add a line containing the product lc

<p>I have the following tree: </p>

```
<pre><code> library (data.tree)
  data (acme)
  t1<!--acme
  &gt; acme
      levelName
1 Acme Inc.
2 |--Accounting
3 | |--New Software
4 | | °--New Accounting Standards
5 | |--Research
6 | | |--New Product Line
7 | | °--New Labs
8 | °--IT
9 | |--Outsource
10 | |--Go agile
11 | °--Switch to R
</code></pre>
```

<p>I would like to enumerate the tree nodes name by adding the number of line to

```
<pre><code>&gt; t1
      levelName
1 Acme Inc._1
2 |--Accounting_2
3 | |--New Software_3
4 | | °--New Accounting Standards_4
5 |--Research_5
6 | | |--New Product Line_6
7 | | °--New Labs_7
8 | °--IT_8
9 | |--Outsource_9
10 | |--Go agile_10
11 | °--Switch to R_11
</code></pre>
```

33460954

Adding numbers to each node in data.tree

<p>I would like to replace the <code>,</code> with <code>.</code> in some Keys li

<p>Given this array:</p>

```
<pre><code>Array
(
    [0] => Array
        (
            [Product line] => Misc
            [Seller] => aaa.com
            [Tracking ID] => bbbb
            [Date shipped] => October 23, 2015
            [Price] => 60,43
            [Referral fee rate] => 3,00%
            [Quantity] => 2
            [Revenue] => 120,86
            [Earnings] => 3,62
            [Sub Tag] => xxxx
        )

    [1] => Array
        (
            [Product line] => Misc
            [Seller] => aaaa.com
            [Tracking ID] => bbbb
            [Date shipped] => October 23, 2015
            [Price] => 9,34
            [Referral fee rate] => 6,96%
            [Quantity] => 1
            [Revenue] => 9,34
            [Earnings] => 0,65
            [Sub Tag] => xxxx
        )
)
</code></pre>
```

<p>And the following function:</p>

```
<pre><code>function str_replace_specific_value($sSearch, $sReplace, &amp;$aSub
foreach($aSubject as $sKey => $uknValue) {
    if(is_array($uknValue)) {
        foreach($sKey as $fKey => $fuknValue) {
            $uknValue['Price'] = str_replace($sSearch, $sReplace, $fuknValue);
        }
    }
}</pre>
```

<p>I am trying to write a macro to copy a range of data from different parts of a wo

```
<pre><code>Dim wb As Workbook
Dim ws As Worksheet
Dim Rng As Range

'create new worksheet, name it "Budget"
Set ws = Sheets.Add
ws.Name = "Budget"
'set column titles in the new sheet
Range("A1").Value = "Period"
Range("B1").Value = "Country"
Range("C1").Value = "Product Line"
Range("D1").Value = "Currency"
Range("E1").Value = "Sales"
'search the entire UsedRange of sheet
For Each ws In ActiveWorkbook.Worksheets
If ws.Name <& "Summary" And ws.Name <& "Template" And ws.Name &
With ws.UsedRange
    Set Rng = .Find(What:="Product Line", _
        After:=.Cells(.Cells.Count), _
        LookIn:=xlValues, _
        LookAt:=xlWhole, _
        SearchOrder:=xlByRows, _
        SearchDirection:=xlNext, _
        MatchCase:=False).Offset(1, 0).Resize(33)
    Sheets("Budget").[F1].End(xlDown).Offset(0, -3).End(xlUp).Offset(1, 0).Resize(R
    Set Rng = .Find(What:="201601", _
        After:=.Cells(.Cells.Count), _
        LookIn:=xlValues, _
        LookAt:=xlWhole, _
        SearchOrder:=xlByRows, _
        SearchDirection:=xlNext, _
        MatchCase:=False).Offset(1, 0).Resize(33)
    Sheets("Budget").[F1].End(xlDown).Offset(0, -1).End(xlUp).Offset(1, 0).Resize(R

End With
End If
Next ws

End Sub
</code></pre>
```

<p>I'm building a filter page, with facets etc, which works as it should.
Now the our customer has a request to, basically "Be able to decide which sorting t
Each product is decorated with a Product Display Order, and is in a Product Line.</p>

<p>We got these example Product Display Orders:
1. Featured Item
2. Core Item
3. Spare Part
4. Utility</p>

<p>And these Product Lines:
1. Hammers
2. Saw
3. Wood</p>

<p>and the sorting is like this:
Sorting should firstly be based on Product Display Orders, secondly by product lines,
So all products which is a Featured Item is listed first, and all thes

<p>The challenge is: I can't just get the sorting of Product Display order items and p

<p>We've thought of Boosting based on if the product are in the different categorie

<p>OR</p>

<p>See if it possible to have some logic in the Sorting.
Sort by productDisplayOrder:
1. featured, 2. core Item ...
Then by ProductLines:
1. Hammers, 2. Saw ...
Then by Name DESC.</p>

<p>Which way is the best way to have this sorting, is it possible to give this logic to e

<p>Hopefully this makes sense for you.
Thanks in advance! :)</p>

<p>I am trying to handle some woocommerce order data into a separate database.

```
<pre><code>add_action( 'woocommerce_payment_complete', 'handle_order_comple
function handle_order_completed( $order_id ){
    $order = wc_get_order( $order_id );
    $name = $order-&gt;billing_first_name . " " . $order-&gt;billing_last_name;
    $billingEmail = $order-&gt;billing_email;
    $billingPhone = $order-&gt;billing_phone;
    $orderlink = $order-&gt;get_view_order_url();
    $products = $order-&gt;get_items();
    $orderMeta = get_post_meta($order_id, 'pass_type');

    foreach($products as $prod){
        $sql_insert = &lt;&lt;&lt;&lt;SQL
            INSERT INTO cards (cardnumber, name, phone, type, sku)
            VALUES ("{$cardnumber}", "{$name}", "{$billingPhone}", "{$type}", "{$prod['product_id']}"
        SQL;
        $prod['product_id'];
    }
}</code></pre>
```

<p>I need to know what the array keys for the <code>\$order->get_items()</code>

33851026

how to process a order items array in wordp

<p>Here is the relevant code: </p>

```
<pre><code>'hides all Location, Account, Product Line, or Sum of Total rows in colu
For Each c In r
    If c.Text = "Location" Or c.Text = "Account" Or c.Text = "Product Line" Or _
        c.Text = "Sum of Total" Then
        c.EntireRow.Hidden = True
    End If
Next c
</code></pre>
```

<p>The issue is that it is hiding most of the columns with those names in column A,

<p>What could be causing this? </p>

<p>I can post the full code that I'm using if required, but for some reason it's just no

<p>Edit: more of the code</p>

```
<pre><code>Set r = Range("a1:a1000")
```

```
'hides all rows with no value
```

```
For Each c In r
    If Len(c.Text) = 0 Then
        c.EntireRow.Hidden = True
    Else
        c.EntireRow.Hidden = False
    End If
Next c
```

```
'unhides all the rows below each grand total row
```

```
For Each c In r
    If c.Text = "Grand Total" Then
        c.Offset(1).EntireRow.Hidden = False
    End If
```

```
Next c
```

```
'unhides all rows below a row with a value
```

```
For Each c In r
    If Len(c.Text) > 0 Then
        c.Offset(1).EntireRow.Hidden = False
    End If
```


<p>Basically in their shopping cart I would like to display the image they upload to p

<pre><code> {% comment %}

This is your /cart template. If you are using the Ajaxify Cart plugin,
your form (with action="/cart") layout will be used in the drawer/modal.

For info on test orders:

- General <http://docs.shopify.com/manual/your-store/orders/test-orders>
- Shopify Payments - <http://docs.shopify.com/manual/more/shopify-payments>,

<!-- Bold: Options 4-1 -->
<script>function update_qty_builder(builder_id, qty){ jQuery('.'+builder_id+
{% include 'bold-cart-handler' %}
<!-- // end Options 4-1 -->

{% endcomment %}
{% if cart.item_count > 0 %}

<form action="/cart" method="post" novalidate class="cart">

<div class="section-header">
<h1 class="section-header__title">{{ 'cart.general.title' | t }}</h1>
</div>

<div class="cart__row medium-down--hide cart__header-labels">
<div class="grid--full">
<div class="grid__item large--one-half push--large--one-half">
<div class="grid--full">
<div class="grid__item one-third medium-down--one-third">
{{ 'cart.label.price' | t }}
</div>
<div class="grid__item one-third medium-down--one-third text-center">
{{ 'cart.label.quantity' | t }}
</div>
<div class="grid__item one-third medium-down--one-third text-right">
{{ 'cart.label.total' | t }}
</div>
</div>
</div>
</div>
</div>

<p>Just cant seem to get magmi to import/work correctly.
My CSV test file is only 27 lines including the header. </p>

<p>My header is as follows:</p>

```
<pre><code>store, type_id, status, visibility, manage_stock, attribute_set, tax_class  
</code></pre>
```

<p>Example of the data:</p>

```
<pre><code>admin, simple, Enabled, 4, 1, Default, Taxable Goods, 0.25, 400100433  
</code></pre>
```

<p>Within Magento I added vendor,product_id, and upc as attributes and assigned

<p>When I do the import it
creates the very first item/product. (though where does one see custom attributes ?
It does not create any of the Categories/sub categories. Including for the 1 product i
It creates an empty attribute per product line (IE 26)
No Yes No Global No No No (Magento Manage Attrib section)</p>

<p>Within magmi (0.7.2.2) I have set:
Attribute Set Importer
Import Report Mail Notifier
Magmi Optimizer
On the fly category creator/importer
Image attributes processor
On the fly indexer
Magento 1.9.2.2</p>

<p>Update - 1-20-16</p>

<p>So far to get magneto Check Data to not error
I have changed type to _type, status from enabled to 1, tax_class_id from Taxable G

<p>So on the magmi import
It still errors out. Creating 26 blank attributes. (reload from backup to clear) I assum
Reading it says "user-defined product attributes which magmi will import natively u
That is all the attributes my test import has.
I am not creating new attribute_sets/groups (yet)
So what is it that I am missing?</p>

<p>Anyone want to help me out? Please. </p>

<p>Here is my test bunny sheet: <a href="https://docs.google.com/spreadsheets/d,

<p>What I am trying to accomplish:</p>

User inputs sales order on the 'salesOrder' Sheet

<p>User submits sales order</p>

<p>a) sales order info is written to 'OrderKey' Sheet

b) the header info (Date, Company, Purchase Order, Sales Order, Contact, email, ph

<p>Having troubles figuring out how to go about doing this.</p>

<p>I have now created a 'kludge' sheet to formulaically copy over live information fi

<p>I named it kludge because It is not an elegant way of solving my problem, and no

<p>At any rate, the 'kludge' method is not working due to appending NULL DATA... :

```
<pre><code>function onOpen() {  
  var ui = SpreadsheetApp.getUi();  
  // Or DocumentApp or FormApp.  
  ui.createMenu('Custom Menu')  
    .addItem('Submit Sales Order', 'menuItem1')  
    .addToUi();  
}
```

```
function menuItem1() {  
  var ss = SpreadsheetApp.getActive();  
  var sheet = ss.getSheetByName("kludge");  
  var sourceInfo = sheet.getRange("A:N65");  
  var targetInfo = ss.getSheetByName("OrderKey");  
  var values = sourceInfo.getValues();  
  targetInfo.appendRow(values[0]);
```

```
  
  sheet.getRange('B4:B5').clearContent();  
  sheet.getRange('B8').clearContent();  
  sheet.getRange('G6:G8').clearContent();  
  sheet.getRange('F10:G10').clearContent();  
  sheet.getRange('A13:B76').clearContent();  
  sheet.getRange('J13:J76').clearContent();  
  var cell = activeSheet.getRange("I1");
```

<p>This is the scenario:</p>

One table with 5 rows.

Row 1 - displays total purchase.

Row 2 - displays total Fruits purchase.

Row 3 - displays total Vegetables purchase.

Row 4 - Is a fruits table with n fruits, generated dynamically with php.

Row 5 - Is a vegetable table with n vegetable, generated dynamically with php.

<p>As you can see in the fiddle link, the user must choose the quantity of a specific

<p>I could do this using jquery, but I would like to accomplish this task using Angula

<p>I've started to code. But so far I have one issue. It dipslays <code>\$NaN</code>

So, how to avoid display this <code>\$NaN</code> when there is nothing inside (

How to link the 3 totals fields to each individual products group?

<p>Note. The approach I have used is not the best one. Feel free to change the app

Any suggestion? JSFIDDL

<pre><code><table style='width:100% ;border: 2px solid #00BABF;' ng-app=''>

<tr>

<td>Total: \$</td>

</tr>

<tr>

<td>Fruit: \$</td>

</tr>

<tr>

<td>Veget: \$</td>

</tr>

<tr id='fruits'>

<td>

<table id='tbl_fruits' style='width:100% ;border: 2px solid red;'>

<tr>

<p>I created a list of sales in the frontend pros "resellers" can refer to. It turns out t

<p>So I need to get the products by Product Line and then check ID</p>

<p>Anyone know how to "filter" by product and "line" purchase? Or someone remo

<p>Code.</p>

```
<pre><code>    &lt;div class="page-title"&gt;
&lt;h1&gt;&lt;?php echo $this-&gt;__('Meus Eventos') ?&gt;&lt;/h1&gt;
&lt;/div&gt;
    &lt;?php echo $this-&gt;getMessagesBlock()-&gt;getGroupedHtml() ?&gt;
    &lt;!--&lt;iframe width='100%' height='700' frameborder='0' src='http://storage.
```

<?php

```
$i = 0;
Mage::getSingleton("core/session", array("name" =&gt; "frontend"));
$session = Mage::getSingleton("customer/session");
if($session-&gt;isLoggedIn())
{
    $customer = Mage::getSingleton('customer/session')-&gt;getCustomer();
    $nome = $customer-&gt;getEmail();
}
?&gt;
```

<?php

```
$collection = Mage::getModel('catalog/product')
-&gt;getCollection()
-&gt;addAttributeToFilter('email_parceiro', $nome)
-&gt;addAttributeToSelect('*');
$parceiro = false;
$i = "0";
$stable = "0";
foreach ($collection as $product) {
    $parceiro = true; //se parceiro tem evento já vendido
    $i++;
    if ($i === 1) {
        echo "&lt;p&gt;Clique nos nomes dos eventos abaixo para mais detalhes&lt;/p&gt;";
    }
}
```

```
$mailparceiro = $product['email_parceiro']; //resgata o e-mail do parceiro no produ
```

```
$id = $product-&gt;getId(); //resgata o ID do produto
```

<p>I am developing a very simple shopping cart where each of the items (courts) in

<p>Here is the product line in the store</p>

```
<pre><code>&lt;div id="courtline" class="courtline&lt;?php echo $row_Courts['syst
&lt;a href="#" func="add" stateName="&lt;?php echo $_SESSION['state'];?&gt;" sys
&lt;/div&gt;
</code></pre>
```

<p>And here is my jQuery. It makes 3 AJAX calls... </p>

```
<ol>
<li>Update the database by adding or removing a product from the shopping cart...
<li>Update the product list by changing the button to a + or x depending on whethe
<li>update a totals div in the cart.</li>
</ol>
```

<p>.</p>

```
<pre><code>$( "#courtline" ).on( "click", "a", function( e ) {
    e.preventDefault();
    var func = $(this).attr("func");
    var stateName = $(this).attr("stateName");
    var courtID = $(this).attr("systemID");
    var userID = $(this).attr("userID");
    var courtSystemID = $(this).attr("courtSystemID");
    var stateID = $(this).attr("systemID");

    // update the court list in the cart
    $.ajax({

        type: "GET",
        url: "http://subscribe.docketlaw.com/ajaxphp/modifyCourt.php",
        data: "user= " + userID + "&amp; court= " + courtID + "&amp; courtsystem= " +
        timeout: 6000,
        success: function (data)
        {
            $(document).ready(
                function() {
                    courtList = data;

                    $('div.cartcourtlist').html(courtList);
                }
            );
            // now update the Court Line
        }
    });
}</pre>
```

<p>I am using the Magento Ultimo theme. I have created a custom block in local.xml

```
<pre><code>&lt;action method="addTab" translate="title" module="catalog"&gt;
    &lt;alias&gt;basic_line&lt;/alias&gt;
    &lt;title&gt;Basic Line Info&lt;/title&gt;
    &lt;block&gt;catalog/product_view_attributes&lt;/block&gt;
    &lt;template&gt;catalog/product/view/basic_line.phtml&lt;/template&gt;
&lt;/action&gt;
</code></pre>
```

<p>I've also created the appropriate basic_line.phtml file, which contains:</p>

```
<pre><code>&lt;?php
if (Mage::getModel('catalog/product')-&gt;load(Mage::registry('current_product')-&
?&gt;
&lt;div class="basic-line-info"&gt;
&lt;?php
echo $this-&gt;getLayout()-&gt;createBlock('cms/block')-&gt;setBlockId('block-ba
?&gt;
&lt;/div&gt;
&lt;?php
}
</code></pre>
```

<p>?></p>

<p>I have an attribute called basic_line, if it is set to yes the div will show. If it is set
The tab should only be displayed if the attribute is set to yes - however, at the mom

<p>Do you have any ideas?</p>

<p>I am pretty new to https so if say something inaccurate I am sorry.
I have running php server that was rewritten in java and now I need to test if it was

<p>Problem is there seems to be very little on this topic and after intensive googling

<p>Web server is https with client autorization and I am using mySQL database</p>

<p>Do you have any experenice with any of these technologies or any advice how sl

36652595

Testing correctnes of rewritten server from p

<p>I am having the hardest time programmatically creating an order in WooComme

<p>The issue seems to be that once the order object is created, it is failing when try

```
<pre><code>function create_vip_order() {

    global $woocommerce;

    $address = array(
        'first_name' => '111Joe',
        'last_name'  => 'Conlin',
        'company'    => 'Speed Society',
        'email'      => 'joe@testing.com',
        'phone'      => '760-555-1212',
        'address_1'  => '123 Main st.',
        'address_2'  => '104',
        'city'       => 'San Diego',
        'state'      => 'Ca',
        'postcode'   => '92121',
        'country'    => 'US'
    );

    // Now we create the order
    $order = wc_create_order();

    // The add_product() function below is located in /plugins/woocommerce/includes
    $order->add_product( get_product( '275962' ), 1 ); // This is an existing SIMPLE
    $order->set_address( $address, 'billing' );
    //
    $order->calculate_totals();
    $order->update_status("Completed", 'Imported order', TRUE);

}

add_action( 'woocommerce_init', 'create_vip_order' );
</code></pre>
```

<p>Here is the error I am getting in my logs:</p>

```
<pre><code>[19-Apr-2016 21:16:38 UTC] PHP Fatal error: Uncaught Error: Call to a
Stack trace:
#0 /Users/joe/Sites/speedsociety-2/wp-includes/plugin.php(525): create_vip_order
#1 /Users/joe/Sites/speedsociety-2/wp-content/plugins/woocommerce/woocomm
```

<p>I have two models related like this:</p>

```
<pre><code>class Report(Model):
    ...
    product_line = models.OneToOneField(ProductLine)

class ProductLine(Model):
    name = models.CharField()
    ...
</code></pre>
```

<p>I want users to upload a report and specify which product line it belongs to. The

<p>My question is how to render this field and how to analysis the value posted bac

<h2>Rendering</h2>

<p>For rendering, I guess I can do this:</p>

```
<pre><code>render():
    allProducts = ProductLine.objects.all() // side question: how to cache this queryse
    names = []
    for p in allProducts:
        names.push(p.name)
    return render(..., {'names': names})
</code></pre>
```

<p>Inside the template, I can loop over <code>names</code> and populate the iter

<h2>Saving</h2>

<p>When saving:</p>

```
<pre><code>postHandler():
    // This is the part I am not so sure
    // Since the value for the product line field will be a string
    // I guess I cannot rely on a form object to validate it and expect
    // it to pass, am I correct?
    // so when I create a form out of ProductLine, I should use
    // a customized validator instead:
```

```
class ReportForm(Form):
    class Meta:
```

<p>Same product showing up twice on invoice. I grouped the report by invoice num

<p>I have a formula that supplies the shipping qty @qtyshipped. </p>

<p>I have this formula in set up in a running total #tlt_QtyShipped so I can combine

<p>This running total is placed in a group footer. In this same group footer I have a t

<p>I'm trying to use the running total #tlt_QtyShipped * Base Price in this formula. </p>

<p>When trying to run I get the following error:</p>

<p>A running total can not refer to a print time formula.

Details: @BaseRecycle. </p>

<p>I know there is an issue with the running total being used in a formula but don't

36996555

Crystal Syntax Reference A Formula That Cou

<p>I have a problem when i View my html page in PDF-form. The problem is that w

<p>Here is an example of the hmtl page, it works perfect

enter image descripi

<p>Then when i convert it to a PDF it looks like this:

enter image descriptio

<p>Here i Render my page to a full html document:</p>

```
<pre><code>def document_to_html_document(document):
```

```
    """
```

```
    Renders the invoice to a full html document with &lt;html>, &lt;head>, and &
```

```
    """
```

```
    return render_to_string('invoice_print.html', {
```

```
        'body': document_to_html(document),
```

```
        'document': document,
```

```
        'base_url': settings.SITE_BASE_URL
```

```
    })
```

```
</code></pre>
```

<p>The code where i build the HTML string and converting it to a pdf:</p>

```
<pre><code>def document_to_pdf(document, server_base_url, target=None):
```

```
    # Build HTML string
```

```
    html = document_to_html_document(document)
```

```
    # Setup input and output files
```

```
    html_file = tempfile.NamedTemporaryFile(suffix='.html')
```

```
    html_file.write(document_to_html_document(document).encode())
```

```
    target = target or tempfile.NamedTemporaryFile()
```

```
    # Convert to pdf
```

```
    command = 'xvfb-run wkhtmltopdf --footer-right "[page]/[topage]" {s} {o}'.format
```

```
    s=html_file.name,
```

```
    o=target.name
```

```
)
```

```
    s = subprocess.Popen(command, shell=True)
```

```
    s.communicate()
```

```
    # Return pdf bytes
```

```
    target.seek(0)
```

```
    return target.read()
```

I am working with an ERP that stores its retail sales and any discounts related to

Product lines are identified by a line type of 0 whereas discount lines are a line t

Unfortunately, the discount records do not have any direct relation back to the p

I need to extract this data and for the discount lines, provide the key for the pro

Discount Lines (6 and 7) ALWAYS come up after 0 LineType and can be identifiec

[http://sqlfiddle.com/;](http://sqlfiddle.com/#!3/80249)

I need my results to look like this:

```
Id      LineType  SequenceNumber  Description      ProductLineId
-----
1  0      1             Product A      NULL
2  6      2             Discount on Product A  1
3  7      3             Loyalty Discount    1
4  0      4             Product B      NULL
5  0      5             Product C      NULL
6  6      6             Discount on Product C  5
```

I know I can use a LAG function, however the offset is not knowr

```
OPEN SalesLines
FETCH NEXT FROM SalesLines INTO @SourceKey, @HeaderSourceKey, @IsMarkedD
```

```
WHILE @@FETCH_STATUS = 0
BEGIN
    IF @RetailLineTypeId = 1 OR @CurrentHeaderSourceKey != @HeaderSourceKey
    BEGIN
        SET @CurrentIsMarkedDownFlag = @IsMarkedDownFlag
        SET @CurrentHeaderSourceKey = @HeaderSourceKey
    END
    ELSE
    BEGIN
        IF @CurrentIsMarkedDownFlag != @IsMarkedDownFlag
        BEGIN
            UPDATE @RawData
            SET IsMarkedDown = @CurrentIsMarkedDownFlag
            WHERE SourceKey = @SourceKey
```

The Problem:

I'm in the process of redoing the make system in our legacy project, changing from

We'd like to break it apart, and CMake's find_package "module mode" seems to

That said, this chunk of code uses Boost's shared pointer in the API, and while di

So ... how does one go about ensuring that versions of common dependencies n

Additional Information:

We're using CMake 3.5.1, but we can upgrade to 3.5.2 if that would make a diff

37486472

Can CMake find_package be "common depe

<p>I have a data set which contains customer name and product list given below:</p>

```
<pre><code>Customer Name  Product Line(L2)
IBM          Linux
IBM          AM-Q
IBM          Linux
Tikona       RHEX
Tikona       BRP
Tikona       RHEX
Tikona       BRP
ICC          AM-Q
ICC          Linux
ICC          AM-Q
ICC          Linux
DataCops     BRP
DataCops     RHEX
DataCops     Linux
DataCops     AM-Q
DCOM         Linux
DCOM         RHEX
DCOM         BRP
DCOM         Linux
</code></pre>
```

<p>I want to convert them in two different data frames:</p>

Data frame contains all the unique product list, which I have done using the code


```
<pre><code>import pandas as pd
import numpy as np
Product_Line = 'Product Line (L2)'
read_xlsx = pd.ExcelFile('C:\Python\TEP_Analysis\TEP_Dataset.xlsx')
df = read_xlsx.parse('Sheet1')
unique_list = np.unique(df[Product_Line])
print(unique_list)
</code></pre>
```

<ol start="2">

Second data frame contains the unique list of products a customer has purchased

<p>Apologize in advance if this has been answered already as I couldn't find what I'

<p>I would like to have a table of part numbers with attributes such that I can join a

```
<pre><code>ABC, OD, 10.125
ABC, ID, 8.125
ABC, WIDTH, 6.500
XYZ, COLOR, Blue
XYZ, LENGTH, 16.375
</code></pre>
```

<p>No problem there. What I want to do next is pivot the records so that I can creat

<p>For pivoted table fields PN, OD, ID, and WIDTH the data would look like this:</p>

```
<pre><code>ABC, 10.125, 8.125, 6.500
</code></pre>
```

<p>I've seen many examples of using PIVOT but they generally hard code the fields

<p>Thanks in advance for any help...</p>

37592646

Dynamic pivot table needed?

<p>I'm using jQuery DataTables. Recently the client added a product line that has lo

```
<pre><code>oTable.row.add(["Quantity &amp; Model", "(1) PPJN 565.058A/4i
</code></pre>
```

<p>This renders:</p>

```
<pre><code>&lt;tr role="row" class="even"&gt;
  &lt;td&gt;Quantity &amp; Model&lt;/td&gt;
  &lt;td&gt;(1) PPJN 565.058A/4FA-J33L/42P.M&lt;/td&gt;
  &lt;td&gt;&lt;/td&gt;
&lt;/tr&gt;
</code></pre>
```

<p>I would like to accomplish something like the following to take advantage of the

```
<pre><code>&lt;tr role="row" class="even"&gt;
  &lt;td&gt;Quantity &amp; Model&lt;/td&gt;
  &lt;td colspan="2"&gt;(1) PPJN 565.058A/4FA-J33L/42P.M&lt;/td&gt;
  &lt;td style="display:none;"&gt;&lt;/td&gt;
&lt;/tr&gt;
</code></pre>
```

<p>Maybe there's a way of eliminating the last column all together.</p>

<p>How can I make this happen? This table is not used for sorting or anything like tl

<p>Being new user I managed to make a spider can romper e- commerce site and e:
Title and variations of each product and the output CSV file and a product line but w
This is a variation by line, please can someone help me move forward in my project.

<p>I'm looking forward to come to the question but unfortunately I can not find an

<p>my spider:</p>

```
<pre><code>import scrapy
from w3lib.html import remove_tags
from products_crawler.items import ProductItem
```

```
class DemostoreSpider(scrapy.Spider):
    name = "demostore"
    allowed_domains = ["adns-grossiste.fr"]
    start_urls = [
        'http://adns-grossiste.fr/17-produits-recommandes',
    ]
    download_delay = 0.5

    def parse(self, response):
        for category_url in response.css('#categories_block_left &gt; div &gt; ul &gt; li ::a'):
            yield scrapy.Request(category_url, callback=self.parse_category, meta={'page_1': 1})

    def parse_category(self, response):
        for product_url in response.css('#center_column &gt; ul &gt; li &gt; div &gt; div.ri'):
            yield scrapy.Request(product_url, callback=self.parse_product)

    def parse_product(self, response):
        item = ProductItem()
        item['url'] = response.url
        item['title'] = response.css('#center_column &gt; div &gt; div.primary_block.clea').text
        item['Déclinaisons'] = remove_tags(response.css('#d_c_1852 &gt; tbody &gt; tr.c')).text
        yield item
</code></pre>
```

<p>sample CSV wish to:

image CSV</p>

<p>I'm a novice in VBScript and XML coding.However, getting my head around and i

<p>I want to read/parse an xml file using VBScript,my XML file is not data but xml sc

<p>Below is the code snippet that I'm using -</p>

```
<pre><code>Sub LoadXMLFile()

Dim objXML    'for xml document
Dim objNode   'for xml node item
Dim i As Integer
i = 0

Set objXML = CreateObject("Microsoft.XMLDOM")
objXML.Load ("C:\path\test.xml")
objXML.setProperty "SelectionLanguage", "XPath"
Set objNode = objXML.SelectNodes("/report/queries/query/selection/dataltem/tex
'MsgBox objNode.Text

For i = 0 To (objNode.Length - 1)
NodeVal = objNode(i).NodeValue
MsgBox NodeVal
Next

End Sub
</code></pre>
```

<p>When I step through the VB code the objNode.Length value always evaluates to

<p>Here is the xml that I'm trying to parse -</p>

```
<pre><code>&lt;report xmlns="http://developer.cognos.com/schemas/report/10.0
&lt;modelPath&gt;
/content/package[@name='GO Sales (query)']/model[@name='model']
&lt;/modelPath&gt;
&lt;drillBehavior/&gt;
&lt;queries&gt;
&lt;query name="Query1"&gt;
&lt;source&gt;
&lt;model/&gt;
&lt;/source&gt;
&lt;selection&gt;
&lt;dataltem aggregate="none" rollupAggregate="none" name="Product line"&gt;
```

<p>I have a method that currently exports the results of a stored procedure to a CSV

<p>The code:</p>

```
<pre><code>protected void ExportFundingSummaryToExcelSA(Object sender, EventArgs e)
{
    const string fileName = "METT Dashboard - Funding Summary";
    const string rowFormat = "{0},{1},{2},{3},{4},{5}\n";

    Response.Clear();
    Response.Buffer = true;
    Response.AddHeader("content-disposition", "attachment;filename=" + fileName);
    Response.Charset = "";
    Response.ContentType = "text/csv";

    GetCompanyGroupCode();

    var sb = new StringBuilder();
    sb.AppendFormat(rowFormat, "Sector", "Product Line", "Program Number", "Program Name", "Funding Amount");

    var customerId = CurrentUser.Company.Id;

    var year = 2015;

    // Set Title Row
    Response.Write(year + " Products Lines for: " + CurrentUser.Company.Name);

    // Set Generated Date (Report Created on: 9/29/2004 3:33:32 PM)
    Response.Write("Report Created on: " + System.DateTime.Now.ToString() + "\n");

    var fundingData = GetFundingData();

    if (fundingData != null)
    {
        if (fundingData.Summary != null && fundingData.Summary.Count > 0)
        {
            var summaries = MoveSetAsidesDown(fundingData.Summary);

            for (var i = 0; i < summaries.Count; i++)
            {
                if (fundingData.Programs != null && fundingData.Programs.Count > 0)
                {
                    foreach (var program in fundingData.Programs)
                    {
                        if (program.Id == summaries[i].ProgramId)
                        {
                            summaries[i].ProgramName = program.Name;
                            summaries[i].FundingAmount = program.FundingAmount;
                        }
                    }
                }
            }

            sb.Append(rowFormat, summaries[0].Sector, summaries[0].ProductLine, summaries[0].ProgramName, summaries[0].ProgramName, summaries[0].FundingAmount);
            for (var i = 1; i < summaries.Count; i++)
            {
                sb.Append(rowFormat, summaries[i].Sector, summaries[i].ProductLine, summaries[i].ProgramName, summaries[i].ProgramName, summaries[i].FundingAmount);
            }
        }
    }

    Response.Write(sb.ToString());
}</pre>
```

<p>The input is retrieve from text file. Which contain information of </p>

product ID

product Name

Product Quantity

<p>product Price</p>

<pre><code>1 RAYBAN 1 450.000000

900 KEYBOARD 100 290.000000

78 MINERALWATER 123 345.000000

2 RAYBAN 2 450.000000

</code></pre>

<p>After printing the output through command prompt. It was not align with the 1s

<p>Here is the output. </p>

<p><img

<p>Here is the full code. With <code>gotoxy</code> function. The display function

<pre><code>int displayProduct()

</code></pre>

<p>There is a line of code for table titles and also the printf from TXT File. </p>

<pre><code>#include <stdio.h>;

#include <stdlib.h>;

#include <windows.h>;

#include <ctype.h>;

void gotoxy(int column, int line);

int main();

int addProduct();

int displayProduct(); //prototype

struct product {

int quantity, reorder, i, id;

char name[20];

float price;

};

<p>I'm creating a simple Web Page wherein I want all the STATIC PARTS like NavBar

<p>So that everytime I create a new page, I just have to call it or link it in order to re

<p>I want to do something like this: </p>

<p><img :

<p>Here's my code:</p>

```
<pre><code>&lt;!DOCTYPE html&gt;
&lt;html&gt;
&lt;head&gt;
  &lt;meta charset="utf-8" /&gt;
  &lt;meta name="viewport" content="width=device-width, initial-scale=1.0"&gt;
  &lt;title&gt;HACMS&lt;/title&gt;
  &lt;link rel="stylesheet" type="text/css" href="css/bootstrap.css"&gt;
  &lt;link rel="stylesheet" type="text/css" href="css/Site.css"&gt;
  &lt;link rel="stylesheet" type="text/css" href="css/dashboard-navbar.css"&gt;
  &lt;link rel="stylesheet" type="text/css" href="css/footer-style.css"&gt;
  &lt;link rel="stylesheet" type="text/css" href="font-awesome/css/font-awesome.
  &lt;script type="text/javascript" src="js/jquery-1.10.2.min.js"&gt;&lt;/script&gt;
  &lt;script type="text/javascript" src="js/csi.min.js"&gt;&lt;/script&gt;
  &lt;script type="text/javascript" src="js/csi.js"&gt;&lt;/script&gt;
  &lt;script type="text/javascript" src="js/bootstrap.js"&gt;&lt;/script&gt;
  &lt;script&gt; $( "#includedContent" ).load("sampleFooter.html"); &lt;/script&gt;
```

```
&lt;/head&gt;
&lt;body&gt;
  &lt;h1&gt;THIS IS THE BODY&lt;/h1&gt;
  &lt;!-- THIS IS MY NAVBAR --&gt;
  &lt;nav class="navbar navbar-inverse navbar-fixed-top navbar-custom" role="n
  &lt;div class="container-fluid"&gt;
    &lt;div class="navbar-header"&gt;
      &lt;button type="button" class="navbar-toggle" data-toggle="collapse" c
      &lt;span class="sr-only"&gt;Toggle navigation&lt;/span&gt;
      &lt;span class="icon-bar"&gt;&lt;/span&gt;
      &lt;span class="icon-bar"&gt;&lt;/span&gt;
      &lt;span class="icon-bar"&gt;&lt;/span&gt;
    &lt;/button&gt;
    &lt;a class="navbar-brand" href="#"&gt;&lt;img src="css/images/SSILogc
  &lt;/div&gt;
  &lt;div class="collanpe navbar-collanpe navbar-ex1-collanpe"&gt;
```

<p>Please help me. I want to find all possible combinations of feature by considerin

<p>Feature Model:</p>

<p><img :
39249293

Software Product Line Feature Model

<p>I am trying to figure out if there is a way for the server to rewrite the contents o

```
<pre><code>// This is just an example of the type of if/else based on preferences  
if( !empty( $_POST( $user-&id, 'romance', true); {  
$product_id = 1300;  
} else {  
$product_id = 0031;  
</code></pre>
```

<p>The specifics of where the data is stored isn't as much of a concern as how a <cc

<p>WORKING EXAMPLE</p>

<p>I am using Woocommerce Subscriptions where customers get a weekly renewal

<p>I know how to display product based on queries, I just can figure out how to incl

<p>Can anyone help point me in the right direction?</p>

39299262

Can I preload product to Woocommerce Sub

<p>I am currently doing a project of spotting fractured or bad products from a strea

<h2>BAD</h2>

<p></p>

<h2>GOOD</h2>

<p></p>

<p>The Edges are quite clear but there are many small regions of meaningless spots

<p>Therefore, I am thinking if there is a way to extract the largest connected region

<p>Thanks a lot!!! </p>

39422585

Image Comparison Method and Noise deduc

<p>I am setting up a shopping feed within <a href="https://www.shopify.com" rel='

<p>I'm using the Amasty app to ;

<p>Because it is a SAAS package, it it hosted at Shopify. All Google info uses the <co

<p>This results in errors, because the URLs do not match. </p>

<p>I want to capture the URL and change it in every product line to use the <code>s

<p>How can I achieve that?</p>

39456619

XML feed change url's

<p>I have a table products that contains a snapshot of an entire product line at a cu

<p>So each day the entire product table is saved in this same table, with the timesta

```
<pre><code>product_id price inventory_count snapshot
1      22   23      20160915
1      22   20      20160916
</code></pre>
```

<p>I want to query this table, and list all products where the inventory_count chang

<p>How can I do this?</p>

<p>I'm not sure how I can inner join the table on itself using the snapshot somehow

39564389

How to perform a query to compare a table :

<p>I am working on a site built on wordpress, salient theme, using visual composer.

<p>The site is (sorry if it runs slow, on a server with hundreds of others!)</p>

<p>If you scroll down, you'll see the staff section,9 people each with a read more fu

<p>The problems are:</p>

when the user opens two or more blocks, and then hits one block's 'hide conten

Also, when opened, the text styles left-align (YAY!) but when closed, it does not

<p>I recommend to inspect the html using firebug (or something similar) as this was

<p>HTML and (each block is identical except for content) the footer funtion:</p>

<p><div class="snippet" data-lang="js" data-hide="false" data-console="true" data-l<div class="snippet-code">

<pre class="snippet-code-js lang-js prettyprint-override"><code>(function(\$) {

\$('.showcontent').click(function() {

\$(this).hide();

\$(this).parent().next('p').show();

\$(this).parent("p").css("text-align", "left");

}}

\$('.hidecontent').click(function() {

\$(this).parent().hide();

\$('.showcontent').show();

\$(this).parent("p").css("text-align", "center");

}}

})(jQuery);</code></pre>

<pre class="snippet-code-html lang-html prettyprint-override"><code><script src

<img title="Howard Rupert" src="http://kingkongco.com.au/c-cor/wp-content/u

<h4 class="light">Howard Rupert</h4>

<div class="position">account director</div>

<p class="description">Howard is a highly capable, deeply experienced technic

Read more...

</p>

<p class="cdscontainer">line which includes passive products such as coaxial c

in 2014 where he was Sales Director for North America and Oceania sales. Previou

product line management for Connectivity Equipment requirements. Howard start

With over 25 years of international technical sales experience Howard has been en

<p>I'm looking into expanding our product line by allowing dynamic images as a gra
I don't know if that makes any sense, but I was just wondering how ThingLink create

<p>Thanks!</p>

39967699

Generate interactive images on Facebook po

<p>Is there any way to control key (cursor) flow, like when you press tab on keyboa

39971344

Odoo 9 Keyboard controls over input fields (

<p>So far, I'm just trying to instantiate my kendo grid and passing through values from the "Type" parameter for public overridable overloads function grid(of T as a class) as a parameter.

<p>Html.Kendo().Grid().Name("kendogrid")</p>

<p>I'm not sure what this error means and I don't know how to go about fixing it.</p>

<p>View</p>

```
<pre><code>$(document).ready(function () {
    var dataSource = new kendo.data.DataSource({
        transport: {
            read: {
                url: "TestAjax",
                dataType: "json",
                type: "GET",
            },
            update: {
                url: "update",
                dataType: "json",
                type: "POST"
            },
            create: {
                url: "CreateInvoiceRecord",
                dataType: "json",
                type: "GET",
            },
            parameterMap: function (options, operation) {
                console.log(operation);
                console.log(options);
                if (operation !== "read" & & options.models) {
                    return { models: kendo.stringify(options.models) };
                }
            }
        },
        batch: true,
        pageSize: 20,
        schema: {
            model: {
                id: "itemID",
                fields: {
                    ItemName: { type: "string" },
                    Amount: { type: "number", editable: false, validation: { required: true } }
                }
            }
        }
    });
    $("#kendogrid").kendoGrid(dataSource);
}</pre>
```

<p>Situation: a part of the product line was upgraded/enhanced with new features,

<p>Problem: need to redirect old URLs to new URLs, but the new URLs contair

<p>Example:

<code>RewriteRule ^.*(PRODUCT-001).*\$ http://www.example.com/PRODUCT-001

<p>How can I specify that I want this exact string to match, and n

<p>E.g. "this rule should match PRODUCT-001 but not

40313688

.htaccess redirects - how to handle "nested"

<p>When I try to deploy my project, this exception happens:</p>

```
<pre><code>Grave: Undeployment failed for context /CRUD_Restful_Pub
Grave: Exception while loading the app : CDI deployment failure:WELD-001408: Un
at injection point [BackedAnnotatedParameter] Parameter 1 of [BackedAnnotated
at com.google.common.util.concurrent.ServiceManager.&lt;init>(ServiceManag
</code></pre>
```

<p>I am using Netbeans + Glassfish. Lib Jersey. All last versions.</p>

<p>I think it is a CDI problem, any annotation that I can't identify.
I really appreciate if someone could help me as soon as possible.
It is my first time here.</p>

<p>Here is my code:</p>

```
<pre><code>package br.unirio.soa.todo.resources;
```

```
import java.io.IOException;
import java.util.ArrayList;
import java.util.List;
```

```
import javax.servlet.http.HttpServletResponse;
import javax.ws.rs.Consumes;
import javax.ws.rs.FormParam;
import javax.ws.rs.GET;
import javax.ws.rs.POST;
import javax.ws.rs.Path;
import javax.ws.rs.PathParam;
import javax.ws.rs.Produces;
import javax.ws.rs.core.Context;
import javax.ws.rs.core.MediaType;
import javax.ws.rs.core.Request;
import javax.ws.rs.core.UriInfo;
```

```
import br.unirio.soa.todo.dao.PublicacaoDao;
import br.unirio.soa.todo.model.Publicacao;
```

```
// Will map the resource to the URL pubs
@Path("/pubs")
public class PubsResource {
```

```
// Allows to insert contextual objects into the class
```


<p>Alright so I use excel a lot because of its cross platform functionality and I'm fed

<p>I've been experimenting with this for about 2 weeks and I'm not happy with any

<p>I need to input several different reports into a spreadsheet. Except all of the rep

<p>If anyone has any ways of helping me out with this then I would be massively ap

40587716

Indexing and Calling Cell information in Excel

I have a spring boot (web) application that has an html, css, and JQuery/Javascript

<p>When the search button is clicked, I send an Ajax request to the server-side (A J

```
<pre><code>@Controller
@RequestMapping("/search")
public class IndexController {
    @RequestMapping(value = "/documents", method = RequestMethod.POST, headers = {
        "Accept: application/json"
    })
    public @ResponseBody List<CoysDocument> searchDocuments(@RequestBody
        documentVo.resolveDates());
    //Other code
}
}
</code></pre>
```

Next, is my jquery datatables code as obtained from the https://datatables.net/release-datatables/examples/server_side/pipel

```
<pre><code>//
// Pipelining function for DataTables. To be used to the `ajax` option of DataTable
//
$.fn.dataTable.pipeline = function ( opts ) {
    var documentVo = new Object();
    documentVo.groupId = $("#propertyGroup").val();
    documentVo.property = $("#properties").val();
    documentVo.filter = $("#filter").val();
    documentVo.startDateString = $("#startDate").val();
    documentVo.endDateString = $("#endDate").val();

    // Configuration options
    var conf = $.extend( {
        pages: 5,    // number of pages to cache
        url: '/search/documents',    // script url
        contentType: "application/json",
        data: JSON.stringify(documentVo), // function or object with parameters to
            // matching how `ajax.data` works in DataTables
        method: 'POST' // Ajax HTTP method
    }, opts );

    // Private variables for storing the cache
    var cacheLower = -1;
    var cacheInner = null;
```

I have Group of Checkbox , inside Treeview (bootstrap)
I'm Trying to create from each in the top Radio Button , Show and Hide function for

Everything I've tried so far has failed.

I have 5 Radio button :
-

- Radio button 1 show all checkbox with id matching FCB & FCTK - HIDE THE REST
- Radio button 2 show only all check boxes with id matching FCB - HIDE THE REST
- Radio Button 3 show only all check boxes with id matching FCTK- HIDE THE REST
- Radio button 4 show All Check boxes
- Radio button 5 i will add new checkbox that he can show ALL options and the new added check boxes

>
>any idea how to correctly do this?

I have an a idea but i failed when i tried to do it:

I thought of doing an array with each Checkbox ID, and then search document
<

```
<code><!DOCTYPE HTML>
<head>
<meta charset="utf-8">
<meta http-equiv="X-UA-Compatible" content="IE=edge" />
<!-- <script src="https://ajax.googleapis.com/ajax/libs/jquery/2.1.0/jquery
<script src="//cdnjs.cloudflare.com/ajax/libs/jquery/2.2.0/jquery.min.js">
<link href="https://maxcdn.bootstrapcdn.com/bootstrap/3.3.7/css/bootstrap
<link type="text/css" rel="stylesheet" href="//cdnjs.cloudflare.com/ajax/libs,
<script src="https://maxcdn.bootstrapcdn.com/bootstrap/3.3.7/js/bootstrap
<!-- <script type="text/javascript" src="http://ajax.googleapis.com/ajax/li

<title>" TZ Generator</title>
</head>

<body>
<form class="form-horizontal" action="ConstructorMain.php" method="post
<fieldset>
```

<p>I have <code>eslint</code> enabled in my vue webapp, I have following code:</p>

```
<pre><code>myApi.get('products/12').then((prodResponse) => {  
  state.commit('ADD_PRODUCT', {product: prodResponse.data})  
},  
error => {  
  console.log('Inside error, fetching product line items failed')  
  router.push({path: '/'})  
})  
</code></pre>
```

<p>This is the error handling I want to do, still I get following error from the liner:</p>

```
<blockquote>  
<p>✖ <a href="http://eslint.org/docs/rules/handle-callback-err" rel="nofollow no  
  ~/vue/src/store/modules/myStore.js:97:9  
    error => {</p>  
</blockquote>
```

<p>I can add following comment to convert this into warning:</p>

```
<pre><code>/* eslint handle-callback-err: "warn" */  
</code></pre>
```

<p>But how do I suppress this completely or modify code, so that this error doesn't

40800675

handle-callback-err Expected error to be han

<p>I am trying to reduce the amount of number lines, by grouping all product line tl

```
<pre><code>
    &lt;t t-set="index" t-value="0"/&gt;
    &lt;t t-set="product" t-value="0"/&gt;
    &lt;t t-foreach="doc.handle_orderline(doc.order_line)" t-as="product_lir
    &lt;t t-set="product_num" t-value="0"/&gt;
    &lt;t t-set="index" t-value="index + 1"/&gt;
    &lt;t t-foreach="product_line" t-as="l"&gt;
        &lt;t t-set="product_num" t-value="product_num+1"/&gt;
        &lt;t t-if="not l.product_uom_qty"&gt;
            &lt;t t-set="index" t-value="index - 1"/&gt;
        &lt;/t&gt;
        &lt;tr t-if="l.product_uom_qty"&gt;
            &lt;t t-if="product_num == 1"&gt;
                &lt;td class="text-center" t-att-rowspan="len(product_line)"&
                &lt;span t-esc="index"/&gt;
                &lt;/td&gt;
                &lt;td class="text-center" t-att-rowspan="len(product_line)"&
                &lt;strong&gt;&lt;span t-field="l.name"/&gt;&lt;/strong&
                &lt;br/&gt;
                &lt;t t-if="l.width_id"&gt;(&lt;span style="font-style:itali
                &lt;/td&gt;
            &lt;/t&gt;
            &lt;td class="text-center"&gt;
                &lt;t t-if="l.width_id"&gt;&lt;span t-field="l.lng"/&gt;&lt;/t&g
            &lt;/td&gt;
            &lt;td class="text-center"&gt;
                &lt;t t-if="l.width_id"&gt;&lt;span t-esc="int(l.quantity_extra)
            &lt;/td&gt;
            &lt;td class="text-center"&gt;
                &lt;t t-if="l.width_id"&gt;
                    &lt;span t-field="l.quantity_sum"/&gt;
                &lt;/t&gt;
                &lt;t t-if="not l.width_id"&gt;
                    &lt;span t-field="l.product_uom_qty"/&gt;
                &lt;/t&gt;
            &lt;/td&gt;

            &lt;td class="text-center"&gt;
                &lt;t t-if="l.width_id"&gt;
                    &lt;span t-field="l.unit_id.name"/&gt;
                &lt;/t&gt;
                &lt;t t-if="not l.width_id"&gt;
```

<p>I'm working on a business' website and I'm got blocks that essentially look like</p>

```
<pre><code>&lt;h2&gt;Product 1&lt;/h2&gt;
&lt;em&gt; Description...&lt;/em&gt;
```

```
&lt;h2&gt;Product 2&lt;/h2&gt;
&lt;em&gt;Description...&lt;/em&gt;
```

```
...
```

```
</code></pre>
```

<p>and so on. Let's say they have 20 products. Suddenly they roll out a new product

41027047

Make blocks of similar text dynamic in HTML

<p>In Paper [A Software Product Line for Static Analyses(2014)], there is an illustration

<p>In this example, Line14 is related to construct call graph. while i check the src code

<p>As my purpose is using OPAL to construct call graph. Is there any demo or document

<p>I'll be really appreciated if anyone can give me some suggestions related this topic

<p>Thanks in advance.</p>

<p>Jiang </p>

41043654

OPAL-Regarding implementing construct call

<p>This is my function. I am able to create a new quotation on clicking a button in n
@api.multi</p>

def action_rfq(self):
rfq_obj = self.env['purchase.order']
for order in self.product_lines:
rfq_id = rfq_obj.create({
'series': self.name,
'order_line': ({
<p>'product_id': order.product_id.id,
 'name': order.name,
 'product_qty': order.product_uom_qty,
 'product_uom': order.product_uom.id,
 'price_unit': order.price_unit,
 'date_planned': datetime.now(),
 'order_id': order.indent_id.id,
 })
})</p>

<pre><code> 'product_id': order.product_id.id,
 'name': order.name,
 'product_qty': order.product_uom_qty,
 'product_uom': order.product_uom.id,
 'price_unit': order.price_unit,
 'date_planned': datetime.now(),
 'order_id': order.indent_id.id,
 })
 })
 return rfq_id
</code></pre>

41365857

How to create a new quotation through cust

<p>Shopify to google-sheets via zapier to get new paid order customer address, em:

```
<pre><code>def combine_pairings(listing):
    out = []
    for index, val in enumerate(listing):
        if index % 2:
            continue
        out.append("{} {}".format(val, listing[index+1]))
    return out
```

```
def get_index(lst, index):
    try:
        return lst[index]
    except:
        return 'empty'
```

```
units = input['units'].split(',')
products = input['product'].split(',')
time = combine_pairings(input.get('time', "").split(','))
```

```
output = []
```

```
for index, product in enumerate(products):
    output.append({
        'units': get_index(units, index),
        'product': product,
        'phone': input['phone'],
        'customer_note': input.get('customer_note', ""),
        'address': input['address'],
        'status': input['status'],
        'customerlastname': input['customerlastname'],
        'customerfirstname': input['customerfirstname'],
        'email': input['email'],
        'time': get_index(time, index)
    })
```

```
return output
</code></pre>
```

<p><img src="https://i.stack.imgur.com/lqM3T.png" alt="enter image description h

<p>I have created a navbar using <code>div tag</code> which contain <code>4 tab:

<p>I have used an <code>affix concept</code> on this navbar. Note my application

```
<pre><code>    &lt;div class="row" style="background-color:#4C97C8;" data-spy='
    &lt;div class="btn col-xs-12 col-sm-6 col-md-3 col-lg-3" style="color:white;hei
    &lt;strong&gt;ABOUT&lt;/strong&gt;
    &lt;/div&gt;
    &lt;div class="btn col-xs-12 col-sm-6 col-md-3 col-lg-3" style="color:white;hei
    &lt;strong&gt;FEATURE REQUEST&lt;/strong&gt;
    &lt;/div&gt;
    &lt;div class="btn col-xs-12 col-sm-6 col-md-3 col-lg-3" style="color:white;hei
    &lt;strong&gt;PRODUCT&lt;/strong&gt;
    &lt;/div&gt;
    &lt;div class="btn col-xs-12 col-sm-6 col-md-3 col-lg-3 bg-primary" style="col
    &lt;strong&gt;PRODUCT LINE&lt;/strong&gt;
    &lt;/div&gt;
    &lt;/div&gt;
</code></pre>
```

<p>css is-</p>

```
<pre><code>.affix {
  top: 0;
  width:100%;
}

.affix + .container-fluid {
  padding-top: 70px;
}
</code></pre>
```

<p>The problem is - other contents like buttons, accordion panel moves over this na:

<p>What is the problem?

jsfiddle link - <a href="https://jsfiddle.net/shashankg/707n3r21/" rel="nofollow nor

<p>I know that PRD doesn't do any ordering, but rather takes in ordered data throu

<p>Example:

I have a report that displays a list of cars and are grouped by the header 'Product Lir

<p>Is there a way of reversing the order, so instead of 'Classic Cars' first, it's 'Vintag

<p>Thanks in advance!</p>

41769055

Order elements in Pentaho Report Designer i

<p>I am completely new to SQL Azure, I use an on-premise SQL Server and aware of

Does SQL Azure has versions like SQL 2014, 2016 or is it a totally different SQL-v:

What additional features/benefits does SQL Azure offer(besides those that natu

What major areas/features SQL Azure differ from SQL Server? Are there any TSC

When is a SQL Server (let's say, also hosted in cloud, like AWS RDS) is preferred c

<p>For this discussion, lets say the SQL server is 2014 or 2016 version.</p>

41769288

How does SQL Azure differ from SQL Server?

<p>We are building a Node.js app. As we are practicing Continuous Delivery with Tr

<p>For several reasons including legal requirements we are expected to deliver a pa

<p>Obviously any new features have to be excluded from the patch release, any we

<p>In order to test (and ship betas) we are building and testing three versions of the

<p>Exclusion of features is done using feature toggles.</p>

<p>Question: How could I exclude dependencies only valid for next feature release

<p>If it were for two lines I would try something using the optional dependencies of

<p>Is there any other way to make sure:</p>

dependencies for 1.1 and after are not making it into 1.0

dependencies for 1.2 and after are not making it into 1.0 and 1.1

require(...) does not fail for not existing dependencies (wrapping with feature to

<p>Is there a way to avoid keeping three <code>package.json</code>'s and pick the

41898931

Node.js: Multiple product line builds from on

<p>How to add the VAT percentage for each product line (as a new column or betw

42054179

Magento add VAT percentage for each produ

<p>I am retrieving records from mongodb .find() and trying to nest them with d3v4

<blockquote>

<p>Error: ambiguous: Product Line 1</p>

</blockquote>

<p>I'm presuming I'm misunderstanding the <a href="https://github.com/d3/d3-hie

<p>While the problem seems close to <a href="http://stackoverflow.com/questions

<p>Can someone help me understand how to use .stratify() properly? Or suggest an

<p>My result set (<code>mongodb_data</code>) is not large (maybe ~2500 produc

<p>My flat <code>mongodb_data</code> looks like this,</p>

```
<pre><code>[
  {
    "name": "Product Line 1",
    "reference": "product 1.A identifier"
  },
  {
    "name": "Product Line 1",
    "reference": "product 1.B identifier"
  },
  {
    "name": "Product Line 2",
    "reference": "product 2.A identifier"
  },
  {
    "name": "Product Line 2",
    "reference": "product 2.B identifier"
  }
];
</code></pre>
```

<p>The desired hierarchical/nested data needs to look like this,</p>

```
<pre><code>{
  "name": "Master Product Catalog",
  "children": [
    {
      "name": "Product Line 1"
```

<p>I'm trying to submit an HTML form that has 3 submit buttons with different nam

<p>HTML:</p>

```
<pre><code>&lt;div class="col-md-12"&gt;
  &lt;form id="validation-form" class="form-horizontal form-label-left"
  data-parsley-priority-enabled="false"
  novalidate="novalidate"
  action="/controller/productlineNewController.php" method="post"&gt;
    &lt;div class="col-md-6"&gt;
      &lt;section class="widget"&gt;
        &lt;div class="body"&gt;
          &lt;fieldset&gt;
            &lt;div class="form-group"&gt;
              &lt;label class="control-label col-md-4" for="pl_name"&gt;Product L
              &lt;div class="col-md-6"&gt;
                &lt;input type="text" id="pl_name" name="pl_name" onBlur="ch
                class="form-control input-transparent"
                placeholder="Enter Product Line Name" required="required"&gt;
                &lt;span class="help-block" id="availability-status"&gt;&lt;/span&
              &lt;/div&gt;
              &lt;p&gt;&lt;img src="img/small_loading.gif" id="loaderIcon" style='
            &lt;/div&gt;
          &lt;/fieldset&gt;
        &lt;/div&gt;
      &lt;/section&gt;
    &lt;/div&gt;
    &lt;div class="col-md-12"&gt;
      &lt;section class="widget"&gt;
        &lt;div class="form-actions"&gt;
          &lt;div class="row"&gt;
            &lt;div class="col-md-10 col-md-offset-2"&gt;
              &lt;button type="submit" name="save" class="btn btn-lg btn-succes
              onclick="needToConfirm = false;"&gt;Save&lt;/button&gt;&amp;nb
              &lt;button type="submit" name="save_new" class="btn btn-lg btn-s
              onclick="needToConfirm = false;"&gt;Save &amp; New Product
              &lt;button type="submit" name="save_project" class="btn btn-lg bt
              onclick="needToConfirm = false;"&gt;Save &amp; Add Project&
              &lt;button type="button" onclick="resetForm()"
              class="btn btn-lg btn-danger"&gt;Reset Form&lt;/button&gt;&amp;
            &lt;/div&gt;
          &lt;/div&gt;
        &lt;/div&gt;
      &lt;/div&gt;
    &lt;/div&gt;
```

<p>I'm currently testing and gathering PCs' hardware information from the laptops

<p>Right now, I want to get info of product line, product model from the json file ge

<blockquote>

<p>lshw command</p>

</blockquote>

<p>However, the result comes out in different ways.</p>

<p>For example:

Lenovo's Laptop:</p>

```
<pre><code>{
  "id" : "mint",
  "class" : "system",
  "claimed" : true,
  "handle" : "DMI:000E",
  "description" : "Notebook",
  "product" : "2353ABU (LENOVO_MT_2353)",
  "vendor" : "LENOVO",
  "version" : "ThinkPad T430s",
  "serial" : "R9YC24W"
}
</code></pre>
```

<p>product line will be ThinkPad, and product model will be <str

<p>In Dell:</p>

```
<pre><code>{
  "id" : "mint",
  "class" : "system",
  "claimed" : true,
  "handle" : "DMI:000E",
  "description" : "Notebook",
  "product" : "Latitude E6400",
  "vendor" : "Dell Inc",
  "version" : "01",
  "serial" : "R9TQ24W"
}
</code></pre>
```

<p>I can't seem to figure out how to do this one. Any help will be appreciated.</p>

<p>Basically I am trying to filter out the product line, and product number from vari

```
<pre><code>Latitude E6430 (Latitude E6430)
HP EliteBook 8460p (H3S08US#ABA)
ThinkPad T60
</code></pre>
```

<p>My expected result:</p>

```
<pre><code>Product line: Latitude
```

Model: E6430

Product line: EliteBook

Model: 8460p

Product line: ThinkPad

Model: T60

```
</code></pre>
```

<p>Thanks in advanced</p>

42398071

Regex on filtering product line and model nu

<p>In C# I'm using Entity Framework and MVC and have:</p>

```
<pre><code>public class Part

public class FinishedGoodsPart: Part
    public int? ProductLineId { get; set; }

public class CompetitorPart : Part
    public int? ProductLineId { get; set; }

public class OEPart: Part

public class ProductLine
    public virtual ICollection<Part> Parts { get; set; }
</code></pre>
```

<p>Observe that FinishedGoodsPart and CompetitorPart have a ProductLine, but O

<p>This puts a column called ProductLine_Id in the FinishedGoodsPart and Competi

<p>How do I prevent E.F. from adding column Part.ProductLine_Id? Is there a bette

<p>The goal is that an instance of the ProductLine model object will have a list of all

<p>FinishedGoodsPart objects will have a lot of attributes, whereas CompetitorPart

<p>I'm trying to filter out information of product line and product model from HP pi

<p>Examples:</p>

```
<pre><code>HP EliteDesk 800 G1 SFF (H3S08US#ABA)
HP Pro 3400 Series MT (H3S08US#ABA)
HP EliteBook 8460p (H3S08US#ABA)
</code></pre>
```

<p>Expected output:</p>

```
<pre><code>Production line: EliteDesk
Production model: 800 G1
```

```
Production line: Pro
Production model: 3400 Series
```

```
Production line: EliteBook
Production model: 8460p
</code></pre>
```

<p>Here is what I have for now.</p>

```
<pre><code>product_line = re.search('([a-zA-Z]+) ([a-zA-Z]*\d+[a-zA-Z]*)', model).gr
product_model = re.search('([a-zA-Z]+) ([a-zA-Z]*\d+[a-zA-Z]*)', model).group(2)
</code></pre>
```

<p>However, the output gives result of 800,3400 on the first and second example.</p>

<p>Is there any better way to filter out these info? thank you so much all in advance

42513002

Regex to filter product model (Python)

<p>I have 2 dataframes. The first one (900 lines) contains corrections that have bee

<p>To link the corrected deals to the corrections I have to compare a number of att

<p>To finish, I create a new column on the Deals dataframe (140 000 lines) where I

<p>My code right now is quite gross, I wanted to factorize a bit but the iteration prc

<p>How can I improve performance? Is multithreading possible to use in this case ?
Here is shorted version of my code, just imagine that the number of if statements is

```
<pre><code>def CreationUniqueid(dataframe,Correction):
```

```
#creating new column to mark the rows we un corrected
```

```
dataframe['Modified']=0
```

```
#getting the link between the corrections and deals
```

```
b=0
```

```
for index in Correction.index:
```

```
    b+=1 #just values to see progression of the program
```

```
    c=0
```

```
    for index1 in dataframe.index:
```

```
        c+=1
```

```
        a=0
```

```
        print('Handling correction '+str(b)+' and deal '+str(c)) # printing progress
```

```
        if (Correction.get_value(index,'BO Branch Code')==dataframe.get_value(index1
```

```
            print('level 1 success')
```

```
            if ((Correction.get_value(index,'BO Trade Id')==dataframe.get_value(index1,"
```

```
                (Correction.get_value(index,'Emetteur Trade Id')==dataframe.get_value(
```

```
                    print('identification success')
```

```
                    # putting the dataframe to the old state, we need the data in the bad shap
```

```
                    if Correction.get_value(index,'Risk Category')!=Correction.get_value(index,
```

```
                        dataframe.set_value(index1,'Risk Category',Correction.get_value(index,'
```

```
                            a=1
```

```
                            print('Corr 1 ')
```

```
                    if Correction.get_value(index,'CEC Ricos')!=Correction.get_value(index,'CEC
```

```
                        dataframe.set_value(index1,'CEC Ricos',Correction.get_value(index,'CEC
```

```
                            a=1
```

```
                            print('Corr 2')
```

```
                    if Correction.get_value(index,'Product Line')!= Correction.get_value(index,'
```

```
                        dataframe.set_value(index1,'Product Line Code Ricos',Correction.get_va
```

```
                            a=1
```

```
                            print ('corr 3')
```

42701468 <p>I am wondering whether there is a function that will add a "price ex Tax" to a pr
Display price Ex Tax in the woocommerce or

<p>I have tried to generate unique name for different cases and set that unique nar
Can someone help me to get this, Here is my code..</p>

```
<pre><code>*** Test Cases ***
```

```
TC100_Unique Variable Checking
Generate Unique Name for Objects-loop  Product Line
Generate Unique Name for Objects-loop  Models
Generate Unique Name for Objects-loop  Portfolio
```

```
*** Keywords ***
```

```
Generate Unique Name for Objects-loop
[Arguments]  ${function}
Set Variable  ${function}
${namePL}=  Run Keyword If  '${function}'=='Product Line'  Run  Keywords  Ge
...  Set Suite Variable  ${namePL}
${nameMOD}=  Run Keyword If  '${function}'=='Models'  Run Keywords  Genera
...  Set Suite Variable  ${nameMOD}
${namePF}  Run Keyword If  '${function}'=='Portfolio'  Run Keywords  Generate
...  Set Suite Variable  ${namePF}
```

```
Generate Unique Name
[Arguments]  ${suffix}  ${filepath}
${name}=  Get String Plus Number  ${suffix}  ${filepath}
Set Test Variable  ${name}
Write Unique Number  ${filepath}
[Return]  ${name}
</code></pre>
```

<p>Error: </p>

```
<blockquote>
<p>Variable '${namePL}' not found.</p>
</blockquote>
```

42757297 Robotframework: Unable to Set Suite variabl

<p>I see there are three product lines on spring cloud. I am a newer of spring cloud

42766822

spring cloud three releases difference Angel,