ALGORHYTHM

A LIBRARY FOR ALGORITHMIC MUSIC COMPOSITION

Joris ten Tusscher, Cas van der Rest, Orestis Melkonian April 5, 2018

Universiteit Utrecht

SOME DEFINITIONS

- · Melody: Notes played in sequence
- · Chords/harmony: Notes played simultaneously
- Scale: a sequence of ascending notes, beginning and starting on the same note.

i.e: C major = C, D, E, F, G, A, B, C

Or in intervals: 2, 2, 1, 2, 2, 2, 1

SOME DEFINITIONS

A piece of music is said to be in a **key** if it (primarily) uses notes from a certain scale

Diatonic music is music that uses scales that have the same pattern as we saw before (2,2,1,2,2,2,1).

MUSIC DSL: REPRESENTATION

Basically, you want to know when to make noise and when to remain silent.

Two pieces of music can be composed in parallel or sequentially.

MUSIC DSL: REPRESENTATION

In order to provide export functionalities, we use a MusicCore type and a typeclass ToMusicCore.

```
type MusicCore =
  Music ((PitchClass, Octave), [PitchAttribute])
```

This ensures that all the necessary information is there when exporting a piece of music

MUSIC DSL: REPRESENTATION

(Abstract) scales and chords are represented as intervals between notes, i.e:

```
major = [P1,M2,M3,P4,P5,M6,M7] -- Major scale
d7b5 = [P1, M3, A4, Mi7] -- Half diminished chord
```

There are many constants for various scales and chords (, as well as common durations:

```
an = 1\%4
```

MUSIC DSL: MANIPULATION

Music can be constructed and manipulated using various operators

```
-- quarter note C in the 4th octave, played softly
let n = (C#4 <: [PPP]) <| qn

-- A half note rest
let r = (hn~~)

-- Instantiate an abstract chord
let cMaj7 = ((C =| maj7) <#) 3 <|| wn</pre>
```

MUSIC DSL: MANIPULATION


A melody in our DSL:

```
line [ (C#6 <: [Dynamic PP]) <| wn
, (D#6 <: [Dynamic MP]) <| wn
, (hn~~)
, (C#6 <: [Dynamic F_]) <| qn
, (D#6 <: [Dynamic F_]) <| qn
, (C#6 <: [Dynamic F_]) <| qn
, (B#5 <: [Dynamic F_]) <| qn
, (D#6 <: [Dynamic MF]) <| qn
, (C#6 <: [Dynamic MP]) <| wn
, (F#5 <: [Dynamic P]) <| wn
]</pre>
```

MUSIC DSL: MANIPULATION

There's also some operators for common operations:

```
C \sim M3 == E
let music' = (music><)</pre>
let music' = music *~ (1%5)
Also, Music is a functor!
^^Ilet rhythm = const () <$> music
```



GENERATION

genState, selectors, diatonic improv, etc...

CHAOS IN MUSIC


- Chaos system: n start values, n update functions. f_x
 calculates x_{i+1} given x_i.
- Chaos: small difference in init values gives very different results.

CHAOS IN MUSIC: EXAMPLE

Table 1: $f_x = max(-1) (min 1 (1 - rx^2))$

r	1.9521	1.9621	0.25
Х	1.2	1.18	1.18
-X ₀	-1.0	-1.0	0.8937
<i>X</i> ₁	-0.9521	-0.9621	0.8002
<i>X</i> ₂	-0.7695	-0.8161	0.8398
<i>X</i> 3	-0.1561	-0.3070	0.8236
<i>X</i> 4	0.9524	0.8149	0.8304
<i>X</i> ₅	-0.7708	-0.3031	0.8276
<i>X</i> ₆	-0.1598	0.8196	0.8287

CHAOS IN MUSIC: HARD TO GET RIGHT



Walker, Elaine. "Chaos melody theory." Music Technology New York University, Master's thesis (2001).

DYNAMIC PERFORMANCE: 1 (CLUSTER NOTES)

K-means

- · x: absolute start time of note
- y: pitch, represented as integer
- k: total music time / beats per standard bar

DYNAMIC PERFORMANCE: 2 (MAP TO DYNAMICS)

- 1. Convert x (abs. time) and y (int pitch) to relative values per cluster in range [0,1].
- 2. Call mapping function on every (x,y) pair
- 3. Convert mapping function result to dynamics
- 4. Add dynamics to note that (x,y) belongs to.

GRAMMARS: PROPERTIES

(Generative) context-free grammars, with a few extra features:

- · Temporal: Rules are parametric to duration
- · Probabilistic: Rules can be assigned weights
- Graph: Allow node sharing (using *let*-expressions)

GRAMMARS: DEFINITION

```
data Grammar meta a =
   a |: [Rule meta a]
data Rule meta a =
    (a, Weight, Dur -> Bool) :-> (Dur -> Term meta a)
data Term meta a =
    a:%: Dur
    Term meta a :-: Term meta a
    | Aux Bool meta (Term meta a)
     Let (Term meta a) (Term meta a -> Term meta a)
(a, w) - f = (a, w, f) :-> (a :%:)
a |-> b = a :-> const b
a \mid --> b = (a, 1, always) \mid -> b
($:) = Aux False
(|\$:) = Aux True
```

GRAMMARS: GENERATION

```
gen :: (Eq a, Eq meta, Expand input meta a b)
     => Grammar meta a -> input -> Dur -> Music b
gen gr i t = rewrite gr t >>> unlet >>> expand i >>> toMusic
```

1. Given an initial duration, rewrite until fixpoint

2. Unfold let-expressions

```
unlet (Let x f) = f x
unlet x = x
```

3. Expand auxiliary wrappers

```
class Expand input meta a b | input meta a -> b where
  expand :: input -> Term meta a -> Term () b
```

4. Convert to music

```
(:%:) ~> (<|)
(:-:) ~> (:+:)
```

GRAMMARS: TABLA RHYTHM

```
tabla :: Grammar () Syllable
tabla = S |:
  S |--> TE1 :-: XI
  . XI |--> TA7 :-: XD
  . XD |--> TA8
  . XG |--> TB2 :-: XA
  , TE4 |--> Ti :-: Rest :-: Dha :-: Ti
  . TC2 |--> Tira :-: Kita
  . TB3 |--> Dha :-: Tira :-: Kita
  . TD1 |--> Rest
instance ToMusicCore Syllable where
```

GRAMMARS: TONAL HARMONY

```
harmony :: Grammar Modulation Degree
harmony = I |:
    (I, 8, (> wn)) :-> \t ->
      Let (I:\%:t/2) (\x -> x :-: x)
  , (I, 6, (> hn) / \ (<= wn)) :-> \t ->
      II:%:t/4 :-: V:%:t/4 :-: I:%:t/2
  (I, 2, (> hn) / (<= wn)) :-> t ->
  V:%:t/2 :-: I:%:t/2
, (I, 2) -| (<= wn)
  , (V, 5, (> hn)) :-> \t -> Modulation P5 $: I:%:t
  , (V, 3) - always
  , (II, 2, (> hn)) :-> \t -> Modulation M2 | \frac{\pi}{2}: I:%:t
  , (II, 8) - | always
instance Expand Config Degree Modulation SemiChord where
voiceLead :: Music SemiChord -> IO (Music Chord)
```

GRAMMARS: JAZZ IMPROVISATION

```
melody :: Grammar () NT
melody = MQ |:
  [ -- Abstract Rhythm { MQ ~> Q }
    (MQ, 1, (== qn)) \rightarrow Q:\%:qn
  (MQ, 25, (> (hn^{\circ}.))) :-> \t -> Q:%:hn :-: MQ:%:(t - hn)
  , (Q, 47, (== wn)) |-> MN:%:qn :-: Q:%:hn :-: MN:%:qn
  , (Q, 6, (== hn)) |->
      MN:\%:(qn^{\wedge \wedge}) :-: MN:\%:(qn^{\wedge \wedge}) :-: MN:\%:(qn^{\wedge \wedge})
  , (MN, 1, (== wn)) |-> N:%:qn :-: N:%:qn :-: MN:%:hn
  , (MN, 1, (== qn)) |->
      N:%:(en^^^) :-: N:%:(en^^^) :-: N:%:(en^^^)
  , (N, 50, (== qn)) |-> ChordTone:%:qn
  , (N, 45, (== qn)) |-> Rest:%:qn
  (N, 1, (== en)) |-> ApproachTone:%:en
```

mkSolo :: Music SemiChord -> Music NT -> IO Melody

```
orientalAlgebras = do
 let ?config = MusicConfig
     basePc = A
   , baseOct = Oct3
   , tempo = 6<mark>%</mark>5
   , instruments = [Piano, Sita<u>r, Tabla]</u>
     beat = sn
 let t = 12 * wn
 har <- voiceLead <$> runGrammar harmony t
 mel <- mkSolo har <$> runGrammar melody t
 rhy <- runGrammar tabla t
 writeToMidiFile "out.mid" (dyn (har :=: mel :=: rhy))
```

DEMO: MUSIC SCORE

