

NATIVE CUSTOM TOKENS IN THE EXTENDED UTXO MODEL

Manuel M.T. Chakravarty, James Chapman, Kenneth MacKenzie,
Orestis Melkonian, Jann Müller, Michael Peyton Jones, Polina Vinogradova, Philip Wadler

October 28, 2020



THE UNIVERSITY *of* EDINBURGH



INPUT | OUTPUT

INTRODUCTION

- Most Ethereum smart contracts manage *user-defined assets*
 - either *fungible tokens* based on ERC-20
 - or *non-fungible tokens* based on ERC-721

- Most Ethereum smart contracts manage *user-defined assets*
 - either *fungible tokens* based on ERC-20
 - or *non-fungible tokens* based on ERC-721
- Unfortunately **non-native**, hence inefficient and expensive


1. Recall EUTXO, an extension of UTXO

1. Recall EUTXO, an extension of UTXO
2. Introduce EUTXO_{ma} to support **native custom tokens**


1. Recall EUTXO, an extension of UTXO
2. Introduce EUTXO_{ma} to support **native custom tokens**
3. Utilise multi-currency features to extend the previous meta-theory and make it more robust

EUTXO


UTXO vs EUTXO




RUNNING EXAMPLE: ASYNCHRONOUS MULTI-SIGNATURE CONTRACT



Pay value (v) to payee (p) until deadline (d)




-
- $\delta \in \{\text{Holding}, \text{Collecting}\}$
 - $\rho \in \{\text{Propose}, \text{Add}, \text{Cancel}, \text{Pay}\}$
-




PREVIOUS WORK [THE EXTENDED UTXO MODEL @ WTSC'20]

- Detailed description of the Extended UTXO model (EUTXO)




- Formalization in  Agda


- Proof of bisimulation with a Constraint Emitting Machines (CEMs)



LIMITATION: INITIAL STATE



- $\delta \in \{\text{Holding, Collecting}\}$
- $\rho \in \{\text{Propose, Add, Cancel, Pay}\}$



$$v(\rho, x, \delta, \sigma) \stackrel{?}{=} \text{True}$$

EUTXO_{MA}

$$\{\mathbb{A} \mapsto \{\mathbb{A} \mapsto 3\}, \text{WoW} \mapsto \{\text{sword} \mapsto 1, \text{shield} \mapsto 1\}\}$$

OPERATIONS ON TOKEN BUNDLES

$$\begin{aligned} & \{ \mathbb{A} \mapsto \{ \mathbb{A} \mapsto 3 \}, \text{WoW} \mapsto \{ \text{sword} \mapsto 1, \text{shield} \mapsto 1 \} \} \\ & + \{ \mathbb{A} \mapsto \{ \mathbb{A} \mapsto 1 \}, \text{WoW} \mapsto \{ \text{armour} \mapsto 1 \} \} \\ & = \{ \mathbb{A} \mapsto \{ \mathbb{A} \mapsto 4 \}, \text{WoW} \mapsto \{ \text{sword} \mapsto 1, \text{shield} \mapsto 1, \text{armour} \mapsto 1 \} \} . \end{aligned}$$

- $Tx = \{\dots forge : \text{TokenBundle}, policies : \sigma \rightarrow \text{Bool} \dots\}$

- $Tx = \{\dots forge : \text{TokenBundle}, policies : \sigma \rightarrow \text{Bool} \dots\}$
- $forge \in \mathbb{Z}^+$ for minting, $forge \in \mathbb{Z}^-$ for burning

- $Tx = \{\dots forge : \text{TokenBundle}, policies : \sigma \rightarrow \text{Bool} \dots\}$
- $forge \in \mathbb{Z}^+$ for minting, $forge \in \mathbb{Z}^-$ for burning
- $\forall p\sharp \in forge.domain : p \in policies \wedge p(\sigma) = \text{True}$

- Tokenised roles
- Fairness in ICO setup
- Algorithmic stablecoins
- \vdots

APPLICATIONS: THREADED STATE MACHINES

- Every CEM instance is associated with a unique token ♦

APPLICATIONS: THREADED STATE MACHINES

- Every CEM instance is associated with a unique token ♦
- **CEM policy:** check ♦ is minted in an initial state

APPLICATIONS: THREADED STATE MACHINES

- Every CEM instance is associated with a unique token ♦
- **CEM policy:** check ♦ is minted in an initial state
- **CEM validator:** check ♦ is propagated at each transition

APPLICATIONS: THREADED STATE MACHINES

- Every CEM instance is associated with a unique token ♦
- **CEM policy:** check ♦ is minted in an initial state
- **CEM validator:** check ♦ is propagated at each transition
⇒ can distinguish between different executions

APPLICATIONS: THREADED STATE MACHINES

- Every CEM instance is associated with a unique token ♦
- **CEM policy:** check ♦ is minted in an initial state
- **CEM validator:** check ♦ is propagated at each transition
 - ⇒ can distinguish between different executions
 - ⇒ solve the initialisation problem

META-THEORY

- $\text{Token} = \text{Policy} \times \text{Asset}$

- $\text{Token} = \text{Policy} \times \text{Asset}$
- $\text{Trace}(l, o, \blacklozenge, n) = t_0, \dots, t_i, t_{i+1}, \dots, t_k$, where
 1. $t_0.\text{forge}^{\blacklozenge} \geq n$
 2. $t_i \xrightarrow{\blacklozenge} t_{i+1} \geq n$
 3. $o \in t_k.\text{outputs}$


- $\text{Token} = \text{Policy} \times \text{Asset}$
- $\text{Trace}(l, o, \diamond, n) = t_0, \dots, t_i, t_{i+1}, \dots, t_k$, where
 1. $t_0.\text{forge}^\diamond \geq n$
 2. $t_i \xrightarrow{\diamond} t_{i+1} \geq n$
 3. $o \in t_k.\text{outputs}$
- $\text{Provenance}(l, o, \diamond) = \dots \text{Trace}(l, o, \diamond, n_i) \dots$ s.t. $\sum n_i \geq o.\text{value}^\diamond$

- Token = Policy \times Asset
- Trace(l, o, \blacklozenge, n) = $t_0, \dots, t_i, t_{i+1}, \dots, t_k$, where
 1. $t_0.\text{forge}^\blacklozenge \geq n$
 2. $t_i \xrightarrow{\blacklozenge} t_{i+1} \geq n$
 3. $o \in t_k.\text{outputs}$
- Provenance(l, o, \blacklozenge) = $\dots \text{Trace}(l, o, \blacklozenge, n_i) \dots$ s.t. $\sum n_i \geq o.\text{value}^\blacklozenge$


Every output has a provenance

$$\frac{o \in \{t.\text{outputs} \mid t \in l\}}{\text{provenance}(l, o, \blacklozenge) : \text{Provenance}(l, o, \blacklozenge)} \text{ PROVENANCE}$$


EXAMPLE TRACES




EXAMPLE TRACES




EXAMPLE TRACES




EXAMPLE TRACES




EXAMPLE TRACES




EXAMPLE TRACES




EXAMPLE TRACES




EXAMPLE TRACES




EXAMPLE TRACES




EXAMPLE TRACES




EXAMPLE TRACES




EXAMPLE TRACES




EXAMPLE TRACES




EXAMPLE TRACES



EXAMPLE TRACES



EXAMPLE TRACES



Provenance is never empty

$$\frac{o \in \{t.outputs \mid t \in l\} \quad o.value^{\blacklozenge} > 0}{|provenance(l, o, \blacklozenge)| > 0} \text{PROVENANCE}^+$$

Provenance is never empty

$$\frac{o \in \{t.outputs \mid t \in l\} \quad o.value^{\blacklozenge} > 0}{|provenance(l, o, \blacklozenge)| > 0} \text{PROVENANCE}^+$$

Global Preservation

$$\sum_{t \in l} t.forge = \sum_{o \in \text{unspentOutputs}(l)} o.value$$

Provenance for non-fungible tokens

$$\frac{o \in \{t.outputs \mid t \in l\} \quad o.value^{\diamond} > 0 \quad \sum_{t \in l} t.forge^{\diamond} \leq 1}{|provenance(l, o, \diamond)| = 1} \text{ NF-PROVENANCE}$$

$$\text{policy}_C(\text{txInfo}, c) = \begin{cases} \text{true} & \text{if } \text{txInfo.forge}^\diamond = 1 \\ & \text{and } \text{origin} \in \text{txInfo.outputRefs} \\ & \text{and } \text{initial}(\text{txInfo.outputs}^\diamond) \\ \text{false} & \text{otherwise} \end{cases}$$

$$\text{policy}_C(\text{txInfo}, c) = \begin{cases} \text{true} & \text{if } \text{txInfo.forge}^\diamond = 1 \\ & \text{and } \text{origin} \in \text{txInfo.outputRefs} \\ & \text{and } \text{initial}(\text{txInfo.outputs}^\diamond) \\ \text{false} & \text{otherwise} \end{cases}$$

$$\text{validator}_C(s, i, \text{txInfo}) = \begin{cases} \text{true} & \text{if } s \xrightarrow{i} (s', \text{tx}^\Xi) \\ & \text{and } \text{satisfies}(\text{txInfo}, \text{tx}^\Xi) \\ & \text{and } \text{checkOutputs}(s', \text{txInfo}) \\ & \text{and } \text{propagates}(\text{txInfo}, \diamond, s, s') \\ \text{false} & \text{otherwise} \end{cases}$$

All traces originate from initial states

$$\frac{o \in \{t.outputs \mid t \in l\} \quad o.value^\diamond > 0}{\exists tr. \text{provenance}(l, o, \diamond) = \{tr\} \wedge \text{policy}_C(tr_0.context) = \text{true}} \text{INITIALITY}$$

Well-rooted sequences

$$\frac{\text{initial}(s) = \text{true}}{s \rightsquigarrow^* s}$$

$$\frac{s \rightsquigarrow^* s' \quad s' \xrightarrow{i} (s'', tx^{\equiv})}{s \rightsquigarrow^* s''}$$

Well-rooted sequences

$$\frac{\text{initial}(s) = \text{true}}{s \rightsquigarrow^* s} \qquad \frac{s \rightsquigarrow^* s' \quad s' \xrightarrow{i} (s'', tx^{\equiv})}{s \rightsquigarrow^* s''}$$

A property P is invariant when:

$$\frac{\text{initial} \implies P \quad \forall (s \rightsquigarrow^* s'). P(s) \implies P(s')}{\text{invariant } P}$$

EXAMPLE: COUNTER CEM

$(\mathbb{Z}, \{\text{inc}\}, \text{step}, \text{initial})$ **where** $\text{step}(i, \text{inc}) = \text{just}(i + 1)$; $\text{initial}(0) = \text{true}$

EXAMPLE: COUNTER CEM

$(\mathbb{Z}, \{\text{inc}\}, \text{step}, \text{initial})$ **where** $\text{step}(i, \text{inc}) = \text{just}(i + 1)$; $\text{initial}(0) = \text{true}$

- $Q = (_ \geq 0)$ is invariant, since $Q(0)$ and $Q(x) \implies Q(x + 1)$

EXAMPLE: COUNTER CEM

$(\mathbb{Z}, \{\text{inc}\}, \text{step}, \text{initial})$ **where** $\text{step}(i, \text{inc}) = \text{just}(i + 1)$; $\text{initial}(0) = \text{true}$

- $Q = (_ \geq 0)$ is invariant, since $Q(0)$ and $Q(x) \implies Q(x + 1)$

Extracting CEM traces from EUTXO traces

$$\frac{\text{provenance}(l, o, \blacklozenge) = \{tr\}}{tr.\text{source} \rightsquigarrow^* tr.\text{destination}} \text{EXTRACTION}$$

- so far only **safety** properties

- so far only **safety** properties
- what about **temporal** ones?

- so far only **safety** properties
- what about **temporal** ones?

$\stackrel{?}{\implies}$ *coinductive* techniques for *infinitary* semantics

- **Scilla** [Sergey et al. @ OOPSLA'19]
 - Ethereum smart contracts as state machines
 - Embed in Coq and prove safety & temporal properties

- **Scilla** [Sergey et al. @ OOPSLA'19]
 - Ethereum smart contracts as state machines
 - Embed in Coq and prove safety & temporal properties
- **Bitcoin Modelling Language (BitML)** [Bartoletti et al. @ CCS'18]
 - High-level process calculus > Bitcoin transactions
 - Small-step operational semantics state machines
 - Support for LTL formulas
 - No (complete) mechanization yet

- **Scilla** [Sergey et al. @ OOPSLA'19]
 - Ethereum smart contracts as state machines
 - Embed in Coq and prove safety & temporal properties
- **Bitcoin Modelling Language (BitML)** [Bartoletti et al. @ CCS'18]
 - High-level process calculus > Bitcoin transactions
 - Small-step operational semantics state machines
 - Support for LTL formulas
 - No (complete) mechanization yet
- **VeriSolid** [Mavridou et al. @ FC'20]
 - Solidity contracts as state machines
 - Support for CTL formulas
 - No mechanized meta-theory

1. Recall EUTXO, an extension of UTXO

1. Recall EUTXO, an extension of UTXO
2. Introduce EUTXO_{ma} to support **native custom tokens**

1. Recall EUTXO, an extension of UTXO
2. Introduce EUTXO_{ma} to support **native custom tokens**
3. Utilise multi-currency features to extend the previous meta-theory and make it more robust

QUESTIONS?