Introduction to Microcomputers

Lab4

The goal of this lab is to make use of function calls and indirect addressing using PIC16F877A assembly instructions.

Assignment

Consider an arbitrary number generator function GenerateNumbers that takes 3 arguments, x, y and N, and generates some arbitrary numbers in a loop, and stores these numbers in an array. It then returns the total number of elements generated and stored in the array. You then write another function AddNumbers that adds the numbers in the array and returns their sum. Finally, you write a function DisplayNumbers that first displays the sum and then the first 5 numbers in the array one after the other as the user presses Button3 connected to PORTB3 (RB3 on PICSIM).

Here is the sketch of the C code that you need to implement in PIC16F877A:

```
uint8_t Multiply(uint8_t x, uint8_t y) {
      uint16_t z = x * y;
      uint8_t* p = (uint8_t*)&z;
      return 2 * p[0] + p[1];
} //end-Multiply
uint8_t GenerateNumbers(uint8_t A[], uint8_t x, uint8_t y, uint8_t N) {
      int8_t count = 0;
      while ((x < N) | | (y < N)) 
             if ((x + y) % 2 == 1) {
                    A[count++] = Multiply(x, y);
                    x = x + 1;
             }
             else {
                    uint8_t tmp = x + y;
                    A[count++] = tmp / 3;
                    y = y + 3;
             } // end-else
      } //end-while
      return count:
} //end-GenerateNumbers
uint8_t AddNumbers(uint8_t A[], uint8_t count) {
      uint8 t sum = 0;
      for (int i = 0; i < count; i++) {</pre>
             sum += A[i];
      } //end-for
      return sum;
} //end-AddNumbers
void DisplayNumbers(uint8 t sum, uint8 t A[]) {
      BANKSEL TRISD; // Select Bank1
      TRISD = 0;
                             // All pins output
                           // All pins input
      TRISB = 0xFF;
```

```
// Select Bank0
      BANKSEL PORTD;
       PORTD = sum;
      while (PORTB3 == 1); // Wait until the user presses RB3;
      for (int i = 0; i < 5; i++) {
             PORTD = A[i];
                                   // Wait for 250 ms
             DelayMs(250);
             while (PORTB3 == 1); // Wait until the user presses RB3;
      } //end-for
} //end-DisplayNumbers
void main() {
      uint8_t x = 112;
      uint8_t y = 100;
      uint8_t N = 125;
      uint8_t A[40];
      uint8_t noElements = GenerateNumbers(A, x, y, N);
      uint8_t sum = AddNumbers(A, noElements);
      DisplayNumbers(sum, A);
      while (1);
}//end-main
```

The expected result for some x, y and N values are given in the following table:

Х	у	N	sum	A[] (First 5 numbers)
112	100	125	129	[70, 77, 72, 194, 73]
200	177	213	56	[26, 40, 53, 42, 92]
224	211	235	109	[248, 60, 232, 61, 227]
7	11	23	56	[6, 196, 7, 16, 8]