

Reverb under Supervisor — install & operations

How to run Laravel **Reverb** (`fundflow-reverb`) as a persistent service on Ubuntu, so Filament's notification bell can push over WebSockets.

Related: `deploy/supervisor/fundflow-reverb.conf`, `docs/production-runbook.md`, `docs/filament-notification-be`

What this service does

Component	Role
Laravel app	With <code>BROADCAST_CONNECTION=reverb</code> , sends events to <code>http://127.0.0.1:8080/apps/{id}/events</code>
Reverb (<code>fundflow-reverb</code>)	Listens on <code>REVERB_SERVER_HOST:REVERB_SERVER_PORT</code> (default <code>127.0.0.1:8080</code>)
Nginx	Proxies browser <code>wss://<domain>/app/... →</code> <code>127.0.0.1:8080</code>
Filament Echo	Connects in the browser; bell updates in real time (polling every 10s remains as fallback)

If Reverb is down, you may see in `storage/logs/laravel.log`:

Pusher error: cURL error 7: Failed to connect to 127.0.0.1 port 8080 ... Couldn't connect to server

One-time server setup

1. Install Supervisor

```
sudo apt update
sudo apt install -y supervisor
sudo systemctl enable supervisor
sudo systemctl start supervisor
sudo systemctl status supervisor
```

2. Redis + PHP redis extension (required for this app)

Reverb's start command uses Laravel's cache (e.g. graceful restart). This project uses `CACHE_STORE=redis` for Stancl tenancy tagged cache.

```
sudo apt install -y redis-server php8.4-redis
sudo systemctl enable redis-server
sudo systemctl start redis-server
redis-cli ping      # expect PONG
php -m | grep redis # expect "redis"
```

3. Application .env (minimum for Reverb)

```
BROADCAST_CONNECTION=reverb
FILAMENT_DATABASE_NOTIFICATIONS_POLLING=10s
```

```
REVERB_APP_ID=...
REVERB_APP_KEY=...
REVERB_APP_SECRET=...
REVERB_HOST=fundflow-saas.osamman.com
REVERB_PORT=443
REVERB_SCHEME=https
REVERB_SERVER_HOST=127.0.0.1
REVERB_SERVER_PORT=8080
REVERB_SERVER_SCHEME=http

VITE_REVERB_APP_KEY="${REVERB_APP_KEY}"
VITE_REVERB_HOST="${REVERB_HOST}"
VITE_REVERB_PORT="${REVERB_PORT}"
VITE_REVERB_SCHEME="${REVERB_SCHEME}"
```

```
CACHE_STORE=redis
REDIS_CLIENT=phpredis
REDIS_HOST=127.0.0.1
REDIS_PORT=6379
```

After changing .env:

```
cd /var/www/fundflow-saas
php artisan config:clear
# use config:cache in production only when you normally cache config
```

4. Frontend assets

```
cd /var/www/fundflow-saas
npm ci && npm run build
```

5. Nginx WebSocket proxy

See docs/production-runbook.md (Reverb section) for a location /app/ block pointing to 127.0.0.1:8080.

Install the fundflow-reverb Supervisor program

From the app root on the server:

```
cd /var/www/fundflow-saas

# Ensure log file is writable by www-data (Supervisor runs as www-data)
touch storage/logs/reverb.log
sudo chown www-data:www-data storage/logs/reverb.log

# Install unit (path must match your deploy directory)
sudo cp deploy/supervisor/fundflow-reverb.conf /etc/supervisor/conf.d/fundflow-reverb.conf

# Load and start
sudo supervisorctl reread
```

```
sudo supervisorctl update
sudo supervisorctl start fundflow-reverb
```

Expected status:

```
sudo supervisorctl status fundflow-reverb
# fundflow-reverb    RUNNING    pid ..., uptime ...
```

Useful commands (cheat sheet)

Supervisor — fundflow-reverb

Action	Command
Status	sudo supervisorctl status fundflow-reverb
Start	sudo supervisorctl start fundflow-reverb
Stop	sudo supervisorctl stop fundflow-reverb
Restart (after deploy / .env)	sudo supervisorctl restart fundflow-reverb
Reload config after editing .conf	sudo supervisorctl reread && sudo supervisorctl update
Tail logs	tail -f /var/www/fundflow-saas/storage/logs/reverb.log
All programs	sudo supervisorctl status

Laravel Reverb

Action	Command
Graceful restart (signals running server)	cd /var/www/fundflow-saas && php artisan reverb:restart
Clear config after .env change	php artisan config:clear
Do not run in production (Supervisor owns the process)	php artisan reverb:start in an SSH session

Use **reverb:restart** when Reverb is already supervised; use **supervisorctl restart fundflow-reverb** after code deploy or if the process crashed.

Verify Reverb is listening

```
ss -tlnp | grep 8080
# LISTEN ... 127.0.0.1:8080 ... users:(("php",pid=...,...))
```

```
pgrep -af 'artisan reverb'
# should show one reverb:start under Supervisor
```

Redis

```
redis-cli ping
sudo systemctl status redis-server
```

Nginx

```
sudo nginx -t
sudo systemctl reload nginx
```

Deploy follow-up (typical)

```
cd /var/www/fundflow-saas
composer install --no-dev --optimize-autoloader
php artisan migrate --force
php artisan tenants:migrate --no-interaction
npm ci && npm run build
php artisan optimize:clear
sudo supervisorctl restart fundflow-reverb
sudo systemctl reload php8.4-fpm
```

Troubleshooting

Symptom	Likely cause	Fix
Address already in use on 8080	Manual <code>reverb:start</code> while Supervisor already runs	<code>sudo supervisorctl status fundflow-reverb;</code> stop stray <code>php artisan reverb</code> PIDs; use Supervisor only
Couldn't connect to 127.0.0.1 port 8080	Reverb not running	<code>sudo supervisorctl start fundflow-reverb</code>
Class "Redis" not found	Missing <code>php8.4-redis</code>	<code>sudo apt install php8.4-redis</code> and restart PHP-FPM
<code>redis-cli ping</code> fails	Redis down	<code>sudo systemctl start redis-server</code>
Echo errors in browser; bell still updates every ~10s	nginx WS proxy or stale Vite build	Fix <code>/app/</code> proxy; <code>npm run build</code> ; hard refresh
FATAL in Supervisor log	Wrong path, permissions, or PHP error	<code>tail -50 storage/logs/reverb.log;</code> check <code>user=www-data</code> can read <code>.env</code> and <code>storage/</code>

Temporary disable broadcasting (polling-only bell):

```
BROADCAST_CONNECTION=log
php artisan config:clear
sudo supervisorctl stop fundflow-reverb # optional
```

Unit file reference

File: `deploy/supervisor/fundflow-reverb.conf`

Setting	Value
Program name	<code>fundflow-reverb</code>
Command	<code>php /var/www/fundflow-saas/artisan</code> <code>reverb:start --no-interaction</code>
User	<code>www-data</code>
Autostart / autorestart	<code>true</code>
Log	<code>/var/www/fundflow-saas/storage/logs/reverb.log</code>

Edit the `command` / `directory` paths if the app is not deployed under `/var/www/fundflow-saas`.

Do not run two Reverb processes

- **Production:** only Supervisor should run `reverb:start`.
- A one-off `php artisan reverb:start` in SSH will bind port 8080 and block Supervisor (or the next deploy restart).
- If you need a clean slate:

```
sudo supervisorctl stop fundflow-reverb
# only if a stray process remains:
pgrep -af 'artisan reverb'
# kill <pid> if needed
sudo supervisorctl start fundflow-reverb
```