

```
Last login: Wed Apr  2 21:45:33 on ttys004
[minjooo@Minjoos-MacBook-Pro ~ % cd documents/GitHub
[minjooo@Minjoos-MacBook-Pro GitHub % git clone https://github.com/ominjoo/CSE110_lab1.git
Cloning into 'CSE110_lab1'...
remote: Enumerating objects: 3, done.
remote: Counting objects: 100% (3/3), done.
remote: Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
Receiving objects: 100% (3/3), done.
minjooo@Minjoos-MacBook-Pro GitHub % cd CSE110_lab1
[minjooo@Minjoos-MacBook-Pro CSE110_lab1 % git branch add-read-me
[minjooo@Minjoos-MacBook-Pro CSE110_lab1 % git checkout add-read-me
[Switched to branch 'add-read-me'
[minjooo@Minjoos-MacBook-Pro CSE110_lab1 % git add README.md
[minjooo@Minjoos-MacBook-Pro CSE110_lab1 % git commit -m "Update readme file"
[add-read-me 8403de8] Update readme file
 1 file changed, 2 insertions(+), 1 deletion(-)
[minjooo@Minjoos-MacBook-Pro CSE110_lab1 % git push
fatal: The current branch add-read-me has no upstream branch.
To push the current branch and set the remote as upstream, use

    git push --set-upstream origin add-read-me

To have this happen automatically for branches without a tracking
upstream, see 'push.autoSetupRemote' in 'git help config'.

[minjooo@Minjoos-MacBook-Pro CSE110_lab1 % git push --set-upstream origin add-read-me
Enumerating objects: 5, done.
Counting objects: 100% (5/5), done.
Writing objects: 100% (3/3), 278 bytes | 278.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0), pack-reused 0
remote:
remote: Create a pull request for 'add-read-me' on GitHub by visiting:
remote:   https://github.com/ominjoo/CSE110_lab1/pull/new/add-read-me
remote:
To https://github.com/ominjoo/CSE110_lab1.git
 * [new branch]      add-read-me -> add-read-me
branch 'add-read-me' set up to track 'origin/add-read-me'.
minjooo@Minjoos-MacBook-Pro CSE110_lab1 %
```