

REFERENCES CITED

References

- [1] International Technology Roadmap for Semiconductor, 2007. <http://www.itrs.net/>.
- [2] K. Kinam and J. Gitae. Memory technologies for sub-40nm node. In *IEEE International Electron Devices Meeting (IEDM)*, pages 27–30, 2007.
- [3] G. W. Burr, B. N. Kurdi, J. C. Scott, C. H. Lam, K. Gopalakrishnan, and R. S. Shenoty. Overview of candidate device technologies for storage-class memory. *IBM Journal Research and Device*, 52(4/5):449–464, 2008.
- [4] Ferdinando Bedeschi et. al. A bipolar-selected phase change memory featuring multi-level cell storage. *IEEE Journal of Solid-State Circuits*, 44(1):217–227, 2009.
- [5] J. H. Oh, J. H. Park, Y. S. Lim, H. S. Lim, Y. T. Oh, J. S. Kim, J. M. Shin, and et al. Full integration of highly manufacturable 512Mb PRAM based on 90nm technology. In *Proceedings of the IEEE International Electron Devices Meeting*, pages 2.6.1–2.6.4, 2006.
- [6] A. Pirovano, A. L. Lacaita, A. Benvenuti, F. Pellizzer, S. Hudgens, and R. Bez. Scaling analysis of phase-change memory technology. In *Proceedings of the IEEE International Electron Devices Meeting (IEDM)*, pages 29.6.1–29.6.4, 2003.
- [7] S. Lai. Current status of the phase change memory and its future. In *Proceedings of the IEEE International Electron Devices Meeting (IEDM)*, pages 10.1.1–10.1.4, 2003.
- [8] S. L. Cho et al. Highly scalable on-axis confined cell structure for high density PRAM beyond 256Mb. In *Symposium on VLSI Technology Digest of Technical Papers*, pages 96–97, 2005.
- [9] S. Kim and H.-S. P. Wong. Generalized phase change memory scaling rule analysis. In *Non-Volatile Semiconductor Memory Workshop*, 2006.
- [10] S. Lai and T. Lowrey. OUM – A 180nm nonvolatile memory cell element technology for standalone and embedded applications. In *IEEE International Electron Devices Meeting (IEDM)*, pages 36.5.1–36.5.4, 2001.
- [11] S. Raoux, G. W. Burr, M. J. Breitwisch, C. T. Rettner, Y.-C.Chen, R. M. Shelby, M. Salinga, and et al. Phase-change random access memory: A scalable technology. *IBM Journal Research and Device*, 52(4/5), 2008.
- [12] T. Nirschl et. al. Write strategies for 2 and 4-bit multi-level phase-change memory. In *Proceedings of the IEEE International Electron Device Meeting Technology (IEDM)*, pages 461–464, 2007.
- [13] W. S. Chen et. al. A novel cross-spacer phase change memory with ultra-small lithography independent contact area. In *IEEE International Electron Devices Meeting (IEDM)*, pages 319–322, 2007.
- [14] D. H. Im et. al. A unified 7.5nm dash-type confined cell for high performance PRAM device. In *IEEE International Electron Devices Meeting (IEDM)*, pages 1–4, 2008.

- [15] D. Ielmini, S. Lavizzari, D. Sharma, and A. L. Lacaita. Physical interpretation, modeling and impact on phase change memory (PCM) reliability of resistance drift due to chalcogenide structural relaxation. In *IEEE International Electron Devices Meeting (IEDM)*, pages 939–942, 2007.
- [16] P. Fantini, G. Betti Beneventi, A. Calderoni, L. Larcher, P. Pavan, and F. Pellizzer. Characterization and modelling of low-frequency noise in PCM devices. In *IEEE International Electron Devices Meeting (IEDM)*, pages 1–4, 2008.
- [17] D. Mantegazza, D. Ielmini, E. Varesi, A. Pirovano, and A. L. Lacaita. Statistical analysis and modeling of programming and retention in PCM arrays. In *IEEE International Electron Devices Meeting (IEDM)*, pages 311–314, 2007.
- [18] S. Hanzawa et. al. A 512KB embedded PRAM with 416KBs write throughput at 100 μ A cell write current. In *IEEE International Solid-State Circuits Conference (ISSCC)*, page 26.2, 2007.
- [19] K-J. Lee et. al. A 90nm 1.8V 512Mb diode-switch PRAM with 266MB/s read throughput. In *IEEE International Solid-State Circuits Conference (ISSCC)*, page 26.1, 2007.
- [20] F. Bedeschi et. al. A multi-level-cell bipolar-selected phase-change memory. In *IEEE International Solid-State Circuits Conference (ISSCC)*, page 23.5, 2008.
- [21] G. De Sandre et. al. A 90nm 4Mb embedded phase-change memory with 1.2V 12ns read access time and 1MB/s write throughput. In *IEEE International Solid-State Circuits Conference (ISSCC)*, page 14.7, 2010.
- [22] C. Villa, D. Mills, G. Barkley, H. Giduturi, S. Schippers, and D. Vimercati. A 45nm 1Gb 1.8V phase-change memory. In *IEEE International Solid-State Circuits Conference (ISSCC)*, page 14.8, 2010.
- [23] M. Hosomi et. al. A novel nonvolatile memory with spin torque transfer magnetization switching: Spin-RAM. In *Proceeding of IEEE International Electron Device Meeting (IEDM)*, pages 459–462, 2005.
- [24] Hiroaki Tanizaki, Takaharu Tsuji, Jun Otani, and et al. A high-density and high-speed 1T-4MTJ MRAM with Voltage Offset Self-Reference Sensing Scheme. In *IEEE Asian Solid-State Circuits Conference*, pages 303–306, 2006.
- [25] W. Zhao, E. Belhaire, Q. Mistral, C. Chappert, V. Javerliac, B. Dieny, and E. Nicolle. Macro-model of spin-transfer torque based magnetic tunnel junction device for hybrid magnetic-CMOS design. In *IEEE International Behavioral Modeling and Simulation Workshop*, pages 40–43, 2006.
- [26] T. M. Maffitt et. al. Design considerations for MRAM. *IBM Journal of Research and Development*, 2006.
- [27] M. Motoyoshi et. al. A study for 0.18 μ m high-density MRAM. In *IEEE VLSI Symposium on Technology*, pages 22–23, 2004.
- [28] Y.K. Ha et. al. MRAM with novel shaped cell using synthetic anti-ferromagnetic free layer. In *VLSI Symposium on Technology*, pages 24–25, 2004.

- [29] T. Kawahara et al. 2Mb spin-transfer torque ram (SPRAM) with bit-by-bit bidirectional current write and parallelizing-direction current read. In *Proc. IEEE International Solid-State Circuits Conference, Tech. Dig*, pages 480–617, 2007.
- [30] Z. Diao, Z. Li, S. Wang, Y. Ding, A. Panchula, E. Chen, L.-C. Wang, and Y. Huai. Spin-transfer torque switching in magnetic tunnel junctions and spin-transfer torque random access memory. *Journal of Physics: Condensed matter*, 19(16):165209, 2007.
- [31] S. Salahuddin, D. Datta, P. Srivastava, and S. Datta. Quantum transport simulation of tunneling based spin torque transfer (STT) devices: Design trade offs and torque efficiency. In *IEEE International Electron Devices Meeting (IEDM)*, pages 121–124, 2007.
- [32] R. Beach et. al. A statistical study of magnetic tunnel junctions for high-density spin torque transfer-MRAM (STT-MRAM). In *IEEE International Electron Devices Meeting (IEDM)*, pages 1–4, 2008.
- [33] T. Kishi et. al. Lower-current and fast switching of a perpendicular TMR for high speed and high density spin-transfer-torque MRAM. In *IEEE International Electron Devices Meeting (IEDM)*, pages 1–4, 2008.
- [34] K. Miura et. al. A novel SPRAM (SPin-transfer torque RAM) with a synthetic ferrimagnetic free layer for higher immunity to read disturbance and reducing write-current dispersion. In *IEEE VLSI Symposium on Technology*, pages 234–235, 2007.
- [35] M. Durlam et. al. A 1-Mbit MRAM based on 1T1MTJ bit cell integrated with copper interconnects. *IEEE Journal of Solid-State Circuits*, 38(5):769–773, 2003.
- [36] X. Lou, Z. Gao, D. V. Dimitrov, and M. X. Tang. Demonstration of multilevel cell spin transfer switching in MgO magnetic tunnel junctions. *Applied Physics Letter*, 93:242502, 2008.
- [37] R. Nebashi et. al. A 90nm 12ns 32Mb 2T1MTJ MRAM. In *IEEE International Solid-State Circuits Conference (ISSCC)*, pages 462–463, 2009.
- [38] T. W. Andre, J. J. Nahas, C. K. Subramanian, B. J. Garni, H. S. Lin, A. Omair, and Jr. W. L. Martino. A 4-Mb 0.18- μ m 1T1MTJ toggle MRAM with balanced three input sensing scheme and locally mirrored unidirectional write drivers. *IEEE Jour. Of Solid-State Circuits*, 40(1):301–309, 2005.
- [39] T. Kawahara et. al. 2 Mb SPRAM (SPin-transfer torque RAM) with bit-by-bit bi-directional current write and parallelizing-direction current read. *IEEE Jour. of Solid-State Circuits*, 43(1):109–120, 2008.
- [40] Y. Chen, X. Wang, H. Li, H. Liu, and D. Dimitrov. Design margin exploration of spin-torque transfer RAM (SPRAM). In *International Symposium on Quality Electronic Design*, pages 684–690, 2008.
- [41] H. Li and Y. Chen. An overview of nonvolatile memory technology and the implication for tools and architectures. In *Design, Automation and Test in Europe Conference and Exhibition*, pages 731–736, 2009.
- [42] J. F. Gibbons and W. E. Beadle. Switching properties of thin NiO films. *Solid State Electronics*, 7:785–797, 1964.

- [43] M. Fujimoto, H. Koyama, M. Konagai, Y. Hosoi, K. Ishihara, S. Ohnishi, and N. Awaya. TiO₂ anatase nanolayer on TiN thin film exhibiting high-speed bipolar resistive switching. *Applied Physics Letter*, 89(22):223509, 2006.
- [44] R. Jung et. al. Decrease in switching voltage fluctuation of Pt/NiO_x/Pt structure by process control. *Applied Physics Letter*, 91(2):022112, 2007.
- [45] M. Janousch, G. I. Meijer, U. Staub, B. Delley, S. F. Karg, and B. P. Andreasson. Role of oxygen vacancies in Cr-doped SrTiO₃ for resistance-change memory. *Adv. Mater.*, 19(7):2232–2235, 2007.
- [46] S. Q. Liu, N. J. Wu, and A. Ignatiev. Electric-pulse-induced reversible resistance change effect in magnetoresistive films. *Applied Physics Letter*, 76(19):2749, 2000.
- [47] S. T. Hsu and T. Li. Resistance random access memory switching mechanism. *Journal of Applied Physics*, 101(2):024517, 2007.
- [48] M.N. Kozicki, M. Balakrishnan, C. Gopalan, C. Ratnakumar, and Mitkova. Programmable metallization cell memory based on Ag-Ge-S and Cu-Ge-S solid electrolytes. In *Non-Volatile Memory Technology Symposium*, pages 83–89, 2005.
- [49] I. H. Inoue, S. Yasuda, H. Akinaga, and H. Takagi. Nonpolar resistance switching of metal/binary-transition-metal oxides/metal sandwiches: Homogeneous/inhomogeneous transition of current distribution. *Physical Review B*, 77(3):035105, 2008.
- [50] L. O. Chua. Memristor – the missing circuit element. *IEEE Trans. Circuit Theory*, CT-18(5):507–519, 1971.
- [51] J. M. Tour and T. He. The fourth element. *Nature*, 453(7191):42–43, 2008.
- [52] Dmitri B. Strukov, Gregory S. Snider, Duncan R. Stewart, and R. StanleyWilliams. The missing memristor found. *Nature*, 453:80–83, 2008.
- [53] L. O. Chua. Memristive devices and systems. *Proc. IEEE*, 64:209–223, 1976.
- [54] Yu. V. Pershin and M. Di Ventra. Spin memristive systems: Spin memory effects in semiconductor spintronics. *Phys. Rev. B, Condens. Matter*, 78(11):113309, 2008.
- [55] X. Wang et al. Spin memristor through spin-torque-induced magnetization motion. *IEEE Electron Device Lett.*, 30(3):294–297, 2009.
- [56] Y. Chen and X. Wang. Compact modeling and corner analysis of spintronic memristor. In *IEEE/ACM International Symposium on Nanoscale Architectures 2009 (Nanoarch09)*, pages 7–12, 2009.
- [57] R. C. Johnson. Superlattices enable small, fast, low-power RRAM, 2010. <http://www.eetimes.com/showArticle.jhtml?articleID=222301490>.
- [58] Rabindranath Balasubramanian and Gregory Bakker. Programmable system on a chip for power-supply voltage and current monitoring and control, 2009. US Patent pending, application number 12/350,419.
- [59] Jongtae Kwak. Delay line circuit, 2009. US Patent US 2009/0243689 A1.

- [60] Mark LaPedus. Unity rolls ‘storageclass’ memory technology, 2009. <http://www.eetimes.eu/217500737>.
- [61] R. Colin Johnson. Memristors ready for prime time, 2008. <http://www.eetimes.com/showArticle.jhtml?articleID=208803176>.
- [62] R. Hoding. NEC develops 32 Megabit MRAM for embedded SoCs, 2009. EETimes, Feb. 12.
- [63] F. Pellizzer, A. Pirovano, F. Ottogalli, M. Magistretti, M. Scaravaggi, and et al. Novel μ Trench Phase-Change Memory Cell for Embedded and Stand-Alone Non-Volatile Memory Applications. In *IEEE Symposium on VLSI Technology 2004*, pages 18–19, 2004.
- [64] Y. Xie, G. Loh, B. Black, and K. Bernstein. Design space exploration for 3D architectures. *ACM Journal of Emerging Technologies in Computing Systems*, 2(2):65–103, 2006.
- [65] Xiangyu Dong, Xiaoxia Wu, Guangyu Sun, Yuan Xie, Hai Li, and Yiran Chen. Circuit and microarchitecture evaluation of 3D stacking magnetic RAM (MRAM) as a universal memory replacement. In *45th ACM/IEEE Design Automation Conference (DAC)*, pages 554–559, 2008.
- [66] <http://www.synopsys.com>.
- [67] <http://www.cadence.com>.
- [68] Spintronic memristors, March 2009. <http://www.spectrum.ieee.org/semiconductors/devices/spintronic-memristors/0>.
- [69] Yuh-Fang Tsai, Yuan Xie, N. Vijaykrishnan, and M. J. Irwin. Three-dimensional cache design exploration using 3DCacti. In *International Conference on Computer Design (ICCD)*, pages 519–524, 2005.
- [70] Yuh-Fang Tsai, Feng Wang, Yuan Xie, N. Vijaykrishnan, and M. J. Irwin. Design space exploration for 3-D cache. *IEEE Transactions on Very Large Scale Integration (VLSI) Systems*, 16(4):444–455, 2008.
- [71] Guangyu Sun, Xiangyu Dong, Yuan Xie, Jian Li, and Yiran Chen. A novel architecture of the 3D stacked MRAM L2 cache for CMPs. In *IEEE 15th International Symposium on High Performance Computer Architecture, 2009.*, pages 239–249, 2009.
- [72] Xiangyu Dong, Norm Jouppi, and Yuan Xie. PCRAMsim: System-level performance, energy, and area modeling for phase-change RAM. In *Proceedings of International Conference on Computer-Aided Design (ICCAD)*, pages 269–275, 2009.
- [73] Benjamin Lee, Engin Ipek, Onur Mutlu, and Doug Burger. Architecting phase change memory as a scalable DRAM alternative. In *The 36th International Symposium on Computer Architecture (ISCA)*, 2009.
- [74] Moinuddin K. Qureshi, Viji Srinivasan, and Jude A. Rivers. Scalable High Performance Main Memory System Using Phase-Change Memory Technology. In *36th International Symposium on Computer Architecture (ISCA)*, 2009.
- [75] I.G. Baek et. al. Multi-layer cross-point binary oxide resistive memory (OxRRAM) for post-NAND storage application. In *IEEE International Electron Devices Meeting (IEDM)*, pages 750–753, 2005.

- [76] A. Asenov, S. Kaya, and A.R. Brown. Intrinsic parameter fluctuations in decananometer mosfets introduced by gate line edge roughness. *IEEE Transactions on Electron Devices*, 50(5):1254–1260, 2003.
- [77] S. Tehrani et al. Recent developments in magnetic tunnel junction MRAM. In *IEEE Trans. Magn.*, volume 36, pages 2752–2757, 2000.
- [78] Gitae Jeong, Wooyoung Cho, S. Ahn, Hongsik Jeong, Gwanhyeob Koh, Youngnam Hwang, and K. Kim. A 0.24 μm 2.0-V 1T1MTJ 16-kb nonvolatile magnetoresistance RAM with self-reference sensing scheme. *IEEE Jour. of Solid-State Circuits*, 38(11):1906–1910, 2003.
- [79] H. Li, Y. Chen, H. Liu, K. Kim, and H. Huang. Spin-transfer torque memory self-reference read scheme. US Patent pending, application number 12/147,723.
- [80] A. Pirovano, A. L. Lacaita, S. A. Kostylev, A. Benvenuti, and R. Bez. Low-field amorphous state resistance and threshold voltage drift in chalcogenide materials. *IEEE Transactions on Electron Devices*, 51:714–719, 2004.
- [81] Y. Ho, G. M. Huang, and P. Li. Nonvolatile memristor memory: device characteristics and design implications. In *IEEE/ACM 2009 International Conference on Computer-Aided Design (ICCAD)*, pages 482–490, 2009.
- [82] W. Xu and T. Zhang. Using time-aware memory sensing to address resistance drift issue in multi-level phase change memory. In *IEEE International Symposium on Quality Electronic Design (ISQED)*, 2010.
- [83] Chih-Yuan Lu, Kuang-Yeu Hsieh, and Rich Liu. Future challenges of flash memory technologies. *Microelectronic Engineering*, 86(3):283–286, 2009.
- [84] Man F. Yan. Non-ohmic device using TiO_2 . US Patent number 4430255.
- [85] Ihun Song et. al. Short channel characteristics of Gallium-Indium-Zinc-Oxide thin film transistors for three-dimensional stacking memory. *IEEE Electron Device Letters*, 29:549–552, 2008.
- [86] Agarwal, H. Li, and K. Roy. Drg-cache: A data retention gated-ground cache for low power. In *39th Design Automation Conference (DAC)*, pages 473–478, 2002.
- [87] Agarwal, H. Li, and K. Roy. A single-vt low-leakage gated-ground cache for deep submicron. *IEEE Jour. Of Solid-State Circuits*, 35(2):319–328, 2003.
- [88] S. Bhunia, H. Li, and K. Roy. A high performance iddq testable cache for scaled cmos technologies. In *IEEE Proceedings of the 11th Asian Test Symposium (ATS’02)*, pages 157–162, 2002.
- [89] Y. Chen, H. Li, H. Liu, Y. Lu, and S. Xue. Data devices including multiple error correction codes and methods of utilizing. US Patent pending, application number 112/198,516.
- [90] H. Li, Y. Chen, D. Setiadi, H. Liu, and B. Lee. Defective bit scheme for multi-layer integrated memory device. US Patent pending, application number 12/502,194.
- [91] Y. Chen, H. Li, H. Liu, R. Wang, and D. Dimitrov. Spin-transfer torque memory non-destructive self-reference read. US Patent pending, application number 112/147,727.

- [92] H. Li, Y. Chen, H. Liu, and X. Wang. Static source line in stat-ram. US Patent pending, application number 12/242,331.
- [93] Y. Chen, H. Li, H. Liu, Y. Lu, and Y. Li. Transmission gate-based spin-transfer torque memory unit. US Patent pending, application number 112/170,549.
- [94] H. Li, Y. Chen, H. Liu, and H. Huang. Non-volatile resistive sense memory on-chip cache. US Patent pending, application number 12/250,027.
- [95] H. Li, Y. Chen, H. Liu, H. Huang, and R. Wang. Write current compensation using word line boosting circuitry. US Patent pending, application number 12/426,098.
- [96] M. Mutyam, Feng Wang, R. Krishnan, V. Narayanan, M. Kandemir, and Y. Xie and M. J. Irwin. Process-variation-aware adaptive cache architecture and management. *IEEE Transactions on Computers*, 58(7):865–877, 2009.
- [97] B. Vaidyanathan, Yu Wang, and Yuan Xie. Cost-aware lifetime yield analysis of heterogeneous 3D on-chip cache. In *IEEE International Workshop on Memory Technology, Design, and Testing*, pages 65–70, 2009.
- [98] Xiaoxia Wu, Jian Li, Lixin Zhang, Evan Speight, Ram Rajamony, and Yuan Xie. Hybrid cache architecture with disparate memory technologies. In *International Conference on Computer Architecture (ISCA)*, pages 34–45, 2009.
- [99] Prasanth Mangalagiri et. al. A low-power phase change memory based hybrid cache architecture. In *Proceedings of the 18th ACM Great Lakes symposium on VLSI*, pages 395–398, 2008.
- [100] <http://www.cse.psu.edu/~yuanxie/>.
- [101] S. Sridharan, M. DeBole, Guangyu Sun, Yuan Xie, and V. Narayanan. A criticality-driven microarchitectural three dimensional (3d) floorplanner. In *Asia and South Pacific Design Automation Conference*, pages 763–768, 2009.
- [102] Dongkook Park, S. Eachempati, R. Das, A. K. Mishra, Y. Xie, N. Vijaykrishnan, and C. R. Das. MIRA: A multi-layered on-chip interconnect router architecture. In *35th International Symposium on Computer Architecture (ISCA)*, pages 251–261, 2008.
- [103] F. Li, C. Nicopoulos, T. Richardson, Y. Xie, N. Vijaykrishnan, and M. Kandemir. Design and management of 3D chip multiprocessors using network-in-memory. In *International Symposium on Computer Architecture (ISCA’06)*, 2006.
- [104] Gabriel H. Loh, Yuan Xie, and Bryan Black. Processor design in 3D die-stacking technologies. *IEEE Micro*, 27(3):31–48, 2007.
- [105] Y. Xie, G. Loh, B. Black, and K. Bernstein. Tutorial: 3D integration for microarchitecture. In *The 39th Annual IEEE/ACM International Symposium on Microarchitecture*, 2006.
- [106] Xiangyu Dong and Yuan Xie. System-level cost analysis and design exploration for three-dimensional integrated circuits (3D ICs). In *Asia and South Pacific Design Automation Conference (ASP-DAC 2009)*, pages 234–241, 2009.
- [107] Xiaoxia Wu, Paul Frankstein, and Yuan Xie. Scan chain design for three-dimensional(3D) ICs. In *International Conference on Computer Design*, 2007.

- [108] Xiaoxia Wu, Yibo Chen, Yuan Xie, and Krish Chakrabarty. Test-access mechanism optimization for core-based three-dimensional SOCs. In *International Conference on Computer Design*, 2008.
- [109] W. L. Hung, G. M. Link, Y. Xie, N. Vijaykrishnan, and M. J. Irwin. Interconnect and thermal-aware floorplanning for 3D microprocessors. In *International Symposium on Quality Electronic Device*, pages 98–104, 2006.
- [110] O. Ozturk, Feng Wang, M. Kandemir, and Yuan Xie. Optimal topology exploration for application-specific 3D architectures. In *Asia and South Pacific Design Automation Conference*, page 6, 2006.