



[Course](#) > [LAB GUIDE](#) > [Lab 6 - Using the N...](#) > Using the Network ...


Using the Network Hierarchy

Using the Network Hierarchy


In this lab, we will explore the Network Hierarchy feature of Qradar. We will create and view a Network Hierarchy Object.

Create a Network Object


1. Navigate to the **Admin** tab and click the **Network Hierarchy** icon in the System configuration section.




2. Click **Add**.



Toolbar with buttons: Add, Edit, Delete. Search input field: Input network name.

3. In the Add network window, click the  **Yellow gear wheel** icon.

4. For **Name** in the Add a new Group window, enter the following text. QRadar.Clients and Click **Save**.



Add a new group

Name:

Save Cancel

5. In the Add network Window, enter the values shown below.


Field	Value
Name	Student
Description	Exercise
IP/CIDR(s)	192.168.42.205

6. Make sure you click the plus icon to add the IP/CIDR(s) value to the object's list.



IP/CIDR(s):  

7. Using the similar process from steps 2 to 6, add a new network object as per the below data.

a. In the Add network window, click the . **Yellow gear wheel icon.**

b. In the Name field, enter QRadar.Managed_Hosts. Click **Save**.

Add a new group


Name:

SaveCancel

c. In the add network window, enter the values shown as below.

Field	Value
Name	<u>On_Premise</u>
Description	Exercise
IP/CIDR(s)	192.168.10.20/32 192.168.10.16/30 192.168.10.12/30 192.168.42.150/31

8. Close the Network Hierarchy Window and Click **Deploy Changes**.




Open the Network hierarchy tab and verify that the **Student** and **On_Premise** network objects are listed.

QRadar		
Clients		
Student	192.168.42.205/32	Exercise
Managed_Hosts		
On_Premise	192.168.10.12/30 192.168.10.16/30 192.168.10.20/32 192.168.42.150/31	Exercise

View Network Objects in Flow

1. To view incoming flows, double-click the **Network Activity** tab.



Note: The double-click resets the tab to its default settings.

2. Wait until you see flows with the IP addresses 192.168.42.150 and 192.168.42.205.

3. To pause the incoming events, click the **Pause**  icon in the upper-right corner of the QRadar user interface.

4. Hover the mouse over either of the IP addresses and review the Network field information.

5. Open a remote shell to the QRadar VM. And run the following commands:


```
cd /labfiles
```

```
./startPcap.sh
```

```
[root@allinone742 labfiles]#  
[root@allinone742 labfiles]# ./startPcap.sh  
Warning: /labfiles/flows/bittorrent1.pcap was captured using a snaplen of 128 bytes. This may mean you have truncated packets.  
Actual: 18 packets (1539 bytes) sent in 13.06 seconds  
Rated: 117.7 Bps, 0.000 Mbps, 1.37 pps  
Flows: 12 flows, 0.91 fps, 16 flow packets, 2 non-flow  
Statistics for network device: ens33  
    Successful packets: 18  
    Failed packets: 0  
    Truncated packets: 0  
    Retried packets (ENOBUFS): 0  
    Retried packets (EAGAIN): 0  
Warning: /labfiles/flows/bittorrent2.pcap was captured using a snaplen of 64 bytes. This may mean you have truncated packets.  
Actual: 53 packets (3392 bytes) sent in 4.42 seconds  
Rated: 766.4 Bps, 0.006 Mbps, 11.97 pps  
Flows: 52 flows, 11.75 fps, 53 flow packets, 0 non-flow  
Statistics for network device: ens33  
    Successful packets: 53  
    Failed packets: 0  
    Truncated packets: 0  
    Retried packets (ENOBUFS): 0  
    Retried packets (EAGAIN): 0  
Warning: /labfiles/flows/bittorrent3.pcap was captured using a snaplen of 64 bytes. This may mean you have truncated packets.
```

6. In the browser return to the Network Activity Tab.

7. If refresh of the Network Activity tab is paused, press the **Play** button in the upper-right corner of the QRadar user interface. Wait for at least one minute.

8. To display only flows with destination IP addresses part of the network objects you created, click **Add Filter** .

a. In the Add Filter window, enter the values shown below.

Field	Value
Parameter	Destination Network
Operator	Equals
Value	Qradar.Managed_Hosts

b. Click **Add Filter**.

Add Filter

Parameter:

Operator:

Value:

Destination Network

Equals

QRadar.Managed_Hosts

Add Filter
Cancel

9. If there are no rows with a Destination Network of **On_Premise** listed.
10. Change the View to show the **Last Hour**.
11. Change the Display to **Destination Network**.
12. Use the right-click option menu on the Destination IP column to apply **Filter on Destination IP is not 192.168.42.150**.
13. Verify that you only see rows with Destination IP 192.168.10.12.
14. However the mouse over the Destination IP address and review the **Network** Field Information.
15. Navigate to the **Admin** tab, click the **Network Hierarchy** icon in the System Configuration section.

- a. Click the plus signs in front of Qradar and Managed_Hosts.
- b. Double click **On_Premise**.
- c. Select **192.168.10.12/30** from the IP/CIDR(s) list and click the red **X**.
- d. Click **Save**.
- e. Close the **Network Hierarchy** Window.
- f. Click **Deploy Changes**.

16. Return to the Network Activity page.

- a. Hover the mouse over the Destination IP address and review the **Network** field information to verify that it no longer displays **QRadar.Managed_Hosts.On_Premise**.
 - b. Clear the **Destination Network is QRadar.Managed_Hosts** filter.
 - c. Reapply the **Destination Network is QRadar.Managed_Hosts** filter.
 - d. Verify that the result set is now empty.
-