ORION OIL

S-32, MIDC Bhosari, Pune - 411026 Cell : +91 82756 35579
Email : orionoilandgas@gmail.com.Website : www.orionoilandgas.in

---

TECHNICAL DATA SHEET

REV: 1

DATE OF ISSUING : 15.12.2026

PRODUCT : RE-RECYCLED BASE OIL (RRBO) SN 150 EQUIVALENT

Sr. No	Parameter	Test Method	Target Specification	Typical Value
1	Appearance	Visual	Clear and Bright	Clear and Bright
2	Colour	ASTM D-1500	1.5 – 2.0 Max	L 1.5
3	Density at 29.5°C, g/cc	ASTM D-1298	0.860 – 0.875	0.865
4	K. Viscosity at 40°C, cSt	ASTM D-445	28.0 – 32.0	30.5
5	K. Viscosity at 100°C, cSt	ASTM D-445	5.0 – 5.5	5.3
6	Viscosity Index	ASTM D-2270	Min 95	98
7	Total Acid Number, mgKOH/gm	ASTM D-974	Max 0.05	0.02
8	Pour Point °C	ASTM D-97	-3 to -6	-6
9	Flash Point °C (COC)	ASTM D-92	Min 200	215

Disclaimer: The values listed in the final column are typical values based on standardized refining performance. We will provide an actual Certificate of Analysis (COA) issued by an independent NABL-accredited facility, along with all other required technical documents, upon dispatch.

Balraj Tavanandi
AUTHORIZED SIGNATORY