ORION OIL

S-32, MIDC Bhosari, Pune - 411026 Cell : +91 82756 35579
Email : orionoilandgas@gmail.com.Website : www.orionoilandgas.in

---

TECHNICAL DATA SHEET

REV: 1

DATE OF ISSUING : 15.12.2026

PRODUCT : RE-RECYCLED BASE OIL (RRBO) SN 300 EQUIVALENT

Sr. No	Parameter	Test Method	Target Specification	Typical Value
1	Appearance	Visual	Clear and Bright	Clear and Bright
2	Colour	ASTM D-1500	2.0 – 2.5 Max	L 2.0
3	Density at 29.5°C, g/cc	ASTM D-1298	0.875 – 0.890	0.880
4	K. Viscosity at 40°C, cSt	ASTM D-445	55.0 – 65.0	59.5
5	K. Viscosity at 100°C, cSt	ASTM D-445	8.0 – 9.0	8.4
6	Viscosity Index	ASTM D-2270	Min 95	98
7	Total Acid Number, mgKOH/gm	ASTM D-974	Max 0.05	0.02
8	Pour Point °C	ASTM D-97	-3 to -6	-6
9	Flash Point °C (COC)	ASTM D-92	Min 220	232

Disclaimer: The values listed in the final column are typical values based on standardized refining performance. We will provide an actual Certificate of Analysis (COA) issued by an independent NABL-accredited facility, along with all other required technical documents, upon dispatch.

Balraj Tavanandi
AUTHORIZED SIGNATORY