

Initialization

- Consider standard building block of NN in terms of *preactivations*:

$$\begin{aligned}\mathbf{f}_k &= \boldsymbol{\beta}_k + \boldsymbol{\Omega}_k \mathbf{h}_k \\ &= \boldsymbol{\beta}_k + \boldsymbol{\Omega}_k \mathbf{a}[\mathbf{f}_{k-1}]\end{aligned}$$

- Set all the biases to 0

$$\boldsymbol{\beta}_k = \mathbf{0}$$

- Weights normally distributed
 - mean 0
 - variance σ_{Ω}^2
- What will happen as we move through the network if σ_{Ω}^2 is very small?
- What will happen as we move through the network if σ_{Ω}^2 is very large?

Backprop summary

Backward pass: We start with the derivative $\partial\ell_i/\partial\mathbf{f}_K$ of the loss function ℓ_i with respect to the network output \mathbf{f}_K and work backward through the network:

$$\begin{aligned}\frac{\partial\ell_i}{\partial\boldsymbol{\beta}_k} &= \frac{\partial\ell_i}{\partial\mathbf{f}_k} & k \in \{K, K-1, \dots, 1\} \\ \frac{\partial\ell_i}{\partial\boldsymbol{\Omega}_k} &= \frac{\partial\ell_i}{\partial\mathbf{f}_k} \mathbf{h}_k^T & k \in \{K, K-1, \dots, 1\} \\ \frac{\partial\ell_i}{\partial\mathbf{f}_{k-1}} &= \mathbb{I}[\mathbf{f}_{k-1} > 0] \odot \left(\boldsymbol{\Omega}_k^T \frac{\partial\ell_i}{\partial\mathbf{f}_k} \right), & k \in \{K, K-1, \dots, 1\}\end{aligned}\tag{7.13}$$

where \odot denotes pointwise multiplication and $\mathbb{I}[\mathbf{f}_{k-1} > 0]$ is a vector containing ones where \mathbf{f}_{k-1} is greater than zero and zeros elsewhere. Finally, we compute the derivatives with respect to the first set of biases and weights:

$$\begin{aligned}\frac{\partial\ell_i}{\partial\boldsymbol{\beta}_0} &= \frac{\partial\ell_i}{\partial\mathbf{f}_0} \\ \frac{\partial\ell_i}{\partial\boldsymbol{\Omega}_0} &= \frac{\partial\ell_i}{\partial\mathbf{f}_0} \mathbf{x}_i^T\end{aligned}$$

Initialization

- Need for initialization
- He initialization
- Interlude: Expectations
- Show that $\mathbb{E}[f'_i] = 0$
- Write variance of pre-activations f' in terms of activations h in previous layer

$$\sigma_{f'}^2 = \sigma_{\Omega}^2 \sum_{j=1}^{D_h} \mathbb{E}[h_j^2]$$

- Write variance of pre-activations f' in terms of pre-activations f in previous layer

$$\sigma_{f'}^2 = \frac{D_h \sigma_{\Omega}^2 \sigma_f^2}{2}$$




Figure 7.4 Weight initialization. Consider a deep network with 50 hidden layers and $D_h = 100$ hidden units per layer. The network has a 100 dimensional input \mathbf{x} initialized with values from a standard normal distribution, a single output fixed at $y = 0$, and a least squares loss function. The bias vectors β_k are initialized to zero and the weight matrices Ω_k are initialized with a normal distribution with mean zero and five different variances $\sigma_{\Omega}^2 \in \{0.001, 0.01, 0.02, 0.1, 1.0\}$. a)


He initialization (assumes ReLU)

- Forward pass: want the variance of hidden unit activations in layer $k+1$ to be the same as variance of activations in layer k :

$$\sigma_{\Omega}^2 = \frac{2}{D_h} \quad \leftarrow \text{Number of units at layer } k$$

- Backward pass: want the variance of gradients at layer k to be the same as variance of gradient in layer $k+1$:

$$\sigma_{\Omega}^2 = \frac{2}{D_{h'}} \quad \leftarrow \text{Number of units at layer } k+1$$



$$\sigma_{\Omega}^2 = \frac{2}{D_h} = \frac{2}{100} = 0.02$$

Figure 7.4 Weight initialization. Consider a deep network with 50 hidden layers and $D_h = 100$ hidden units per layer. The network has a 100 dimensional input \mathbf{x} initialized with values from a standard normal distribution, a single output fixed at $y = 0$, and a least squares loss function. The bias vectors β_k are initialized to zero and the weight matrices Ω_k are initialized with a normal distribution with mean zero and five different variances $\sigma_{\Omega}^2 \in \{0.001, 0.01, 0.02, 0.1, 1.0\}$. a)

Expectations

Function $g[\bullet]$	Expectation
x	mean, μ
x^k	k th moment about zero
$(x - \mu)^k$	k th moment about the mean
$(x - \mu)^2$	variance
$(x - \mu)^3$	skew
$(x - \mu)^4$	kurtosis

Table B.1 Special cases of expectation. For some functions $g[x]$, the expectation $\mathbb{E}[g[x]]$ is given a special name. Here we use the notation μ_x to represent the mean with respect to random variable x .

Rules for manipulating expectation

$$\mathbb{E}[k] = k$$

$$\mathbb{E}[k \cdot g[x]] = k \cdot \mathbb{E}[g[x]]$$

$$\mathbb{E}[f[x] + g[x]] = \mathbb{E}[f[x]] + \mathbb{E}[g[x]]$$

$$\mathbb{E}[f[x]g[y]] = \mathbb{E}[f[x]]\mathbb{E}[g[y]] \quad \text{if } x, y \text{ independent}$$

Now let's prove:

$$\mathbb{E} [(x - \mu)^2] = \mathbb{E}[x^2] - \mathbb{E}[x]^2$$

Keeping in mind:

$$\mathbb{E}[x] = \mu$$

Rule 1: $\mathbb{E}[k] = k$

Rule 2: $\mathbb{E}[k \cdot g[x]] = k \cdot \mathbb{E}[g[x]]$

Rule 3: $\mathbb{E}[f[x] + g[x]] = \mathbb{E}[f[x]] + \mathbb{E}[g[x]]$

Def'n $\mathbb{E}[x] = \mu$



$$\begin{aligned}\mathbb{E}[(x - \mu)^2] &= \mathbb{E}[x^2 - 2x\mu + \mu^2] \\&= \mathbb{E}[x^2] - \mathbb{E}[2x\mu] + \mathbb{E}[\mu^2] \\&= \mathbb{E}[x^2] - 2\mu\mathbb{E}[x] + \mu^2 \\&= \mathbb{E}[x^2] - 2\mu^2 + \mu^2 \\&= \mathbb{E}[x^2] - \mu^2 \\&= \mathbb{E}[x^2] - E[x]^2\end{aligned}$$

Initialization

- Need for initialization
- He initialization
- Interlude: Expectations
- Show that $\mathbb{E}[f'_i] = 0$
- Write variance of pre-activations f' in terms of activations h in previous layer

$$\sigma_{f'}^2 = \sigma_{\Omega}^2 \sum_{j=1}^{D_h} \mathbb{E}[h_j^2]$$

- Write variance of pre-activations f' in terms of pre-activations f in previous layer

$$\sigma_{f'}^2 = \frac{D_h \sigma_{\Omega}^2 \sigma_f^2}{2}$$

Initialization

- Consider standard building block of NN in terms of *preactivations*:

$$\begin{aligned}\mathbf{f}_k &= \boldsymbol{\beta}_k + \boldsymbol{\Omega}_k \mathbf{h}_k \\ &= \boldsymbol{\beta}_k + \boldsymbol{\Omega}_k \mathbf{a}[\mathbf{f}_{k-1}]\end{aligned}$$

- Set all the biases to 0

$$\boldsymbol{\beta}_k = \mathbf{0}$$

- Weights normally distributed

- mean 0
- variance σ_Ω^2

- What will happen as we move through the network if σ_Ω^2 is very small?
- What will happen as we move through the network if σ_Ω^2 is very large?

Aim: keep variance same between two layers

$$\mathbf{f}' = \boldsymbol{\beta} + \boldsymbol{\Omega}\mathbf{h}$$

Consider the mean of the pre-activations:

$$\mathbb{E}[f'_i] = \mathbb{E} \left[\beta_i + \sum_{j=1}^{D_h} \Omega_{ij} h_j \right]$$

Rule 1:	$\mathbb{E}[k] = k$
Rule 2:	$\mathbb{E}[k \cdot g[x]] = k \cdot \mathbb{E}[g[x]]$
Rule 3:	$\mathbb{E}[f[x] + g[x]] = \mathbb{E}[f[x]] + \mathbb{E}[g[x]]$
Rule 4:	$\mathbb{E}[f[x]g[y]] = \mathbb{E}[f[x]]\mathbb{E}[g[y]]$ if x, y independent

$$\mathbb{E}[f'_i] = \mathbb{E} \left[\beta_i + \sum_{j=1}^{D_h} \Omega_{ij} h_j \right]$$

$$= \mathbb{E} [\beta_i] + \sum_{j=1}^{D_h} \mathbb{E} [\Omega_{ij} h_j]$$

Set all the biases to 0

$$= \mathbb{E} [\beta_i] + \sum_{j=1}^{D_h} \mathbb{E} [\Omega_{ij}] \mathbb{E} [h_j]$$

Weights normally distributed

mean 0

variance σ_{Ω}^2

$$= 0 + \sum_{j=1}^{D_h} 0 \cdot \mathbb{E} [h_j] = 0$$

Initialization

- Need for initialization
- He initialization
- Interlude: Expectations
- Show that $\mathbb{E}[f'_i] = 0$
- Write variance of pre-activations f' in terms of activations h in previous layer

$$\sigma_{f'}^2 = \sigma_{\Omega}^2 \sum_{j=1}^{D_h} \mathbb{E}[h_j^2]$$

- Write variance of pre-activations f' in terms of pre-activations f in previous layer

$$\sigma_{f'}^2 = \frac{D_h \sigma_{\Omega}^2 \sigma_f^2}{2}$$

Aim: keep variance same between two layers

$$\mathbf{f}' = \boldsymbol{\beta} + \boldsymbol{\Omega}\mathbf{h}$$

$$\mathbf{h} = \mathbf{a}[\mathbf{f}],$$

$$\sigma_{f'}^2 = \mathbb{E}[f_i'^2] - \mathbb{E}[f_i']^2$$

$$\longrightarrow \mathbb{E}[(x - \mu)^2] = \mathbb{E}[x^2] - \mathbb{E}[x]^2$$

Rule 1:	$\mathbb{E}[k] = k$
Rule 2:	$\mathbb{E}[k \cdot g[x]] = k \cdot \mathbb{E}[g[x]]$
Rule 3:	$\mathbb{E}[f[x] + g[x]] = \mathbb{E}[f[x]] + \mathbb{E}[g[x]]$
Rule 4:	$\mathbb{E}[f[x]g[y]] = \mathbb{E}[f[x]]\mathbb{E}[g[y]]$ if x, y independent

$$\begin{aligned}\sigma_{f'}^2 &= \mathbb{E}[f_i'^2] - \mathbb{E}[f_i']^2 \\ &= \mathbb{E} \left[\left(\beta_i + \sum_{j=1}^{D_h} \Omega_{ij} h_j \right)^2 \right] - 0 \\ &= \mathbb{E} \left[\left(\sum_{j=1}^{D_h} \Omega_{ij} h_j \right)^2 \right]\end{aligned}$$

Set all the biases to 0

Weights normally distributed
mean 0
variance σ_{Ω}^2

$$\begin{aligned}&= \sum_{j=1}^{D_h} \mathbb{E} [\Omega_{ij}^2] \mathbb{E} [h_j^2] \\ &= \sum_{j=1}^{D_h} \sigma_{\Omega}^2 \mathbb{E} [h_j^2] = \sigma_{\Omega}^2 \sum_{j=1}^{D_h} \mathbb{E} [h_j^2]\end{aligned}$$

Initialization

- Need for initialization
- He initialization
- Interlude: Expectations
- Show that $\mathbb{E}[f'_i] = 0$
- Write variance of pre-activations f' in terms of activations h in previous layer

$$\sigma_{f'}^2 = \sigma_{\Omega}^2 \sum_{j=1}^{D_h} \mathbb{E}[h_j^2]$$

- Write variance of pre-activations f' in terms of pre-activations f in previous layer

$$\sigma_{f'}^2 = \frac{D_h \sigma_{\Omega}^2 \sigma_f^2}{2}$$

$$\begin{aligned}
\sigma_{f'}^2 &= \sigma_{\Omega}^2 \sum_{j=1}^{D_h} \mathbb{E} [h_j^2] \\
&= \sigma_{\Omega}^2 \sum_{j=1}^{D_h} \mathbb{E} [\text{ReLU}[f_j]^2] \\
&= \sigma_{\Omega}^2 \sum_{j=1}^{D_h} \int_{-\infty}^{\infty} \text{ReLU}[f_j]^2 Pr(f_j) df_j \\
&= \sigma_{\Omega}^2 \sum_{j=1}^{D_h} \int_{-\infty}^{\infty} (\mathbb{I}[f_j > 0] f_j)^2 Pr(f_j) df_j \\
&= \sigma_{\Omega}^2 \sum_{j=1}^{D_h} \int_0^{\infty} f_j^2 Pr(f_j) df_j \\
&= \sigma_{\Omega}^2 \sum_{j=1}^{D_h} \frac{\sigma_f^2}{2} = \frac{D_h \sigma_{\Omega}^2 \sigma_f^2}{2}
\end{aligned}$$

Aim: keep variance same between two layers

$$\sigma_{f'}^2 = \frac{D_h \sigma_{\Omega}^2 \sigma_f^2}{2}$$

Should choose:

$$\sigma_{\Omega}^2 = \frac{2}{D_h}$$

This is called **He initialization**.