SMARTSCAN

AI-POWERED PORT SCANNER & VULNERABILITY ANALYZER

AI Powered by Groq — LLaMA 3.3 70B (FREE)

Target: **192.168.10.26 / Metasploitable: 2** | Scan Time: **2026-08-12 02:04:30** | Author: **Omkar Sawant** | github.com/omkarsawant1337

1	23	17	YES
HOSTS SCANNED	OPEN PORTS	CVEs FOUND	AI ANALYSIS

HOST INFORMATION

1 hosts

IP : 192.168.10.26
Hostname : N/A
State : up
Open Ports: 23
OS Guess : Linux 2.6.9 - 2.6.33 (100% accuracy)

OPEN PORTS

23 ports

PORT	SERVICE	VERSION	RISK	EXTRA INFO
21/tcp	ftp	vsftpd 2.3.4	CRITICAL	—
22/tcp	ssh	OpenSSH 4.7p1 Debian 8ubuntu1	HIGH	protocol 2.0

PORT	SERVICE	VERSION	RISK	EXTRA INFO
23/tcp	telnet	Linux telnetd	CRITICAL	—
25/tcp	smtp	Postfix smtpd	MEDIUM	—
53/tcp	domain	ISC BIND 9.4.2	MEDIUM	—
80/tcp	http	Apache httpd 2.2.8	HIGH	(Ubuntu) DAV/2
111/tcp	rpcbind	2	MEDIUM	RPC #100000
139/tcp	netbios-ssn	Samba smbd 3.X - 4.X	LOW	workgroup: WORKGROUP
445/tcp	netbios-ssn	Samba smbd 3.0.20-Debian	CRITICAL	workgroup: WORKGROUP
512/tcp	exec	netkit-rsh rexecd	CRITICAL	—
513/tcp	login	Unknown	CRITICAL	—
514/tcp	tcpwrapped	Unknown	CRITICAL	—
1099/tcp	java-rmi	GNU Classpath grmiregistry	LOW	—
1524/tcp	bindshell	Metasploitable root shell	LOW	—
2049/tcp	nfs	2-4	MEDIUM	RPC #100003
2121/tcp	ftp	ProFTPD 1.3.1	CRITICAL	—
3306/tcp	mysql	MySQL 5.0.51a-3ubuntu5	HIGH	—
5432/tcp	postgresql	PostgreSQL DB 8.3.0 - 8.3.7	HIGH	—
5900/tcp	vnc	VNC	CRITICAL	

PORT	SERVICE	VERSION	RISK	EXTRA INFO
				protocol 3.3
6000/tcp	X11	Unknown	LOW	access denied
6667/tcp	irc	UnrealIRCd	LOW	—
8009/tcp	ajp13	Apache Jserv	LOW	Protocol v1.3
8180/tcp	http	Apache Tomcat/ Coyote JSP engine 1.1	LOW	—

CVE FINDINGS

17 CVEs

CVE ID	PORT	CVSS SCORE	SEVERITY	DESCRIPTION
CVE-2011-2523	192.168.10.26:21	9.8	CRITICAL	vsftpd 2.3.4 downloaded betw 20110703 contains a backdoo on port 6200/tcp.
CVE-1999-0661	192.168.10.26:22	10.0	HIGH	A system is running a versio was replaced with a Trojan H distribution points, such as 7.6, (2) util-linux 2.9g, (3 (wuftpd) 2.2 and 2.1f, (4)
CVE-2000-0525	192.168.10.26:22	10.0	HIGH	OpenSSH does not properly di the UseLogin option is enabl local users to execute arbit providing the command to the
CVE-2000-0535	192.168.10.26:22	5.0	MEDIUM	OpenSSL 0.9.4 and OpenSSH fo properly check for the exist random or /dev/urandom devic on FreeBSD Alpha systems, wh produce weak keys which may
CVE-2000-1169	192.168.10.26:22	7.5	HIGH	OpenSSH SSH client before 2 properly disable X11 or agen could allow a malicious SSH

CVE ID	PORT	CVSS SCORE	SEVERITY	DESCRIPTION
				access to the X11 display ar or gain access to the ssh-ag
CVE-2001-1459	192.168.10.26:22	7.5	HIGH	OpenSSH 2.9 and earlier does Pluggable Authentication Mod commands are executed with r local users to bypass resour set in pam.d.
CVE-2000-1195	192.168.10.26:23	7.5	HIGH	telnet daemon (telnetd) from package before netkit-telnet attackers to bypass authenti is running with the -L comma
CVE-2020-8797	192.168.10.26:23	6.7	MEDIUM	Juplink RX4-1500 v1.0.3 allo to gain root access to the I an unsanitized exec call (al Injection), if the undocumen is enabled and the attacker
CVE-2021-27171	192.168.10.26:23	9.8	CRITICAL	An issue was discovered on I devices through RP2613. It i a Linux telnetd as root on p the CLI interface commands (tshell).
CVE-2022-39028	192.168.10.26:23	7.5	HIGH	telnetd in GNU Inetutils thr appl through 1.0.3, and deri NULL pointer dereference via 0xf8. In a typical installat application would crash but
CVE-2004-0925	192.168.10.26:25	5.0	MEDIUM	Postfix on Mac OS X 10.3.x t SMTPD AUTH enabled, does not username between authenticat allows users with the longes prevent other valid users fr
CVE-2005-0337	192.168.10.26:25	7.5	HIGH	Postfix 2.1.3, when /proc/ne available and permit_mx_back smtpd_recipient_restrictions attackers to bypass e-mail r perform mail relaying by ser
CVE-2023-51764	192.168.10.26:25	5.3	MEDIUM	Postfix through 3.8.5 allows unless configured with smtpd_data_restrictions=reje and smtpd_discard_ehlo_keywo certain other options that e versions). Remot...

CVE ID	PORT	CVSS SCORE	SEVERITY	DESCRIPTION
CVE-2024-27305	192.168.10.26:25	5.3	MEDIUM	aiosmtpd is a reimplementati stdlib smtpd.py based on asy vulnerable to inbound SMTP s smuggling is a novel vulnera so novel interpretation dif
CVE-2008-0122	192.168.10.26:53	10.0	HIGH	Off-by-one error in the inet libbind in ISC BIND 9.4.2 an in libc in FreeBSD 6.2 throu allows context-dependent att denial of service (crash) an
CVE-2008-4163	192.168.10.26:53	7.8	HIGH	Unspecified vulnerability in W1, 9.4.2-P2-W1, and 9.5.0-P allows remote attackers to c service (UDP client handler unknown vectors.
CVE-2003-1070	192.168.10.26:111	5.0	MEDIUM	Unknown vulnerability in rpc through 9 allows remote atta denial of service (rpcbind c

.

AI SECURITY ANALYSIS

Groq · LLaMA 3.3 70B · FREE

1. EXECUTIVE SUMMARY

The overall risk level of the target system is **Critical**. Key findings include the presence of multiple critical vulnerabilities in services such as vsftpd, OpenSSH, and Linux telnetd, which can be exploited to gain unauthorized access to the system. The system is running outdated software, including Linux 2.6.9-2.6.33, vsftpd 2.3.4, and OpenSSH 4.7p1, which are vulnerable to various attacks. An attacker can exploit these vulnerabilities to gain root access to the system, allowing them to execute arbitrary commands and steal sensitive data.

2. CRITICAL CVEs TO PRIORITIZE

The following CVEs pose the highest immediate risk:

* **CVE-2011-2523** (vsftpd 2.3.4): This vulnerability allows an attacker to gain a shell on port 6200/tcp, providing unauthorized access to the system.
* **CVE-2021-27171** (Linux telnetd): This vulnerability allows an attacker to start a Linux telnetd as root on port 26/tcp, providing

unauthorized access to the system.
* **CVE-2008-0122** (ISC BIND 9.4.2): This vulnerability allows an attacker to cause a denial of service (UDP client handler termination) via unknown vectors.
These CVEs are critical because they can be exploited to gain unauthorized access to the system or cause a denial of service, which can have significant consequences.

3. OPEN PORT RISK ANALYSIS
Here is a per-port risk analysis:
* **Port 21/tcp (vsftpd)**: High risk, exploitation likelihood: High
* **Port 22/tcp (OpenSSH)**: High risk, exploitation likelihood: Medium
* **Port 23/tcp (Linux telnetd)**: Critical risk, exploitation likelihood: High
* **Port 25/tcp (Postfix)**: Medium risk, exploitation likelihood: Medium
* **Port 53/tcp (ISC BIND)**: High risk, exploitation likelihood: Medium
* **Port 111/tcp (rpcbind)**: Medium risk, exploitation likelihood: Low
* **Port 139/tcp (Samba)**: Medium risk, exploitation likelihood: Medium
* **Port 445/tcp (Samba)**: Medium risk, exploitation likelihood: Medium

4. ATTACK CHAIN
An attacker could chain these vulnerabilities as follows:
1. Exploit **CVE-2011-2523** to gain a shell on port 6200/tcp.
2. Use the shell to exploit **CVE-2021-27171** to start a Linux telnetd as root on port 26/tcp.
3. Use the telnetd to exploit **CVE-2008-0122** to cause a denial of service (UDP client handler termination) via unknown vectors.
4. Use the denial of service to disrupt the system and gain unauthorized access.

5. NMAP FOLLOW-UP COMMANDS
To enumerate discovered services deeper, the following nmap commands can be used:
* `nmap -sV -p 21 --script=ftp-vsftpd-backdoor 192.168.10.26`
* `nmap -sV -p 22 --script=ssh-auth-methods 192.168.10.26`
* `nmap -sV -p 23 --script=telnet-encryption 192.168.10.26`
* `nmap -sV -p 25 --script=smtp-commands 192.168.10.26`
* `nmap -sV -p 53 --script=dns-nsid 192.168.10.26`

6. EXPLOITATION GUIDANCE
Relevant Metasploit modules include:
* `use exploit/unix/ftp/vsftpd_234_backdoor`
* `use exploit/unix/ssh/openssh_auth_bypass`

* `use exploit/unix/telnet/linux_telnetd_root`

Manual exploitation steps or PoC references for top CVEs can be found in the following resources:

* **CVE-2011-2523**: https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-2523
* **CVE-2021-27171**: https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2021-27171
* **CVE-2008-0122**: https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0122

7. REMEDIATION PRIORITY LIST

The following is an ordered list of remediation steps by urgency:

1. **Update vsftpd to version 2.3.5 or later** to fix **CVE-2011-2523**.
2. **Update OpenSSH to version 4.7p1-10 or later** to fix **CVE-2000-0525**, **CVE-2000-0535**, **CVE-2000-1169**, and **CVE-2001-1459**.
3. **Update Linux telnetd to version 0.17 or later** to fix **CVE-2021-27171**.
4. **Update ISC BIND to version 9.4.2-P3 or later** to fix **CVE-2008-0122**.
5. **Update Postfix to version 3.8.5 or later** to fix **CVE-2023-51764** and **CVE-2024-27305**.
6. **Disable unnecessary services** such as telnet and ftp.
7. **Implement a firewall** to restrict access to the system.
8. **Monitor the system for suspicious activity** and update the system regularly to ensure the latest security patches are applied.