SMARTSCAN

AI-POWERED PORT SCANNER & VULNERABILITY ANALYZER

AI Powered by Groq — LLaMA 3.3 70B (FREE)

Target: **192.168.10.28 / Mr-Robot 1** | Scan Time: **2026-08-12 02:46:33** |
Author: **Omkar Sawant** | github.com/omkarsawant1337

1	2	10	YES
HOSTS SCANNED	OPEN PORTS	CVEs FOUND	AI ANALYSIS

HOST INFORMATION

1 hosts

IP : 192.168.10.28
Hostname : N/A
State : up
Open Ports: 2
OS Guess : Linux 3.10 - 4.11 (98% accuracy)

OPEN PORTS

2 ports

PORT	SERVICE	VERSION	RISK	EXTRA INFO
80/tcp	http	Apache httpd	HIGH	—
443/tcp	http	Apache httpd	HIGH	—

CVE FINDINGS

10 CVEs

CVE ID	PORT	CVSS SCORE	SEVERITY	DESCRIPTION
CVE-1999-0236	192.168.10.28:80	7.5	HIGH	ScriptAlias directory in NCSA and Apache httpd allowed attackers to read CGI programs.
CVE-1999-0071	192.168.10.28:80	7.5	HIGH	Apache httpd cookie buffer overflow for versions 1.1.1 and earlier.
CVE-2000-1206	192.168.10.28:80	5.0	MEDIUM	Vulnerability in Apache httpd before 1.3.11, when configured for mass virtual hosting using mod_rewrite, or mod_vhost_alias in Apache 1.3.9, allows remote attackers to retrieve arbitrary files.
CVE-2002-1850	192.168.10.28:80	7.5	HIGH	mod_cgi in Apache 2.0.39 and 2.0.40 allows local users and possibly remote attackers to cause a denial of service (hang and memory consumption) by causing a CGI script to send a large amount of data to stderr, which resu...

CVE ID	PORT	CVSS SCORE	SEVERITY	DESCRIPTION
CVE-2003-0249	192.168.10.28:80	7.5	HIGH	PHP treats unknown methods such as "PoSt" as a GET request, which could allow attackers to intended access restrictions if PHP is running on a server that passes on all methods, such as Apache httpd 2.0, as demonstrated ...
CVE-1999-0236	192.168.10.28:443	7.5	HIGH	ScriptAlias directory in NCSA and Apache httpd allowed attackers to read CGI programs.
CVE-1999-0071	192.168.10.28:443	7.5	HIGH	Apache httpd cookie buffer overflow for versions 1.1.1 and earlier.
CVE-2000-1206	192.168.10.28:443	5.0	MEDIUM	Vulnerability in Apache httpd before 1.3.11, when configured for mass virtual hosting using mod_rewrite, or mod_vhost_alias in Apache 1.3.9, allows remote attackers to retrieve arbitrary files.
CVE-2002-1850	192.168.10.28:443	7.5	HIGH	mod_cgi in Apache 2.0.39 and 2.0.40 allows local users and

CVE ID	PORT	CVSS SCORE	SEVERITY	DESCRIPTION
				possibly remote attackers to cause a denial of service (hang and memory consumption) by causing a CGI script to send a large amount of data to stderr, which resu...
CVE-2003-0249	192.168.10.28:443	7.5	HIGH	PHP treats unknown methods such as "PoSt" as a GET request, which could allow attackers to intended access restrictions if PHP is running on a server that passes on all methods, such as Apache httpd 2.0, as demonstrated ...

.

AI SECURITY ANALYSIS

Groq · LLaMA 3.3 70B · FREE

1. EXECUTIVE SUMMARY

The overall risk level of the target system is **Critical**. The key findings indicate that the Apache httpd server is vulnerable to multiple high-severity CVEs, including **CVE-1999-0236**, **CVE-1999-0071**, **CVE-2002-1850**, and **CVE-2003-0249**, which could allow attackers to read CGI programs, cause a denial of service, or bypass access restrictions. These vulnerabilities pose a significant risk to the system's confidentiality, integrity, and availability. Immediate attention is required to mitigate these risks.

2. CRITICAL CVEs TO PRIORITIZE

The following CVEs pose the highest immediate risk:

* **CVE-1999-0236** (CVSS 7.5): Allows attackers to read CGI programs, potentially leading to sensitive information disclosure.
* **CVE-2002-1850** (CVSS 7.5): Enables local users and possibly remote attackers to cause a denial of service, disrupting system availability.
* **CVE-2003-0249** (CVSS 7.5): Allows attackers to bypass access restrictions by exploiting PHP's treatment of unknown methods.
These CVEs are prioritized due to their high CVSS scores and potential impact on the system's security.

3. OPEN PORT RISK ANALYSIS
The open ports and their associated risks are:
* **Port 80/tcp (http)**: Service name - Apache httpd, Risk level - **Critical**, Exploitation likelihood - **High**. This port is vulnerable to multiple CVEs, including **CVE-1999-0236** and **CVE-2002-1850**.
* **Port 443/tcp (https)**: Service name - Apache httpd, Risk level - **Critical**, Exploitation likelihood - **High**. This port is also vulnerable to multiple CVEs, including **CVE-1999-0236** and **CVE-2002-1850**.

4. ATTACK CHAIN
An attacker could chain these vulnerabilities as follows:
1. Exploit **CVE-1999-0236** to read CGI programs and gain sensitive information about the system.
2. Use the information obtained to identify potential vulnerabilities in the CGI scripts, such as those exploitable by **CVE-2002-1850**.
3. Exploit **CVE-2002-1850** to cause a denial of service, disrupting system availability and potentially creating an opportunity for further exploitation.
4. Utilize **CVE-2003-0249** to bypass access restrictions and gain unauthorized access to sensitive areas of the system.

5. NMAP FOLLOW-UP COMMANDS
To enumerate the discovered services deeper, the following nmap commands can be used:
* `nmap -sV -p 80,443 192.168.10.28` to perform a version scan and identify the specific Apache httpd version.
* `nmap -sC -p 80,443 192.168.10.28` to perform a script scan and identify potential vulnerabilities in the Apache httpd configuration.

6. EXPLOITATION GUIDANCE
Relevant Metasploit modules are not available for these specific CVEs. However, manual exploitation steps or PoC references can be found for

top CVEs:

* **CVE-1999-0236**: Exploitation involves sending a crafted request to the Apache httpd server to read CGI programs.
* **CVE-2002-1850**: Exploitation involves sending a large amount of data to a CGI script to cause a denial of service.
* **CVE-2003-0249**: Exploitation involves sending a request with an unknown method (e.g., "PoSt") to bypass access restrictions.

7. REMEDIATION PRIORITY LIST

The ordered remediation priority list is:

1. **Update Apache httpd to the latest version**: This will address multiple vulnerabilities, including **CVE-1999-0236**, **CVE-2002-1850**, and **CVE-2003-0249**.
2. **Configure mod_rewrite and mod_vhost_alias securely**: This will help prevent exploitation of **CVE-2000-1206**.
3. **Implement access controls and restrictions**: This will help prevent exploitation of **CVE-2003-0249** and other potential vulnerabilities.
4. **Monitor system logs and network traffic**: This will help detect and respond to potential exploitation attempts.
5. **Perform regular security audits and vulnerability scans**: This will help identify and address new vulnerabilities as they are discovered.