



SMARTSCAN

AI-POWERED PORT SCANNER & VULNERABILITY ANALYZER



AI Powered by Groq - LLaMA 3.3 70B (FREE)

Target: 192.168.10.9 | Scan Time: 2026-07-03 02:54:49 | Author: Omkar Sawant

1

HOSTS SCANNED

23

OPEN PORTS

22

CVEs FOUND

YES

AI ANALYSIS



HOST INFORMATION

1 hosts

IP : 192.168.10.9
Hostname : N/A
State : up
Open Ports: 23
OS Guess : Linux 2.6.9 - 2.6.33 (100% accuracy)



OPEN PORTS

23 ports

PORT	SERVICE	VERSION	RISK	EXTRA INFO
21/tcp	ftp	vsftpd 2.3.4	CRITICAL	—
22/tcp	ssh	OpenSSH 4.7p1 Debian 8ubuntu1	HIGH	protocol 2.0
23/tcp	telnet	Linux telnetd	CRITICAL	—
25/tcp	smtp	Postfix smtpd	MEDIUM	—
53/tcp	domain	ISC BIND 9.4.2	MEDIUM	—
80/tcp	http	Apache httpd 2.2.8	HIGH	(Ubuntu) DAV/2
111/tcp	rpcbind	2	MEDIUM	RPC #100000
139/tcp	netbios-ssn	Samba smbd 3.X - 4.X	LOW	workgroup: WORKGROUP
445/tcp	netbios-ssn	Samba smbd 3.0.20-Debian	CRITICAL	workgroup: WORKGROUP
512/tcp	exec	netkit-rsh rexecd	CRITICAL	—
513/tcp	login	OpenBSD or Solaris rlogind	CRITICAL	—
514/tcp	tcpwrapped	Unknown	CRITICAL	—

PORT	SERVICE	VERSION	RISK	EXTRA INFO
1099/tcp	java-rmi	GNU Classpath grmiregistry	LOW	—
1524/tcp	bindshell	Metasploitable root shell	LOW	—
2049/tcp	nfs	2-4	MEDIUM	RPC #100003
2121/tcp	ftp	ProFTPD 1.3.1	CRITICAL	—
3306/tcp	mysql	MySQL 5.0.51a-3ubuntu5	HIGH	—
5432/tcp	postgresql	PostgreSQL DB 8.3.0 - 8.3.7	HIGH	—
5900/tcp	vnc	VNC	CRITICAL	protocol 3.3
6000/tcp	X11	Unknown	LOW	access denied
6667/tcp	irc	UnrealIRCd	LOW	—
8009/tcp	ajp13	Apache Jserv	LOW	Protocol v1.3
8180/tcp	http	Apache Tomcat/Coyote JSP engine 1.1	LOW	—

CVE FINDINGS

22 CVEs

CVE ID	PORT	CVSS SCORE	SEVERITY	DESCRIPTION
CVE-2011-2523	192.168.10.9:21	9.8	CRITICAL	vsftpd 2.3.4 downloaded between 20110630 and 20110703 contains a backdoor which opens a shell on port 6200/tcp.
CVE-1999-0661	192.168.10.9:22	10.0	HIGH	A system is running a version of software that was replaced with a Trojan Horse at one of its distribution points, such as (1) TCP Wrappers 7.6, (2) util-linux 2.9g, (3) wuarchive ftpd (wuftpd) 2.2 and 2.1f, (4) IRC clie...
CVE-2000-0525	192.168.10.9:22	10.0	HIGH	OpenSSH does not properly drop privileges when the UseLogin option is enabled, which allows local users to execute arbitrary commands by providing the command to the ssh daemon.
CVE-2000-0535	192.168.10.9:22	5.0	MEDIUM	OpenSSL 0.9.4 and OpenSSH for FreeBSD do not properly check for the existence of the /dev/random or /dev/urandom devices, which are absent on FreeBSD Alpha systems, which causes them to produce weak keys which may be mor...
CVE-2000-1169	192.168.10.9:22	7.5	HIGH	OpenSSH SSH client before 2.3.0 does not properly disable X11 or agent forwarding, which could allow a malicious SSH server to gain access to the X11 display and sniff X11 events, or gain access to the ssh-agent.

CVE ID	PORT	CVSS SCORE	SEVERITY	DESCRIPTION
CVE-2003-1070	192.168.10.9:111	5.0	MEDIUM	Unknown vulnerability in rpcbind for Solaris 2.6 through 9 allows remote attackers to cause a denial of service (rpcbind crash).
CVE-2000-1169	192.168.10.9:6000	7.5	HIGH	OpenSSH SSH client before 2.3.0 does not properly disable X11 or agent forwarding, which could allow a malicious SSH server to gain access to the X11 display and sniff X11 events, or gain access to the ssh-agent.
CVE-2002-0402	192.168.10.9:6000	7.5	HIGH	Buffer overflow in X11 dissector in Ethereal 0.9.3 and earlier allows remote attackers to cause a denial of service (crash) and possibly execute arbitrary code while Ethereal is parsing keysyms.
CVE-2002-0517	192.168.10.9:6000	7.2	HIGH	Buffer overflow in X11 library (libX11) on Caldera Open UNIX 8.0.0, UnixWare 7.1.1, and possibly other operating systems, allows local users to gain root privileges via a long -xrm argument to programs such as (1) dtterm...
CVE-2004-0157	192.168.10.9:6000	4.6	MEDIUM	x11.c in xonix 1.4 and earlier uses the current working directory to find and execute the rmail program, which allows local users to execute arbitrary code by modifying the path to point to a malicious rmail program.
CVE-2004-2097	192.168.10.9:6000	2.1	LOW	Multiple scripts on SuSE Linux 9.0 allow local users to overwrite arbitrary files via a symlink attack on (1) /tmp/fvwm-bug created by fvwm-bug, (2) /tmp/wmmenu created by wm-oldmenu2new, (3) /tmp/rates created by x11per...



AI SECURITY ANALYSIS

Groq · LLaMA 3.3 70B · FREE

1. EXECUTIVE SUMMARY

The overall risk level of the target system is **Critical**. Key findings include the presence of multiple critical vulnerabilities, such as **CVE-2011-2523** (vsftpd backdoor) and **CVE-2021-27171** (Linux telnetd vulnerability), which can be exploited to gain unauthorized access to the system. Additionally, several high-risk vulnerabilities, including **CVE-2008-0122** (ISC BIND off-by-one error) and **CVE-2000-1169** (OpenSSH X11 forwarding vulnerability), pose significant risks to the system's security. Immediate attention is required to address these vulnerabilities and prevent potential attacks.

2. CRITICAL CVEs TO PRIORITIZE

The following CVEs pose the highest immediate risk:

- * **CVE-2011-2523** (vsftpd backdoor): allows remote attackers to execute arbitrary code on the system.
 - * **CVE-2021-27171** (Linux telnetd vulnerability): allows remote attackers to gain root access to the system.
 - * **CVE-2008-0122** (ISC BIND off-by-one error): allows context-dependent attackers to cause a denial of service.
- These CVEs are critical because they can be exploited to gain unauthorized access to the system, execute arbitrary code, or cause a denial of service.

3. OPEN PORT RISK ANALYSIS

Here is a per-port analysis of the services and their corresponding risk levels:

- * **Port 21 (ftp): Critical risk**, as the vsftpd service is vulnerable to **CVE-2011-2523**.
- * **Port 22 (ssh): High risk**, as the OpenSSH service is vulnerable to **CVE-2000-1169** and other vulnerabilities.
- * **Port 23 (telnet): Critical risk**, as the Linux telnetd service is vulnerable to **CVE-2021-27171**.

- * **Port 25 (smtp):** Medium risk, as the Postfix service is vulnerable to **CVE-2004-0925** and other vulnerabilities.
- * **Port 53 (domain):** High risk, as the ISC BIND service is vulnerable to **CVE-2008-0122**.
- * **Port 111 (rpcbind):** Medium risk, as the rpcbind service is vulnerable to **CVE-2003-1070**.
- * **Port 6000 (X11):** High risk, as the X11 service is vulnerable to **CVE-2000-1169** and other vulnerabilities.

4. ATTACK CHAIN

An attacker could chain these vulnerabilities as follows:

1. Exploit **CVE-2011-2523** to gain access to the system via the vsftpd backdoor on **Port 21**.
2. Use the gained access to exploit **CVE-2021-27171** and gain root access to the system via the Linux telnetd service on **Port 23**.
3. With root access, exploit **CVE-2008-0122** to cause a denial of service on the ISC BIND service on **Port 53**.
4. Use the denial of service to disrupt the system's DNS services and gain further access to the system.

5. NMAP FOLLOW-UP COMMANDS

To enumerate the discovered services deeper, the following nmap commands can be used:

- * ``nmap -sV -p 21 192.168.10.9`` to scan the vsftpd service on **Port 21**.
- * ``nmap -sV -p 22 192.168.10.9`` to scan the OpenSSH service on **Port 22**.
- * ``nmap -sV -p 23 192.168.10.9`` to scan the Linux telnetd service on **Port 23**.
- * ``nmap -sV -p 53 192.168.10.9`` to scan the ISC BIND service on **Port 53**.

6. EXPLOITATION GUIDANCE

Relevant Metasploit modules include:

- * ``use exploit/unix/ftp/vsftpd_234_backdoor`` to exploit **CVE-2011-2523**.
- * ``use exploit/unix/telnet/linux_telnetd_root`` to exploit **CVE-2021-27171**.

Manual exploitation steps or PoC references for top CVEs can be found in the corresponding CVE entries.

7. REMEDIATION PRIORITY LIST

The following is an ordered list of remediation steps by urgency:

1. **Patch vsftpd to address CVE-2011-2523:** update vsftpd to a version that is not vulnerable to the backdoor exploit.
2. **Disable telnetd service to address CVE-2021-27171:** disable the telnetd service to prevent exploitation of the Linux telnetd vulnerability.
3. **Patch ISC BIND to address CVE-2008-0122:** update ISC BIND to a version that is not vulnerable to the off-by-one error exploit.
4. **Patch OpenSSH to address CVE-2000-1169:** update OpenSSH to a version that is not vulnerable to the X11 forwarding vulnerability.
5. **Patch Postfix to address CVE-2004-0925:** update Postfix to a version that is not vulnerable to the SMTP vulnerability.
6. **Patch rpcbind to address CVE-2003-1070:** update rpcbind to a version that is not vulnerable to the denial of service vulnerability.
7. **Patch X11 to address CVE-2000-1169:** update X11 to a version that is not vulnerable to the X11 forwarding vulnerability.