Laxmi Charitable Trust's
Sheth L.U.J College of Arts & Sir M.V. College of Science and Commerce
Department of Information Technology (B.Sc.I.T Semester V)
Enterprise Java

Practical – V

Roll No. : 45	Name: Omkar thukarul
Class : TYIT	Date/Time of Submission : 1/08/2026

AIM:Implement the following JSP JSTL and EL Applications.

A): Create an html page with fields, eno, name, age, designation, salary. Now on submit this data to a JSP page which will update the employee table of database with matching eno.

CODE:

index.jsp:

```
<!DOCTYPE html>
<html>
<head>
   <title>Update Employee</title>
</head>
<body>
<h2>Employee Update Form</h2>
<form action="updateEmployee.jsp" method="post">
Employee No:
<input type="text" name="eno"><br><br>
Name:
<input type="text" name="name"><br><br>
Age:
<input type="number" name="age"><br><br>
Designation:
<input type="text" name="designation"><br><br>
Salary:
<input type="number" name="salary"><br><br>
<input type="submit" value="Update Employee">
</form>
</body>
</html>
```

updateEmployee.jsp:

```
<%@ page import="java.sql.*" %>
<%
String eno = request.getParameter("eno");
String name = request.getParameter("name");
String age = request.getParameter("age");
String designation = request.getParameter("designation");
String salary = request.getParameter("salary");
Connection con = null;
PreparedStatement ps = null;
try
{
  Class.forName("com.mysql.jdbc.Driver");
con = DriverManager.getConnection(
   "jdbc:mysql://localhost:3306/studentdb",
   "root",
   "root"
);
```

OUTPUT:

```
mysql> USE studentdb;
Database changed
mysql>
mysql> CREATE TABLE employee (
    ->     eno INT PRIMARY KEY,
    ->     name VARCHAR(50),
    ->     age INT,
    ->     designation VARCHAR(50),
    ->     salary DOUBLE
    -> );
```

```
mysql> INSERT INTO employee VALUES
    -> (101,'Rahul',22,'Developer',30000),
    -> (102,'Amit',25,'Manager',45000);
```

```
mysql> SELECT * FROM employee;
+-----+-------+------+-------------+--------+
| eno | name  | age  | designation | salary |
+-----+-------+------+-------------+--------+
| 101 | Rahul |   22 | Developer   |  30000 |
| 102 | Amit  |   25 | Manager     |  45000 |
+-----+-------+------+-------------+--------+
2 rows in set (0.00 sec)
```

Employee Update Form

Employee No: 101

Name: omkar thukarul

Age: 20

Designation: intern

Salary: 1000000

Update Employee

```
   String sql = "UPDATE employee SET name=?, age=?, designation=?, salary=? WHERE eno=?";
   ps = con.prepareStatement(sql);
 ps.setString(1,name);
   ps.setInt(2,Integer.parseInt(age));
   ps.setString(3,designation);
   ps.setDouble(4,Double.parseDouble(salary));
   ps.setInt(5,Integer.parseInt(eno));
  int i = ps.executeUpdate();
if(i>0)
      out.println("<h2>Employee Updated Successfully.</h2>");
   else
      out.println("<h2>Employee Number Not Found.</h2>");
}
catch(Exception e)
{
   out.println(e);
}
finally
{
   if(ps!=null)
      ps.close();
   if(con!=null)
      con.close();
}
%>
```

Employee Updated Successfully.

```
mysql> SELECT * FROM employee;
+-----+----------------+------+-------------+---------+
| eno | name           | age  | designation | salary  |
+-----+----------------+------+-------------+---------+
| 101 | omkar thukarul |   20 | intern      | 1000000 |
| 102 | Amit           |   25 | Manager     |   45000 |
+-----+----------------+------+-------------+---------+
2 rows in set (0.00 sec)
```

B)Create a JSP page to demonstrate the use of Expression language.

CODE:

elDemo.jsp

```
<%@page contentType="text/html" pageEncoding="ISO-8859-1"%>
<!DOCTYPE html>
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=ISO-8859-1">
<title>Expression Language Demo</title>
</head>
<body>

<div id="demoDivId">
   <span>Expression is: </span>
   <span>${12+2}</span>
</div>
<div id="demoDivId">
   <span>Expression is: </span>
   <span>${12-2}</span>
</div>
<div id="demoDivId">
   <span>Expression is: </span>
   <span>${12/2}</span>
</div>
<div id="demoDivId">
   <span>Expression is: </span>
   <span>${12*2}</span>
</div>
<div id="demoDivId">
   <span>Expression is: </span>
   <span>${12%2}</span>
```

OUTPUT:

Expression is: 14
Expression is: 10
Expression is: 6.0
Expression is: 24
Expression is: 0

```
</div>
</body>
</html>
```

C)Create a JSP application to demonstrate the use of JSTL.

CODE:

coreTag

```
<%@ taglib prefix="c" uri="http://java.sun.com/jsp/jstl/core" %>
<%@ page contentType="text/html" pageEncoding="UTF-8" %>

<!DOCTYPE html>
<html>
<head>
   <meta charset="UTF-8">
   <title>Core Tag Example</title>
</head>
<body>

   <h2>JSTL Core Tag Example</h2>

   <c:forEach var="j" begin="5" end="15">
      Item <c:out value="${j}"/><br>
   </c:forEach>

</body>
</html>
```

OUTPUT:

JSTL Core Tag Example

Item 5
Item 6
Item 7
Item 8
Item 9
Item 10
Item 11
Item 12
Item 13
Item 14
Item 15