

```
import numpy as np
import pandas as pd

df = pd.read_csv('/spam.csv',encoding='ISO-8859-1')
df.head()
```

	v1	v2	Unnamed: 2	Unnamed: 3	Unnamed: 4
0	ham	Go until jurong point, crazy.. Available only ...	NaN	NaN	NaN
1	ham	Ok lar... Joking wif u oni...	NaN	NaN	NaN
2	spam	Free entry in 2 a wkly comp to win FA Cup fina...	NaN	NaN	NaN
3	ham	U dun say so early hor... U c already then say...	NaN	NaN	NaN
4	ham	Nah I don't think he goes to usf, he lives aro...	NaN	NaN	NaN

```
df.info()

<class 'pandas.core.frame.DataFrame'>
RangeIndex: 5572 entries, 0 to 5571
Data columns (total 5 columns):
#   Column      Non-Null Count  Dtype
---  ---
0    v1          5572 non-null    object
1    v2          5572 non-null    object
2    Unnamed: 2   50 non-null     object
3    Unnamed: 3   12 non-null     object
4    Unnamed: 4    6 non-null     object
dtypes: object(5)
memory usage: 217.8+ KB
```

```
df.groupby('v1').describe()
```

v1	v2			Unnamed: 2				Unnamed: 3		
	count	unique	top	freq	count	unique	top	freq	count	unique
ham	4825	4516		30	45	39	bt not his girlfrnd... G o o d n i g h t . . . @"	3	10	
spam	747	653	Please call our customer service representativ...	4	5	4	PO Box 5249	2	2	

```
df['spam'] = df['v1'].apply(lambda x:1 if x=='spam' else 0)
df.head()
```

	v1	v2	Unnamed: 2	Unnamed: 3	Unnamed: 4	spam
0	ham	Go until jurong point, crazy.. Available only ...	NaN	NaN	NaN	0
1	ham	Ok lar... Joking wif u oni...	NaN	NaN	NaN	0
2	spam	Free entry in 2 a wkly comp to win FA Cup fina...	NaN	NaN	NaN	1
3	ham	U dun say so early hor... U c already then say...	NaN	NaN	NaN	0
4	ham	Nah I don't think he goes to usf, he lives aro...	NaN	NaN	NaN	0

```
new_df = df[['v1','v2','spam']]
new_df.head()
```

	v1	v2	spam
0	ham	Go until jurong point, crazy.. Available only ...	0
1	ham	Ok lar... Joking wif u oni...	0
2	spam	Free entry in 2 a wkly comp to win FA Cup fina...	1
3	ham	U dun say so early hor... U c already then say...	0
4	ham	Nah I don't think he goes to usf, he lives aro...	0

```
from sklearn.model_selection import train_test_split as tts
x_train,x_test,y_train,y_test=tts(df.v2,df.spam)
from sklearn.feature_extraction.text import CountVectorizer
```

```
v=CountVectorizer()
x_train_count=v.fit_transform(x_train.values)
x_train_count.toarray()[:2]
```

```
array([[0, 0, 0, ..., 0, 0, 0],
       [0, 0, 0, ..., 0, 0, 0]])
```

```
from sklearn.naive_bayes import MultinomialNB
model=MultinomialNB()
model.fit(x_train_count,y_train)
```

```
▼ MultinomialNB
MultinomialNB()
```

```
emails=["How are you brother?", "Free entry"]
email_count=v.transform(emails)
model.predict(email_count)
```

```
array([0, 1])
```

```
x_test_count=v.transform(x_test)
model.score(x_test_count,y_test)
```

```
0.9856424982053122
```