«requirement»

Flight plan filed by dispatcher

id = HLR-OPS-02
text = The dispatcher shall file each flight's plan with air traffic control before departure.

«deriveReqt»

«requirement»

Flight plan filed with ATC

id = SLR-PLN-06
text = The NAS shall file each flight plan with air traffic control before the flight departs.
also from SN-ATC-02, SN-ATC-03

«deriveReqt»

«requirement»

Flight controlled as cleared

id = HLR-CRW-01
text = The flight crew shall safely control the flight from origin to destination, as cleared by air traffic control with or without negotiation, and in collaboration with flight operations.
also from SLR-CLR-08, SLR-PLN-05

«deriveReqt»

«requirement»

Cleared path held by autoflight

id = HLR-ACF-02
text = The auto flight control system shall hold the aircraft on its cleared route, altitude and speed within the tolerances of the airspace.

«deriveReqt»

«requirement»

Conformance to cleared path

id = SLR-EXE-02
text = The NAS shall fly each aircraft along its cleared route and at its cleared altitude and speed within the navigation and altitude tolerances of the airspace.
also from SN-ATC-03

«deriveReqt»

«requirement»

Separation kept with conformance margin

id = HLR-ATC-01
text = Air traffic control shall keep each pair of aircraft it controls separated by at least the applicable minimum, allowing for each aircraft's permitted deviation from its cleared route, altitude and speed.

«deriveReqt»

«requirement»

Separation minima maintained

id = SLR-CLR-01
text = The NAS shall keep each pair of controlled aircraft separated by at least the minimum that JO 7110.65BB sets for the airspace they are in.
also from SN-CRW-06, SN-PAX-01

«deriveReqt»

«requirement» [improved]

Conflict resolved with flyable clearance

id = HLR-ATC-04
text = Air traffic control shall resolve each predicted conflict with a clearance that every aircraft it moves can fly.
also from SLR-CLR-10

«deriveReqt»

«requirement»

Separation assured

id = SN-ATC-01
text = The NAS shall keep every controlled aircraft separated from every other aircraft by at least the applicable separation minimum.
owner: StakeholderRequirements::AirTrafficControl (Air traffic control)

«deriveReqt»

«requirement»

Conflicts predicted

id = SLR-CLR-02
text = The NAS shall predict a loss of separation between controlled aircraft before it occurs.
also from SN-CRW-06

«deriveReqt»

«requirement»

ADS-B state broadcast

id = HLR-ACF-06
text = The aircraft's surveillance system shall broadcast the aircraft's position, altitude, velocity and identity by ADS-B Out.

«deriveReqt»

«requirement» [out of study]

Position altitude identity to facility

id = SLR-CLR-03
text = The NAS shall give the controlling facility the position, altitude and identity of each controlled aircraft.
also from SN-ATC-03

«deriveReqt»

«requirement»

Controller alerted to predicted conflict

id = HLR-ATC-02
text = ATC decision support shall alert the sector controller to each predicted loss of separation before it occurs.

«deriveReqt»

«requirement» [out of study]

Change only by clearance

id = SLR-CLR-05
text = The NAS shall change a controlled aircraft's cleared route, altitude or speed only by a clearance from the facility that has control of that aircraft.
also from SN-GOV-02

«deriveReqt»

«requirement»

Filed intent to sector controller

id = SLR-INF-01
text = The NAS shall give the sector controller the filed route, requested altitude and requested speed of each aircraft before it enters the sector.
also from SN-ATC-03

«deriveReqt»

«requirement»

Filed intent shown to controller

id = HLR-ATC-03
text = The en-route center shall inform the sector controller of each aircraft's filed route, requested altitude and requested speed before the aircraft enters the sector.

Circle-plus: ownership (the package or requirement on the left owns those on the right). Dashed arrow: deriveReqt, pointing from the derived requirement to its source. Grey: out of study (D-031). Lilac: background. Orange border: improved architecture (D-018).
Generated 2026-10-27 17:32 from commit 574431f (plus any uncommitted edits) by tools/export_requirements_diagram.py.