«requirement» [background]

Operating rules followed

id = SN-GOV-01
text = The NAS shall conduct every flight within the operating rules of 14 CFR and the FAA's air traffic orders.
owner: StakeholderRequirements::GovernmentsAndStandardsOrganizations (Regulator)

«requirement»

Fuel reserve

id = SLR-PLN-04
text = The NAS shall load each flight with fuel to reach its destination, then its most distant alternate, then fly 45 minutes at normal cruise.
also from SN-PAX-01

«requirement»

Flight planned from aircraft performance

id = HLR-OPS-01
text = Flight operations shall plan each flight's route, cruise altitude, cruise speed and fuel load from a model of the performance of the aircraft assigned to it, with the fuel reserve the operating rules require.
also from SLR-PLN-01, SLR-PLN-02

«requirement»

Joint release

id = SLR-PLN-05
text = The NAS shall release a flight only when the dispatcher and the captain both agree that it can be flown safely as planned.
also from SN-CRW-01, SN-GOV-02

«requirement»

Dispatcher releases with captain

id = HLR-OPS-04
text = The dispatcher shall release a flight only with the captain's agreement that it can be flown safely as planned.

«requirement» [out of study]

Crew duty within part117

id = SLR-PLN-09
text = The NAS shall assign to each flight a crew whose duty period, including forecast delay, stays within the limits of 14 CFR Part 117.
also from SN-CRW-05

«requirement»

Flight controlled as cleared

id = HLR-CRW-01
text = The flight crew shall safely control the flight from origin to destination, as cleared by air traffic control with or without negotiation, and in collaboration with flight operations.
also from SLR-EXE-02

«requirement»

Captain may deviate for safety

id = SLR-CLR-08
text = The NAS shall allow the captain to deviate from a clearance when safety requires it, with air traffic control told as soon as practical.
also from SN-CRW-01, SN-PAX-01

«requirement»

Dispatcher told of trajectory changes

id = HLR-CRW-04
text = The flight crew shall tell the dispatcher of each change to the cleared trajectory.
also from SLR-INF-07, SLR-CLR-04

«requirement»

Low fuel prediction alert

id = SLR-EXE-06
text = The NAS shall alert the flight crew, dispatchers and controllers when the fuel predicted at the destination falls below the required reserve.
also from SN-CRW-03, SN-PAX-01, SN-CRW-02

«requirement»

Flight re planned with crew

id = HLR-OPS-06
text = The dispatcher shall re-plan the flight with its crew when a trajectory change puts the arrival time, the fuel at the destination or flight safety at risk.
also from SLR-CLR-04, SLR-INF-07

«requirement»

Crew alerted to low predicted fuel

id = HLR-ACF-03
text = The flight management system shall alert the flight crew when the fuel it predicts at the destination falls below the required reserve.

«requirement»

Trajectory decisions recorded

id = SLR-MEA-01
text = The NAS shall record each change to an aircraft's trajectory, to its clearance, or to the constraints imposed on it, with the authority that issued it and the time.
also from SN-GOV-02

«requirement»

Clearances recorded

id = HLR-ATC-09
text = Air traffic control shall record each clearance it issues with the issuing facility and the time.

«deriveReqt»

Circle-plus: ownership (the package or requirement on the left owns those on the right). Dashed arrow: deriveReqt, pointing from the derived requirement to its source. Grey: out of study (D-031). Lilac: background. Orange border: improved architecture (D-018).
Generated 2026-10-27 17:32 from commit 574431f (plus any uncommitted edits) by tools/export_requirements_diagram.py.