

JS object.js > ...

```
1 // Object is kind of like map/dictionary where we have key-value
2 var details = ["Raghav",24,92.5,false];
3
4 let x = {
5   name: "Raghav",
6   age: 24,
7   percentage: 92.5,
8   isMarried: false
9 };
10
```

PROBLEMS

DEBUG CONSOLE

TERMINAL

PORTS

OUTPUT

 Code +

node "/Users/raghavgarg/Desktop/Dev_Course/JavaScript_Course/object.js"

● raghavgarg@Raghavs-MacBook-Pro JavaScript_Course % node "/Users/raghavgarg/Desktop/Dev_Course/JavaScript_Course/object.js"

{ name: 'Raghav', age: 24, percentage: 92.5, isMarried: false }

○ raghavgarg@Raghavs-MacBook-Pro JavaScript_Course %

```
3
4   let x = {
5       name: "Raghav",
6       "nick name": "Raghu",
7       age: 24,
8       percentage: 92.5,
9       isMarried: false
10  };
11
```

PROBLEMS

DEBUG CONSOLE

TERMINAL

```
/JavaScript_Course/object.js"
{
  name: 'Raghav',
  'nick name': 'Raghu',
  age: 24,
  percentage: 92.5,
  isMarried: false
}
```

```
3
4   let x = {
5       name: "Raghav",
6       age: 24,
7       percentage: 92.5,
8       'is Married': false
9   };
10  
11  console.log(x.age);
```

PROBLEMS

More Actions...



See Real World Examples From

- raghavgarg@Raghavs-MacBook-Pro JavaScript: /JavaScript_Course/object.js"

24

- raghavgarg@Raghavs-MacBook-Pro JavaScript

```
console.log(x['is Married']);
```

```

s forin.js > ...
1 let x = { // x is the object
2   name: "Raghav",
3   age: 24,
4   percentage: 92.5,
5   'is Married': false
6 };
7
8 for (const key in x) {
9   if (Object.hasOwnProperty.call(x, key)) {
10    console.log(x.key);
11   }
12 }

```

node "/Users/ragha
Desktop/Dev_Course/
ript_Course/forin.js
undefined
undefined
undefined
undefined
raghavgarg@Raghavs-
k-Pro JavaScript_Co

```

s forin.js > ...
1 let x = { // x is the object
2   name: "Raghav",
3   age: 24,
4   percentage: 92.5,
5   'is Married': false
6 };
7
8 for (const key in x) {
9   if (Object.hasOwnProperty.call(x, key)) {
10    console.log(key);
11   }
12 }

```

node "/Users/ragha
Desktop/Dev_Course/
ript_Course/forin.js
name
age
percentage
is Married
raghavgarg@Raghavs-
k-Pro JavaScript_Co

```

s forin.js > ...
1 let x = { // x is the object
2   name: "Raghav",
3   age: 24,
4   percentage: 92.5,
5   'is Married': false
6 };
7
8 for (const key in x) {
9   console.log(x[key]);
10 }

```

node "/Users/ragha
Desktop/Dev_Course/
ript_Course/forin.js
name Raghav
age 24
percentage 92.5
is Married false
raghavgarg@Raghavs-
k-Pro JavaScript_Co

```

s function.js > ...
1  function OnetoN(n){
2      for(let i=1;i<=n;i++){
3          console.log(i);
4      }
5  }
6
7  OnetoN(19);

```

node "/Users/raghav/Desktop/Dev_Course/JavaScript_Course/function.js" 1 2 3 4 5 6 7 8

```

s callback.js > ...
1  // Callback function ek esa function hota hai
   // jo ek function ke andar pass hota hai
2
3  function product(a,b,c){
4      return a*b*c;
5  }
6

```

o JavaScript_Course % node "/Users/raghav/Desktop/Dev_Course/JavaScript_Course/callback.js" -14
raghav@Raghavs-MacBook-Pro:~\$

```

s setTimeout.js > ...
1  // print 1 to 10 but with delay of 1 sec
   // after each number gets printed
2
3  for(let i=30;i>=1;i--){
4      setTimeout(function(){
5          console.log(i);
6      },i*500)
7  }
8
9
10
11
12
13
14
15
16
17

```

o JavaScript_Course % node "/Users/raghav/Desktop/Dev_Course/JavaScript_Course/setTimeout.js" 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21

```
s setTimeout.js > ...
    after each number gets printed
2
3 // for(let i=1;i<=10;i++){
4 //     console.log(i);
5 // }
6
7 function hello(){
8     console.log("hello");
9 }
10 function mello(){
11     console.log("mello");
12 }
13
14 setTimeout(hello,2*1000);
15 setTimeout(mello,1*1000);
16
```

o JavaScript_Course % n
Users/raghavgarg/Desktop
Course/JavaScript_Cours
imeout.js"
mello
hello
raghavgarg@Raghavs-MacB
o JavaScript_Course % [

```
s setTimeout.js > ...
2
3 // for(let i=1;i<=10;i++){
4 //     console.log(i);
5 // }
6
7
8
9 setTimeout(function(){
10     console.log("hello");
11 },2*1000);
12 setTimeout(function(){
13     console.log("mello");
14 },1*1000);
15
16
17
```

o JavaScript_Course % n
Users/raghavgarg/Desktop
Course/JavaScript_Cours
imeout.js"
mello
hello
raghavgarg@Raghavs-MacB
o JavaScript_Course % [

```
mathematicalFunctions.js
1 console.log(Math.abs(-7.6));
2
3 console.log(Math.max(5,5.01));
4 console.log(Math.min(-5,1));
5 console.log(Math.max(4,8,90,399,23));
6
7 console.log(Math.pow(3.14,3.14));
8 console.log(Math.log(2.81));
9
10 console.log(Math.sqrt(3.14));
11 console.log(Math.cbrt(10));
12
13 console.log(Math.floor(-3.5));
14 console.log(Math.floor(5.8));
15 console.log(Math.ceil(5.8));
16
17 console.log(Math.random());
18
```

node "/Users/ragha
Desktop/Dev_Course/
ript_Course/mathema
unctions.js"
7.6
5.01
-5
399
36.33783888017471
1.0331844833456545
1.772004514666935
2.154434690031884
-4
5
6
raghavgarg@Raghavs-
k-Pro JavaScript_Co
o []

```
// Write code to generate a random integer  
between 0 and 9 (included)  
let num = Math.floor(Math.random()*10);  
console.log(num);
```

```
// HOMEWORK - Write code to generate a random  
integer between 0 and 10 (included)  
  
// HOMEWORK - Write code to generate a random  
integer between -10 and 10 (included)
```


callback.js

```
// Callback function ek esa function hota hai  
jo ek function ke andar pass hota hai
```



callback.js > ...

```
// Callback function ek esa function hota hai  
jo ek function ke andar pass hota hai
```

```
function product(a,b,c){  
    return a*b*c;  
}
```

```
function fun(x,y){  
    console.log(x-y);  
}
```

```
fun(product(3,8,9),7);
```

- o JavaScript, Users/raghav Course/JavaScript back.js" 209 raghavgarg@R
- o JavaScript,