

```
// for (const ele of brr) {  
//     console.log(ele);  
// }
```

```
brr = [3,7,6,8,0,2];  
brr.forEach((ele,i) => {  
    console.log(ele,i);  
});  
|
```

Course/a
3 0
7 1
6 2
8 3
0 4
2 5
raghavgar
o -Pro Java

```
3 if(undefined){  
4     console.log("Hello"); // truthy  
5 }  
6 else console.log("mello"); // falsy  
7   
8 console.log(typeof(a));
```

PROBLEMS

DEBUG CONSOLE

TERMINAL

PORTS

- raghavgarg@Raghavs-MacBook-Pro JavaScript_Course/JavaScript_Course/truthyFalsy.js"
mello
undefined
- raghavgarg@Raghavs-MacBook-Pro JavaScript_Course

strings.js > ...

```
1 let a = "omor sultan";
2
3 console.log(a , a.length);
4
5
```

```
omor@pc:~/Omor/Al
omor sultan 11
```

```
let s = "garg";
console.log(s,s.length);
// for(let i=0;i<s.length;i++){
//     console.log(s[i]);
// }
// for (const char of s) {
//     console.log(char);
// }
// for each loop does not work for strings
```

```
let s = "Raghav Garg";
console.log(s);
console.log(s.toUpperCase());
console.log(s);
// console.log(s.toLowerCase());
```

- raghavgarg@Raghavs-
Course/JavaScript_C
Raghav Garg
RAGHAV GARG
Raghav Garg

JS stringsBuiltIn.js > ...

```
1 let s = "Raghav Garg";  
2 console.log(s);  
3 s.toUpperCase();  
4 console.log(s)  
5 // console.log(s.toUpperCase())  
6 // console.log(s.toLowerCase())
```

PROBLEMS

DEBUG CONSOLE

TERMINAL

- raghavgarg@Raghavs-MacBook-Pro JavaScript_Course/stringsBuiltIn.js
Raghav Garg
Raghav Garg
- raghavgarg@Raghavs-MacBook-Pro JavaScript_Course/stringsBuiltIn.js

JS stringsBuiltIn.js > ...

```
1 let s = "Raghav Garg";  
2 console.log(s);  
3 s.toUpperCase(); // ye kuch nahi ka  
4 let s2 = s.toUpperCase();  
5 console.log(s,s2);  
6 // console.log(s.toUpperCase());  
7 // console.log(s.toLowerCase());
```

PROBLEMS

DEBUG CONSOLE

TERMINAL

PORT

- raghavgarg@Raghavs-MacBook-Pro JavaScript_Co
Course/JavaScript_Course/stringsBuiltIn.js"
Raghav Garg
Raghav Garg RAGHAV GARG
- raghavgarg@Raghavs-MacBook-Pro JavaScript_Co

JS stringsBuiltIn.js > ...

```
1 let s = "  Raghav Garg  ";
2 console.log(s,s.length);
3 let s2 = s.trim();
4 console.log(s2,s2.length);
5
```

PROBLEMS

DEBUG CONSOLE

TERMINAL

PORT

- raghavgarg@Raghavs-MacBook-Pro JavaScript_Co
Course/JavaScript_Course/stringsBuiltIn.js"
Raghav Garg 16
Raghav Garg 11
- raghavgarg@Raghavs-MacBook-Pro JavaScript_Co

JS stringsBuiltIn.js > ...

```
1 let s = "  Raghav  Garg  ";
2 console.log(s,s.length);
3 let s2 = s.trim();
4 console.log(s2,s2.length);
5
```

PROBLEMS

DEBUG CONSOLE

TERMINAL

PORT

- raghavgarg@Raghavs-MacBook-Pro JavaScript_Co
Course/JavaScript_Course/stringsBuiltIn.js"
Raghav Garg 20
Raghav Garg 15
- raghavgarg@Raghavs-MacBook-Pro JavaScript_Co

JS stringsBuiltIn.js > ...

```
1 let s = "  Raghav Garg  ";
2 console.log(s,s.length);
3 let s2 = s.trim(); // s2 = "Raghav G
4 console.log(s2,s2.length);
5 console.log(s2.indexOf('a'));
6 console.log(s2.lastIndexOf('a'));
7 console.log(s2.charAt(3));
8 console.log(s2[3]);
```

I

PROBLEMS

DEBUG CONSOLE

TERMINAL

PORT

● raghavgarg@Raghavs-MacBook-Pro JavaScript_Co
Course/JavaScript_Course/stringsBuiltIn.js"

Raghav Garg 16

Raghav Garg 11

1

8

h

h

● raghavgarg@Raghavs-MacBook-Pro JavaScript Co


```
10 let s = "raghavgarg";  
11 console.log(s.slice(0));
```

PROBLEMS

DEBUG CONSOLE

TERMINAL

PORT

- raghavgarg@Raghavs-MacBook-Pro JavaScript_Cou
Course/JavaScript_Course/stringsBuiltIn.js"
raghavgarg

```
10 let s = "raghavgarg";  
11 console.log(s.slice(2));
```

PROBLEMS

DEBUG CONSOLE

TERMINAL

PORT

- raghavgarg@Raghavs-MacBook-Pro JavaScript_Cou
Course/JavaScript_Course/stringsBuiltIn.js"
ghavgarg

```
10 let s = "raghavgarg";
11 console.log(s.slice(5));
12 console.log(s.slice(2,6)); // substring from index 2 to 5
```

PROBLEMS

DEBUG CONSOLE

TERMINAL

PORTS

OUTPUT



```
● raghavgarg@Raghavs-MacBook-Pro JavaScript_Course % node "/Users/raghavgarg@Raghavs-MacBook-Pro:~/JavaScript_Course/stringsBuiltIn.js"
```

raghavgarg
ghav

```
10 let s = "raghavgarg";
11 console.log(s.slice(5)); // substring from index i to end
12 console.log(s.slice(2,6)); // substring from index i to j-1
13 s2 = s.slice(2,5);
14 console.log(s,s2);
```

PROBLEMS

DEBUG CONSOLE

TERMINAL

PORTS

OUTPUT



Cod

```
● raghavgarg@Raghavs-MacBook-Pro JavaScript_Course % node "/Users/raghavgarg@Raghavs-MacBook-Pro:~/JavaScript_Course/stringsBuiltIn.js"
```

raghavgarg
ghav

```
15
16 let s = "raghav garg is a teacher at physics wallah";
17 console.log(s);
18 let arr = s.split();
19 console.log(arr);
```

PROBLEMS

DEBUG CONSOLE

TERMINAL

PORTS

OUTPUT



Cod

```
● raghavgarg@Raghavs-MacBook-Pro JavaScript_Course % node "/Users/raghavgarg@Raghavs-MacBook-Pro:~/JavaScript_Course/stringsBuiltIn.js"
```

raghav garg is a teacher at physics wallah
['raghav garg is a teacher at physics wallah']

```
15
16 let s = "raghav garg is a teacher at physics wallah";
17 console.log(s);
18 let arr = s.split(' ');
19 console.log(arr);
```

PROBLEMS

DEBUG CONSOLE

TERMINAL

PORTS

OUTPUT

Cod

```
● raghavgarg@Raghavs-MacBook-Pro JavaScript_Course % node "/Users/ragha
Course/JavaScript_Course/stringsBuiltIn.js"
raghav garg is a teacher at physics wallah
[
  'raghav', 'garg',
  'is', 'a',
  'teacher', 'at',
  'physics', 'wallah'
```

```
16 let s = "raghav garg is a teacher at physics wallah";
17 console.log(s);
18 let arr = s.split(' ');
19 for (const ele of arr) {
20   console.log(ele);
21 }
```

PROBLEMS

DEBUG CONSOLE

TERMINAL

PORTS

OUTPUT

Cod

```
raghav garg is a teacher at physics wallah
raghav
garg
is
a
teacher
at
physics
```

```
15
16   let s = "a,gh,b,rtf,w,v";
17   console.log(s);
18   let arr = s.split(',');
19   for (const ele of arr) {
20       console.log(ele);
21   }
```

PROBLEMS

DEBUG CONSOLE

TERMINAL

PO

Course/JavaScript_Course/stringsBuiltIn.js'

a,gh,b,rtf,w,v

a

gh

b

rtf

w

v

JS templateLiteral.js > ...

```
1 let age = 30;
2 let exp = 10;
3 // console.log("My age is "+age+" and my experience is "+exp);
4 console.log(`My age is ${age} and my experience is ${exp}`);
5
```

PROBLEMS

DEBUG CONSOLE

TERMINAL

PORTS

OUTPUT

 Code +

```
● raghavgarg@Raghavs-MacBook-Pro JavaScript_Course % node "/Users/raghavgarg/
Course/JavaScript_Course/templateLiteral.js"
My age is 30 and my experience is 10
raghavgarg@Raghavs-MacBook-Pro JavaScript_Course %
```

```
7 console.log("rag\"hav");
8 console.log(`rag"hav`);
9 console.log('rag"hav');
10 console.log(`rag'hav`);
```

PROBLEMS

DEBUG CONSOLE

TERMINAL

PORTS

OUTPUT

 Code +

```
● raghavgarg@Raghavs-MacBook-Pro JavaScript_Course % node "/Users/raghavgarg/
Course/JavaScript_Course/templateLiteral.js"
My age is 30 and my experience is 10
rag"hav
rag"hav
rag"hav
rag'hav
```

```

arr = [1,6,8,3];
n = arr.length;
// for(let i=0;i<n;i++){
//     console.log(arr[i]);
// }
console.log(arr[2]);

```

```

// C++ : Vectors, Java : ArrayList

```

```

arr = [1,6,8,3];
console.log(arr);
arr.push(9); // add at last
console.log(arr);
arr.push(0);
console.log(arr);
arr.pop(); // removes last element
console.log(arr);
arr.unshift(2); // add at first
console.log(arr);
arr.shift();
console.log(arr); // removes first element
// n = arr.length;

```

```

/Users/raghavgarg/Desktop/Dev_Course/JavaScript_Course/arrays.js"
[ 1, 6, 8, 3 ]
[ 1, 6, 8, 3, 9 ]
[ 1, 6, 8, 3, 9, 0 ]
[ 1, 6, 8, 3, 9 ]
[ 2, 1, 6, 8, 3, 9 ]
[ 1, 6, 8, 3, 9 ]
raghavgarg@Raghavs-MacBook
-Pro JavaScript_Course %

```

```

const arr = [2,8,3,3];
arr.push(3);
console.log(arr);

```

```

/Users/raghavgarg/Desktop/Dev_Course/JavaScript_Course/arrays2.js"
[ 2, 8, 3, 3, 3 ]
raghavgarg@Raghavs-MacBook
-Pro JavaScript_Course %

```

```
let arr = [2,8,3,3];  
arr[0] = 9;  
console.log(arr);
```

```
...Users/raghavgarg/Desktop/Dev_Course/JavaScript_Course/arrays2.js"  
[ 9, 8, 3, 3 ]  
raghavgarg@Raghavs-MacBook  
-Pro JavaScript_Course %
```

```
const arr = [2,8,3,3];  
arr[0] = 9;  
console.log(arr);
```

```
...Users/raghavgarg/Desktop/Dev_Course/JavaScript_Course/arrays2.js"  
[ 9, 8, 3, 3 ]  
raghavgarg@Raghavs-MacBook  
-Pro JavaScript_Course %
```

```
const arr = [2,8,3,3];  
arr[0] = 9;  
console.log(arr);  
arr = 2.4;  
console.log(arr);
```

```
...Users/raghavgarg/Desktop/Dev_Course/JavaScript_Course/arrays2.js"  
[ 9, 8, 3, 3 ]  
/Users/raghavgarg/Desktop/Dev_Course/JavaScript_Course/arrays2.js:4  
arr = 2.4;  
^
```

TypeError: Assignment to constant variable.
at Object.<anonymous>
(/Users/raghavgarg/Desktop/Dev_Course/JavaScript_Course/arrays2.js:4:1)

```
let arr = [2,8,3,3];  
arr[0] = 9;  
console.log(arr);  
arr = 2.4;  
console.log(arr);
```

```
...Users/raghavgarg/Desktop/Dev_Course/JavaScript_Course/arrays2.js"  
[ 9, 8, 3, 3 ]  
2.4  
raghavgarg@Raghavs-MacBook  
-Pro JavaScript_Course %
```

```
arr = [4, "raghav", 7.9, true]  
console.log(arr);
```



```
ktop/dev_course/javascript  
_Course/arrays2.js"  
[ 4, 'raghav', 7.9, true ]  
raghavgarg@Raghavs-MacBook  
-Pro JavaScript_Course %
```

```
brr = [[1,2,2],[5,8,4]];  
console.log(brr);
```

```
[ [ 1, 2, 2 ], [ 5, 8, 4 ] ]  
raghavgarg@Raghavs-MacBook  
-Pro JavaScript_Course %
```

```
[ 4, 'raghav', 7.9, true ]  
[ [ 1, 2, 2 ], [ 5, 8, 4, 9, 1 ] ]  
raghavgarg@Raghavs-MacBook-Pro Jav  
aScript_Course %
```

```
brr = [[1,2,2],[5,8,4,9,1]];  
console.log(brr);
```



```
arr = [4,"raghav",7.9,true,[4,7,4,8]]  
console.log(arr);
```

```
ys2.js"  
[ 4, 'raghav', 7.9, true, [ 4  
  , 7, 4, 8 ] ]  
raghavgarg@Raghavs-MacBook-Pr  
o JavaScript Course %
```

```
arr = [4,"raghav",7.9,true,[4,7,4,8]]  
console.log(typeof(arr));
```

```
ys2.js  
object  
raghavg
```

```
brr = [3,7,3,8,0,2];  
// console.log(brr);  
// for(let i=0;i<arr.length;i++){  
//     brr[i] *= 2;  
// }  
// console.log(brr);  
console.log(brr);  
for (let ele of brr) {  
    ele *= 2;  
}  
console.log(brr);  
// // ForOf Loop
```

```
_course/arrays2.js  
[ 3, 7, 3, 8, 0, 2 ]  
[ 3, 7, 3, 8, 0, 2 ]  
raghavgarq@Raghavs-Mac
```

```
brr = [3,7,6,8,0,2];  
brr.forEach(ele => {  
    console.log(ele);  
});
```

declaring
data types. A variable can hold any type at any time.