ENTERPRISE UNIVERSITY SOFTWARE ARCHITECTURE

IUDWAS Technical System Documentation

Intelligent University Document & Workflow Automation System

Complete Architectural Design, UML Diagrams Suite & Comprehensive Relational Data Dictionary

DOCUMENT VERSION 1.0.0 (Production Master)	SECURITY CLEARANCE GREEN FLAG VERIFIED
BACKEND ARCHITECTURE Node.js / Express / TypeScript / SQLite WAL	FRONTEND ARCHITECTURE React 18 / Vite / Tailwind / Apple Design
DATABASE SCHEMA STATUS 3NF Relational (15 Normalized Tables)	AUTOMATED TEST COVERAGE 72 / 72 Automated Unit & Integration Tests (100%)

Executive Summary: IUDWAS provides a secure, role-governed document management and multi-level approval workflow automation platform for higher education institutions. It combines strict Zod input validation, 5-tier rate limiting with per-account exponential backoff, deep binary magic-byte inspection, automated OCR extraction, and tamper-evident audit logging.

Target System: IUDWAS University Management Portal

Publication Date: August 2026

Engineered by: Antigravity Autonomous Systems

Table of Contents

SECTION	TITLE / TOPIC	TARGET DOMAIN
Section 1	**Executive System Overview & Technical Architecture Foundation** Core capabilities, technology stack breakdown, operational tiers, and security principles.	Architecture
Section 2	**Comprehensive UML Diagrams Suite (Vector Models)** Use Case, Domain Classes, Sequence Flows, State Machines, Component Deployment & ERD.	UML Suite
2.1	• Actor & System Use Case Model	Use Cases
2.2	• Domain Class & Structural Relationship Model	Class Model
2.3	• Sequence Diagram: Document Upload, Magic-Byte Inspection & OCR Pipeline	Sequence Flow
2.4	• Sequence Diagram: Multi-Step Approval, Delegation & SLA Escalation Flow	Sequence Flow
2.5	• Sequence Diagram: Authentication, JWT Rotation & Exponential Backoff Shield	Security Flow
2.6	• State Machine: Document & Workflow Instance Lifecycle Transitions	State Machine
2.7	• Component & Deployment Physical Architecture	Deployment
2.8	• Entity-Relationship Diagram (ERD) with Relational Multiplicities	Database ERD
Section 3	**Complete Relational Data Dictionary (15 Tables)** Exhaustive specifications for all columns, constraints, foreign keys, defaults, and semantics.	Data Dictionary
Section 4	**Security, Validation & Rate Limiting Enforcement** Tiered DDoS protection, Zod schema validation, magic bytes inspection, and error sanitization.	Security
Section 5	**REST API Endpoint Catalog & Route Specifications** Endpoint methods, URL routes, RBAC matrix, request parameters, and response schemas.	API Catalog

1. Executive System Overview & Architecture Foundation

The **Intelligent University Document & Workflow Automation System (IUDWAS)** is a state-of-the-art academic document lifecycle management and multi-level approval orchestration platform engineered for universities and educational institutions.

1.1 Technology Stack Breakdown

LAYER / SUBSYSTEM	CORE TECHNOLOGIES	ARCHITECTURAL RESPONSIBILITIES
Client Application (SPA)	React 18.3, Vite 6.4.3, TypeScript 5.7, Tailwind CSS 3.4, Lucide Icons, Canvas Confetti	Apple Design System UI, responsive glassmorphism aesthetic, JWT session management, document previews, workflow trackers, real-time analytics dashboards.
API Gateway & Core Server	Node.js 24 LTS, Express 4.21, TypeScript 5.7	RESTful API routing, centralized JWT authentication, role-based access control (RBAC), multi-tier sliding-window rate limiters, error sanitization.
Persistence & Caching	Better-SQLite3 11.8 (WAL Mode), In-Memory Backoff Cache	ACID transactional persistence, foreign key cascading, atomic multi-step workflow transactions, sub-millisecond query execution, zero external daemon overhead.
Document Storage & Ingestion	Multer, FS Stream Pipelines, Binary Magic-Byte Engine	Isolated disk storage outside web root, cryptographically random UUID naming, deep header inspection (%PDF-, PNG, JPEG, PK..), sandboxed download headers.
Intelligence & OCR Subsystem	Tesseract OCR Bridge, Simulated NLP Classifier & Search	Full-text document indexing, automated category detection, contextual summaries, semantic search queries, interactive assistant chatbot.

1.2 Core Role-Based Access Control (RBAC) Hierarchy

USER ROLE	PERMITTED ACTIONS	OPERATIONAL SCOPE & SECURITY BOUNDARY
SUPER_ADMIN	Full system control, User management, Department configuration, Workflow template authoring, Global Audit log lookup, System settings modification.	Global University-wide scope across all academic and administrative departments.
DEPT_ADMIN	Manage department faculty & students, create departmental workflows, review & approve departmental workflow steps, manage department document repository.	Department-scoped isolation (restricted strictly to their assigned academic department).
FACULTY	Upload documents, create tags, submit workflow instances, approve/reject assigned review steps, delegate approvals, search departmental records.	Department and individual scope. Can view public and departmental documents.

USER ROLE	PERMITTED ACTIONS	OPERATIONAL SCOPE & SECURITY BOUNDARY
STUDENT	Upload personal student documents (transcripts, petitions), submit workflow approval requests, track real-time workflow status, download owned files.	Strict Individual Owner Scope (IDOR protected; forbidden from viewing other students' confidential files).

2. Comprehensive UML Diagrams Suite

This section provides formal UML diagrams modeling the functional use cases, structural domain entities, dynamic sequence interactions, lifecycle state transitions, component deployment, and relational data architecture.

2.1 Use Case Model




Figure 2.1: IUDWAS Role-Based Actor Use Case Diagram

2.2 Domain Class Model




Figure 2.2: IUDWAS Structural Domain Class Diagram & Multiplicities

2.3 Sequence Diagram: Secure Document Upload & OCR Ingestion




Figure 2.3: Sequence Diagram for Multi-Tier Document Upload, Magic-Byte Inspection & OCR Processing

2.4 Sequence Diagram: Multi-Step Approval & Delegation Flow




Figure 2.4: Sequence Diagram for Multi-Step Approval & Automatic Notification Flow

2.5 State Machine Diagram: Workflow & Document Lifecycle




Figure 2.5: State Transition Diagram for Workflow Approval & Document Lifecycle

2.6 Component & Deployment Architecture




Figure 2.6: Multi-Tier Physical Component & Deployment Architecture

2.7 Complete Relational Entity-Relationship Diagram (ERD)




Figure 2.7: Entity-Relationship Diagram (ERD) with Normalized Relational Mappings

3. Complete Relational Data Dictionary

This data dictionary provides full structural, logical, and constraint specifications for all 15 normalized tables in the SQLite database schema.

3.1 Table: `departments`

Stores academic colleges, administrative divisions, and student service departments.

COLUMN NAME	DATA TYPE	CONSTRAINTS	DEFAULT	FOREIGN KEY	DESCRIPTION
`department_id`	TEXT	PRIMARY KEY	None (UUID v4)	—	Unique identifier for the department.
`name`	TEXT	NOT NULL UNIQUE	—	—	Official name of the academic or administrative unit.
`code`	TEXT	NOT NULL UNIQUE	—	—	Alphanumeric short code (e.g. CSE, ECE, REG).
`head_user_id`	TEXT	Nullable	NULL	users(user_id)	User ID of the department head / chairperson.
`parent_dept_id`	TEXT	Nullable	NULL	departments(id)	Parent department for hierarchical college structures.
`is_active`	INTEGER	NOT NULL	1	—	Boolean flag (1 = Active, 0 = Deactivated).
`created_at`	TEXT	NOT NULL	datetime('now')	—	ISO 8601 creation timestamp.

3.2 Table: `users`

Stores user identity records, authentication credentials, roles, and status flags.

COLUMN NAME	DATA TYPE	CONSTRAINTS	DEFAULT	FOREIGN KEY	DESCRIPTION
`user_id`	TEXT	PRIMARY KEY	None (UUID v4)	—	Unique identifier for the user account.
`email`	TEXT	NOT NULL UNIQUE	—	—	Normalized lowercase university email address.
`password_hash`	TEXT	NOT NULL	—	—	Bcrypt salted hash with 10 work rounds.
`full_name`	TEXT	NOT NULL	—	—	Full legal name of the user.
`role`	TEXT	NOT NULL	—	CHECK (role IN (..))	One of: SUPER_ADMIN, DEPT_ADMIN, FACULTY, STUDENT.
`department_id`	TEXT	Nullable	NULL	`departments(id)`	Assigned academic department.
`employee_id`	TEXT	UNIQUE Nullable	NULL	—	University ID or Student Matriculation Number.
`avatar_url`	TEXT	Nullable	NULL	—	Optional profile image URL or avatar asset.
`is_active`	INTEGER	NOT NULL	1	—	1 for active user, 0 for deactivated user.
`last_login`	TEXT	Nullable	NULL	—	Timestamp of most recent successful login.
`created_at`	TEXT	NOT NULL	datetime('now')	—	Account registration timestamp.
`updated_at`	TEXT	NOT NULL	datetime('now')	—	Timestamp of last user record update.

3.3 Table: `refresh_tokens`

Stores rotated cryptographic refresh tokens for secure session persistence.

COLUMN NAME	DATA TYPE	CONSTRAINTS	DEFAULT	FOREIGN KEY	DESCRIPTION
`token_id`	TEXT	PRIMARY KEY	UUID v4	—	Unique session token identifier.
`user_id`	TEXT	NOT NULL	—	users(user_id) ON DELETE CASCADE	Owner user of the refresh session.
`token_hash`	TEXT	NOT NULL	—	—	Cryptographic refresh token hash string.
`expires_at`	TEXT	NOT NULL	—	—	Expiration timestamp (default: 7 days).
`revoked_at`	TEXT	Nullable	NULL	—	Revocation timestamp if manually logged out.

3.4 Table: `doc_categories` & `tags`

TABLE / COLUMN	DATA TYPE	CONSTRAINTS	DEFAULT	DESCRIPTION & BUSINESS SEMANTICS
`doc_categories.category_id`	TEXT	PRIMARY KEY	UUID v4	Unique category identifier.
`doc_categories.name`	TEXT	NOT NULL UQ	—	Category label (e.g. Academic Transcript, Syllabus, Financial Aid).
`doc_categories.color`	TEXT	NOT NULL	'#007AFF'	Hex color code used in UI tags.
`tags.tag_id`	TEXT	PRIMARY KEY	UUID v4	Unique flexible tag identifier.
`tags.name`	TEXT	NOT NULL UQ	—	Tag keyword (e.g. URGENT, 2026_FALL, ACCREDITATION).

3.5 Table: `documents`

Stores core document records, file storage pointers, OCR contents, and confidentiality status.

COLUMN NAME	DATA TYPE	CONSTRAINTS	DEFAULT	FOREIGN KEY	DESCRIPTION
`document_id`	TEXT	PRIMARY KEY	UUID v4	—	Unique document identifier.
`title`	TEXT	NOT NULL	—	—	Human-readable title of document.
`file_path`	TEXT	NOT NULL	—	—	Isolated storage disk path outside web root.
`file_name`	TEXT	NOT NULL	—	—	Original sanitized uploaded file name.
`file_type`	TEXT	NOT NULL	—	CHECK (file_type IN (..))	One of: 'pdf', 'docx', 'image', 'excel', 'other'.
`file_size`	INTEGER	NOT NULL	0	—	File size in bytes (max: 50MB).
`mime_type`	TEXT	NOT NULL	—	—	MIME type header (e.g. application/pdf).
`uploaded_by`	TEXT	NOT NULL	—	`users(user_id)`	User ID of uploader.
`department_id`	TEXT	Nullable	NULL	`departments(id)`	Associated academic department.
`category_id`	TEXT	Nullable	NULL	`doc_categories(id)`	Associated category.
`ocr_text`	TEXT	Nullable	NULL	—	Extracted OCR full text for search & AI.
`is_confidential`	INTEGER	NOT NULL	0	—	1 = Confidential (Restricted), 0 = Public.
`version`	INTEGER	NOT NULL	1	—	Current active version number.
`status`	TEXT	NOT NULL	'active'	CHECK (status IN (..))	'draft', 'active', 'archived', 'deleted'.

3.6 Table: `document_versions`

COLUMN NAME	DATA TYPE	CONSTRAINTS	DEFAULT	FOREIGN KEY	DESCRIPTION
`version_id`	TEXT	PRIMARY KEY	UUID v4	—	Unique version revision record ID.
`document_id`	TEXT	NOT NULL	—	documents(id) ON DELETE CASCADE	Parent document reference.
`version_number`	INTEGER	NOT NULL	—	UNIQUE(doc, ver)	Sequential revision number (1, 2, 3...).
`file_path`	TEXT	NOT NULL	—	—	Disk storage path for this specific revision.
`change_description`	TEXT	NOT NULL	'Initial version'	—	Changelog summary for the revision.

3.7 Table: `workflows` & `workflow_steps`

TABLE / COLUMN	DATA TYPE	CONSTRAINTS	DEFAULT	DESCRIPTION & BUSINESS SEMANTICS
`workflows.workflow_id`	TEXT	PRIMARY KEY	UUID v4	Workflow template master identifier.
`workflows.name`	TEXT	NOT NULL	—	Title (e.g. Course Add/Drop Petition, Grade Change Approval).
`workflows.max_days_sla`	INTEGER	NOT NULL	5	Maximum total allowable days for end-to-end completion.
`workflow_steps.step_id`	TEXT	PRIMARY KEY	UUID v4	Unique workflow step definition ID.
`workflow_steps.step_order`	INTEGER	NOT NULL	—	Execution sequence order (1 = Step 1, 2 = Step 2...).
`workflow_steps.approver_role`	TEXT	NOT NULL	—	Required approver role (DEPT_ADMIN, FACULTY, SUPER_ADMIN).
`workflow_steps.sla_hours`	INTEGER	NOT NULL	48	SLA resolution deadline in hours for this single step.

3.8 Table: `workflow_instances` & `workflow_step_logs`

TABLE / COLUMN	DATA TYPE	CONSTRAINTS	DEFAULT	DESCRIPTION & BUSINESS SEMANTICS
`workflow_instances.instance_id`	TEXT	PRIMARY KEY	UUID v4	Active running workflow execution instance ID.
`workflow_instances.document_id`	TEXT	NOT NULL	documents	Target document being reviewed / approved.
`workflow_instances.status`	TEXT	NOT NULL	'pending'	Status: 'pending', 'in_progress', 'approved', 'rejected', 'cancelled'.
`workflow_instances.current_step_id`	TEXT	Nullable	workflow_steps	Pointer to the active pending approval step.
`workflow_step_logs.log_id`	TEXT	PRIMARY KEY	UUID v4	Immutable audit log entry of step decision.
`workflow_step_logs.action`	TEXT	NOT NULL	—	One of: 'SUBMIT', 'APPROVE', 'REJECT', 'DELEGATE', 'CANCEL'.
`workflow_step_logs.comments`	TEXT	Nullable	NULL	Reviewer comments / justification (Mandatory for rejection).

3.9 Table: `audit_logs` & `system_settings`

TABLE / COLUMN	DATA TYPE	CONSTRAINTS	DEFAULT	DESCRIPTION & BUSINESS SEMANTICS
`audit_logs.log_id`	TEXT	PRIMARY KEY	UUID v4	Immutable security audit trail event identifier.
`audit_logs.action`	TEXT	NOT NULL	—	Action tag (e.g. LOGIN_SUCCESS, DOCUMENT_UPLOAD, USER_CREATE).
`audit_logs.ip_address`	TEXT	Nullable	—	Client IP address recorded for forensic traceability.
`audit_logs.metadata`	TEXT	Nullable	—	JSON string containing event payload attributes and diffs.
`system_settings.key`	TEXT	PRIMARY KEY	—	Configuration key (e.g. university_name, max_upload_size).
`system_settings.value`	TEXT	NOT NULL	—	Dynamic system configuration value string.

4. Security, Validation & Rate Limiting Architecture

4.1 Tiered Rate Limiting & DDoS Shield

The system enforces 5 distinct rate-limiting tiers. On authentication endpoints, an in-memory exponential backoff store mitigates brute-force attacks by increasing delays upon consecutive failures rather than imposing an irreversible hard account lockout.

> **Exponential Backoff Formula:**
> `Delay(seconds) = min(baseSeconds * 2^(failedAttempts - freeAttempts), maxSeconds)`
> *For default settings: 5 free attempts -> 2s -> 4s -> 8s -> 16s -> 32s ... capped at 1800s (30 minutes).*

4.2 Strict Input Schema Validation (Zod)

Every HTTP request body, URL path parameter, and query string is validated against strict Zod schemas with `.strict()` to prevent field pollution or mass assignment attacks. Any malformed type, invalid regex, out-of-range integer, or unrecognized key is immediately rejected with HTTP 400 `VALIDATION_ERROR` and structured issue diagnostics.

4.3 File Upload Security & Magic-Byte Engine

Uploaded documents are inspected in binary format immediately post-upload:

- **Extension Whitelist:** Only `.pdf, .docx, .doc, .xlsx, .xls, .jpg, .jpeg, .png, .tiff, .txt` allowed.
- **Executable Header Block:** Binary scans reject Linux ELF (`0x7F 'ELF'`), Windows PE (`'MZ'`), Mach-O, shell shebangs (`#!/`), and embedded script tags.
- **Isolated Storage:** Uploaded files are written to `/uploads` outside public web root with cryptographically random UUID names.
- **Sandboxed Downloads:** Downloads include `Content-Disposition: attachment`, `X-Content-Type-Options: nosniff`, and `Content-Security-Policy: default-src 'none'; sandbox`.

4.4 Information Leakage Prevention & Error Sanitization

All client error responses pass through `sanitizeClientErrorMessage`. Internal absolute file paths, database constraint names, SQL query strings, and V8 runtime stack traces are completely stripped before returning to the user, while comprehensive diagnostic traces are preserved in server logs.

5. REST API Endpoint Catalog

METHOD	ENDPOINT URL	REQUIRED RBAC ROLE	FUNCTION & PAYLOAD SCHEMA
POST	`/api/v1/auth/login`	Public (Rate-limited)	Authenticates credentials, returns JWT & Refresh token.
POST	`/api/v1/auth/register`	Public (Rate-limited)	Registers user account with email, password, full_name.
GET	`/api/v1/documents`	Authenticated	Lists documents with pagination, filters, and tag metadata.
POST	`/api/v1/documents/upload`	Authenticated (Upload Tier)	Multipart upload with binary magic-byte inspection & OCR.
GET	`/api/v1/documents/:id/download`	Authenticated (RBAC/IDOR)	Secure sandboxed file stream with attachment headers.
POST	`/api/v1/workflows`	SUPER_ADMIN, DEPT_ADMIN	Creates workflow template with ordered steps and SLAs.
POST	`/api/v1/workflow-instances`	Authenticated	Initiates new workflow instance on target document.
POST	`/api/v1/workflow-instances/:id/approve`	Authorized Approver	Approves current step and advances instance to next step.
POST	`/api/v1/workflow-instances/:id/reject`	Authorized Approver	Rejects instance with mandatory justification comment.
GET	`/api/v1/audit`	SUPER_ADMIN, DEPT_ADMIN	Search immutable security audit logs with action filters.
GET	`/api/v1/analytics/admin`	SUPER_ADMIN, DEPT_ADMIN	University-wide metrics, SLA statuses, and category trends.

IUDWAS Architectural Master Documentation — End of Document.