

Vidyavardhini's College of Engineering & Technology
Department of Artificial Intelligence and Data Science

Experiment No. 7
Implement Booth's algorithm using c-programming
Name: OM PATIL
Roll Number:43
Date of Performance:
Date of Submission:

Vidyavardhini's College of Engineering & Technology

Department of Artificial Intelligence and Data Science



Vidyavardhini's College of Engineering & Technology

Department of Artificial Intelligence and Data Science

Aim: To implement Booth's algorithm using c-programming.

Objective - 1. To understand the working of Booths algorithm.

2. To understand how to implement Booth's algorithm using c-programming.

Theory:

Booth's algorithm is a multiplication algorithm that multiplies two signed binary numbers in 2's complement notation. Booth used desk calculators that were faster at shifting than adding and created the algorithm to increase their speed. The algorithm works as per the following conditions :

1. If Q_n and Q_{n+1} are same i.e. 00 or 11 perform arithmetic shift by 1 bit.


2. If $Q_n Q_{n+1} = 10$ do $A = A - B$ and perform arithmetic shift by 1 bit.

3. If $Q_n Q_{n+1} = 01$ do $A + B$ and perform arithmetic shift by 1 bit.

Multiplicand (B)	0 1	Multiplier (Q)	1 0 0 (4)
Steps			Operati o n
	0 0 0 0	0 1 0 0	Initial
Step 1	0 0 0 0	0 0 1	Shift right
Step 2	0 0 0	0 0 0 1	Shift right
step 3	1 1	0 0 1	
	1 0	1 0 0 c	Shift right
	1 1		

Vidyavardhini's College of Engineering & Technology
Department of Artificial Intelligence and Data Science

Step 4 :	o o 1 o	o o o	1	
	o o o	o 1 o o		Shift right
Result	o o o = +20			



Program: `#include <stdio.h>`
`#include <math.h>`

Vidyavardhini's College of Engineering & Technology
Department of Artificial Intelligence and Data Science

```
int a = 0,b = 0, c = 0, a1 = 0, b1 = 0, com[5] = { 1, 0, 0, 0, 0}; int  
anum[5] = {0}, anumcp[5] = {0}, bnum[5] = {0}; int  
acom[5] = {0}, bcomp[5] = {0}, pro[5] = {0}, res[5] = {0};
```

```
void  
binary(){    a1 =  
fabs(a);    b1 =  
fabs(b);    int r,  
r2, i, temp;    for  
(i = 0; i < 5;  
i++){        r =  
a1 % 2;        a1  
= a1 / 2;        r2  
= b1 % 2;  
b1 = b1 / 2;  
anum[i] = r;  
anumcp[i] = r;  
bnum[i] = r2;  
if(r2 ==  
0){            bco  
mp[i] = 1;  
        }  
        if(r ==  
0){            acomp[i] =1;  
        }  
    }  
    c = 0;    for ( i = 0; i < 5;  
i++){        res[i] = com[i]+  
bcomp[i] + c;        if(res[i] >=  
2){            c = 1;        }        else  
c = 0;        res[i] = res[i] % 2;  
    }
```

Vidyavardhini's College of Engineering & Technology
Department of Artificial Intelligence and Data Science

```
    for (i = 4; i >= 0; i-
-){    bcomp[i] = res[i];
    }
    if (a < 0){
        c = 0;    for (i = 4; i
>= 0; i--){        res[i] =
0;
    }
    for ( i = 0; i < 5; i++){        res[i]
= com[i] + acomp[i] + c;        if
(res[i] >= 2){            c = 1;        }
else            c = 0;
        res[i] = res[i]%2;
    }
    for (i = 4; i >= 0; i-
-){        anum[i] = res[i];
anumcp[i] = res[i];
    }

}

if(b < 0){    for (i = 0; i <
5; i++){        temp =
bnum[i];        bnum[i] =
bcomp[i];        bcomp[i]
= temp;
    }
}

}

void add(int
num[]){ int i; c =
0;
    for ( i = 0; i < 5; i++){
```

Vidyavardhini's College of Engineering & Technology
Department of Artificial Intelligence and Data Science

```
        res[i] = pro[i] + num[i] + c;
if (res[i] >= 2){          c =
1;          }          else{          c =
0;
        }
        res[i] = res[i]%2;
    }
    for (i = 4; i >= 0; i-
-){          pro[i] = res[i];
printf("%d",pro[i]);
    }
    printf(":");  for (i = 4; i >= 0;
i--){          printf("%d",
anumcp[i]);
    }
}
void arshift(){//for arithmetic shift right    int
temp = pro[4], temp2 = pro[0], i;    for (i = 1; i <
5 ; i++){//shift the MSB of product    pro[i-1] =
pro[i];
    }
    pro[4] = temp;    for (i = 1; i < 5 ; i++){//shift
the LSB of product    anumcp[i-1] = anumcp[i];
    }
    anumcp[4] = temp2; printf("\nAR-SHIFT:
");//display together for (i = 4; i >= 0; i-
-){
        printf("%d",pro[i]);
    }
    printf(":");    for(i = 4; i >=
0; i--){          printf("%d",
anumcp[i]);
```

Vidyavardhini's College of Engineering & Technology
Department of Artificial Intelligence and Data Science

```
    }  
}  
  
void main(){  
    int i, q = 0;  
    printf("\t\tBOOTH'S MULTIPLICATION ALGORITHM");  
    printf("\nEnter two numbers to multiply: ");  
    printf("\nBoth must be less than 16"); //simulating  
    for two numbers each below 16  
    do{    printf("\nEnter A:  
");    scanf("%d",&a);  
    printf("Enter B: ");  
    scanf("%d",  
&b);    }while(a >=16 || b  
>=16);  
  
    printf("\nExpected product = %d", a * b);  
    binary();    printf("\n\nBinary Equivalentents  
are: ");    printf("\nA = ");    for (i = 4; i >=  
0; i--){    printf("%d", anum[i]);  
    }  
    printf("\nB = ");  
    for (i = 4; i >= 0; i--){  
        printf("%d", bnum[i]);  
    }  
    printf("\nB'+ 1 = ");    for  
(i = 4; i >= 0; i-  
-){    printf("%d",  
bcomp[i]);  
    }  
    printf("\n\n");    for  
(i = 0; i < 5;  
i++){    if (anum[i]
```

Vidyavardhini's College of Engineering & Technology
Department of Artificial Intelligence and Data Science

```
==
q){      printf("\n--
>");      arshift();
q = anum[i];
    }
    else if(anum[i] == 1 && q ==
0){      printf("\n-->");
printf("\nSUB B: ");
add(bcomp);      arshift();
q = anum[i];
    }
    else{//add ans shift for 01
printf("\n-->");
printf("\nADD B: ");
add(bnum);      arshift();
q = anum[i];
    }
}

    printf("\nProduct is = ");
for (i = 4; i >= 0; i-
-){      printf("%d", pro[i]);
    }
    for (i = 4; i >= 0; i-
-){      printf("%d",
anumcp[i]);
    }
}
```


Vidyavardhini's College of Engineering & Technology

Department of Artificial Intelligence and Data Science

Output:

```
Both must be less than 16
Enter A: 2
Enter B: 4
Expected product = 8

Binary Equivalents are:
A = 00010
B = 00100
B'+ 1 = 11100

-->
AR-SHIFT: 00000:00001
-->
SUB B: 11100:00001
AR-SHIFT: 11110:00000
-->
ADD B: 00010:00000
AR-SHIFT: 00001:00000
-->
```

Conclusion - The aim was to implement Booth's algorithm in C programming, an efficient method for binary multiplication, reducing partial products and enhancing computational speed through a sequential approach.