

Speidel Braumeister

Home Assistant Integration

Documentation v2.0

1. Overview

This Home Assistant integration allows you to monitor your Speidel Braumeister brewing system in real-time. It uses XHR polling (the same method as the My Speidel web interface) to fetch live brewing data, including temperature, pump/heating status, recipe information, and brewing progress.

2. Features

2.1 Sensors

Sensor	Description
Connection Status	Connection state: online, offline, invalid_uuid
Temperature	Current temperature in Celsius
Target Temperature	Target temperature for current phase
Pump Status	Pump state (Ein/Aus - German On/Off)
Heating Status	Heating element state (Ein/Aus)
Process Status	Brewing process status (running, idle)
Current Phase	Current brewing step (Einmaischen, Rast, Kochen)
Remaining Time	Estimated remaining time in minutes
Brew Name	Name of the current recipe
Device Type	Braumeister model (e.g., "Braumeister 20 Liter")
Device Mode	Current mode (Automatik, wartet)
Current Step	Full step name (e.g., "Stone IPA - Einmaischen")
Brewing Progress	Progress percentage of current brew
Last Online	Last time the device was connected

2.2 Recipe Matching

The Brew Name sensor includes additional attributes that link device recipes to account recipes. The Braumeister stores up to 5 recipes in device slots (0-4). The integration automatically matches these to recipes

in your My Speidel account by name:

- Exact match: Recipe names match exactly (case-insensitive)
- Partial match: Device name is contained in account name

Matched recipes show the account_recipe_id, creation date, and beer style as sensor attributes.

2.3 Translations

The integration includes translations for English and German. Sensor names are automatically displayed in your Home Assistant language setting.

3. Installation

3.1 HACS (Recommended)

1. Open HACS in Home Assistant
2. Go to "Integrations" and click "+"
3. Search for "Speidel Braumeister"
4. Click "Download" and restart Home Assistant

3.2 Manual Installation

1. Copy the custom_components/speidel_braumeister directory to your Home Assistant custom_components folder
2. Restart Home Assistant

4. Configuration

1. Go to Settings > Devices & Services
2. Click "Add Integration"
3. Search for "Speidel Braumeister"
4. Enter your My Speidel credentials (username and password)
5. Enter your Machine UUID (see below)

5. Finding Your Machine UUID

The Machine UUID is a unique identifier for your Braumeister. The most reliable method to find it:

1. Log in to myspeidel.com
2. Go to your Braumeister control page
3. Right-click and select "View Page Source" or "Inspect"

4. Search for data-machine= in the HTML
5. Copy the full value (e.g., 0004A30B003D70F4.323)

6. How It Works

The integration uses XHR polling to fetch real-time data from the My Speidel web interface. This is the same method used by the web interface itself, ensuring reliable data without requiring a paid subscription.

6.1 Data Sources

- XHR Polling: Primary method for real-time temperature, pump, heating, and time data
- Device Info JSON: Additional metadata (device type, mode, step, progress)
- Recipe Endpoints: Device and account recipes for name matching

7. Dashboard Example

YAML Dashboard Card:

```
type: entities
title: Braumeister
entities:
- entity: sensor.braumeister_brew_name
- entity: sensor.braumeister_temperature
- entity: sensor.braumeister_target_temperature
- entity: sensor.braumeister_current_step
- entity: sensor.braumeister_brewing_progress
- entity: sensor.braumeister_remaining_time
- entity: sensor.braumeister_pump_status
- entity: sensor.braumeister_heating_status
```

8. Troubleshooting

Sensors show "Unknown"

- Verify your Braumeister is online in the My Speidel app
- Check that credentials are correct
- Review Home Assistant logs for errors

Connection Status shows "offline"

- The device may be powered off or not brewing
- Check WiFi connectivity on the Braumeister